



COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS			E N D S	F N I S H
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm					
0.296	7.52	XX-52	1.25	31.8	.216	5.5	20	3.5	.41	10	8.1	36	.56	14.2	0.040	1.0	13.0	SPR	C	Z	
0.296	7.52	Y-79	1.25	31.8	.186	4.7	84	15	.23	5.7	19	85	.72	18.2	0.055	1.4	13.0	SPR	CG	N	
0.296	7.52	CC-67	1.28	32.5	.236	6.0	6.5	1.1	.53	13	3.4	15	.32	8.0	0.030	0.8	10.5	SST	CG	N	
0.296	7.52	O-63	1.28	32.5	.188	4.8	62	11	.29	7.4	18	80	.86	21.9	0.054	1.4	16.0	SPR	CG	N	
0.296	7.52	M-96	1.28	32.5	.182	4.6	129	23	.16	4.1	21	94	.60	15.2	0.057	1.4	10.5	SPR	CG	Z	
0.296	7.52	B7-9	1.31	33.3	.244	6.2	3.7	.65	.90	23	3.3	15	.29	7.3	0.026	0.7	11.0	MW	CG	N	
0.296	7.52	S-3076	1.31	33.3	.238	6.0	5.4	.95	.57	15	3.1	14	.33	8.5	0.029	0.7	10.5	SST	C	N	
0.296	7.52	F-32	1.31	33.3	.206	5.2	32	5.6	.36	9.1	11	51	.61	15.4	0.045	1.1	13.5	SPR	CG	Z	
0.296	7.52	I-77	1.31	33.3	.206	5.2	32	5.7	.35	9.0	11	51	.61	15.4	0.045	1.1	13.5	SPR	CG	N	
0.296	7.52	AA-57	1.31	33.3	.176	4.5	98	17	.25	6.3	24	108	.99	25.1	0.060	1.5	16.5	SPR	CG	N	
0.296	7.52	WW-56	1.38	34.9	.258	6.6	1.2	.22	1.1	29	1.4	6.2	.19	4.8	0.019	0.5	9.00	MW	C	Z	
0.296	7.52	3855	1.38	34.9	.240	6.1	4.3	.76	.96	24	4.2	19	.38	9.6	0.028	0.7	12.5	MW	C	Z	
0.296	7.52	KK-28	1.38	34.9	.236	6.0	6.2	1.1	.82	21	5.1	23	.36	9.1	0.030	0.8	12.0	MW	CG	GI	
0.296	7.52	4319	1.38	34.9	.234	5.9	4.7	.82	.82	21	3.8	17	.56	14.2	0.031	0.8	17.0	MW	C	Z	
0.296	7.52	A13-46	1.38	34.9	.218	5.5	15	2.6	.48	12	7.1	31	.54	13.6	0.039	1.0	13.8	SST	CG	N	
0.296	7.52	A12-70	1.38	34.9	.218	5.5	20	3.4	.53	14	10	47	.51	12.9	0.039	1.0	12.0	MW	C	Z	
0.296	7.52	2889	1.38	34.9	.214	5.4	16	2.8	.54	14	8.7	39	.74	18.7	0.041	1.0	17.0	SPR	C	Z	
0.296	7.52	B15-57	1.38	34.9	.210	5.3	24	4.3	.41	11	10	45	.62	15.8	0.043	1.1	14.5	SPR	CG	Z	
0.296	7.52	A11-13	1.38	34.9	.200	5.1	34	5.9	.38	9.7	13	58	.72	18.3	0.048	1.2	15.0	SST	CG	N	
0.296	7.52	11405	1.41	35.7	.248	6.3	2.6	.46	1.1	27	2.8	12	.29	7.3	0.024	0.6	11.0	MW	C	Z	
0.296	7.52	Q-54	1.44	36.5	.202	5.1	28	4.9	.44	11	12	54	.75	19.1	0.047	1.2	16.0	SST	CG	N	
0.296	7.52	K-86	1.44	36.5	.196	5.0	40	7.0	.34	8.7	14	61	.75	19.1	0.050	1.3	15.0	SST	CG	N	
0.296	7.52	H-83	1.50	38.1	.256	6.5	.72	.13	1.2	30	.85	3.8	.32	8.1	0.020	0.5	15.0	SST	C	N	
0.296	7.52	4280	1.50	38.1	.238	6.0	4.1	.71	1.0	26	4.2	19	.46	11.8	0.029	0.7	15.0	MW	C	Z	
0.296	7.52	11408	1.50	38.1	.226	5.7	8.8	1.5	.86	22	7.6	34	.59	14.9	0.035	0.9	15.8	MW	C	Z	
0.296	7.52	B9-10	1.50	38.1	.226	5.7	9.3	1.6	.59	15	5.5	25	.53	13.3	0.035	0.9	15.0	SPR	CG	N	
0.296	7.52	11900	1.50	38.1	.222	5.6	11	1.9	.55	14	6.1	27	.54	13.6	0.037	0.9	14.5	SST	CG	N	
0.296	7.52	A13-8	1.50	38.1	.212	5.4	17	3.0	.50	13	8.8	39	.66	16.8	0.042	1.1	15.8	SST	CG	N	
0.296	7.52	10057	1.50	38.1	.206	5.2	26	4.6	.44	11	11	51	.77	19.4	0.045	1.1	16.0	SPR	C	GI	
0.296	7.52	A14-36	1.50	38.1	.206	5.2	23	4.1	.46	12	11	48	.72	18.3	0.045	1.1	16.0	SST	CG	N	
0.296	7.52	2840	1.63	41.3	.228	5.8	5.9	1.0	.95	24	5.6	25	.68	17.2	0.034	0.9	19.9	MW	CG	Z	
0.296	7.52	S-1558	1.63	41.3	.228	5.8	4.5	.79	.83	21	3.7	17	.80	20.3	0.034	0.9	22.5	SST	C	N	
0.296	7.52	3532	1.66	42.1	.222	5.6	9.3	1.6	.70	18	6.5	29	.68	17.4	0.037	0.9	18.5	SPR	CG	GI	
0.296	7.52	A-37	1.69	42.8	.170	4.3	105	18	.26	6.7	28	124	1.26	32.0	0.063	1.6	19.0	HD	C	N	
0.296	7.52	U-36	1.72	43.6	.224	5.7	8.6	1.5	.70	18	6.0	27	.65	16.5	0.036	0.9	18.0	SPR	CG	GI	
0.296	7.52	F-29	1.72	43.6	.172	4.4	126	22	.21	5.4	27	119	.99	25.2	0.062	1.6	15.0	SPR	C	Z	
0.296	7.52	S-1433	1.75	44.5	.256	6.5	.99	.17	1.1	28	1.1	4.8	.25	6.4	0.020	0.5	11.5	SST	C	N	
0.296	7.52	10203	1.75	44.5	.252	6.4	1.9	.34	1.1	29	2.2	9.6	.23	5.9	0.022	0.6	10.5	MW	CG	Z	
0.296	7.52	AA-55	1.75	44.5	.246	6.2	2.5	.44	1.2	30	3.0	13	.35	8.9	0.025	0.6	13.0	MW	C	Z	
0.296	7.52	QQ-64	1.75	44.5	.246	6.2	1.6	.28	1.2	31	2.0	8.8	.51	13.0	0.025	0.6	19.5	MW	C	Z	
0.296	7.52	3603	1.75	44.5	.232	5.9	6.6	1.2	.93	24	6.2	27	.49	12.4	0.032	0.8	14.3	MW	C	Z	
0.296	7.52	B12-15	1.78	45.2	.214	5.4	16	2.7	.56	14	8.7	39	.73	18.5	0.041	1.0	17.8	SPR	CG	N	
0.296	7.52	1747	1.81	46.0	.244	6.2	3.3	.58	1.0	25	3.3	15	.34	8.6	0.026	0.7	12.0	MW	C	Z	
0.296	7.52	M-124	1.88	47.6	.218	5.5	12	2.2	.61	15	7.6	34	.72	18.3	0.039	1.0	17.5	SPR	C	GI	
0.296	7.52	3366	1.88	47.6	.216	5.5	14	2.4	.81	20	11	50	.74	18.8	0.040	1.0	17.5	MW	C	Z	
0.296	7.52	2633	1.88	47.6	.172	4.4	109	19	.34	8.6	37	165	1.05	26.8	0.062	1.6	17.0	MW	CG	Z	
0.296	7.52	11476	1.94	49.2	.236	6.0	4.4	.77	1.2	29	5.1	23	.51	13.0	0.030	0.8	16.0	MW	CG	GI	
0.296	7.52	A10-68	1.94	49.2	.212	5.4	13	2.3	.66	17	8.8	39	.84	21.3	0.042	1.1	20.0	SST	CG	N	
0.296	7.52	B4-14	1.95	49.6	.172	4.4	111	19	.24	6.1	27	119	1.12	28.3	0.062	1.6	17.0	SPR	C	N	
0.296	7.52	S-1006	2.00	50.8	.234	5.9	3.5	.61	1.1	27	3.8	17	.64	16.1	0.031	0.8	19.5	SST	C	N	
0.296	7.52	10071	2.00	50.8	.208	5.3	18	3.2	.58	15	11	48	.88	22.4	0.044	1.1	20.0	SPR	CG	Z	
0.296	7.52	B10-7	2.09	53.2	.218	5.5	10	1.8	.74	19	7.6	34	.83	21.1	0.039	1.0	21.3	SPR	CG	N	
0.296	7.52	B15-62	2.16	54.8	.204	5.2	17	3.0	.71	18	12	54	1.24	31.5	0.046	1.2	26.0	SPR	C	N	
0.296	7.52	S-1026	2.16	54.8	.202	5.1	16	2.8	.75	19	12	54	1.27	32.2	0.047	1.2	26.0	SST	C	N	
0.296	7.52	S-880	2.28	57.9	.238	6.0	1.4	.25	1.3	32	1.8	8.1	1.02	25.8	0.029	0.7	34.0	SST	C	N	
0.296	7.52	Q-15	2.56	65.1	.218	5.5	9.6	1.7	.79	20	7.6	34	.88	22.3	0.039	1.0	22.5	SPR	CG	N	
0.296	7.52	3651	2.56	65.1	.200	5.1	16	2.9	.84	21	14	61	1.54	39.0	0.048	1.					

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS			E N D S	F I N I S H
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm		MAT'L			
0.300	7.62	70887S	.38	9.7	.224	5.7	55	9.6	.12	3.0	6.5	29	.18	4.5	0.038	1.0	4.63	SST	CG	N	
0.300	7.62	70906	.38	9.7	.220	5.6	78	14	.14	3.6	11	50	.19	4.8	0.040	1.0	4.75	MW	CG	N	
0.300	7.62	70906S	.38	9.7	.220	5.6	66	12	.11	2.9	7.5	33	.19	4.8	0.040	1.0	4.75	SST	CG	N	
0.300	7.62	70925	.38	9.7	.216	5.5	107	19	.12	3.1	13	57	.19	4.8	0.042	1.1	4.50	MW	CG	N	
0.300	7.62	70925S	.38	9.7	.216	5.5	91	16	.10	2.4	8.7	39	.19	4.8	0.042	1.1	4.50	SST	CG	N	
0.300	7.62	70944	.38	9.7	.210	5.3	124	22	.13	3.2	16	70	.22	5.6	0.045	1.1	4.88	MW	CG	N	
0.300	7.62	70944S	.38	9.7	.210	5.3	105	18	.10	2.6	11	47	.22	5.6	0.045	1.1	4.88	SST	CG	N	
0.300	7.62	70963	.38	9.7	.206	5.2	159	28	.11	2.8	18	79	.22	5.7	0.047	1.2	4.75	MW	CG	N	
0.300	7.62	70963S	.38	9.7	.206	5.2	135	24	.09	2.3	12	53	.22	5.7	0.047	1.2	4.75	SST	CG	N	
0.300	7.62	70984	.38	9.7	.202	5.1	190	33	.11	2.7	20	89	.23	5.9	0.049	1.2	4.75	MW	CG	N	
0.300	7.62	70984S	.38	9.7	.202	5.1	161	28	.08	2.1	14	60	.23	5.9	0.049	1.2	4.75	SST	CG	N	
0.300	7.62	71005	.38	9.7	.198	5.0	228	40	.09	2.3	21	94	.24	6.2	0.051	1.3	4.75	MW	CG	N	
0.300	7.62	71005S	.38	9.7	.198	5.0	194	34	.07	1.9	14	63	.24	6.2	0.051	1.3	4.75	SST	CG	N	
0.300	7.62	70780	.44	11.2	.256	6.5	7.2	1.3	.30	7.5	2.1	9.5	.09	2.3	0.022	0.6	4.13	MW	CG	N	
0.300	7.62	70780S	.44	11.2	.256	6.5	6.1	1.1	.23	5.9	1.4	6.3	.09	2.3	0.022	0.6	4.13	SST	CG	N	
0.300	7.62	70803	.44	11.2	.248	6.3	13	2.3	.25	6.4	3.3	15	.11	2.9	0.026	0.7	4.38	MW	CG	N	
0.300	7.62	70803S	.44	11.2	.248	6.3	11	2.0	.20	5.0	2.2	9.8	.11	2.9	0.026	0.7	4.38	SST	CG	N	
0.300	7.62	70826	.44	11.2	.240	6.1	21	3.6	.24	6.2	5.0	22	.15	3.7	0.030	0.8	4.88	MW	CG	N	
0.300	7.62	70826S	.44	11.2	.240	6.1	18	3.1	.19	4.9	3.4	15	.15	3.7	0.030	0.8	4.88	SST	CG	N	
0.300	7.62	70848	.44	11.2	.236	6.0	27	4.8	.22	5.7	6.1	27	.16	4.0	0.032	0.8	4.88	MW	CG	N	
0.300	7.62	70848S	.44	11.2	.236	6.0	23	4.0	.18	4.5	4.1	18	.16	4.0	0.032	0.8	4.88	SST	CG	N	
0.300	7.62	70869	.44	11.2	.230	5.8	38	6.7	.20	5.0	7.5	34	.18	4.4	0.035	0.9	5.00	MW	CG	N	
0.300	7.62	70869S	.44	11.2	.230	5.8	33	5.7	.16	4.0	5.1	23	.18	4.4	0.035	0.9	5.00	SST	CG	N	
0.300	7.62	70888	.44	11.2	.224	5.7	53	9.3	.18	4.6	9.6	43	.19	4.9	0.038	1.0	5.13	MW	CG	N	
0.300	7.62	70888S	.44	11.2	.224	5.7	45	7.9	.14	3.6	6.5	29	.19	4.9	0.038	1.0	5.13	SST	CG	N	
0.300	7.62	70907	.44	11.2	.220	5.6	65	11	.17	4.3	11	50	.21	5.3	0.040	1.0	5.25	MW	CG	N	
0.300	7.62	70907S	.44	11.2	.220	5.6	56	9.7	.14	3.4	7.5	33	.21	5.3	0.040	1.0	5.25	SST	CG	N	
0.300	7.62	70926	.44	11.2	.216	5.5	89	16	.14	3.6	13	57	.20	5.2	0.042	1.1	4.88	MW	CG	N	
0.300	7.62	70926S	.44	11.2	.216	5.5	76	13	.11	2.9	8.7	39	.20	5.2	0.042	1.1	4.88	SST	CG	N	
0.300	7.62	70945	.44	11.2	.210	5.3	105	18	.15	3.8	16	70	.24	6.1	0.045	1.1	5.38	MW	CG	N	
0.300	7.62	70945S	.44	11.2	.210	5.3	89	16	.12	3.0	11	47	.24	6.1	0.045	1.1	5.38	SST	CG	N	
0.300	7.62	70964	.44	11.2	.206	5.2	132	23	.13	3.4	18	79	.25	6.3	0.047	1.2	5.25	MW	CG	N	
0.300	7.62	70964S	.44	11.2	.206	5.2	112	20	.11	2.7	12	53	.25	6.3	0.047	1.2	5.25	SST	CG	N	
0.300	7.62	70985	.44	11.2	.202	5.1	156	27	.13	3.3	20	89	.26	6.7	0.049	1.2	5.38	MW	CG	N	
0.300	7.62	70985S	.44	11.2	.202	5.1	133	23	.10	2.6	14	60	.26	6.7	0.049	1.2	5.38	SST	CG	N	
0.300	7.62	71006	.44	11.2	.198	5.0	187	33	.11	2.9	21	94	.27	7.0	0.051	1.3	5.38	MW	CG	N	
0.300	7.62	71006S	.44	11.2	.198	5.0	159	28	.09	2.3	14	63	.27	7.0	0.051	1.3	5.38	SST	CG	N	
0.300	7.62	B4-69	.47	11.9	.258	6.6	2.7	.47	.31	7.8	.83	3.7	.16	4.1	0.021	0.5	6.75	MW	C	GI	
0.300	7.62	70781	.50	12.7	.256	6.5	6.6	1.1	.33	8.3	2.1	9.5	.10	2.4	0.022	0.6	4.38	MW	CG	N	
0.300	7.62	70781S	.50	12.7	.256	6.5	5.6	.97	.25	6.5	1.4	6.3	.10	2.4	0.022	0.6	4.38	SST	CG	N	
0.300	7.62	70804	.50	12.7	.248	6.3	11	2.0	.29	7.4	3.3	15	.13	3.2	0.026	0.7	4.88	MW	CG	N	
0.300	7.62	70804S	.50	12.7	.248	6.3	9.6	1.7	.23	5.8	2.2	9.8	.13	3.2	0.026	0.7	4.88	SST	CG	N	
0.300	7.62	70827	.50	12.7	.240	6.1	18	3.1	.28	7.2	5.0	22	.16	4.1	0.030	0.8	5.38	MW	CG	N	
0.300	7.62	70827S	.50	12.7	.240	6.1	15	2.6	.22	5.7	3.4	15	.16	4.1	0.030	0.8	5.38	SST	CG	N	
0.300	7.62	70849	.50	12.7	.236	6.0	23	4.1	.26	6.6	6.1	27	.17	4.4	0.032	0.8	5.38	MW	CG	N	
0.300	7.62	70849S	.50	12.7	.236	6.0	20	3.5	.21	5.2	4.1	18	.17	4.4	0.032	0.8	5.38	SST	CG	N	
0.300	7.62	70870	.50	12.7	.230	5.8	33	5.8	.23	5.8	7.5	34	.19	4.9	0.035	0.9	5.50	MW	CG	N	
0.300	7.62	70870S	.50	12.7	.230	5.8	28	4.9	.18	4.6	5.1	23	.19	4.9	0.035	0.9	5.50	SST	CG	N	
0.300	7.62	70889	.50	12.7	.224	5.7	46	8.1	.21	5.3	9.6	43	.21	5.4	0.038	1.0	5.63	MW	CG	N	
0.300	7.62	70889S	.50	12.7	.224	5.7	39	6.9	.17	4.2	6.5	29	.21	5.4	0.038	1.0	5.63	SST	CG	N	
0.300	7.62	70908	.50	12.7	.220	5.6	55	9.7	.20	5.1	11	50	.23	5.8	0.040	1.0	5.75	MW	CG	N	
0.300	7.62	70908S	.50	12.7	.220	5.6	47	8.3	.16	4.1	7.5	33	.23	5.8	0.040	1.0	5.75	SST	CG	N	
0.300	7.62	70927	.50	12.7	.216	5.5	70	12	.18	4.6	13	57	.24	6.1	0.042	1.1	5.75	MW	CG	N	
0.300	7.62	70927S	.50	12.7	.216	5.5	60	10	.15	3.7	8.7	39	.24	6.1	0.042	1.1	5.75	SST	CG	N	
0.300	7.62	70946	.50	12.7	.210	5.3	91	16	.17	4.4	16	70	.26	6.7	0.045	1.1	5.88	MW	CG	N	
0.300	7.62	70946S	.50	12.7	.210	5.3	78	14	.14	3.5	11	47	.26	6.7	0.045	1.1	5.88	SST	CG	N	




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS			E N D S	F N D H
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm					
0.300	7.62	70966	.56	14.2	.206	5.2	97	17	.18	4.6	18	79	.31	7.8	0.047	1.2	6.50	MW	CG	N	
0.300	7.62	70966S	.56	14.2	.206	5.2	83	14	.15	3.7	12	53	.31	7.8	0.047	1.2	6.50	SST	CG	N	
0.300	7.62	70987	.56	14.2	.202	5.1	116	20	.17	4.4	20	89	.32	8.1	0.049	1.2	6.50	MW	CG	N	
0.300	7.62	70987S	.56	14.2	.202	5.1	98	17	.14	3.5	14	60	.32	8.1	0.049	1.2	6.50	SST	CG	N	
0.300	7.62	71008	.56	14.2	.198	5.0	137	24	.15	3.9	21	94	.34	8.6	0.051	1.3	6.63	MW	CG	N	
0.300	7.62	71008S	.56	14.2	.198	5.0	116	20	.12	3.1	14	63	.34	8.6	0.051	1.3	6.63	SST	CG	N	
0.300	7.62	B4-34	.56	14.3	.224	5.7	37	6.5	.26	6.6	9.6	43	.25	6.3	0.038	1.0	6.50	MW	CG	GI	
0.300	7.62	70783	.63	16.0	.256	6.5	5.0	.88	.43	11	2.1	9.5	.11	2.9	0.022	0.6	5.13	MW	CG	N	
0.300	7.62	70783S	.63	16.0	.256	6.5	4.3	.74	.33	8.5	1.4	6.3	.11	2.9	0.022	0.6	5.13	SST	CG	N	
0.300	7.62	70806	.63	16.0	.248	6.3	9.0	1.6	.37	9.4	3.3	15	.15	3.7	0.026	0.7	5.63	MW	CG	N	
0.300	7.62	70806S	.63	16.0	.248	6.3	7.6	1.3	.29	7.4	2.2	9.8	.15	3.7	0.026	0.7	5.63	SST	CG	N	
0.300	7.62	70829	.63	16.0	.240	6.1	14	2.4	.36	9.2	5.0	22	.19	4.8	0.030	0.8	6.25	MW	CG	N	
0.300	7.62	70829S	.63	16.0	.240	6.1	12	2.1	.28	7.2	3.4	15	.19	4.8	0.030	0.8	6.25	SST	CG	N	
0.300	7.62	70851	.63	16.0	.236	6.0	18	3.2	.34	8.5	6.1	27	.20	5.2	0.032	0.8	6.38	MW	CG	N	
0.300	7.62	70851S	.63	16.0	.236	6.0	15	2.7	.26	6.7	4.1	18	.20	5.2	0.032	0.8	6.38	SST	CG	N	
0.300	7.62	70872	.63	16.0	.230	5.8	26	4.5	.29	7.5	7.5	34	.23	5.8	0.035	0.9	6.50	MW	CG	N	
0.300	7.62	70872S	.63	16.0	.230	5.8	22	3.8	.23	6.0	5.1	23	.23	5.8	0.035	0.9	6.50	SST	CG	N	
0.300	7.62	70891	.63	16.0	.224	5.7	35	6.1	.27	7.0	9.6	43	.26	6.5	0.038	1.0	6.75	MW	CG	N	
0.300	7.62	70891S	.63	16.0	.224	5.7	30	5.2	.22	5.5	6.5	29	.26	6.5	0.038	1.0	6.75	SST	CG	N	
0.300	7.62	70910	.63	16.0	.220	5.6	43	7.5	.26	6.6	11	50	.28	7.0	0.040	1.0	6.88	MW	CG	N	
0.300	7.62	70910S	.63	16.0	.220	5.6	37	6.4	.21	5.2	7.5	33	.28	7.0	0.040	1.0	6.88	SST	CG	N	
0.300	7.62	70929	.63	16.0	.216	5.5	52	9.1	.25	6.3	13	57	.29	7.5	0.042	1.1	7.00	MW	CG	N	
0.300	7.62	70929S	.63	16.0	.216	5.5	44	7.7	.20	5.0	8.7	39	.29	7.5	0.042	1.1	7.00	SST	CG	N	
0.300	7.62	70948	.63	16.0	.210	5.3	68	12	.23	5.8	16	70	.33	8.3	0.045	1.1	7.25	MW	CG	N	
0.300	7.62	70948S	.63	16.0	.210	5.3	58	10	.18	4.6	11	47	.33	8.3	0.045	1.1	7.25	SST	CG	N	
0.300	7.62	70967	.63	16.0	.206	5.2	86	15	.21	5.2	18	79	.33	8.4	0.047	1.2	7.00	MW	CG	N	
0.300	7.62	70967S	.63	16.0	.206	5.2	73	13	.16	4.2	12	53	.33	8.4	0.047	1.2	7.00	SST	CG	N	
0.300	7.62	70988	.63	16.0	.202	5.1	102	18	.20	5.0	20	89	.35	8.9	0.049	1.2	7.13	MW	CG	N	
0.300	7.62	70988S	.63	16.0	.202	5.1	87	15	.16	4.0	14	60	.35	8.9	0.049	1.2	7.13	SST	CG	N	
0.300	7.62	71009	.63	16.0	.198	5.0	121	21	.17	4.4	21	94	.37	9.4	0.051	1.3	7.25	MW	CG	N	
0.300	7.62	71009S	.63	16.0	.198	5.0	103	18	.14	3.5	14	63	.37	9.4	0.051	1.3	7.25	SST	CG	N	
0.300	7.62	70784	.69	17.5	.256	6.5	4.6	.81	.46	12	2.1	9.5	.12	3.0	0.022	0.6	5.38	MW	CG	N	
0.300	7.62	70784S	.69	17.5	.256	6.5	3.9	.68	.36	9.2	1.4	6.3	.12	3.0	0.022	0.6	5.38	SST	CG	N	
0.300	7.62	70807	.69	17.5	.248	6.3	7.9	1.4	.42	11	3.3	15	.16	4.0	0.026	0.7	6.00	MW	CG	N	
0.300	7.62	70807S	.69	17.5	.248	6.3	6.7	1.2	.33	8.4	2.2	9.8	.16	4.0	0.026	0.7	6.00	SST	CG	N	
0.300	7.62	70823	.69	17.5	.242	6.1	9.0	1.6	.47	12	4.2	19	.22	5.6	0.029	0.7	7.63	MW	CG	N	
0.300	7.62	70823S	.69	17.5	.242	6.1	7.7	1.3	.40	10	3.1	14	.22	5.6	0.029	0.7	7.63	SST	CG	N	
0.300	7.62	70830	.69	17.5	.240	6.1	13	2.2	.40	10	5.0	22	.20	5.1	0.030	0.8	6.75	MW	CG	N	
0.300	7.62	70830S	.69	17.5	.240	6.1	11	1.9	.32	8.1	3.4	15	.20	5.1	0.030	0.8	6.75	SST	CG	N	
0.300	7.62	70852	.69	17.5	.236	6.0	16	2.8	.38	9.6	6.1	27	.22	5.6	0.032	0.8	6.88	MW	CG	N	
0.300	7.62	70852S	.69	17.5	.236	6.0	14	2.4	.30	7.5	4.1	18	.22	5.6	0.032	0.8	6.88	SST	CG	N	
0.300	7.62	70873	.69	17.5	.230	5.8	23	4.0	.33	8.4	7.5	34	.25	6.3	0.035	0.9	7.13	MW	CG	N	
0.300	7.62	70873S	.69	17.5	.230	5.8	19	3.4	.26	6.7	5.1	23	.25	6.3	0.035	0.9	7.13	SST	CG	N	
0.300	7.62	70892	.69	17.5	.224	5.7	30	5.3	.32	8.1	9.6	43	.29	7.2	0.038	1.0	7.50	MW	CG	N	
0.300	7.62	70892S	.69	17.5	.224	5.7	26	4.5	.25	6.4	6.5	29	.29	7.2	0.038	1.0	7.50	SST	CG	N	
0.300	7.62	70911	.69	17.5	.220	5.6	38	6.7	.29	7.4	11	50	.30	7.6	0.040	1.0	7.50	MW	CG	N	
0.300	7.62	70911S	.69	17.5	.220	5.6	32	5.7	.23	5.9	7.5	33	.30	7.6	0.040	1.0	7.50	SST	CG	N	
0.300	7.62	70930	.69	17.5	.216	5.5	46	8.0	.28	7.2	13	57	.33	8.3	0.042	1.1	7.75	MW	CG	N	
0.300	7.62	70930S	.69	17.5	.216	5.5	39	6.8	.22	5.7	8.7	39	.33	8.3	0.042	1.1	7.75	SST	CG	N	
0.300	7.62	70949	.69	17.5	.210	5.3	62	11	.25	6.5	16	70	.35	8.9	0.045	1.1	7.75	MW	CG	N	
0.300	7.62	70949S	.69	17.5	.210	5.3	52	9.2	.20	5.2	11	47	.35	8.9	0.045	1.1	7.75	SST	CG	N	
0.300	7.62	70968	.69	17.5	.206	5.2	77	13	.23	5.9	18	79	.36	9.1	0.047	1.2	7.63	MW	CG	N	
0.300	7.62	70968S	.69	17.5	.206	5.2	65	11	.18	4.7	12	53	.36	9.1	0.047	1.2	7.63	SST	CG	N	
0.300	7.62	70989	.69	17.5	.202	5.1	90	16	.22	5.6	20	89	.38	9.6	0.049	1.2	7.75	MW	CG	N	
0.300	7.62	70989S	.69	17.5	.202	5.1	77	13	.18	4.5	14	60	.38	9.6	0.049	1.2	7.75	SST	CG	N	
0.300	7.62	71010	.69	17.5	.198	5.0	107	19	.20	5.0	21	94	.40	10.2	0.051	1.3	7.88	MW	CG	N	
0.300	7.62	71010S	.69	17.5	.198	5.0	91	16	.16	4.0	14	63	.40	10.2	0.051	1.3	7.88	SST	CG	N	
0.300	7.62	70785	.75	19.1	.256	6.															

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL				
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm	COILS	MAT'L		ENDS	FINISH
0.300	7.62	71011S	.75	19.1	.198	5.0	82	14	.17	4.4	14	63	.43	11.0	0.051	1.3	8.50	SST	CG	N	
0.300	7.62	70786	.81	20.6	.256	6.5	3.7	.64	.58	15	2.1	9.5	.14	3.5	0.022	0.6	6.25	MW	CG	N	
0.300	7.62	70786S	.81	20.6	.256	6.5	3.1	.54	.46	12	1.4	6.3	.14	3.5	0.022	0.6	6.25	SST	CG	N	
0.300	7.62	70809	.81	20.6	.248	6.3	6.9	1.2	.48	12	3.3	15	.17	4.4	0.026	0.7	6.63	MW	CG	N	
0.300	7.62	70809S	.81	20.6	.248	6.3	5.8	1.0	.38	9.6	2.2	9.8	.17	4.4	0.026	0.7	6.63	SST	CG	N	
0.300	7.62	70832	.81	20.6	.240	6.1	10	1.8	.48	12	5.0	22	.23	5.8	0.030	0.8	7.63	MW	CG	N	
0.300	7.62	70832S	.81	20.6	.240	6.1	8.9	1.6	.38	9.6	3.4	15	.23	5.8	0.030	0.8	7.63	SST	CG	N	
0.300	7.62	70854	.81	20.6	.236	6.0	14	2.4	.45	11	6.1	27	.25	6.3	0.032	0.8	7.75	MW	CG	N	
0.300	7.62	70854S	.81	20.6	.236	6.0	12	2.0	.35	9.0	4.1	18	.25	6.3	0.032	0.8	7.75	SST	CG	N	
0.300	7.62	70875	.81	20.6	.230	5.8	19	3.3	.40	10	7.5	34	.28	7.2	0.035	0.9	8.13	MW	CG	N	
0.300	7.62	70875S	.81	20.6	.230	5.8	16	2.8	.31	8.0	5.1	23	.28	7.2	0.035	0.9	8.13	SST	CG	N	
0.300	7.62	70894	.81	20.6	.224	5.7	26	4.5	.37	9.4	9.6	43	.32	8.1	0.038	1.0	8.38	MW	CG	N	
0.300	7.62	70894S	.81	20.6	.224	5.7	22	3.9	.29	7.5	6.5	29	.32	8.1	0.038	1.0	8.38	SST	CG	N	
0.300	7.62	70913	.81	20.6	.220	5.6	32	5.5	.35	9.0	11	50	.35	8.8	0.040	1.0	8.63	MW	CG	N	
0.300	7.62	70913S	.81	20.6	.220	5.6	27	4.7	.28	7.1	7.5	33	.35	8.8	0.040	1.0	8.63	SST	CG	N	
0.300	7.62	70932	.81	20.6	.216	5.5	38	6.6	.34	8.6	13	57	.37	9.5	0.042	1.1	8.88	MW	CG	N	
0.300	7.62	70932S	.81	20.6	.216	5.5	32	5.6	.27	6.9	8.7	39	.37	9.5	0.042	1.1	8.88	SST	CG	N	
0.300	7.62	70951	.81	20.6	.210	5.3	51	9.0	.31	7.8	16	70	.41	10.3	0.045	1.1	9.00	MW	CG	N	
0.300	7.62	70951S	.81	20.6	.210	5.3	43	7.6	.24	6.2	11	47	.41	10.3	0.045	1.1	9.00	SST	CG	N	
0.300	7.62	70970	.81	20.6	.206	5.2	63	11	.28	7.1	18	79	.42	10.6	0.047	1.2	8.88	MW	CG	N	
0.300	7.62	70970S	.81	20.6	.206	5.2	54	9.4	.22	5.7	12	53	.42	10.6	0.047	1.2	8.88	SST	CG	N	
0.300	7.62	70991	.81	20.6	.202	5.1	75	13	.27	6.8	20	89	.44	11.2	0.049	1.2	9.00	MW	CG	N	
0.300	7.62	70991S	.81	20.6	.202	5.1	64	11	.21	5.4	14	60	.44	11.2	0.049	1.2	9.00	SST	CG	N	
0.300	7.62	71012	.81	20.6	.198	5.0	89	16	.24	6.0	21	94	.47	11.8	0.051	1.3	9.13	MW	CG	N	
0.300	7.62	71012S	.81	20.6	.198	5.0	75	13	.19	4.8	14	63	.47	11.8	0.051	1.3	9.13	SST	CG	N	
0.300	7.62	70787	.88	22.4	.256	6.5	3.3	.58	.65	16	2.1	9.5	.15	3.8	0.022	0.6	6.75	MW	CG	N	
0.300	7.62	70787S	.88	22.4	.256	6.5	2.8	.49	.51	13	1.4	6.3	.15	3.8	0.022	0.6	6.75	SST	CG	N	
0.300	7.62	70810	.88	22.4	.248	6.3	6.1	1.1	.55	14	3.3	15	.19	4.8	0.026	0.7	7.25	MW	CG	N	
0.300	7.62	70810S	.88	22.4	.248	6.3	5.1	.90	.43	11	2.2	9.8	.19	4.8	0.026	0.7	7.25	SST	CG	N	
0.300	7.62	70833	.88	22.4	.240	6.1	9.7	1.7	.52	13	5.0	22	.24	6.2	0.030	0.8	8.13	MW	CG	N	
0.300	7.62	70833S	.88	22.4	.240	6.1	8.2	1.4	.41	10	3.4	15	.24	6.2	0.030	0.8	8.13	SST	CG	N	
0.300	7.62	70855	.88	22.4	.236	6.0	12	2.2	.49	13	6.1	27	.27	6.8	0.032	0.8	8.38	MW	CG	N	
0.300	7.62	70855S	.88	22.4	.236	6.0	10	1.8	.39	9.9	4.1	18	.27	6.8	0.032	0.8	8.38	SST	CG	N	
0.300	7.62	70876	.88	22.4	.230	5.8	18	3.1	.43	11	7.5	34	.30	7.7	0.035	0.9	8.63	MW	CG	N	
0.300	7.62	70876S	.88	22.4	.230	5.8	15	2.6	.34	8.7	5.1	23	.30	7.7	0.035	0.9	8.63	SST	CG	N	
0.300	7.62	70895	.88	22.4	.224	5.7	23	4.0	.41	11	9.6	43	.35	8.9	0.038	1.0	9.25	MW	CG	N	
0.300	7.62	70895S	.88	22.4	.224	5.7	20	3.4	.33	8.4	6.5	29	.35	8.9	0.038	1.0	9.25	SST	CG	N	
0.300	7.62	70914	.88	22.4	.220	5.6	29	5.1	.38	9.7	11	50	.37	9.3	0.040	1.0	9.13	MW	CG	N	
0.300	7.62	70914S	.88	22.4	.220	5.6	25	4.3	.30	7.7	7.5	33	.37	9.3	0.040	1.0	9.13	SST	CG	N	
0.300	7.62	70933	.88	22.4	.216	5.5	34	5.9	.38	9.6	13	57	.40	10.3	0.042	1.1	9.63	MW	CG	N	
0.300	7.62	70933S	.88	22.4	.216	5.5	29	5.0	.30	7.7	8.7	39	.40	10.3	0.042	1.1	9.63	SST	CG	N	
0.300	7.62	70952	.88	22.4	.210	5.3	46	8.1	.34	8.6	16	70	.44	11.1	0.045	1.1	9.75	MW	CG	N	
0.300	7.62	70952S	.88	22.4	.210	5.3	39	6.9	.27	6.9	11	47	.44	11.1	0.045	1.1	9.75	SST	CG	N	
0.300	7.62	70971	.88	22.4	.206	5.2	58	10	.31	7.8	18	79	.45	11.3	0.047	1.2	9.50	MW	CG	N	
0.300	7.62	70971S	.88	22.4	.206	5.2	49	8.6	.24	6.2	12	53	.45	11.3	0.047	1.2	9.50	SST	CG	N	
0.300	7.62	70992	.88	22.4	.202	5.1	68	12	.29	7.4	20	89	.47	12.0	0.049	1.2	9.63	MW	CG	N	
0.300	7.62	70992S	.88	22.4	.202	5.1	58	10	.23	5.9	14	60	.47	12.0	0.049	1.2	9.63	SST	CG	N	
0.300	7.62	71013	.88	22.4	.198	5.0	81	14	.26	6.6	21	94	.50	12.6	0.051	1.3	9.75	MW	CG	N	
0.300	7.62	71013S	.88	22.4	.198	5.0	69	12	.21	5.3	14	63	.50	12.6	0.051	1.3	9.75	SST	CG	N	
0.300	7.62	70789	.94	23.9	.256	6.5	3.3	.58	.65	16	2.1	9.5	.15	3.8	0.022	0.6	6.75	MW	CG	N	
0.300	7.62	70789S	.94	23.9	.256	6.5	2.8	.49	.51	13	1.4	6.3	.15	3.8	0.022	0.6	6.75	SST	CG	N	
0.300	7.62	70811	.94	23.9	.248	6.3	5.5	.96	.60	15	3.3	15	.20	5.1	0.026	0.7	7.75	MW	CG	N	
0.300	7.62	70811S	.94	23.9	.248	6.3	4.7	.82	.47	12	2.2	9.8	.20	5.1	0.026	0.7	7.75	SST	CG	N	
0.300	7.62	70834	.94	23.9	.240	6.1	9.0	1.6	.56	14	5.0	22	.26	6.6	0.030	0.8	8.63	MW	CG	N	
0.300	7.62	70834S	.94	23.9	.240	6.1	7.6	1.3	.44	11	3.4	15	.26	6.6	0.030	0.8	8.63	SST	CG	N	
0.300	7.62	70856	.94	23.9	.236	6.0	11	2.0	.55	14	6.1	27	.29	7.3	0.032	0.8	9.00	MW			




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS			E N D S	F N D H
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm					
0.300	7.62	70857S	1.00	25.4	.236	6.0	8.8	1.5	.47	12	4.1	18	.31	7.8	0.032	0.8	9.63	SST	CG	N	
0.300	7.62	70878	1.00	25.4	.230	5.8	15	2.7	.50	13	7.5	34	.34	8.6	0.035	0.9	9.63	MW	CG	N	
0.300	7.62	70878S	1.00	25.4	.230	5.8	13	2.3	.40	10	5.1	23	.34	8.6	0.035	0.9	9.63	SST	CG	N	
0.300	7.62	70897	1.00	25.4	.224	5.7	21	3.6	.46	12	9.6	43	.38	9.7	0.038	1.0	10.0	MW	CG	N	
0.300	7.62	70897S	1.00	25.4	.224	5.7	18	3.1	.37	9.3	6.5	29	.38	9.7	0.038	1.0	10.0	SST	CG	N	
0.300	7.62	70916	1.00	25.4	.220	5.6	25	4.4	.44	11	11	50	.41	10.4	0.040	1.0	10.3	MW	CG	N	
0.300	7.62	70916S	1.00	25.4	.220	5.6	22	3.8	.35	8.9	7.5	33	.41	10.4	0.040	1.0	10.3	SST	CG	N	
0.300	7.62	70935	1.00	25.4	.216	5.5	30	5.3	.43	11	13	57	.45	11.3	0.042	1.1	10.6	MW	CG	N	
0.300	7.62	70935S	1.00	25.4	.216	5.5	26	4.5	.34	8.6	8.7	39	.45	11.3	0.042	1.1	10.6	SST	CG	N	
0.300	7.62	70954	1.00	25.4	.210	5.3	40	7.0	.39	9.9	16	70	.49	12.4	0.045	1.1	10.9	MW	CG	N	
0.300	7.62	70954S	1.00	25.4	.210	5.3	34	6.0	.31	7.9	11	47	.49	12.4	0.045	1.1	10.9	SST	CG	N	
0.300	7.62	70973	1.00	25.4	.206	5.2	50	8.8	.35	9.0	18	79	.50	12.7	0.047	1.2	10.6	MW	CG	N	
0.300	7.62	70973S	1.00	25.4	.206	5.2	43	7.5	.28	7.2	12	53	.50	12.7	0.047	1.2	10.6	SST	CG	N	
0.300	7.62	70994	1.00	25.4	.202	5.1	59	10	.34	8.6	20	89	.53	13.5	0.049	1.2	10.9	MW	CG	N	
0.300	7.62	70994S	1.00	25.4	.202	5.1	50	8.8	.27	6.8	14	60	.53	13.5	0.049	1.2	10.9	SST	CG	N	
0.300	7.62	71015	1.00	25.4	.198	5.0	70	12	.30	7.6	21	94	.56	14.2	0.051	1.3	11.0	MW	CG	N	
0.300	7.62	71015S	1.00	25.4	.198	5.0	60	10	.24	6.1	14	63	.56	14.2	0.051	1.3	11.0	SST	CG	N	
0.300	7.62	70792	1.13	28.7	.256	6.5	2.7	.47	.79	20	2.1	9.5	.17	4.3	0.022	0.6	7.75	MW	CG	N	
0.300	7.62	70792S	1.13	28.7	.256	6.5	2.3	.40	.62	16	1.4	6.3	.17	4.3	0.022	0.6	7.75	SST	CG	N	
0.300	7.62	70814	1.13	28.7	.248	6.3	4.6	.81	.72	18	3.3	15	.23	5.9	0.026	0.7	9.00	MW	CG	N	
0.300	7.62	70814S	1.13	28.7	.248	6.3	3.9	.68	.57	14	2.2	9.8	.23	5.9	0.026	0.7	9.00	SST	CG	N	
0.300	7.62	70837	1.13	28.7	.240	6.1	7.6	1.3	.66	17	5.0	22	.29	7.4	0.030	0.8	9.75	MW	CG	N	
0.300	7.62	70837S	1.13	28.7	.240	6.1	6.5	1.1	.52	13	3.4	15	.29	7.4	0.030	0.8	9.75	SST	CG	N	
0.300	7.62	70859	1.13	28.7	.236	6.0	9.5	1.7	.64	16	6.1	27	.33	8.3	0.032	0.8	10.3	MW	CG	N	
0.300	7.62	70859S	1.13	28.7	.236	6.0	8.1	1.4	.50	13	4.1	18	.33	8.3	0.032	0.8	10.3	SST	CG	N	
0.300	7.62	70879	1.13	28.7	.230	5.8	13	2.4	.56	14	7.5	34	.37	9.4	0.035	0.9	10.6	MW	CG	N	
0.300	7.62	70879S	1.13	28.7	.230	5.8	11	2.0	.45	11	5.1	23	.37	9.4	0.035	0.9	10.6	SST	CG	N	
0.300	7.62	70898	1.13	28.7	.224	5.7	19	3.3	.51	13	9.6	43	.41	10.5	0.038	1.0	10.9	MW	CG	N	
0.300	7.62	70898S	1.13	28.7	.224	5.7	16	2.8	.41	10	6.5	29	.41	10.5	0.038	1.0	10.9	SST	CG	N	
0.300	7.62	70917	1.13	28.7	.220	5.6	22	3.9	.50	13	11	50	.46	11.6	0.040	1.0	11.4	MW	CG	N	
0.300	7.62	70917S	1.13	28.7	.220	5.6	19	3.3	.40	10	7.5	33	.46	11.6	0.040	1.0	11.4	SST	CG	N	
0.300	7.62	70936	1.13	28.7	.216	5.5	28	4.8	.47	12	13	57	.48	12.3	0.042	1.1	11.5	MW	CG	N	
0.300	7.62	70936S	1.13	28.7	.216	5.5	23	4.1	.37	9.4	8.7	39	.48	12.3	0.042	1.1	11.5	SST	CG	N	
0.300	7.62	70955	1.13	28.7	.210	5.3	36	6.3	.43	11	16	70	.53	13.6	0.045	1.1	11.9	MW	CG	N	
0.300	7.62	70955S	1.13	28.7	.210	5.3	31	5.4	.35	8.8	11	47	.53	13.6	0.045	1.1	11.9	SST	CG	N	
0.300	7.62	70974	1.13	28.7	.206	5.2	44	7.7	.40	10	18	79	.55	14.0	0.047	1.2	11.8	MW	CG	N	
0.300	7.62	70974S	1.13	28.7	.206	5.2	38	6.6	.32	8.1	12	53	.55	14.0	0.047	1.2	11.8	SST	CG	N	
0.300	7.62	70995	1.13	28.7	.202	5.1	52	9.2	.38	9.7	20	89	.59	14.9	0.049	1.2	12.0	MW	CG	N	
0.300	7.62	70995S	1.13	28.7	.202	5.1	44	7.8	.30	7.7	14	60	.59	14.9	0.049	1.2	12.0	SST	CG	N	
0.300	7.62	71016	1.13	28.7	.198	5.0	62	11	.34	8.7	21	94	.62	15.9	0.051	1.3	12.3	MW	CG	N	
0.300	7.62	71016S	1.13	28.7	.198	5.0	52	9.2	.27	6.9	14	63	.62	15.9	0.051	1.3	12.3	SST	CG	N	
0.300	7.62	70793	1.25	31.8	.256	6.5	2.4	.42	.89	23	2.1	9.5	.19	4.7	0.022	0.6	8.50	MW	CG	N	
0.300	7.62	70793S	1.25	31.8	.256	6.5	2.0	.36	.70	18	1.4	6.3	.19	4.7	0.022	0.6	8.50	SST	CG	N	
0.300	7.62	70815	1.25	31.8	.248	6.3	4.3	.75	.77	19	3.3	15	.24	6.2	0.026	0.7	9.38	MW	CG	N	
0.300	7.62	70815S	1.25	31.8	.248	6.3	3.7	.64	.60	15	2.2	9.8	.24	6.2	0.026	0.7	9.38	SST	CG	N	
0.300	7.62	70838	1.25	31.8	.240	6.1	6.6	1.2	.76	19	5.0	22	.33	8.4	0.030	0.8	11.0	MW	CG	N	
0.300	7.62	70838S	1.25	31.8	.240	6.1	5.6	.98	.60	15	3.4	15	.33	8.4	0.030	0.8	11.0	SST	CG	N	
0.300	7.62	70860	1.25	31.8	.236	6.0	8.6	1.5	.71	18	6.1	27	.36	9.0	0.032	0.8	11.1	MW	CG	N	
0.300	7.62	70860S	1.25	31.8	.236	6.0	7.3	1.3	.56	14	4.1	18	.36	9.0	0.032	0.8	11.1	SST	CG	N	
0.300	7.62	70880	1.25	31.8	.230	5.8	12	2.1	.63	16	7.5	34	.41	10.4	0.035	0.9	11.8	MW	CG	N	
0.300	7.62	70880S	1.25	31.8	.230	5.8	10	1.8	.50	13	5.1	23	.41	10.4	0.035	0.9	11.8	SST	CG	N	
0.300	7.62	70899	1.25	31.8	.224	5.7	16	2.9	.59	15	9.6	43	.47	11.8	0.038	1.0	12.3	MW	CG	N	
0.300	7.62	70899S	1.25	31.8	.224	5.7	14	2.4	.47	12	6.5	29	.47	11.8	0.038	1.0	12.3	SST	CG	N	
0.300	7.62	70918	1.25	31.8	.220	5.6	20	3.4	.57	14	11	50	.51	12.8	0.040	1.0	12.6	MW	CG	N	
0.300	7.62	70918S	1.25	31.8	.220	5.6	17	2.9	.45	11	7.5	33	.51	12.8	0.040	1.0	12.6	SST	CG	N	
0.300	7.62	70937	1.25	31.8	.216	5.5	24	4.2	.53	14	13	57	.54	13.7	0.042	1.1	12.9	MW	CG	N	
0.300	7.62	70937S	1.25	31.8	.216	5.5	20	3.6	.42	11	8.7	39	.54	13.7	0.042	1.1	12.9	SST</			

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	E N D S	F I N I S H
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.300	7.62	70938S	1.38	35.1	.216	5.5	19	3.3	.47	12	8.7	39	.58	14.8	0.042	1.1	13.9	SST	CG	N
0.300	7.62	70957	1.38	35.1	.210	5.3	29	5.1	.54	14	16	70	.64	16.3	0.045	1.1	14.3	MW	CG	N
0.300	7.62	70957S	1.38	35.1	.210	5.3	25	4.3	.43	11	11	47	.64	16.3	0.045	1.1	14.3	SST	CG	N
0.300	7.62	70976	1.38	35.1	.206	5.2	35	6.2	.50	13	18	79	.67	17.0	0.047	1.2	14.3	MW	CG	N
0.300	7.62	70976S	1.38	35.1	.206	5.2	30	5.3	.40	10	12	53	.67	17.0	0.047	1.2	14.3	SST	CG	N
0.300	7.62	70997	1.38	35.1	.202	5.1	42	7.3	.48	12	20	89	.72	18.2	0.049	1.2	14.6	MW	CG	N
0.300	7.62	70997S	1.38	35.1	.202	5.1	35	6.2	.38	9.7	14	60	.72	18.2	0.049	1.2	14.6	SST	CG	N
0.300	7.62	71018	1.38	35.1	.198	5.0	49	8.6	.43	11	21	94	.75	19.1	0.051	1.3	14.8	MW	CG	N
0.300	7.62	71018S	1.38	35.1	.198	5.0	42	7.3	.34	8.6	14	63	.75	19.1	0.051	1.3	14.8	SST	CG	N
0.300	7.62	70796	1.50	38.1	.256	6.5	2.1	.36	1.0	26	2.1	9.5	.21	5.4	0.022	0.6	9.63	MW	CG	N
0.300	7.62	70796S	1.50	38.1	.256	6.5	1.7	.31	.81	21	1.4	6.3	.21	5.4	0.022	0.6	9.63	SST	CG	N
0.300	7.62	70818	1.50	38.1	.248	6.3	3.5	.61	.94	24	3.3	15	.29	7.3	0.026	0.7	11.1	MW	CG	N
0.300	7.62	70818S	1.50	38.1	.248	6.3	3.0	.52	.74	19	2.2	9.8	.29	7.3	0.026	0.7	11.1	SST	CG	N
0.300	7.62	70841	1.50	38.1	.240	6.1	5.5	.95	.92	23	5.0	22	.39	9.8	0.030	0.8	12.9	MW	CG	N
0.300	7.62	70841S	1.50	38.1	.240	6.1	4.6	.81	.73	18	3.4	15	.39	9.8	0.030	0.8	12.9	SST	CG	N
0.300	7.62	70863	1.50	38.1	.236	6.0	7.1	1.2	.86	22	6.1	27	.42	10.7	0.032	0.8	13.1	MW	CG	N
0.300	7.62	70863S	1.50	38.1	.236	6.0	6.0	1.0	.68	17	4.1	18	.42	10.7	0.032	0.8	13.1	SST	CG	N
0.300	7.62	70882	1.50	38.1	.230	5.8	9.9	1.7	.76	19	7.5	34	.48	12.2	0.035	0.9	13.8	MW	CG	N
0.300	7.62	70882S	1.50	38.1	.230	5.8	8.4	1.5	.61	15	5.1	23	.48	12.2	0.035	0.9	13.8	SST	CG	N
0.300	7.62	70901	1.50	38.1	.224	5.7	14	2.4	.70	18	9.6	43	.54	13.6	0.038	1.0	14.1	MW	CG	N
0.300	7.62	70901S	1.50	38.1	.224	5.7	12	2.0	.56	14	6.5	29	.54	13.6	0.038	1.0	14.1	SST	CG	N
0.300	7.62	70920	1.50	38.1	.220	5.6	16	2.8	.70	18	11	50	.61	15.4	0.040	1.0	15.1	MW	CG	N
0.300	7.62	70920S	1.50	38.1	.220	5.6	14	2.4	.55	14	7.5	33	.61	15.4	0.040	1.0	15.1	SST	CG	N
0.300	7.62	70939	1.50	38.1	.216	5.5	20	3.5	.65	16	13	57	.64	16.1	0.042	1.1	15.1	MW	CG	N
0.300	7.62	70939S	1.50	38.1	.216	5.5	17	3.0	.51	13	8.7	39	.64	16.1	0.042	1.1	15.1	SST	CG	N
0.300	7.62	70958	1.50	38.1	.210	5.3	26	4.6	.60	15	16	70	.70	17.7	0.045	1.1	15.5	MW	CG	N
0.300	7.62	70958S	1.50	38.1	.210	5.3	22	3.9	.48	12	11	47	.70	17.7	0.045	1.1	15.5	SST	CG	N
0.300	7.62	12758	1.50	38.1	.206	5.2	27	4.8	.44	11	12	53	.74	18.8	0.047	1.2	15.8	SST	CG	N
0.300	7.62	70977	1.50	38.1	.206	5.2	32	5.7	.55	14	18	79	.72	18.4	0.047	1.2	15.4	MW	CG	N
0.300	7.62	70977S	1.50	38.1	.206	5.2	27	4.8	.44	11	12	53	.72	18.4	0.047	1.2	15.4	SST	CG	N
0.300	7.62	70998	1.50	38.1	.202	5.1	38	6.7	.53	13	20	89	.77	19.6	0.049	1.2	15.8	MW	CG	N
0.300	7.62	70998S	1.50	38.1	.202	5.1	32	5.7	.42	11	14	60	.77	19.6	0.049	1.2	15.8	SST	CG	N
0.300	7.62	71019	1.50	38.1	.198	5.0	45	7.9	.47	12	21	94	.82	20.7	0.051	1.3	16.0	MW	CG	N
0.300	7.62	71019S	1.50	38.1	.198	5.0	38	6.7	.37	9.5	14	63	.82	20.7	0.051	1.3	16.0	SST	CG	N
0.300	7.62	70797	1.75	44.5	.256	6.5	1.7	.30	1.2	31	2.1	9.5	.24	6.2	0.022	0.6	11.1	MW	CG	N
0.300	7.62	70797S	1.75	44.5	.256	6.5	1.5	.26	.97	25	1.4	6.3	.24	6.2	0.022	0.6	11.1	SST	CG	N
0.300	7.62	70819	1.75	44.5	.248	6.3	3.0	.53	1.1	28	3.3	15	.33	8.3	0.026	0.7	12.6	MW	CG	N
0.300	7.62	70819S	1.75	44.5	.248	6.3	2.6	.45	.87	22	2.2	9.8	.33	8.3	0.026	0.7	12.6	SST	CG	N
0.300	7.62	70842	1.75	44.5	.240	6.1	4.7	.81	1.1	27	5.0	22	.44	11.2	0.030	0.8	14.8	MW	CG	N
0.300	7.62	70842S	1.75	44.5	.240	6.1	4.0	.69	.85	22	3.4	15	.44	11.2	0.030	0.8	14.8	SST	CG	N
0.300	7.62	70864	1.75	44.5	.236	6.0	6.0	1.1	1.0	26	6.1	27	.48	12.2	0.032	0.8	15.0	MW	CG	N
0.300	7.62	70864S	1.75	44.5	.236	6.0	5.1	.89	.80	20	4.1	18	.48	12.2	0.032	0.8	15.0	SST	CG	N
0.300	7.62	70883	1.75	44.5	.230	5.8	8.4	1.5	.90	23	7.5	34	.55	14.0	0.035	0.9	15.8	MW	CG	N
0.300	7.62	70883S	1.75	44.5	.230	5.8	7.1	1.3	.71	18	5.1	23	.55	14.0	0.035	0.9	15.8	SST	CG	N
0.300	7.62	70902	1.75	44.5	.224	5.7	11	2.0	.85	22	9.6	43	.64	16.3	0.038	1.0	16.9	MW	CG	N
0.300	7.62	70902S	1.75	44.5	.224	5.7	9.5	1.7	.68	17	6.5	29	.64	16.3	0.038	1.0	16.9	SST	CG	N
0.300	7.62	70921	1.75	44.5	.220	5.6	14	2.4	.81	20	11	50	.69	17.4	0.040	1.0	17.1	MW	CG	N
0.300	7.62	70921S	1.75	44.5	.220	5.6	12	2.1	.64	16	7.5	33	.69	17.4	0.040	1.0	17.1	SST	CG	N
0.300	7.62	70940	1.75	44.5	.216	5.5	16	2.9	.78	20	13	57	.75	19.1	0.042	1.1	17.9	MW	CG	N
0.300	7.62	70940S	1.75	44.5	.216	5.5	14	2.4	.62	16	8.7	39	.75	19.1	0.042	1.1	17.9	SST	CG	N
0.300	7.62	70959	1.75	44.5	.210	5.3	22	3.8	.72	18	16	70	.83	21.0	0.045	1.1	18.4	MW	CG	N
0.300	7.62	70959S	1.75	44.5	.210	5.3	18	3.2	.57	15	11	47	.83	21.0	0.045	1.1	18.4	SST	CG	N
0.300	7.62	70978	1.75	44.5	.206	5.2	28	4.8	.65	16	18	79	.83	21.2	0.047	1.2	17.8	MW	CG	N
0.300	7.62	70978S	1.75	44.5	.206	5.2	23	4.1	.51	13	12	53	.83	21.2	0.047	1.2	17.8	SST	CG	N
0.300	7.62	70999	1.75	44.5	.202	5.1	32	5.7	.62	16	20	89	.89	22.6	0.049	1.2	18.1	MW	CG	N
0.300	7.62	70999S	1.75	44.5	.202	5.1	28	4.8	.49	13	14	60	.89	22.6	0.049	1.2	18.1	SST	CG	N
0.300	7.62	71020	1.75	44.5</																




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.300	7.62	71021	2.00	50.8	.198	5.0	33	5.8	.64	16	21	94	1.07	27.2	0.051	1.3	21.0	MW	CG	N
0.300	7.62	71021S	2.00	50.8	.198	5.0	28	4.9	.51	13	14	63	1.07	27.2	0.051	1.3	21.0	SST	CG	N
0.300	7.62	70799	2.25	57.2	.256	6.5	1.3	.23	.16	41	2.1	9.5	.31	7.8	0.022	0.6	14.0	MW	CG	N
0.300	7.62	70799S	2.25	57.2	.256	6.5	1.1	.19	1.3	32	1.4	6.3	.31	7.8	0.022	0.6	14.0	SST	CG	N
0.300	7.62	70821	2.25	57.2	.248	6.3	2.4	.42	1.4	35	3.3	15	.40	10.1	0.026	0.7	15.3	MW	CG	N
0.300	7.62	70821S	2.25	57.2	.248	6.3	2.0	.36	1.1	27	2.2	9.8	.40	10.1	0.026	0.7	15.3	SST	CG	N
0.300	7.62	70844	2.25	57.2	.240	6.1	3.6	.63	1.4	36	5.0	22	.56	14.2	0.030	0.8	18.6	MW	CG	N
0.300	7.62	70844S	2.25	57.2	.240	6.1	3.0	.53	1.1	28	3.4	15	.56	14.2	0.030	0.8	18.6	SST	CG	N
0.300	7.62	70866	2.25	57.2	.236	6.0	4.8	.84	1.3	32	6.1	27	.59	14.9	0.032	0.8	18.4	MW	CG	N
0.300	7.62	70866S	2.25	57.2	.236	6.0	4.1	.71	1.0	25	4.1	18	.59	14.9	0.032	0.8	18.4	SST	CG	N
0.300	7.62	70885	2.25	57.2	.230	5.8	6.5	1.1	1.2	30	7.5	34	.70	17.8	0.035	0.9	20.0	MW	CG	N
0.300	7.62	70885S	2.25	57.2	.230	5.8	5.5	.96	.93	24	5.1	23	.70	17.8	0.035	0.9	20.0	SST	CG	N
0.300	7.62	70904	2.25	57.2	.224	5.7	8.8	1.5	1.1	28	9.6	43	.80	20.3	0.038	1.0	21.0	MW	CG	N
0.300	7.62	70904S	2.25	57.2	.224	5.7	7.5	1.3	.87	22	6.5	29	.80	20.3	0.038	1.0	21.0	SST	CG	N
0.300	7.62	70923	2.25	57.2	.220	5.6	11	1.8	1.1	27	11	50	.88	22.2	0.040	1.0	21.9	MW	CG	N
0.300	7.62	70923S	2.25	57.2	.220	5.6	9.0	1.6	.84	21	7.5	33	.88	22.2	0.040	1.0	21.9	SST	CG	N
0.300	7.62	70942	2.25	57.2	.216	5.5	13	2.2	1.0	25	13	57	.94	23.9	0.042	1.1	22.4	MW	CG	N
0.300	7.62	70942S	2.25	57.2	.216	5.5	11	1.9	.80	20	8.7	39	.94	23.9	0.042	1.1	22.4	SST	CG	N
0.300	7.62	70961	2.25	57.2	.210	5.3	17	2.9	.93	24	16	70	1.04	26.4	0.045	1.1	23.1	MW	CG	N
0.300	7.62	70961S	2.25	57.2	.210	5.3	14	2.5	.74	19	11	47	1.04	26.4	0.045	1.1	23.1	SST	CG	N
0.300	7.62	70980	2.25	57.2	.206	5.2	21	3.7	.84	21	18	79	1.06	26.9	0.047	1.2	22.5	MW	CG	N
0.300	7.62	70980S	2.25	57.2	.206	5.2	18	3.1	.67	17	12	53	1.06	26.9	0.047	1.2	22.5	SST	CG	N
0.300	7.62	71001	2.25	57.2	.202	5.1	25	4.3	.81	21	20	89	1.13	28.8	0.049	1.2	23.1	MW	CG	N
0.300	7.62	71001S	2.25	57.2	.202	5.1	21	3.7	.64	16	14	60	1.13	28.8	0.049	1.2	23.1	SST	CG	N
0.300	7.62	71022	2.25	57.2	.198	5.0	29	5.1	.72	18	21	94	1.20	30.4	0.051	1.3	23.5	MW	CG	N
0.300	7.62	71022S	2.25	57.2	.198	5.0	25	4.4	.57	15	14	63	1.20	30.4	0.051	1.3	23.5	SST	CG	N
0.300	7.62	70800	2.50	63.5	.256	6.5	1.2	.21	1.8	46	2.1	9.5	.34	8.5	0.022	0.6	15.3	MW	CG	N
0.300	7.62	70800S	2.50	63.5	.256	6.5	1.0	.18	1.4	36	1.4	6.3	.34	8.5	0.022	0.6	15.3	SST	CG	N
0.300	7.62	70822	2.50	63.5	.248	6.3	2.1	.37	1.5	39	3.3	15	.44	11.1	0.026	0.7	16.9	MW	CG	N
0.300	7.62	70822S	2.50	63.5	.248	6.3	1.8	.32	1.2	31	2.2	9.8	.44	11.1	0.026	0.7	16.9	SST	CG	N
0.300	7.62	70845	2.50	63.5	.240	6.1	3.2	.57	1.6	39	5.0	22	.61	15.4	0.030	0.8	20.3	MW	CG	N
0.300	7.62	70845S	2.50	63.5	.240	6.1	2.8	.48	1.2	31	3.4	15	.61	15.4	0.030	0.8	20.3	SST	CG	N
0.300	7.62	70867	2.50	63.5	.236	6.0	4.3	.74	1.4	36	6.1	27	.65	16.6	0.032	0.8	20.4	MW	CG	N
0.300	7.62	70867S	2.50	63.5	.236	6.0	3.6	.63	1.1	29	4.1	18	.65	16.6	0.032	0.8	20.4	SST	CG	N
0.300	7.62	70886	2.50	63.5	.230	5.8	5.9	1.0	1.3	33	7.5	34	.77	19.4	0.035	0.9	21.9	MW	CG	N
0.300	7.62	70886S	2.50	63.5	.230	5.8	5.0	.87	1.0	26	5.1	23	.77	19.4	0.035	0.9	21.9	SST	CG	N
0.300	7.62	70905	2.50	63.5	.224	5.7	8.0	1.4	1.2	31	9.6	43	.87	22.2	0.038	1.0	23.0	MW	CG	N
0.300	7.62	70905S	2.50	63.5	.224	5.7	6.8	1.2	.96	24	6.5	29	.87	22.2	0.038	1.0	23.0	SST	CG	N
0.300	7.62	70924	2.50	63.5	.220	5.6	9.5	1.7	1.2	30	11	50	.96	24.4	0.040	1.0	24.0	MW	CG	N
0.300	7.62	70924S	2.50	63.5	.220	5.6	8.1	1.4	.93	24	7.5	33	.96	24.4	0.040	1.0	24.0	SST	CG	N
0.300	7.62	70943	2.50	63.5	.216	5.5	12	2.0	1.1	28	13	57	1.02	25.9	0.042	1.1	24.3	MW	CG	N
0.300	7.62	70943S	2.50	63.5	.216	5.5	9.9	1.7	.87	22	8.7	39	1.02	25.9	0.042	1.1	24.3	SST	CG	N
0.300	7.62	70962	2.50	63.5	.210	5.3	15	2.7	1.0	26	16	70	1.13	28.6	0.045	1.1	25.0	MW	CG	N
0.300	7.62	70962S	2.50	63.5	.210	5.3	13	2.3	.81	21	11	47	1.13	28.6	0.045	1.1	25.0	SST	CG	N
0.300	7.62	70981	2.50	63.5	.206	5.2	19	3.3	.94	24	18	79	1.17	29.7	0.047	1.2	24.9	MW	CG	N
0.300	7.62	70981S	2.50	63.5	.206	5.2	16	2.8	.75	19	12	53	1.17	29.7	0.047	1.2	24.9	SST	CG	N
0.300	7.62	71002	2.50	63.5	.202	5.1	22	3.9	.90	23	20	89	1.25	31.7	0.049	1.2	25.5	MW	CG	N
0.300	7.62	71002S	2.50	63.5	.202	5.1	19	3.3	.72	18	14	60	1.25	31.7	0.049	1.2	25.5	SST	CG	N
0.300	7.62	71023	2.50	63.5	.198	5.0	26	4.6	.80	20	21	94	1.33	33.7	0.051	1.3	26.0	MW	CG	N
0.300	7.62	71023S	2.50	63.5	.198	5.0	22	3.9	.64	16	14	63	1.33	33.7	0.051	1.3	26.0	SST	CG	N
0.300	7.62	70982	2.75	69.9	.206	5.2	17	3.0	1.0	26	18	79	1.29	32.7	0.047	1.2	27.4	MW	CG	N
0.300	7.62	70982S	2.75	69.9	.206	5.2	15	2.5	.83	21	12	53	1.29	32.7	0.047	1.2	27.4	SST	CG	N
0.300	7.62	71003	2.75	69.9	.202	5.1	20	3.5	.99	25	20	89	1.37	34.8	0.049	1.2	28.0	MW	CG	N
0.300	7.62	71003S	2.75	69.9	.202	5.1	17	3.0	.79	20	14	60	1.37	34.8	0.049	1.2	28.0	SST	CG	N
0.300	7.62	71024	2.75	69.9	.198	5.0	24	4.2	.88	22	21	94	1.45	36.9	0.051	1.3	28.5	MW	CG	N
0.300	7.62	71024S	2.75	69.9	.198	5.0	20	3.5	.71	18	14	63	1.45	36.9	0.051	1.3	28.5	SST	CG	N
0.300	7.62	12640	2.88	73.0	.260	6.6	.33	.06	2.3	57	.73	3.3	.62	15.7	0.020	0.5	30.0	SST	C	N
0.300	7.62	70983	3.00	76.2	.206	5.2	16	2.7	1.1	29	18	79	1.39	35.4	0.047	1.2	29.6	MW	CG	N
0.300	7.62	70983S	3.00	76.2	.206	5.2	13	2.3	.90	23	12	53	1.39	35.4	0.047	1.2	29.6	SST	CG	N
0.300	7.62	71004	3.00	76.2	.202	5.1	18	3.2	1.1	28	20	89	1.49	38.0	0.049	1.2	30.5	MW	CG	N
0.300	7.62	71004S	3.00	76.2	.202	5.1	16	2.7	.87	22	14	60	1.49	38.0	0.049	1.2	30.5	SST	CG	N
0.300	7.62	71025	3.00	76.2	.198	5.0	22	3.8	.97	25	21	94	1.58	40.2	0.051	1.3	31.0	MW	CG	N
0.300	7.62	71025S	3.00	76.2	.198	5.0	18	3.2	.77	20	14	63	1.58	40.2	0.051	1.3	31.0	SST	CG	N
0.304	7.72	A9-39	.78	19.8	.190	4.8	93	16	.22	5.6	21	92	.46	11.8	0.057	1.4	8.00	PB	CG	N
0.312	7.92	II-25	.19	4.8	.252	6.4	45	7.9	.07	1.7	3.1	14	.12	3.0	0.030	0.8	3.00	SST	C	N
0.312	7.92	KK-86	.22	5.6	.260	6.6	17	2.9	.10	2.6	1.7	7.5	.12	3.0	0.026	0.7	3.50	SST	C	N
0.312	7.92	NN-86	.25	6.4	.258	6.6	17	2.9	.12	2.9	1.9	8.4	.14	3.4	0.027	0.7	4.00	MW	C	N
0.312	7.92	A15-5	.25	6.4	.252	6.4	16	2.7	.10	2.5	1.6	7.0	.15	3.8	0.030	0.8	5.00	SST	CG	N
0.312	7.92	EE-4	.25	6.4	.232	5.9	80	14	.09	2.3	7.2</									

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	END S	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.312	7.92	11356	.38	9.5	.266	6.8	3.3	.58	.23	5.7	.74	3.3	.15	3.8	0.023	0.6	6.50	SST	CG	N
0.312	7.92	OO-35	.38	9.5	.264	6.7	5.8	1.0	.23	5.9	1.3	5.9	.14	3.7	0.024	0.6	5.00	SST	C	N
0.312	7.92	O-87	.38	9.5	.256	6.5	13	2.3	.24	6.0	3.0	13	.14	3.6	0.028	0.7	5.00	MW	CG	N
0.312	7.92	Z-78	.38	9.5	.242	6.1	51	8.9	.10	2.6	5.2	23	.14	3.6	0.035	0.9	4.00	SPR	CG	N
0.312	7.92	2915	.38	9.5	.228	5.8	76	13	.12	3.0	8.9	40	.25	6.4	0.042	1.1	5.00	SPR	C	Z
0.312	7.92	EE-9	.38	9.5	.226	5.7	101	18	.09	2.4	9.6	43	.19	4.9	0.043	1.1	4.50	SPR	CG	Z
0.312	7.92	S-1086	.38	9.5	.218	5.5	131	23	.09	2.2	12	52	.21	5.4	0.047	1.2	4.50	SST	CG	N
0.312	7.92	K-93	.38	9.5	.218	5.5	94	17	.09	2.4	8.8	39	.28	7.2	0.047	1.2	6.00	SPR	CG	Z
0.312	7.92	S-1125	.38	9.5	.214	5.4	158	28	.08	2.1	13	58	.22	5.6	0.049	1.2	4.50	SST	CG	N
0.312	7.92	3688	.41	10.3	.272	6.9	2.3	.40	.27	6.8	.61	2.7	.14	3.6	0.020	0.5	6.00	MW	C	Z
0.312	7.92	JJ-22	.41	10.3	.244	6.2	26	4.6	.18	4.5	4.7	21	.20	5.2	0.034	0.9	5.00	SST	C	N
0.312	7.92	FF-3	.44	11.1	.280	7.1	.91	.16	.33	8.3	.30	1.3	.11	2.8	0.016	0.4	6.00	MW	C	N
0.312	7.92	KK-92	.44	11.1	.252	6.4	11	2.0	.23	5.8	2.6	11	.21	5.3	0.030	0.8	6.00	SST	C	N
0.312	7.92	A11-23	.44	11.1	.246	6.2	26	4.6	.18	4.5	4.6	21	.17	4.3	0.033	0.8	5.00	SPR	CG	GI
0.312	7.92	A14-25	.44	11.1	.236	6.0	15	2.7	.32	8.1	4.9	22	.12	3.0	0.038	1.0	5.25	SST	CG	N
0.312	7.92	LL-16	.44	11.1	.232	5.9	41	7.1	.18	4.6	7.3	32	.24	6.1	0.040	1.0	6.00	SST	CG	N
0.312	7.92	S-484	.44	11.1	.230	5.8	43	7.5	.18	4.6	7.8	35	.25	6.4	0.041	1.0	6.13	SST	CG	N
0.312	7.92	B9-30	.44	11.1	.230	5.8	82	14	.10	2.6	8.3	37	.18	4.7	0.041	1.0	4.50	SPR	CG	N
0.312	7.92	H-96	.44	11.1	.212	5.4	167	29	.08	2.1	14	62	.25	6.4	0.050	1.3	5.00	SPR	CG	Z
0.312	7.92	II-23	.44	11.1	.212	5.4	136	24	.10	2.4	13	58	.26	6.7	0.050	1.3	5.25	SST	CG	N
0.312	7.92	2920	.44	11.1	.180	4.6	697	122	.04	1.1	30	136	.31	7.8	0.066	1.7	4.63	SPR	CG	Z
0.312	7.92	NN-6	.47	11.9	.272	6.9	2.0	.36	.33	8.3	.67	3.0	.14	3.6	0.020	0.5	6.00	SST	C	N
0.312	7.92	J-27	.47	11.9	.252	6.4	11	2.0	.26	6.6	2.9	13	.21	5.3	0.030	0.8	6.00	SST	C	N
0.312	7.92	A10-36	.47	11.9	.250	6.4	18	3.1	.20	5.1	3.6	16	.16	3.9	0.031	0.8	5.00	SST	CG	N
0.312	7.92	DD-85	.47	11.9	.242	6.1	29	5.2	.17	4.2	4.9	22	.21	5.3	0.035	0.9	5.00	SST	C	N
0.312	7.92	J-52	.47	11.9	.238	6.0	43	7.6	.14	3.6	6.2	27	.22	5.6	0.037	0.9	5.00	SPR	C	N
0.312	7.92	10487	.50	12.7	.284	7.2	1.0	.18	.43	11	.45	2.0	.07	1.8	0.014	0.4	4.00	MW	C	N
0.312	7.92	4231	.50	12.7	.282	7.2	.51	.09	.37	9.5	.19	.84	.13	3.2	0.015	0.4	7.50	MW	C	N
0.312	7.92	4199	.50	12.7	.276	7.0	1.2	.21	.36	9.0	.42	1.9	.14	3.7	0.018	0.5	7.00	MW	C	Z
0.312	7.92	H-69	.50	12.7	.272	6.9	1.4	.24	.32	8.1	.44	1.9	.18	4.6	0.020	0.5	8.00	SST	C	N
0.312	7.92	B14-5	.50	12.7	.270	6.9	2.3	.40	.35	9.0	.80	3.6	.15	3.7	0.021	0.5	7.00	MW	CG	N
0.312	7.92	S-727	.50	12.7	.268	6.8	4.8	.84	.28	7.2	1.4	6.1	.12	3.1	0.022	0.6	4.50	SST	C	N
0.312	7.92	B2-28	.50	12.7	.266	6.8	7.4	1.3	.32	8.0	2.3	10	.12	3.1	0.023	0.6	4.25	MW	C	N
0.312	7.92	PP-31	.50	12.7	.256	6.5	13	2.3	.31	7.8	4.0	18	.14	3.6	0.028	0.7	5.00	MW	CG	N
0.312	7.92	10229	.50	12.7	.248	6.3	17	3.0	.25	6.2	4.2	19	.22	5.7	0.032	0.8	6.00	SPR	C	Z
0.312	7.92	931	.50	12.7	.238	6.0	37	6.5	.23	5.9	8.5	38	.20	5.2	0.037	0.9	5.50	MW	CG	Z
0.312	7.92	L-8	.50	12.7	.236	6.0	42	7.4	.15	3.8	6.3	28	.23	5.8	0.038	1.0	5.00	SST	C	N
0.312	7.92	10856	.50	12.7	.230	5.8	51	8.9	.16	4.1	8.3	37	.25	6.2	0.041	1.0	6.00	SPR	CG	N
0.312	7.92	DD-34	.50	12.7	.192	4.9	291	51	.08	2.0	23	104	.36	9.1	0.060	1.5	6.00	SPR	CG	N
0.312	7.92	S-1265	.53	13.5	.238	6.0	28	4.9	.21	5.2	5.8	26	.26	6.6	0.037	0.9	6.00	SST	C	N
0.312	7.92	HH-29	.53	13.5	.232	5.9	36	6.3	.20	5.1	7.3	32	.26	6.6	0.040	1.0	6.50	SST	CG	N
0.312	7.92	CC-11	.53	13.5	.232	5.9	52	9.1	.15	3.8	7.8	35	.26	6.6	0.040	1.0	5.50	SPR	C	N
0.312	7.92	MM-65	.53	13.5	.212	5.4	148	26	.09	2.2	13	58	.25	6.4	0.050	1.3	5.00	SST	CG	N
0.312	7.92	S-27	.53	13.5	.210	5.3	121	21	.11	2.9	14	61	.31	7.8	0.051	1.3	6.00	SST	CG	N
0.312	7.92	S-1016	.56	14.3	.282	7.2	.44	.08	.43	11	.19	.85	.13	3.2	0.015	0.4	7.50	SST	C	N
0.312	7.92	A-24	.56	14.3	.278	7.1	.49	.09	.37	9.3	.18	.80	.20	5.0	0.017	0.4	10.5	SST	C	N
0.312	7.92	2850	.56	14.3	.272	6.9	4.6	.81	.34	8.5	1.5	6.9	.10	2.5	0.020	0.5	4.00	MW	C	Z
0.312	7.92	YY-41	.56	14.3	.272	6.9	.73	.13	.28	7.2	.21	.92	.28	7.1	0.020	0.5	13.0	SST	C	N
0.312	7.92	10931	.56	14.3	.268	6.8	3.9	.69	.42	11	1.7	7.4	.14	3.6	0.022	0.6	5.50	MW	C	Z
0.312	7.92	3853	.56	14.3	.264	6.7	6.7	1.2	.40	10	2.7	12	.14	3.7	0.024	0.6	5.00	MW	C	Z
0.312	7.92	K-76	.56	14.3	.262	6.7	5.9	1.0	.39	9.8	2.3	10	.18	4.4	0.025	0.6	6.00	MW	C	Z
0.312	7.92	B7-13	.56	14.3	.262	6.7	9.5	1.7	.30	7.6	2.8	13	.11	2.9	0.025	0.6	4.50	MW	CG	N
0.312	7.92	MM-15	.56	14.3	.252	6.4	12	2.0	.37	9.3	4.2	19	.20	5.0	0.030	0.8	6.50	MW	CG	N
0.312	7.92	H-66	.56	14.3	.204	5.2	237	42	.07	1.8	17	77	.27	6.9	0.054	1.4	5.00	SPR	CG	N
0.312	7.92	LL-73	.56	14.3	.192	4.9	258	45	.08	2.2	22	98	.36	9.1	0.060	1.5	6.00	SST	CG	N
0.312	7.92	10509	.59	15.1	.220	5.6	76	13	.15	3.9	12	52	.35	8.8	0.046	1.2	6.50	SPR	C	Z
0.312	7.92	A11-67	.63	15.9	.266	6.8	4.4	.78	.47	12	2.1	9.3	.16	3.9	0.023	0.6	5.75	MW	C	N
0.312	7.92	S-388	.63	15.9	.262	6.7	5.3	.93	.36	9.0	1.9	8.4	.17	4.4	0.025	0.6	5.88	SST	C	N




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS			E N D S	F N D H
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm					
0.312	7.92	B9-38	.69	17.4	.220	5.6	53	9.2	.22	5.6	12	52	.39	9.9	0.046	1.2	8.50	SPR	CG	Z	
0.312	7.92	L-39	.69	17.4	.216	5.5	64	11	.21	5.2	13	59	.41	10.4	0.048	1.2	8.50	SPR	CG	Z	
0.312	7.92	O-48	.69	17.4	.212	5.4	67	12	.19	4.9	13	58	.43	10.8	0.050	1.3	8.50	SST	CG	N	
0.312	7.92	Z-32	.69	17.4	.188	4.8	197	35	.12	3.1	24	107	.56	14.2	0.062	1.6	8.00	SST	C	N	
0.312	7.92	3516	.69	17.4	.184	4.7	243	43	.11	2.9	28	124	.54	13.8	0.064	1.6	8.50	SPR	CG	Z	
0.312	7.92	10013	.69	17.5	.236	6.0	24	4.3	.27	7.0	6.7	30	.30	7.7	0.038	1.0	8.00	SPR	CG	Z	
0.312	7.92	KK-74	.72	18.2	.240	6.1	15	2.7	.34	8.6	5.2	23	.38	9.6	0.036	0.9	9.50	SPR	C	N	
0.312	7.92	4246	.75	19.1	.282	7.2	.35	.06	.59	15	.20	.90	.17	4.2	0.015	0.4	10.0	MW	C	T	
0.312	7.92	S-1072	.75	19.1	.282	7.2	.24	.04	.56	14	.13	.60	.20	5.0	0.015	0.4	12.0	SST	C	N	
0.312	7.92	S-23	.75	19.1	.278	7.1	.81	.14	.61	16	.50	2.2	.14	3.5	0.017	0.4	7.00	SST	C	N	
0.312	7.92	10422	.75	19.1	.274	7.0	.85	.15	.60	15	.51	2.3	.15	3.7	0.019	0.5	6.75	PB	C	N	
0.312	7.92	FF-25	.75	19.1	.272	6.9	.46	.08	.31	7.9	.14	.64	.44	11.2	0.020	0.5	22.0	MW	CG	N	
0.312	7.92	B12-32	.75	19.1	.272	6.9	1.5	.27	.57	14	.88	3.9	.18	4.6	0.020	0.5	8.00	MW	C	N	
0.312	7.92	S-728	.75	19.1	.268	6.8	3.2	.56	.43	11	1.4	6.1	.15	3.8	0.022	0.6	5.75	SST	C	N	
0.312	7.92	WW-44	.75	19.1	.268	6.8	3.5	.60	.60	15	2.1	9.1	.15	3.9	0.022	0.6	6.00	MW	C	N	
0.312	7.92	2539	.75	19.1	.266	6.8	3.7	.65	.58	15	2.1	9.5	.17	4.4	0.023	0.6	6.50	MW	C	Z	
0.312	7.92	FF-93	.75	19.1	.264	6.7	1.9	.34	.46	12	.89	4.0	.29	7.3	0.024	0.6	11.0	SST	C	N	
0.312	7.92	II-29	.75	19.1	.264	6.7	4.0	.70	.56	14	2.2	9.9	.19	4.9	0.024	0.6	7.00	MW	C	Z	
0.312	7.92	Z-65	.75	19.1	.262	6.7	4.0	.69	.53	13	2.1	9.2	.23	5.7	0.025	0.6	8.00	MW	C	Z	
0.312	7.92	3245	.75	19.1	.258	6.6	6.6	1.2	.53	14	3.5	16	.22	5.5	0.027	0.7	7.00	MW	C	Z	
0.312	7.92	3190	.75	19.1	.248	6.3	9.8	1.7	.46	12	4.5	20	.29	7.3	0.032	0.8	9.00	MW	CG	GI	
0.312	7.92	946	.75	19.1	.248	6.3	13	2.3	.45	11	5.9	26	.26	6.7	0.032	0.8	7.25	MW	C	Z	
0.312	7.92	S-730	.75	19.1	.248	6.3	11	2.0	.35	8.8	3.9	17	.26	6.7	0.032	0.8	7.25	SST	C	N	
0.312	7.92	W-17	.75	19.1	.246	6.2	13	2.3	.35	9.0	4.6	21	.30	7.5	0.033	0.8	8.00	SPR	C	N	
0.312	7.92	2978	.75	19.1	.244	6.2	9.9	1.7	.38	9.6	3.7	17	.37	9.5	0.034	0.9	11.0	SPR	CG	Z	
0.312	7.92	S-146	.75	19.1	.242	6.1	13	2.2	.39	9.9	4.9	22	.35	8.9	0.035	0.9	9.00	SST	C	N	
0.312	7.92	S-934	.75	19.1	.242	6.1	14	2.5	.35	8.8	4.9	22	.29	7.3	0.035	0.9	8.25	SST	CG	N	
0.312	7.92	2585	.75	19.1	.238	6.0	20	3.5	.43	11	8.5	38	.31	8.0	0.037	0.9	8.50	MW	CG	Z	
0.312	7.92	B1-5	.75	19.1	.236	6.0	21	3.6	.30	7.7	6.3	28	.31	8.0	0.038	1.0	8.25	SST	CG	N	
0.312	7.92	B12-1	.75	19.1	.228	5.8	35	6.1	.26	6.5	8.9	40	.36	9.1	0.042	1.1	8.50	SPR	CG	N	
0.312	7.92	O-123	.75	19.1	.220	5.6	57	10	.20	5.2	12	52	.37	9.3	0.046	1.2	8.00	SPR	CG	Z	
0.312	7.92	B17-125	.75	19.1	.216	5.5	69	12	.19	4.8	13	59	.38	9.8	0.048	1.2	8.00	SPR	CG	Z	
0.312	7.92	O-32	.75	19.1	.210	5.3	137	24	.11	2.7	15	65	.31	7.8	0.051	1.3	6.00	SPR	CG	Z	
0.312	7.92	S-204	.78	19.8	.272	6.9	.82	.14	.52	13	.43	1.9	.26	6.6	0.020	0.5	12.0	SST	C	N	
0.312	7.92	FF-45	.78	19.8	.252	6.4	8.7	1.5	.54	14	4.7	21	.24	6.1	0.030	0.8	8.00	MW	CG	Z	
0.312	7.92	NN-30	.78	19.8	.252	6.4	8.7	1.5	.54	14	4.7	21	.24	6.1	0.030	0.8	8.00	MW	CG	N	
0.312	7.92	S-877	.78	19.8	.218	5.5	56	9.8	.21	5.3	12	52	.38	9.6	0.047	1.2	8.00	SST	CG	N	
0.312	7.92	BB-62	.78	19.8	.214	5.4	50	8.7	.26	6.7	13	58	.49	12.4	0.049	1.2	10.0	SST	CG	N	
0.312	7.92	2617	.78	19.8	.188	4.8	175	31	.15	3.7	26	114	.60	15.4	0.062	1.6	9.75	HD	CG	Z	
0.312	7.92	CC-56	.81	20.6	.244	6.2	10	1.8	.45	12	4.7	21	.36	9.1	0.034	0.9	9.50	SST	C	N	
0.312	7.92	3678	.81	20.6	.240	6.1	13	2.2	.42	11	5.3	24	.40	10.1	0.036	0.9	11.0	SPR	CG	Z	
0.312	7.92	VV-35	.81	20.6	.240	6.1	16	2.9	.35	8.8	5.7	25	.32	8.2	0.036	0.9	9.00	SPR	CG	N	
0.312	7.92	LL-52	.81	20.6	.222	5.6	56	9.9	.19	4.9	11	49	.34	8.6	0.045	1.1	7.50	SPR	CG	N	
0.312	7.92	S-476	.84	21.4	.244	6.2	9.7	1.7	.47	12	4.6	20	.37	9.5	0.034	0.9	10.0	SST	C	N	
0.312	7.92	MM-38	.84	21.4	.232	5.9	18	3.2	.36	9.2	6.6	30	.48	12.2	0.040	1.0	12.0	SPR	CG	Z	
0.312	7.92	2614	.84	21.4	.208	5.3	89	16	.24	6.2	22	96	.46	11.6	0.052	1.3	8.75	MW	CG	Z	
0.312	7.92	2949	.88	22.2	.272	6.9	1.8	.32	.72	18	1.3	5.9	.16	4.1	0.020	0.5	7.00	MW	C	Z	
0.312	7.92	J-81	.88	22.2	.272	6.9	.80	.14	.62	16	.49	2.2	.26	6.6	0.020	0.5	12.0	SST	C	N	
0.312	7.92	M-89	.88	22.2	.272	6.9	1.9	.34	.72	18	1.4	6.2	.16	3.9	0.020	0.5	6.75	MW	C	N	
0.312	7.92	Q-43	.88	22.2	.272	6.9	1.3	.23	.70	18	.93	4.1	.18	4.6	0.020	0.5	8.00	SST	C	N	
0.312	7.92	EE-37	.88	22.2	.272	6.9	1.3	.23	.68	17	.89	4.0	.20	5.1	0.020	0.5	9.00	MW	C	N	
0.312	7.92	10544	.88	22.2	.270	6.9	1.4	.25	.64	16	.91	4.1	.23	5.9	0.021	0.5	10.0	MW	C	Z	
0.312	7.92	S-729	.88	22.2	.268	6.8	2.7	.47	.51	13	1.4	6.1	.17	4.2	0.022	0.6	6.50	SST	C	N	
0.312	7.92	II-17	.88	22.2	.252	6.4	8.7	1.5	.56	14	4.8	22	.24	6.1	0.030	0.8	8.00	MW	CG	N	
0.312	7.92	S-731	.88	22.2	.248	6.3	9.6	1.7	.41	10	3.9	17	.30	7.5	0.032	0.8	8.25	SST	C	N	
0.312	7.92	W-71	.88	22.2	.188	4.8	161	28	.15	3.8	24	107	.59	15.0	0.062	1.6	9.50	SST	CG	N	
0.312	7.92	S-244	.91	23.0	.276	7.0	.69	.12	.72	18	.49	2.2	.19	4.8	0.018	0.5	9.50	SST	C	N	
0.312	7.92	3735	.91	23.0	.230	5.8	26	4.5	.33	8.3	8.3	37	.41	10.4	0.041	1.0	10.0	SPR	CG		

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	E N D S	F I N I S H
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.312	7.92	G-10	1.00	25.4	.232	5.9	17	2.9	.47	12	7.8	35	.52	13.2	0.040	1.0	13.0	HD	CG	N
0.312	7.92	S-733	1.00	25.4	.228	5.8	23	4.0	.37	9.4	8.4	37	.49	12.5	0.042	1.1	10.8	SST	C	N
0.312	7.92	3736	1.00	25.4	.226	5.7	22	3.8	.38	9.6	8.3	37	.62	15.8	0.043	1.1	13.5	SPR	C	Z
0.312	7.92	3764	1.00	25.4	.188	4.8	247	43	.10	2.6	26	114	.47	11.8	0.062	1.6	7.50	HD	CG	Z
0.312	7.92	S-1580	1.03	26.2	.252	6.4	2.6	.45	.40	10	1.0	4.6	.63	16.0	0.030	0.8	20.0	SST	C	N
0.312	7.92	S-790	1.03	26.2	.232	5.9	15	2.6	.49	13	7.3	32	.52	13.2	0.040	1.0	13.0	SST	CG	N
0.312	7.92	Z-51	1.03	26.2	.186	4.7	244	43	.11	2.8	27	119	.57	14.4	0.063	1.6	8.00	SPR	C	N
0.312	7.92	GG-12	1.06	27.0	.284	7.2	.35	.06	.94	24	.33	1.4	.13	3.2	0.014	0.4	8.00	MW	C	N
0.312	7.92	S-996	1.06	27.0	.276	7.0	.43	.08	.79	20	.34	1.5	.27	6.9	0.018	0.5	14.0	SST	C	N
0.312	7.92	AA-10	1.06	27.0	.272	6.9	.40	.07	.60	15	.24	1.1	.46	11.7	0.020	0.5	22.0	SST	C	N
0.312	7.92	A9-67	1.06	27.0	.254	6.5	6.4	1.1	.68	17	4.4	20	.29	7.4	0.029	0.7	9.00	MW	C	Z
0.312	7.92	3296	1.06	27.0	.252	6.4	6.9	1.2	.70	18	4.8	22	.32	8.0	0.030	0.8	9.50	MW	C	Z
0.312	7.92	V-62	1.06	27.0	.246	6.2	8.0	1.4	.54	14	4.3	19	.35	8.8	0.033	0.8	10.5	SST	CG	N
0.312	7.92	3092	1.06	27.0	.208	5.3	85	15	.18	4.6	15	69	.47	11.9	0.052	1.3	9.00	SPR	CG	Z
0.312	7.92	W-57	1.06	27.0	.204	5.2	56	9.9	.29	7.3	16	72	.70	17.8	0.054	1.4	13.0	SST	CG	N
0.312	7.92	11162	1.13	28.6	.274	7.0	.96	.17	.92	23	.88	3.9	.20	5.2	0.019	0.5	9.75	MW	C	Z
0.312	7.92	10910	1.13	28.6	.272	6.9	.99	.17	.90	23	.89	4.0	.23	5.7	0.020	0.5	10.3	SST	C	N
0.312	7.92	2791	1.13	28.6	.272	6.9	1.3	.23	.93	23	1.2	5.4	.20	5.1	0.020	0.5	9.00	MW	C	GI
0.312	7.92	CC-33	1.13	28.6	.272	6.9	1.5	.27	.97	25	1.5	6.6	.16	4.1	0.020	0.5	8.00	MW	CG	Z
0.312	7.92	S-483	1.13	28.6	.262	6.7	2.1	.36	.80	20	1.7	7.3	.33	8.3	0.025	0.6	12.0	SST	C	N
0.312	7.92	A9-41	1.13	28.6	.258	6.6	4.1	.72	.83	21	3.4	15	.30	7.5	0.027	0.7	10.0	MW	C	N
0.312	7.92	3514	1.13	28.6	.256	6.5	3.4	.59	.72	18	2.4	11	.41	10.3	0.028	0.7	13.5	MW	C	Z
0.312	7.92	3746	1.13	28.6	.252	6.4	6.9	1.2	.70	18	4.8	22	.32	8.0	0.030	0.8	9.50	MW	C	Z
0.312	7.92	HH-97	1.13	28.6	.246	6.2	8.0	1.4	.54	14	4.3	19	.38	9.6	0.033	0.8	10.5	SST	C	N
0.312	7.92	S-791	1.13	28.6	.242	6.1	7.4	1.3	.64	16	4.7	21	.49	12.4	0.035	0.9	14.0	SST	CG	N
0.312	7.92	10147	1.13	28.6	.236	6.0	13	2.3	.50	13	6.7	30	.49	12.5	0.038	1.0	13.0	SPR	CG	Z
0.312	7.92	S-788	1.13	28.6	.204	5.2	58	10	.28	7.1	16	72	.70	17.7	0.054	1.4	12.0	SST	CG	N
0.312	7.92	S-36	1.13	28.6	.186	4.7	104	18	.21	5.4	22	98	.91	23.2	0.063	1.6	14.5	SST	CG	N
0.312	7.92	S-1182	1.16	29.4	.262	6.7	3.4	.60	.55	14	1.9	8.4	.23	5.7	0.025	0.6	8.00	SST	C	N
0.312	7.92	K-43	1.19	30.2	.238	6.0	8.8	1.5	.61	16	5.4	24	.57	14.6	0.037	0.9	15.5	SST	C	N
0.312	7.92	10732	1.19	30.2	.230	5.8	29	5.1	.29	7.3	8.3	37	.37	9.4	0.041	1.0	9.00	SPR	CG	Z
0.312	7.92	B-49	1.19	30.2	.222	5.6	25	4.3	.44	11	11	49	.65	16.6	0.045	1.1	14.5	SPR	CG	Z
0.312	7.92	L-95	1.19	30.2	.168	4.3	279	49	.13	3.3	37	164	.86	21.9	0.072	1.8	12.0	HD	CG	Z
0.312	7.92	S-1686	1.20	30.5	.228	5.8	25	4.3	.34	8.6	8.4	37	.42	10.7	0.042	1.1	10.0	SST	CG	N
0.312	7.92	2807	1.22	31.0	.260	6.6	2.9	.50	.91	23	2.6	12	.31	7.8	0.026	0.7	11.8	MW	CG	Z
0.312	7.92	10504	1.22	31.0	.196	5.0	110	19	.19	4.9	21	94	.70	17.7	0.058	1.5	11.0	SPR	C	Z
0.312	7.92	1859	1.22	31.0	.194	4.9	134	24	.23	5.8	31	137	.65	16.5	0.059	1.5	10.0	MW	C	Z
0.312	7.92	N-38	1.25	31.8	.274	7.0	.81	.14	1.0	26	.84	3.7	.21	5.3	0.019	0.5	10.0	SST	C	N
0.312	7.92	11368	1.25	31.8	.272	6.9	.91	.16	1.0	26	.92	4.1	.24	6.1	0.020	0.5	11.0	SST	C	N
0.312	7.92	10049	1.25	31.8	.264	6.7	2.9	.50	.93	24	2.7	12	.24	6.1	0.024	0.6	9.00	MW	C	GI
0.312	7.92	S-3114	1.25	31.8	.262	6.7	3.4	.60	.55	14	1.9	8.4	.23	5.7	0.025	0.6	8.00	SST	C	N
0.312	7.92	G-3	1.25	31.8	.260	6.6	2.2	.38	.83	21	1.8	8.0	.42	10.6	0.026	0.7	15.0	MW	C	Z
0.312	7.92	AA-84	1.25	31.8	.252	6.4	4.3	.76	.80	20	3.5	15	.45	11.4	0.030	0.8	14.0	MW	C	Z
0.312	7.92	A9-46	1.25	31.8	.250	6.4	4.6	.81	.78	20	3.6	16	.42	10.6	0.031	0.8	13.5	SST	CG	N
0.312	7.92	3715	1.25	31.8	.246	6.2	6.0	1.0	.75	19	4.5	20	.50	12.7	0.033	0.8	15.0	SPR	CG	Z
0.312	7.92	2	1.25	31.8	.230	5.8	17	3.0	.49	12	8.3	37	.62	15.6	0.041	1.0	14.0	HD	C	Z
0.312	7.92	S-495	1.25	31.8	.230	5.8	11	2.0	.53	13	6.0	26	.72	18.4	0.041	1.0	17.7	SST	CG	N
0.312	7.92	S-734	1.25	31.8	.228	5.8	18	3.1	.48	12	8.4	37	.60	15.2	0.042	1.1	13.3	SST	C	N
0.312	7.92	3615	1.25	31.8	.218	5.5	25	4.4	.45	11	11	50	.80	20.3	0.047	1.2	17.0	HD	CG	Z
0.312	7.92	S-3131	1.25	31.8	.210	5.3	39	6.8	.36	9.0	14	61	.73	18.5	0.051	1.3	14.3	SST	CG	N
0.312	7.92	1543	1.25	31.8	.198	5.0	114	20	.18	4.5	20	90	.63	15.9	0.057	1.4	10.0	SPR	C	Z
0.312	7.92	10294	1.31	33.3	.258	6.6	3.0	.53	.93	24	2.8	12	.38	9.6	0.027	0.7	13.0	MW	C	Z
0.312	7.92	10021	1.31	33.3	.256	6.5	3.5	.61	.92	23	3.2	14	.39	10.0	0.028	0.7	13.0	MW	C	Z
0.312	7.92	1857	1.31	33.3	.252	6.4	3.8	.67	.82	21	3.1	14	.50	12.6	0.030	0.8	15.5	MW	C	Z
0.312	7.92	10328	1.31	33.3	.250	6.4	3.6	.63	.71	18	2.6	11	.61	15.4	0.031	0.8	18.5	MW	C	Z
0.312	7.92	3533	1.31	33.3	.250	6.4	5.1	.89	.85	22	4.4	19	.46	11.6	0.031	0.8	13.8	MW	C	Z
0.312	7.92	10193	1.31	33.3	.248	6.3	4.9	.86	.80	20	3.9	17	.51	13.0	0.032	0.8				




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.312	7.92	B3-69	1.48	37.6	.252	6.4	3.1	.53	.88	22	2.7	12	.60	15.2	0.030	0.8	19.0	MW	C	N
0.312	7.92	10736	1.50	38.1	.270	6.9	1.0	.18	1.2	31	1.2	5.5	.29	7.5	0.021	0.5	13.0	MW	C	GI
0.312	7.92	2759	1.50	38.1	.266	6.8	1.1	.19	1.1	27	1.2	5.2	.42	10.7	0.023	0.6	17.3	MW	C	Z
0.312	7.92	3	1.50	38.1	.266	6.8	1.8	.32	1.2	31	2.2	9.8	.28	7.2	0.023	0.6	11.3	MW	C	Z
0.312	7.92	S-44	1.50	38.1	.252	6.4	4.1	.72	.79	20	3.2	14	.42	10.7	0.030	0.8	13.0	SST	C	N
0.312	7.92	6	1.50	38.1	.244	6.2	6.7	1.2	.75	19	5.0	22	.55	14.0	0.034	0.9	15.3	HD	C	Z
0.312	7.92	K-23	1.50	38.1	.242	6.1	6.5	1.1	.75	19	4.9	22	.58	14.7	0.035	0.9	15.5	SST	C	N
0.312	7.92	3908	1.50	38.1	.228	5.8	17	3.1	.51	13	8.9	40	.67	17.1	0.042	1.1	15.0	SPR	C	Z
0.312	7.92	S-735	1.50	38.1	.228	5.8	14	2.5	.58	15	8.4	37	.70	17.9	0.042	1.1	15.8	SST	C	N
0.312	7.92	N-70	1.50	38.1	.222	5.6	27	4.7	.41	10	11	49	.61	15.4	0.045	1.1	13.5	SPR	CG	GI
0.312	7.92	B14-31	1.50	38.1	.220	5.6	26	4.6	.44	11	12	52	.74	18.7	0.046	1.2	15.0	SPR	C	Z
0.312	7.92	936	1.50	38.1	.218	5.5	29	5.1	.43	11	12	55	.75	19.1	0.047	1.2	15.0	HD	C	Z
0.312	7.92	11237	1.50	38.1	.208	5.3	37	6.5	.41	11	15	69	.99	25.1	0.052	1.3	18.0	SPR	C	Z
0.312	7.92	11383	1.50	38.1	.198	5.0	87	15	.23	5.9	20	90	.71	18.1	0.057	1.4	12.5	HD	CG	Z
0.312	7.92	2823	1.53	38.9	.240	6.1	8.5	1.5	.93	24	7.9	35	.56	14.2	0.036	0.9	15.5	MW	CG	Z
0.312	7.92	S-180	1.59	40.5	.264	6.7	1.4	.24	1.2	31	1.7	7.5	.36	9.1	0.024	0.6	15.0	SST	CG	N
0.312	7.92	PP-65	1.63	41.3	.272	6.9	.92	.16	1.4	35	1.3	5.7	.24	6.1	0.020	0.5	12.0	MW	CG	Z
0.312	7.92	J-100	1.63	41.3	.242	6.1	6.3	1.1	.78	20	4.9	22	.56	14.2	0.035	0.9	16.0	SST	CG	N
0.312	7.92	WW-59	1.63	41.3	.242	6.1	6.3	1.1	.83	21	5.2	23	.63	16.0	0.035	0.9	18.0	SPR	CG	N
0.312	7.92	116	1.63	41.3	.230	5.8	13	2.2	.65	17	8.3	37	.78	19.8	0.041	1.0	18.0	HD	C	Z
0.312	7.92	10127	1.63	41.3	.228	5.8	17	3.1	.51	13	8.9	40	.67	17.1	0.042	1.1	15.0	SPR	C	Z
0.312	7.92	10916	1.63	41.3	.208	5.3	37	6.4	.42	11	15	69	1.00	25.4	0.052	1.3	18.3	SPR	C	N
0.312	7.92	10535	1.63	41.3	.202	5.1	48	8.5	.38	9.5	18	81	1.05	26.5	0.055	1.4	18.0	SPR	C	Z
0.312	7.92	A15-38	1.66	42.1	.256	6.5	1.6	.29	1.0	26	1.7	7.5	.64	16.2	0.028	0.7	22.8	SST	CG	N
0.312	7.92	12432	1.72	43.6	.250	6.4	5.3	.93	1.0	26	5.3	24	.44	11.2	0.031	0.8	13.3	MW	C	Z
0.312	7.92	202-C	1.75	44.5	.280	7.1	.39	.07	1.6	39	.61	2.7	.20	5.0	0.016	0.4	11.3	MW	C	T
0.312	7.92	FF-42	1.75	44.5	.272	6.9	.97	.17	1.5	38	1.5	6.5	.25	6.4	0.020	0.5	11.5	MW	C	Z
0.312	7.92	4196	1.75	44.5	.260	6.6	2.8	.49	1.1	29	3.2	14	.34	8.6	0.026	0.7	12.0	MW	C	Z
0.312	7.92	JJ-100	1.75	44.5	.232	5.9	7.6	1.3	.79	20	6.0	27	.96	24.4	0.040	1.0	23.0	SST	C	N
0.312	7.92	10100	1.75	44.5	.222	5.6	23	4.0	.48	12	11	49	.74	18.9	0.045	1.1	15.5	SPR	C	Z
0.312	7.92	HH-93	1.75	44.5	.212	5.4	29	5.1	.47	12	14	62	.95	24.1	0.050	1.3	19.0	SPR	CG	N
0.312	7.92	3395	1.75	44.5	.198	5.0	48	8.4	.42	11	20	90	1.20	30.4	0.057	1.4	21.0	SPR	CG	Z
0.312	7.92	1937	1.75	44.5	.196	5.0	78	14	.27	6.9	21	94	.91	23.2	0.058	1.5	14.8	SPR	C	Z
0.312	7.92	B15-25	1.75	44.5	.180	4.6	126	22	.24	6.1	30	136	1.16	29.3	0.066	1.7	16.5	SPR	C	N
0.312	7.92	3183	1.78	45.2	.248	6.3	6.1	1.1	.97	25	5.9	26	.46	11.6	0.032	0.8	13.3	MW	C	Z
0.312	7.92	OO-87	1.88	47.6	.242	6.1	5.1	.89	1.0	26	5.2	23	.81	20.4	0.035	0.9	22.0	SPR	C	Z
0.312	7.92	10481	1.88	47.6	.230	5.8	11	2.0	.74	19	8.3	37	.86	21.9	0.041	1.0	20.0	SPR	C	Z
0.312	7.92	U-54	1.94	49.2	.260	6.6	2.0	.35	1.5	39	3.1	14	.42	10.6	0.026	0.7	16.0	MW	C	N
0.312	7.92	1942	1.94	49.2	.232	5.9	10	1.8	.75	19	7.8	35	.83	21.1	0.040	1.0	19.8	SPR	C	Z
0.312	7.92	J-87	1.94	49.2	.232	5.9	9.9	1.7	.73	19	7.3	32	.72	18.3	0.040	1.0	18.0	SST	CG	N
0.312	7.92	S-910	2.00	50.8	.264	6.7	1.4	.25	1.2	31	1.8	7.9	.34	8.5	0.024	0.6	14.0	SST	CG	N
0.312	7.92	9	2.00	50.8	.218	5.5	18	3.1	.70	18	12	55	1.14	28.9	0.047	1.2	23.3	HD	C	Z
0.312	7.92	S-297	2.00	50.8	.218	5.5	20	3.5	.58	15	12	52	.90	23.0	0.047	1.2	18.3	SST	C	N
0.312	7.92	3128	2.00	50.8	.214	5.4	28	5.0	.49	12	14	62	.93	23.6	0.049	1.2	18.0	SPR	C	Z
0.312	7.92	937	2.00	50.8	.204	5.2	44	7.8	.39	9.9	17	77	1.03	26.1	0.054	1.4	18.0	HD	C	Z
0.312	7.92	4122	2.13	54.0	.232	5.9	10	1.8	.76	19	7.8	35	.84	21.3	0.040	1.0	20.0	SPR	C	Z
0.312	7.92	S-821	2.16	54.8	.240	6.1	4.1	.71	1.2	30	4.8	21	.99	25.1	0.036	0.9	26.5	SST	C	N
0.312	7.92	S-1030	2.25	57.2	.228	5.8	9.9	1.7	.85	22	8.4	37	.92	23.5	0.042	1.1	22.0	SST	CG	N
0.312	7.92	Z-61	2.25	57.2	.228	5.8	13	2.3	.69	17	8.9	40	.82	20.8	0.042	1.1	19.5	SPR	CG	GI
0.312	7.92	12262	2.31	58.7	.256	6.5	1.9	.34	1.7	42	3.2	14	.64	16.4	0.028	0.7	22.0	MW	C	Z
0.312	7.92	12196	2.34	59.5	.216	5.5	22	3.8	.60	15	13	59	1.01	25.6	0.048	1.2	21.0	SPR	CG	Z
0.312	7.92	G-28	2.38	60.3	.218	5.5	17	2.9	.69	18	12	52	1.03	26.3	0.047	1.2	22.0	SST	CG	N
0.312	7.92	A9-62	2.50	63.5	.250	6.4	3.0	.52	1.8	45	5.3	24	.71	18.1	0.031	0.8	22.0	MW	C	Z
0.312	7.92	F-58	2.50	63.5	.208	5.3	24	4.2	.65	16	15	69	1.40	35.7	0.052	1.3	27.0	SPR	CG	GI
0.312	7.92	S-218	2.75	69.9	.260	6.6	.86	.15	1.9	49	1.7	7.4	.81	20.6	0.026	0.7	30.3	SST	C	N
0.312	7.92	B9-58	2.75	69.9	.202	5.1	36	6.2	.51	13	18	81	1.31	33.2	0.055	1.4	23.8	SPR	CG	N
0.312	7.92	S-1684	2.88	73.0	.274	7.0	.23	.04	2.3	58	.52	2.3	.60	15.2	0.019	0.5	30.5	SST	C	N
0.312	7.92	KK-11	3.00	76.2	.252	6.4	1.7	.30	1.9	48	3.2	14	.90	22.9	0.030	0.8	29.0	SST	C	N
0.312	7.92	Y-13	3.00	76.2	.248	6.3	2.3	.40	1.7	44	3.9	17	.94	23.8	0.032	0.8	28.3	SST	C	N
0.312	7.92	M-115	3.13	79.4	.216	5.5	12	2.1	1.1	28	13	59	1.78	45.1	0.048	1.2	37.0	SPR	CG	N
0.312	7.92	F-57	3.25	82.6	.224	5.7	8.5	1.5	1.2	31	10	46	1.54	39.1	0.044	1.1	35.0	HD	CG	Z
0.312	7.92	4109	3.25	82.6	.220	5.6	13	2.3	.87	22	12	52	1.31	33.3	0.046	1.2	27.5	SPR	C	N
0.312	7.92	1573	3.38	85.7	.242	6.1	4.2	.73	1.3	32	5.2	23	.95	24.2	0.035	0.9	26.3	SPR	C	Z
0.312	7.92	12498	3.44	87.4	.276	7.0	.21	.04	2.9	73	.61	2.7	.56	14.2	0.018	0.5	30.0	MW	C	Z
0.312	7.92	10479	3.66	92.9	.272	6.9	.36	.06	3.1	78	1.1	4.9	.58	14.6	0.020	0.5	27.8	MW	C	T
0.312	7.92	B2-60	4.00	101.6	.276	7.0	.21	.04	3.4	87	.73	3.2	.56	14.2	0.018	0.5	30.0	MW	C	N
0.312	7.92	10222	4.00	101.6	.216	5.5	15	2.6	.89	23	13	59	1.49	37.8	0.048	1.2	30.0	SPR	C	Z
0.312	7.92	3087	5.00	127.0	.224	5.7	5.5	.96	1.9	47	10	46	2.33	59.2	0.044	1.1	53.0	SPR	CG	Z
0.312	7.92	10092	6.50	165.1	.230	5.8	2.6	.46	3.2	81	8.3	37	3.26	82.8	0.041	1.0	79.5	SPR	CG	Z
0.312	7.92	10772	7.44</																	

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH	
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm					
0.328	8.33	B2-16	.28	7.1	.264	6.7	39	6.8	.10	2.6	4.0	18	.14	3.7	0.032	0.8	3.50	SPR	C	Z	
0.328	8.33	B2-5	.30	7.5	.264	6.7	39	6.8	.10	2.6	4.0	18	.14	3.7	0.032	0.8	3.50	SPR	CL	Z	
0.328	8.33	G-39	.31	7.9	.280	7.1	14	2.4	.19	4.7	2.5	11	.10	2.6	0.024	0.6	3.25	MW	C	N	
0.328	8.33	FF-14	.31	7.9	.268	6.8	12	2.1	.11	2.8	1.3	5.7	.20	5.1	0.030	0.8	5.75	MW	C	N	
0.328	8.33	NN-50	.31	7.9	.204	5.2	491	86	.05	1.2	23	103	.25	6.3	0.062	1.6	4.00	SST	CG	N	
0.328	8.33	H-58	.34	8.7	.296	7.5		.92	.16	2.5	.23	1.0	.10	2.4	0.016	0.4	5.00	SST	C	N	
0.328	8.33	EE-32	.38	9.5	.270	6.9	8.3	1.4	.20	5.1	1.7	7.4	.17	4.4	0.029	0.7	6.00	SST	CG	N	
0.328	8.33	XX-44	.38	9.5	.264	6.7	29	5.1	.14	3.5	4.0	18	.16	4.1	0.032	0.8	4.00	HD	C	Z	
0.328	8.33	MM-69	.38	9.7	.208	5.3	429	75	.05	1.2	21	94	.30	7.6	0.060	1.5	4.00	SST	C	N	
0.328	8.33	S-4	.41	10.3	.280	7.1	4.9	.86	.26	6.7	1.3	5.7	.14	3.7	0.024	0.6	5.00	SST	C	N	
0.328	8.33	I-38	.44	11.1	.276	7.0	12	2.1	.25	6.5	3.0	13	.10	2.6	0.026	0.7	4.00	MW	CG	GI	
0.328	8.33	II-31	.44	11.1	.268	6.8	22	3.9	.21	5.3	4.6	21	.12	3.0	0.030	0.8	4.00	MW	CG	Z	
0.328	8.33	KK-1	.44	11.1	.268	6.8	5.5	.96	.14	3.5	.76	3.4	.30	7.6	0.030	0.8	10.0	MW	CG	Z	
0.328	8.33	GG-24	.44	11.1	.258	6.6	25	4.4	.18	4.7	4.7	21	.18	4.4	0.035	0.9	5.00	SST	CG	N	
0.328	8.33	2944	.44	11.1	.256	6.5	52	9.1	.11	2.7	5.4	24	.18	4.5	0.036	0.9	4.00	SPR	C	Z	
0.328	8.33	A10-27	.44	11.1	.256	6.5	34	6.0	.15	3.8	5.1	23	.16	4.1	0.036	0.9	4.50	SST	CG	N	
0.328	8.33	S-817	.44	11.1	.252	6.4	27	4.7	.21	5.3	5.6	25	.23	5.8	0.038	1.0	6.00	SST	CG	N	
0.328	8.33	VV-43	.44	11.1	.246	6.2	40	7.0	.19	4.8	7.5	33	.24	6.0	0.041	1.0	5.75	SST	CG	N	
0.328	8.33	3669	.44	11.1	.244	6.2	64	11	.13	3.4	8.5	38	.21	5.3	0.042	1.1	5.00	SPR	CG	Z	
0.328	8.33	Y-71	.44	11.1	.238	6.0	116	20	.09	2.3	10	46	.19	4.9	0.045	1.1	4.25	SPR	CG	N	
0.328	8.33	O-117	.50	12.7	.264	6.7	12	2.0	.24	6.2	2.8	13	.26	6.5	0.032	0.8	7.00	SPR	C	GI	
0.328	8.33	2578	.50	12.7	.262	6.7	17	2.9	.27	6.7	4.4	20	.23	5.9	0.033	0.8	6.00	HD	C	Z	
0.328	8.33	W-86	.50	12.7	.238	6.0	57	9.9	.17	4.4	9.8	44	.27	6.9	0.045	1.1	6.00	SST	CG	N	
0.328	8.33	A10-51	.50	12.7	.236	6.0	31	5.5	.18	4.5	5.6	25	.32	8.2	0.046	1.2	7.00	SPR	CG	N	
0.328	8.33	B4-11	.50	12.7	.236	6.0	72	13	.16	3.9	11	50	.28	7.0	0.046	1.2	6.00	SPR	CG	Z	
0.328	8.33	3717	.50	12.7	.192	4.9	437	77	.07	1.8	32	142	.41	10.4	0.068	1.7	6.00	SPR	CG	N	
0.328	8.33	J-76	.50	12.7	.184	4.7	768	134	.05	1.2	35	158	.36	9.1	0.072	1.8	5.00	SPR	CG	Z	
0.328	8.33	2673	.56	14.3	.264	6.7	27	4.8	.21	5.2	5.6	25	.13	3.4	0.032	0.8	4.00	MW	CG	GI	
0.328	8.33	11132	.56	14.3	.238	6.0	61	11	.17	4.3	10	46	.33	8.3	0.045	1.1	6.25	SPR	C	Z	
0.328	8.33	I-11	.56	14.3	.226	5.7	101	18	.13	3.3	13	59	.31	7.8	0.051	1.3	6.00	SST	CG	N	
0.328	8.33	O-1	.59	15.1	.302	7.7		.19	.03	.46	12	.09	.39	.13	3.3	0.013	0.3	9.00	MW	C	GI
0.328	8.33	2671	.59	15.1	.288	7.3	3.9	.69	.37	9.5	1.5	6.6	.10	2.5	0.020	0.5	4.00	MW	C	Z	
0.328	8.33	CC-97	.59	15.1	.242	6.1	42	7.4	.22	5.5	9.1	41	.30	7.6	0.043	1.1	7.00	SPR	CG	Z	
0.328	8.33	A-17	.63	15.9	.300	7.6		.25	.04	.49	12	.12	.55	.14	3.6	0.014	0.4	9.00	MW	C	T
0.328	8.33	BB-97	.63	15.9	.278	7.1	4.0	.71	.43	11	1.7	7.6	.20	5.1	0.025	0.6	7.00	MW	C	Z	
0.328	8.33	L-36	.63	15.9	.278	7.1	4.5	.79	.46	12	2.1	9.2	.16	4.1	0.025	0.6	6.50	MW	CG	N	
0.328	8.33	S-1429	.63	15.9	.270	6.9	8.3	1.4	.34	8.6	2.8	12	.20	5.2	0.029	0.7	6.00	SST	C	N	
0.328	8.33	W-65	.63	15.9	.264	6.7	15	2.5	.28	7.0	4.0	18	.22	5.7	0.032	0.8	6.00	SPR	C	Z	
0.328	8.33	FF-47	.63	15.9	.258	6.6	19	3.3	.25	6.4	4.7	21	.21	5.3	0.035	0.9	6.00	SST	CG	N	
0.328	8.33	S-797	.63	15.9	.258	6.6	15	2.6	.31	8.0	4.7	21	.25	6.2	0.035	0.9	7.00	SST	CG	N	
0.328	8.33	A13-45	.63	15.9	.242	6.1	35	6.2	.26	6.6	9.1	41	.34	8.7	0.043	1.1	8.00	SPR	CG	N	
0.328	8.33	LL-94	.63	15.9	.204	5.2	245	43	.09	2.4	23	103	.37	9.4	0.062	1.6	6.00	SST	CG	N	
0.328	8.33	B3-44	.66	16.7	.282	7.2	2.4	.41	.45	11	1.1	4.7	.21	5.3	0.023	0.6	8.00	MW	C	T	
0.328	8.33	O-142	.66	16.7	.246	6.2	30	5.3	.24	6.2	7.5	33	.29	7.3	0.041	1.0	7.00	SST	CG	N	
0.328	8.33	Z-92	.66	16.7	.244	6.2	55	9.6	.16	4.0	8.5	38	.27	6.9	0.042	1.1	5.50	SPR	C	Z	
0.328	8.33	I-76	.66	16.7	.236	6.0	51	8.9	.20	5.2	10	46	.32	8.2	0.046	1.2	7.00	SST	CG	N	
0.328	8.33	B15-56	.69	17.4	.302	7.7		.19	.03	.57	14	.11	.49	.12	3.0	0.013	0.3	8.00	SST	C	N
0.328	8.33	S-893	.69	17.4	.274	7.0	6.6	1.2	.34	8.7	2.3	10	.18	4.6	0.027	0.7	5.75	SST	C	N	
0.328	8.33	CC-77	.69	17.4	.272	6.9	6.9	1.2	.50	13	3.4	15	.19	4.8	0.028	0.7	6.75	MW	CG	N	
0.328	8.33	A12-32	.69	17.4	.262	6.7	14	2.5	.28	7.2	4.1	18	.23	5.9	0.033	0.8	6.00	SST	C	N	
0.328	8.33	S-3143	.69	17.4	.246	6.2	40	7.0	.19	4.8	7.5	33	.28	7.0	0.041	1.0	5.75	SST	C	N	
0.328	8.33	U-40	.69	17.4	.234	5.9	53	9.2	.22	5.7	12	53	.38	9.6	0.047	1.2	8.00	SPR	CG	Z	
0.328	8.33	A9-43	.72	18.2	.278	7.1	4.5	.78	.40	10	1.8	8.0	.18	4.4	0.025	0.6	6.00	SST	C	N	
0.328	8.33	2872	.72	18.2	.270	6.9	5.9	1.0	.44	11	2.6	12	.28	7.0	0.029	0.7	8.50	MW	C	Z	
0.328	8.33	12500	.72	18.3	.228	5.8	73	13	.18	4.6	13	59	.44	11.1	0.050	1.3	7.75	SPR	C	N	
0.328	8.33	MM-17	.75	19.1	.300	7.6		.20	.03	.58	15	.12	.51	.17	4.3	0.014	0.4	11.0	MW	C	Z
0.328	8.33	I-19	.75	19.1	.296	7.5		.56	.10	.61	16	.35	1.5	.14	3.5	0.016	0.4	7.50	MW	C	N
0.328	8.33	S-3000	.75	19.1	.272	6.9	4.7	.83	.50	13	2.4	11	.25	6.4	0.028	0.7	8.00	SST	C	N	
0.328	8.33	KK-46	.75	19.1	.268	6.8	9.8	1.7	.32	8.1	3.1	14	.18	4.6	0.030	0.8	6.00	SST	CG	N	
0.328	8.33	Y-88	.75	19.1	.268	6.8	5.5	.96	.45	11	2.5	11	.30	7.6	0.030	0.8	9.00	SST	C	N	
0.328	8.33	10022	.75	19.1	.266	6.8	6.3	1.1	.41	10	2.6	12	.34	8.7	0.031	0.8	10.0	MW	C	Z	
0.328	8.33	2546	.75	19.1	.258	6.6	12	2.1	.40	10	4.9	22	.35	8.9	0.035	0.9	9.00	MW	C	Z	
0.328	8.33	A-86	.75	19.1	.248	6.3	26	4.5	.29	7.3	7.4	33	.32	8.1	0.040	1.0	8.00	SPR	CG	Z	
0.328	8.33	K-68	.75	19.1	.248	6.3	27	4.7	.26	6.6	6.9	31	.28	7.1	0.040	1.0	7.00	SST	CG	N	
0.328	8.33	2919	.75	19.1	.234	5.9	53	9.2	.22	5.7	12	53	.38	9.6	0.047	1.2	8.00	HD	CG	Z	
0.328	8.33	RR-24	.75	19.1	.234	5.9	52	9.2	.21	5.4	11	49	.34	8.7	0.047	1.2	7.25	SST	CG	N	
0.328	8.33	VW-61	.75	19.1	.216	5.5	117	21	.16	4.0	18	82	.50	12.8	0.056	1.4	8.00	SPR	C	Z	
0.328	8.33	FF-95	.78	19.8	.268	6.8	5.5	.96	.48	12	2.6	12	.30	7.6	0.030	0.8	9.00	SST	C	N	
0.328	8.33	A9-13	.78	19.8	.232	5.9	50	8.8	.23	6.0	12	52	.39	9.9	0.048	1.2	8.00	SST	CG	N	
0.328	8.33	K-100	.81	20.6	.248	6.3	21	3.6	.34	8.5	6.9	31	.34	8.6	0.040	1.0	8.50	SST	CG	N	




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.328	8.33	3207	.91	23.0	.234	5.9	45	7.9	.26	6.7	12	53	.47	11.9	0.047	1.2	9.00	HD	C	Z
0.328	8.33	1821	.91	23.0	.218	5.5	92	16	.26	6.7	24	108	.55	14.0	0.055	1.4	9.00	MW	C	Z
0.328	8.33	4182	.94	23.8	.220	5.6	66	12	.25	6.4	17	74	.65	16.5	0.054	1.4	11.0	SPR	C	Z
0.328	8.33	H-73	.97	24.6	.282	7.2	1.1	.19	.63	16	.68	3.0	.33	8.5	0.023	0.6	13.5	SST	C	N
0.328	8.33	GG-91	.97	24.6	.276	7.0	3.5	.62	.58	15	2.0	9.0	.23	5.9	0.026	0.7	8.00	SST	C	N
0.328	8.33	HH-38	1.00	25.4	.282	7.2	1.4	.25	.70	18	.99	4.4	.30	7.6	0.023	0.6	12.0	MW	C	N
0.328	8.33	I-9	1.00	25.4	.274	7.0	3.3	.58	.69	18	2.3	10	.31	7.9	0.027	0.7	10.5	MW	C	Z
0.328	8.33	VW-53	1.00	25.4	.254	6.5	14	2.4	.41	10	5.5	25	.33	8.5	0.037	0.9	9.00	SST	CG	N
0.328	8.33	CC-69	1.00	25.4	.248	6.3	19	3.4	.38	9.8	7.4	33	.40	10.2	0.040	1.0	10.0	SPR	CG	Z
0.328	8.33	2581	1.00	25.4	.242	6.1	33	5.7	.39	9.8	13	56	.41	10.4	0.043	1.1	8.50	MW	C	Z
0.328	8.33	10040	1.00	25.4	.238	6.0	37	6.5	.28	7.1	10	46	.45	11.4	0.045	1.1	9.00	SPR	C	Z
0.328	8.33	10536	1.00	25.4	.238	6.0	27	4.8	.38	9.7	10	46	.56	14.3	0.045	1.1	11.5	SPR	C	Z
0.328	8.33	B4-25	1.00	25.4	.238	6.0	33	5.7	.44	11	14	64	.45	11.4	0.045	1.1	10.0	MW	CG	N
0.328	8.33	J-16	1.00	25.4	.224	5.7	71	13	.21	5.3	15	66	.47	11.9	0.052	1.3	9.00	SPR	CG	Z
0.328	8.33	O-103	1.03	26.2	.256	6.5	13	2.3	.42	11	5.4	24	.38	9.6	0.036	0.9	9.50	SPR	C	GI
0.328	8.33	A-69	1.06	27.0	.276	7.0	2.0	.35	.70	18	1.4	6.2	.36	9.2	0.026	0.7	14.0	MW	CG	N
0.328	8.33	Y-96	1.06	27.0	.232	5.9	40	7.0	.32	8.1	13	56	.52	13.1	0.048	1.2	10.8	SPR	CG	GI
0.328	8.33	B14-28	1.09	27.8	.290	7.4	.63	.11	.87	22	.55	2.4	.23	5.8	0.019	0.5	12.0	MW	CG	N
0.328	8.33	10255	1.09	27.8	.278	7.1	2.2	.39	.79	20	1.8	7.9	.30	7.6	0.025	0.6	11.0	MW	C	N
0.328	8.33	W-27	1.09	27.8	.220	5.6	59	10	.27	6.7	16	69	.59	15.1	0.054	1.4	11.0	SST	CG	N
0.328	8.33	CC-51	1.13	28.6	.268	6.8	6.8	1.2	.68	17	4.6	21	.29	7.2	0.030	0.8	8.50	MW	C	T
0.328	8.33	HH-27	1.13	28.6	.268	6.8	4.6	.80	.67	17	3.1	14	.32	8.0	0.030	0.8	10.5	SST	CG	N
0.328	8.33	A-98	1.13	28.6	.256	6.5	11	2.0	.48	12	5.4	24	.38	9.6	0.036	0.9	10.5	HD	CG	N
0.328	8.33	S-229	1.13	28.6	.242	6.1	28	5.0	.30	7.7	8.6	38	.37	9.3	0.043	1.1	8.50	SST	C	N
0.328	8.33	Q-40	1.13	28.6	.238	6.0	18	3.2	.47	12	8.5	38	.65	16.6	0.045	1.1	14.5	SST	CG	N
0.328	8.33	S-413	1.13	28.6	.228	5.8	39	6.8	.32	8.1	12	55	.58	14.6	0.050	1.3	11.5	SST	CG	N
0.328	8.33	OO-72	1.13	28.6	.228	5.8	119	21	.11	2.8	13	59	.28	7.0	0.050	1.3	5.50	SPR	CG	Z
0.328	8.33	3606	1.13	28.6	.220	5.6	99	17	.17	4.2	17	74	.49	12.3	0.054	1.4	8.00	HD	C	Z
0.328	8.33	NN-36	1.19	30.2	.268	6.8	6.0	1.1	.52	13	3.1	14	.29	7.2	0.030	0.8	8.50	SST	C	N
0.328	8.33	B7-26	1.19	30.2	.248	6.3	13	2.3	.55	14	7.4	33	.54	13.7	0.040	1.0	13.5	SPR	CG	N
0.328	8.33	11101	1.19	30.2	.234	5.9	40	6.9	.30	7.6	12	53	.47	11.9	0.047	1.2	10.0	SPR	CG	Z
0.328	8.33	3958	1.19	30.2	.226	5.7	46	8.0	.31	7.8	14	62	.61	15.5	0.051	1.3	12.0	SPR	CG	Z
0.328	8.33	1507	1.19	30.2	.204	5.2	150	26	.23	5.7	34	151	.59	15.0	0.062	1.6	9.50	MW	CG	Z
0.328	8.33	I-3	1.22	31.0	.230	5.8	40	7.0	.33	8.5	13	59	.56	14.3	0.049	1.2	11.5	SPR	CG	N
0.328	8.33	PP-34	1.25	31.8	.288	7.3	.70	.12	.99	25	.69	3.1	.26	6.6	0.020	0.5	12.0	SST	C	N
0.328	8.33	3565	1.25	31.8	.272	6.9	4.1	.72	.92	23	3.8	17	.31	7.8	0.028	0.7	10.0	MW	C	Z
0.328	8.33	MM-74	1.25	31.8	.264	6.7	5.3	.93	.70	18	3.7	17	.40	10.2	0.032	0.8	11.5	SST	C	N
0.328	8.33	NN-27	1.25	31.8	.248	6.3	11	2.0	.61	15	6.9	31	.60	15.2	0.040	1.0	14.0	SST	C	N
0.328	8.33	EE-90	1.25	31.8	.188	4.8	251	44	.13	3.3	33	146	.70	17.8	0.070	1.8	10.0	SPR	CG	N
0.328	8.33	HH-2	1.25	31.8	.148	3.8	777	136	.08	2.0	62	276	.99	25.1	0.090	2.3	11.0	SPR	CG	GI
0.328	8.33	10876	1.28	32.5	.288	7.3	.87	.15	1.1	27	.93	4.1	.22	5.6	0.020	0.5	10.0	SST	C	N
0.328	8.33	10576	1.28	32.5	.258	6.6	7.6	1.3	.62	16	4.7	21	.42	10.7	0.035	0.9	12.0	SST	CG	N
0.328	8.33	10720	1.28	32.5	.246	6.2	16	2.7	.51	13	8.0	35	.57	14.6	0.041	1.0	13.0	SPR	C	Z
0.328	8.33	OO-97	1.28	32.5	.208	5.3	143	25	.15	3.7	21	94	.54	13.7	0.060	1.5	8.00	SST	C	N
0.328	8.33	2783	1.31	33.3	.266	6.8	7.9	1.4	.64	16	5.1	23	.29	7.4	0.031	0.8	8.25	MW	C	Z
0.328	8.33	S-186	1.31	33.3	.204	5.2	109	19	.21	5.4	23	103	.68	17.3	0.062	1.6	11.0	SST	CG	N
0.328	8.33	3644	1.38	34.9	.296	7.5	.41	.07	1.2	31	.50	2.2	.17	4.3	0.016	0.4	9.50	MW	C	N
0.328	8.33	11452	1.38	34.9	.234	5.9	35	6.2	.34	8.6	12	53	.56	14.3	0.047	1.2	11.0	HD	C	Z
0.328	8.33	1905	1.38	34.9	.146	3.7	823	144	.08	2.0	64	284	1.00	25.4	0.091	2.3	11.0	SPR	CG	Z
0.328	8.33	10534	1.41	35.7	.266	6.8	3.7	.65	.89	23	3.3	15	.52	13.2	0.031	0.8	15.8	MW	C	Z
0.328	8.33	S-825	1.41	35.7	.236	6.0	21	3.6	.50	13	10	46	.64	16.4	0.046	1.2	14.0	SST	CG	N
0.328	8.33	12468	1.47	37.3	.284	7.2	.98	.17	1.2	29	1.1	5.1	.31	7.8	0.022	0.6	14.0	MW	CG	Z
0.328	8.33	KK-59	1.47	37.3	.228	5.8	35	6.1	.38	9.6	13	59	.70	17.8	0.050	1.3	14.0	SPR	CG	N
0.328	8.33	MM-72	1.50	38.1	.288	7.3	.87	.15	1.1	29	.98	4.4	.22	5.6	0.020	0.5	10.0	SST	C	N
0.328	8.33	S-1159	1.50	38.1	.278	7.1	1.8	.32	.98	25	1.8	8.0	.31	7.9	0.025	0.6	11.5	SST	C	N
0.328	8.33	12251	1.50	38.1	.268	6.8	2.7	.47	1.0	26	2.7	12	.50	12.6	0.030	0.8	16.5	SST	CG	N
0.328	8.33	VV-70	1.50	38.1	.266	6.8	3.0	.52	.88	22	2.6	12	.62	15.7	0.031	0.8	19.0	MW	C	Z
0.328	8.33	K-30	1.50	38.1	.252	6.4	8.5	1.5	.70	18	6.0	27	.59	15.0	0.038	1.0	14.5	SST	C	N
0.328	8.33	O-59	1.50	38.1	.250	6.4	8.6	1.5	.80	20	6.9	31	.70	17.8	0.039	1.0	18.0	SPR	CG	Z
0.328	8.33	Q-47	1.59	40.5	.260	6.6	5.0	.88	.96	24	4.8	21	.58	14.7	0.034	0.9	17.0	SPR	CG	N
0.328	8.33	A11-57	1.59	40.5	.256	6.5	14	2.4	.39	10	5.4	24	.36	9.1	0.036	0.9	9.00	SPR	C	Z
0.328	8.33	L-54	1.69	42.8	.234	5.9	21	3.7	.56	14	12	53	.80	20.3	0.047	1.2	17.0	SPR	CG	Z
0.328	8.33	RR-69	1.69	42.8	.184	4.7	149	26	.24	6.1	35	158	1.26	32.0	0.072	1.8	17.5	HD	CG	Z
0.328	8.33	12212	1.75	44.5	.244	6.2	16	2.8	.54	14	8.5	38	.59	14.9	0.042	1.1	14.0	SPR	CG	GI
0.328	8.33	N-104	1.75	44.5	.218	5.5	31	5.4	.49	12	15	66	1.27	32.1	0.055	1.4	23.0	SPR	CG	Z
0.328	8.33	Q-36	1.88	47.6	.278	7.1	.88	.15	1.3	34	1.2	5.2	.55	14.0	0.025	0.6	22.0	SST	C	N
0.328	8.33	12406	1.88	47.6	.246	6.2	9.5	1.7	.83	21	8.0	35	.86	21.9	0.041	1.0	20.0	SPR	C	Z
0.328	8.33	LL-24	1.88	47.6	.208	5.3	65	11	.35	8.8	22	99	1.02	25.9	0.060	1.5	17.0	SPR	CG	Z
0.328	8.33	2695	1.91	48.4	.184	4.7	146	26	.24	6.2	35	158	1.28	32.5	0.07					

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.328	8.33	B-92	2.69	68.2	.276	7.0	1.1	.19	2.0	52	2.2	9.7	.66	16.7	0.026	0.7	24.3	MW	C	N
0.328	8.33	S-3025	2.75	69.9	.288	7.3	.20	.03	2.0	51	.40	1.8	.75	19.1	0.020	0.5	36.5	SST	C	N
0.328	8.33	OO-75	2.75	69.9	.208	5.3	37	6.5	.56	14	21	94	1.50	38.1	0.060	1.5	25.0	SST	CG	N
0.328	8.33	B11-23	3.00	76.2	.236	6.0	15	2.6	.76	19	11	50	.99	25.1	0.046	1.2	21.5	SPR	CG	N
0.328	8.33	B17-173	3.22	81.8	.238	6.0	9.3	1.6	1.1	29	10	46	1.35	34.3	0.045	1.1	30.0	SPR	CG	Z
0.328	8.33	1934	3.38	85.7	.254	6.5	4.3	.76	1.4	35	5.9	26	1.05	26.5	0.037	0.9	27.3	SPR	C	Z
0.328	8.33	S-3074	4.13	104.8	.274	7.0	.80	.14	2.8	72	2.3	10	.90	23.0	0.027	0.7	32.5	SST	C	N
0.328	8.33	S-3099	4.25	108.0	.274	7.0	.63	.11	3.1	79	2.0	8.8	1.12	28.5	0.027	0.7	40.5	SST	C	N
0.328	8.33	K-54	4.25	108.0	.258	6.6	2.0	.34	2.4	61	4.7	21	1.44	36.4	0.035	0.9	40.0	SST	C	N
0.338	8.59	12753	1.48	37.7	.274	7.0	5.3	.92	.74	19	3.9	17	.42	10.6	0.032	0.8	12.0	SPR	C	N
0.343	8.71	W-99	.16	4.0	.295	7.5	6.5	1.1	.04	.91	.23	1.0	.12	3.0	0.024	0.6	4.00	SST	C	N
0.343	8.71	S-855	.19	4.8	.285	7.2	46	8.0	.06	1.5	2.7	12	.08	1.9	0.029	0.7	2.50	SST	C	N
0.343	8.71	S-1324	.25	6.4	.273	6.9	32	5.6	.08	1.9	2.4	11	.18	4.4	0.035	0.9	4.00	SST	C	N
0.343	8.71	U-95	.28	7.1	.283	7.2	19	3.3	.16	4.1	3.1	14	.12	3.0	0.030	0.8	4.00	MW	CG	N
0.343	8.71	PP-51	.28	7.1	.243	6.2	211	37	.06	1.4	12	53	.18	4.4	0.050	1.3	3.50	SST	CG	N
0.343	8.71	DD-77	.31	7.9	.315	8.0	.31	.05	.20	5.1	.06	.28	.11	2.8	0.014	0.4	7.00	MW	C	N
0.343	8.71	GG-54	.31	7.9	.295	7.5	9.8	1.7	.20	5.2	2.0	8.9	.11	2.7	0.024	0.6	3.50	MW	C	N
0.343	8.71	U-74	.31	7.9	.283	7.2	8.3	1.4	.10	2.6	.84	3.7	.21	5.3	0.030	0.8	6.00	SST	C	N
0.343	8.71	2731	.31	7.9	.275	7.0	65	11	.07	1.8	4.6	21	.14	3.5	0.034	0.9	3.00	SPR	C	Z
0.343	8.71	B7-25	.34	8.7	.303	7.7	3.9	.68	.27	6.8	1.0	4.6	.08	1.9	0.020	0.5	3.75	MW	CG	N
0.343	8.71	G-52	.34	8.7	.261	6.6	49	8.6	.14	3.5	6.8	30	.21	5.2	0.041	1.0	5.00	SPR	CG	Z
0.343	8.71	B-71	.38	9.5	.315	8.0	.52	.09	.29	7.4	.15	.67	.08	2.1	0.014	0.4	5.00	MW	C	Z
0.343	8.71	O-53	.38	9.5	.293	7.4	7.6	1.3	.23	5.8	1.7	7.7	.13	3.2	0.025	0.6	4.00	SST	C	N
0.343	8.71	NN-40	.38	9.5	.283	7.2	19	3.3	.23	5.7	4.3	19	.15	3.8	0.030	0.8	4.00	MW	C	Z
0.343	8.71	B14-33	.38	9.5	.277	7.0	13	2.4	.17	4.3	2.3	10	.21	5.2	0.033	0.8	6.25	SPR	CG	N
0.343	8.71	MM-76	.38	9.5	.233	5.9	192	34	.07	1.8	14	62	.30	7.7	0.055	1.4	4.50	SST	C	N
0.343	8.71	V-55	.38	9.5	.231	5.9	212	37	.08	2.0	17	74	.25	6.4	0.056	1.4	4.50	SST	CG	N
0.343	8.71	A-5	.41	10.3	.263	6.7	33	5.8	.19	4.7	6.1	27	.22	5.6	0.040	1.0	5.50	SST	CG	N
0.343	8.71	I-28	.41	10.3	.245	6.2	130	23	.10	2.5	13	57	.22	5.6	0.049	1.2	4.50	SPR	CG	N
0.343	8.71	1925	.44	11.1	.281	7.1	22	3.8	.22	5.7	4.9	22	.16	3.9	0.031	0.8	4.00	MW	C	Z
0.343	8.71	2950	.44	11.1	.275	7.0	33	5.7	.14	3.6	4.6	21	.17	4.3	0.034	0.9	4.00	SPR	C	Z
0.343	8.71	A12-3	.45	11.5	.263	6.7	48	8.4	.15	3.8	7.1	32	.23	5.8	0.040	1.0	4.75	SPR	C	N
0.343	8.71	W-97	.47	11.9	.275	7.0	19	3.4	.22	5.7	4.3	19	.20	5.2	0.034	0.9	5.00	SST	C	N
0.343	8.71	3873	.47	11.9	.273	6.9	6.7	1.2	.02	.56	.15	.66	.49	12.4	0.035	0.9	13.0	SPR	C	T
0.343	8.71	Q-98	.47	11.9	.265	6.7	16	2.8	.10	2.5	1.6	7.0	.37	9.4	0.039	1.0	8.50	SST	C	N
0.343	8.71	11451	.50	12.7	.305	7.7	2.4	.43	.40	10	.98	4.4	.10	2.5	0.019	0.5	4.25	MW	C	N
0.343	8.71	N-39	.50	12.7	.301	7.6	1.7	.29	.36	9.2	.60	2.7	.14	3.5	0.021	0.5	6.50	SST	CG	N
0.343	8.71	BB-56	.50	12.7	.295	7.5	4.3	.75	.36	9.0	1.5	6.7	.14	3.7	0.024	0.6	5.00	SST	C	N
0.343	8.71	2568	.50	12.7	.287	7.3	14	2.5	.26	6.5	3.6	16	.14	3.6	0.028	0.7	4.00	MW	C	Z
0.343	8.71	II-43	.50	12.7	.283	7.2	3.3	.58	.07	1.7	.21	.95	.44	11.0	0.030	0.8	13.5	MW	C	N
0.343	8.71	S-114	.50	12.7	.279	7.1	13	2.3	.27	6.8	3.6	16	.20	5.1	0.032	0.8	5.25	SST	C	N
0.343	8.71	I-86	.50	12.7	.275	7.0	19	3.3	.23	5.8	4.3	19	.20	5.2	0.034	0.9	5.00	SST	C	N
0.343	8.71	3453	.50	12.7	.273	6.9	25	4.3	.20	5.0	4.8	21	.21	5.3	0.035	0.9	5.00	SPR	C	GI
0.343	8.71	MM-64	.50	12.7	.263	6.7	23	4.0	.22	5.6	5.1	23	.28	7.1	0.040	1.0	7.00	SST	CG	N
0.343	8.71	10882	.50	12.7	.251	6.4	89	16	.17	4.2	15	66	.22	5.6	0.046	1.2	4.75	MW	CG	N
0.343	8.71	MM-35	.50	12.7	.243	6.2	84	15	.15	3.8	13	57	.31	7.9	0.050	1.3	6.25	SPR	CG	Z
0.343	8.71	DD-30	.50	12.7	.243	6.2	79	14	.15	3.8	12	53	.30	7.6	0.050	1.3	6.00	SST	CG	N
0.343	8.71	G-93	.50	12.7	.235	6.0	110	19	.14	3.4	15	67	.32	8.2	0.054	1.4	6.00	SST	CG	N
0.343	8.71	BB-39	.50	12.7	.183	4.6	1177	206	.04	.99	46	204	.38	9.7	0.080	2.0	4.75	SPR	CG	N
0.343	8.71	B17-145	.53	13.5	.313	8.0	.25	.04	.36	9.2	.09	.40	.17	4.3	0.015	0.4	10.3	MW	C	N
0.343	8.71	L-89	.53	13.5	.299	7.6	2.9	.51	.39	9.9	1.1	5.0	.14	3.6	0.022	0.6	5.50	MW	C	Z
0.343	8.71	H-88	.53	13.5	.293	7.4	8.7	1.5	.30	7.5	2.6	11	.13	3.2	0.025	0.6	4.00	MW	C	N
0.343	8.71	A10-69	.53	13.5	.285	7.2	5.3	.93	.31	8.0	1.7	7.4	.22	5.5	0.029	0.7	7.50	SST	CG	N
0.343	8.71	3509	.53	13.5	.283	7.2	11	1.9	.37	9.3	4.0	18	.17	4.2	0.030	0.8	5.50	MW	CG	Z
0.343	8.71	Q-97	.53	13.5	.283	7.2	6.7	1.2	.29	7.4	2.0	8.7	.24	6.1	0.030	0.8	7.00	SST	C	N
0.343	8.71	II-32	.53	13.5	.279	7.1	9.4	1.6	.32	8.0	2.9	13	.22	5.5	0.032	0.8	6.75	SST	CG	N
0.343	8.71	B-67	.53	13.5	.279	7.1	10	1.8	.28	7.0	2.8	12	.26	6.5	0.032	0.8	7.00	HD	C	N
0.343	8.71	JJ-61	.53	13.5	.259	6.6	36	6.2	.22	5.5	7.7	34	.25	6.4	0.042	1.1	6.00	SST	CG	N
0.343	8.71	1655	.53	13.5	.189	4.8	716	125	.06	1.5	41	183	.44	11.3	0.077	2.0	5.75	SPR	CG	Z
0.343	8.71	10730	.56	14.3	.309	7.8	1.4	.24	.47	12	.65	2.9	.09	2.4	0.017	0.4	4.50	MW	C	N
0.343	8.71	S-1040	.56	14.3	.309	7.8	1.0	.18	.46	12	.46	2.1	.10	2.6	0.017	0.4	5.00	SST	C	N
0.343	8.71	S-3122	.56	14.3	.301	7.6	1.2	.21	.37	9.5	.45	2.0	.19	4.8	0.021	0.5	8.00	SST	C	N
0.343	8.71	11342	.56	14.3	.293	7.4	3.3	.57	.39	10	1.3	5.7	.17	4.3	0.025	0.6	6.75	SST	CG	N
0.343	8.71	K-71	.56	14.3	.291	7.4	4.3	.76	.39	9.8	1.7	7.5	.18	4.5	0.026	0.7	6.75	MW	CG	N
0.343	8.71	KK-76	.56	14.3	.279	7.1	14	2.5	.27	6.8	3.9	17	.21	5.3	0.032	0.8	5.50	SPR	C	N
0.343	8.71	G-87	.56	14.3	.261	6.6	37	6.5	.21	5.3	7.6	34	.25	6.2	0.041	1.0	6.00	SPR	CG	Z
0.343	8.71	Q-30	.63	15.9	.303	7.7	1.1	.20	.45	11	.51	2.3	.18	4.6	0.020	0.5	8.00	MW	C	N
0.343	8.71	A-60-A	.63	15.9	.293	7.4	1.9	.34	.35	8.9	.68	3.0	.28	7.0	0.025	0.6	10.0	SST	C	N
0.343	8.71	MM-68	.63	15.9	.279	7.1	8.7	1.5	.40	10	3.5	16	.22	5.7	0.032	0.8	7.00	SST	CG	N
0.343	8.71	N-46	.63	15.9	.273	6.9	18	3.2	.26	6.6	4.8	21	.21	5.3	0.035	0.9	6.00			




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.343	8.71	B2-64	.66	16.7	.221	5.6	197	35	.16	4.0	31	139	.40	10.1	0.061	1.5	6.50	MW	CG	Z
0.343	8.71	B-68	.69	17.4	.291	7.4	3.7	.64	.48	12	1.8	7.8	.21	5.3	0.026	0.7	7.00	SST	C	N
0.343	8.71	RR-64	.69	17.4	.271	6.9	14	2.4	.37	9.5	5.2	23	.29	7.3	0.036	0.9	8.00	SPR	CG	Z
0.343	8.71	4114	.69	17.4	.263	6.7	38	6.6	.19	4.8	7.1	32	.26	6.6	0.040	1.0	5.50	SPR	C	Z
0.343	8.71	K-89	.69	17.4	.261	6.6	23	4.1	.31	7.8	7.2	32	.31	7.8	0.041	1.0	7.50	SST	CG	N
0.343	8.71	B9-46	.69	17.4	.261	6.6	37	6.5	.21	5.3	7.6	34	.25	6.2	0.041	1.0	6.00	SPR	CG	N
0.343	8.71	YY-59	.69	17.4	.241	6.1	130	23	.10	2.6	13	60	.26	6.5	0.051	1.3	5.00	SPR	CG	Z
0.343	8.71	B-86	.72	18.2	.299	7.6	2.2	.39	.56	14	1.2	5.5	.15	3.9	0.022	0.6	6.00	SST	C	N
0.343	8.71	10106	.72	18.3	.263	6.7	33	5.8	.21	5.5	7.1	32	.28	7.1	0.040	1.0	6.00	SPR	C	N
0.343	8.71	S-1094	.75	19.1	.317	8.1	.14	.02	.62	16	.09	.39	.13	3.3	0.013	0.3	9.00	SST	C	N
0.343	8.71	S-1002	.75	19.1	.303	7.7	1.5	.26	.61	15	.91	4.0	.14	3.6	0.020	0.5	6.00	SST	C	N
0.343	8.71	1527	.75	19.1	.297	7.5	2.7	.48	.58	15	1.6	7.0	.17	4.4	0.023	0.6	6.50	MW	C	Z
0.343	8.71	S-309	.75	19.1	.293	7.4	3.6	.63	.48	12	1.7	7.7	.18	4.6	0.025	0.6	6.25	SST	C	N
0.343	8.71	PP-58	.75	19.1	.287	7.3	6.1	1.1	.39	10	2.4	11	.17	4.3	0.028	0.7	6.00	SST	CG	N
0.343	8.71	H-79	.75	19.1	.283	7.2	8.3	1.4	.36	9.1	3.0	13	.18	4.6	0.030	0.8	6.00	SST	C	N
0.343	8.71	GG-98	.75	19.1	.275	7.0	9.4	1.7	.44	11	4.2	19	.31	7.8	0.034	0.9	8.00	SST	C	N
0.343	8.71	A10-47	.75	19.1	.269	6.8	17	2.9	.34	8.7	5.7	25	.28	7.2	0.037	0.9	7.75	SPR	CG	N
0.343	8.71	10804	.75	19.1	.267	6.8	18	3.1	.35	8.8	6.1	27	.30	7.7	0.038	1.0	8.00	SPR	CG	BO
0.343	8.71	S-1180	.75	19.1	.267	6.8	15	2.7	.37	9.5	5.7	25	.34	8.7	0.038	1.0	8.00	SST	C	N
0.343	8.71	I-20	.75	19.1	.257	6.5	29	5.0	.29	7.3	8.2	37	.32	8.2	0.043	1.1	7.50	SST	CG	N
0.343	8.71	GG-70	.75	19.1	.243	6.2	79	14	.15	3.8	12	53	.30	7.6	0.050	1.3	6.00	SST	CG	N
0.343	8.71	CC-100	.75	19.1	.239	6.1	62	11	.22	5.5	13	60	.42	10.6	0.052	1.3	8.00	SST	CG	N
0.343	8.71	Z-57	.75	19.1	.229	5.8	100	17	.19	4.7	19	83	.48	12.3	0.057	1.4	8.50	SPR	CG	Z
0.343	8.71	B-100	.75	19.1	.227	5.8	108	19	.18	4.6	20	87	.49	12.5	0.058	1.5	8.50	SPR	CG	N
0.343	8.71	B14-35	.75	19.1	.223	5.7	117	21	.18	4.7	22	96	.54	13.7	0.060	1.5	9.00	SPR	CG	N
0.343	8.71	FF-69	.75	19.1	.223	5.7	113	20	.19	4.8	22	96	.56	14.1	0.060	1.5	9.25	SPR	CG	Z
0.343	8.71	S-3127	.75	19.1	.219	5.6	145	25	.15	3.9	22	99	.48	12.2	0.062	1.6	7.75	SST	CG	N
0.343	8.71	OO-36	.78	19.8	.303	7.7	1.5	.27	.63	16	.96	4.3	.15	3.8	0.020	0.5	6.50	MW	C	N
0.343	8.71	10817	.78	19.8	.275	7.0	14	2.5	.44	11	6.4	29	.22	5.6	0.034	0.9	6.50	MW	CG	Z
0.343	8.71	I-90	.78	19.8	.255	6.5	33	5.7	.27	6.9	8.8	39	.33	8.4	0.044	1.1	7.50	SST	CG	N
0.343	8.71	12641	.78	19.8	.241	6.1	49	8.5	.26	6.6	13	56	.46	11.7	0.051	1.3	9.00	SST	CG	N
0.343	8.71	A-92	.81	20.6	.311	7.9	.60	.10	.69	18	.41	1.8	.12	3.0	0.016	0.4	6.50	MW	C	N
0.343	8.71	KK-84	.81	20.6	.287	7.3	2.9	.51	.49	12	1.4	6.3	.32	8.2	0.028	0.7	10.5	SST	C	N
0.343	8.71	M-120	.81	20.6	.277	7.0	17	2.9	.24	6.0	3.9	17	.20	5.0	0.033	0.8	5.00	SST	C	N
0.343	8.71	WW-49	.81	20.6	.277	7.0	17	2.9	.24	6.0	3.9	17	.20	5.0	0.033	0.8	5.00	SST	C	N
0.343	8.71	XX-22	.81	20.6	.277	7.0	7.6	1.3	.47	12	3.6	16	.35	8.8	0.033	0.8	9.50	SPR	C	GI
0.343	8.71	S-1232	.81	20.6	.273	6.9	12	2.0	.39	9.8	4.5	20	.26	6.7	0.035	0.9	7.50	SST	CG	N
0.343	8.71	3020	.81	20.6	.235	6.0	84	15	.19	4.8	16	71	.49	12.3	0.054	1.4	8.00	HD	C	Z
0.343	8.71	A-6	.81	20.6	.223	5.7	137	24	.16	4.0	22	96	.48	12.2	0.060	1.5	8.00	HD	CG	Z
0.343	8.71	B5-17	.84	21.4	.279	7.1	13	2.2	.31	7.8	3.9	17	.22	5.7	0.032	0.8	6.00	SPR	C	N
0.343	8.71	A10-66	.84	21.4	.219	5.6	160	28	.15	3.8	24	105	.50	12.6	0.062	1.6	8.00	SPR	CG	Z
0.343	8.71	OO-59	.88	22.2	.311	7.9	.29	.05	.70	18	.20	.91	.18	4.5	0.016	0.4	10.0	SST	C	N
0.343	8.71	S-3105	.88	22.2	.303	7.7	.79	.14	.67	17	.53	2.3	.21	5.3	0.020	0.5	9.50	SST	C	N
0.343	8.71	II-76	.88	22.2	.303	7.7	.34	.06	.42	11	.14	.63	.46	11.7	0.020	0.5	22.0	MW	C	N
0.343	8.71	HH-25	.88	22.2	.293	7.4	3.9	.68	.67	17	2.6	11	.19	4.8	0.025	0.6	6.50	MW	C	N
0.343	8.71	S-3081	.88	22.2	.293	7.4	3.8	.66	.46	12	1.7	7.7	.18	4.4	0.025	0.6	6.00	SST	C	N
0.343	8.71	BB-72	.88	22.2	.293	7.4	2.4	.43	.67	17	1.6	7.2	.21	5.2	0.025	0.6	8.25	SST	CG	N
0.343	8.71	L-77	.88	22.2	.285	7.2	4.4	.77	.60	15	2.6	12	.28	7.0	0.029	0.7	9.50	MW	CG	GI
0.343	8.71	Z-1	.88	22.2	.283	7.2	6.0	1.1	.49	13	3.0	13	.26	6.5	0.030	0.8	7.50	SST	C	N
0.343	8.71	A15-39	.88	22.2	.281	7.1	7.8	1.4	.42	11	3.3	15	.22	5.5	0.031	0.8	7.00	SST	CG	N
0.343	8.71	Q-62	.88	22.2	.273	6.9	7.6	1.3	.51	13	3.8	17	.37	9.3	0.035	0.9	10.5	SST	CG	N
0.343	8.71	11398	.88	22.2	.269	6.8	12	2.1	.44	11	5.3	24	.37	9.4	0.037	0.9	9.00	SST	C	N
0.343	8.71	B6-23	.88	22.2	.269	6.8	16	2.9	.34	8.7	5.7	25	.28	7.2	0.037	0.9	7.70	SPR	CG	N
0.343	8.71	O-78	.88	22.2	.269	6.8	16	2.7	.36	9.2	5.7	25	.33	8.5	0.037	0.9	8.00	SPR	C	GI
0.343	8.71	10064	.88	22.2	.261	6.6	20	3.4	.39	9.9	7.6	34	.39	9.9	0.041	1.0	9.50	SPR	CG	Z
0.343	8.71	3520	.88	22.2	.243	6.2	65	11	.27	6.9	18	79	.38	9.5	0.050	1.3	7.50	MW	CG	Z
0.343	8.71	MM-95	.88	22.2	.203	5.2	242	42	.13	3.3	32	141	.63	16.0	0.070	1.8	9.00	SPR	CG	N
0.343	8.71	MM-86	.88	22.2	.199	5.1	307	54	.10	2.7	32	143	.54	13.7	0.072	1.8	7.50	SST	CG	N
0.343	8.71	B12-25	.88	22.2	.191	4.9	315	55	.12	2.9	36	161	.76	19.3	0.076	1.9	10.0	SPR	CG	N
0.343	8.71	H-82	.91	23.0	.261	6.6	11	1.8	.21	5.3	2.2	9.8	.70	17.7	0.041	1.0	16.0	SPR	C	Z
0.343	8.71	2604	.91	23.0	.249	6.3	39	6.8	.41	10	16	70	.42	10.7	0.047	1.2	9.00	MW	CG	Z
0.343	8.71	O-145	.91	23.0	.245	6.2	59	10	.22	5.5	13	57	.37	9.3	0.049	1.2	7.50	SPR	CG	N
0.343	8.71	Z-4	.94	23.8	.293	7.4	2.5	.44	.69	17	1.7	7.6	.25	6.4	0.025	0.6	9.00	MW	C	N
0.343	8.71	U-37	.94	23.8	.273	6.9	11	1.9	.42	11	4.5	20	.28	7.1	0.035	0.9	8.00	SST	CG	N
0.343	8.71	JJ-86	.94	23.8	.259	6.6	21	3.6	.40	10	8.2	36	.46	11.7	0.042	1.1	10.0	SPR	C	Z
0.343	8.71	L-69	.94	23.8	.247	6.3	42	7.4	.28	7.2	12	54	.48	12.2	0.048	1.2	9.00	SPR	C	Z
0.343	8.71	PP-29	.94	23.8	.203	5.2	201	35	.15	3.8	30	132	.67	16.9	0.070	1.8	9.50	SST	CG	N
0.343	8.71	PP-28	.97	24.6	.263	6.7	20	3.6	.35	8.9	7.1	32	.34	8.6	0.040	1.0	8.50	SPR	CG	Z
0.343	8.71	L-13	.97	24.6	.249	6.3	34	5.9	.34	8.6	11	51	.52	13.1	0.047	1.2	10.0	SPR	C	Z
0.343	8.71	3658	1.00	25.4	.305	7.7	.79	.14	.81	21	.64	2.8	.19	4.8	0.019	0.5	9.00	MW	C	GI
0.343	8.71	11469	1.00	25.4	.303	7.7</														

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.343	8.71	K-22	1.00	25.4	.247	6.3	37	6.5	.33	8.3	12	54	.48	12.2	0.048	1.2	10.0	SPR	CG	N
0.343	8.71	2786	1.00	25.4	.241	6.1	39	6.8	.34	8.8	13	60	.61	15.5	0.051	1.3	12.0	SPR	CG	Z
0.343	8.71	K-14	1.00	25.4	.231	5.9	66	12	.27	6.7	18	78	.62	15.6	0.056	1.4	11.0	SPR	CG	GI
0.343	8.71	S-268	1.00	25.4	.225	5.7	94	17	.20	5.2	19	86	.53	13.5	0.059	1.5	9.00	SST	CG	N
0.343	8.71	S-3097	1.00	25.4	.173	4.4	543	95	.09	2.4	51	225	.77	19.4	0.085	2.2	9.00	SST	CG	N
0.343	8.71	Q-5	1.03	26.2	.295	7.5	1.5	.26	.74	19	1.1	4.9	.29	7.3	0.024	0.6	12.0	MW	CG	N
0.343	8.71	PP-25	1.03	26.2	.283	7.2	4.2	.74	.67	17	2.8	13	.36	9.1	0.030	0.8	11.0	MW	C	Z
0.343	8.71	S-1056	1.06	27.0	.291	7.4	2.2	.39	.78	20	1.7	7.7	.29	7.3	0.026	0.7	10.0	SST	C	N
0.343	8.71	S-1456	1.06	27.0	.281	7.1	4.2	.74	.72	18	3.0	14	.34	8.7	0.031	0.8	11.0	SST	CG	N
0.343	8.71	A14-6	1.06	27.0	.277	7.0	6.8	1.2	.58	15	3.9	17	.31	8.0	0.033	0.8	9.50	SST	CG	N
0.343	8.71	S-1695	1.06	27.0	.273	6.9	11	1.9	.42	11	4.5	20	.32	8.0	0.035	0.9	8.00	SST	C	N
0.343	8.71	S-1347	1.06	27.0	.269	6.8	8.6	1.5	.62	16	5.3	24	.43	10.8	0.037	0.9	11.5	SST	CG	N
0.343	8.71	L-53	1.06	27.0	.263	6.7	19	3.3	.38	9.6	7.1	32	.36	9.1	0.040	1.0	9.00	SPR	CG	Z
0.343	8.71	4202	1.06	27.0	.253	6.4	25	4.3	.41	10	10	45	.54	13.7	0.045	1.1	11.0	SPR	C	Z
0.343	8.71	I-21	1.06	27.0	.253	6.4	17	2.9	.40	10	6.7	30	.66	16.9	0.045	1.1	13.8	SST	CG	N
0.343	8.71	CC-85	1.06	27.0	.235	6.0	72	13	.22	5.6	16	71	.49	12.3	0.054	1.4	9.00	SPR	CG	Z
0.343	8.71	OO-70	1.13	28.6	.283	7.2	4.2	.74	.71	18	3.0	13	.30	7.6	0.030	0.8	10.0	SST	CG	N
0.343	8.71	M-76	1.13	28.6	.273	6.9	9.2	1.6	.52	13	4.8	21	.35	8.9	0.035	0.9	10.0	SPR	CG	N
0.343	8.71	S-1057	1.13	28.6	.267	6.8	10	1.8	.56	14	5.7	25	.42	10.6	0.038	1.0	11.0	SST	CG	N
0.343	8.71	10387	1.19	30.2	.299	7.6	1.3	.22	.97	25	1.2	5.5	.22	5.6	0.022	0.6	10.0	MW	CG	Z
0.343	8.71	10273	1.19	30.2	.219	5.6	128	22	.19	4.7	24	105	.59	15.0	0.062	1.6	9.50	SPR	CG	Z
0.343	8.71	W-11	1.22	31.0	.273	6.9	7.1	1.2	.63	16	4.5	20	.39	9.8	0.035	0.9	11.0	SST	CG	N
0.343	8.71	S-1223	1.25	31.8	.279	7.1	4.4	.76	.82	21	3.6	16	.42	10.6	0.032	0.8	12.0	SST	C	N
0.343	8.71	12499	1.25	31.8	.275	7.0	8.7	1.5	.49	13	4.3	19	.32	8.2	0.034	0.9	8.50	SST	C	N
0.343	8.71	11256	1.25	31.8	.273	6.9	11	2.0	.59	15	6.6	30	.33	8.4	0.035	0.9	8.50	MW	C	Z
0.343	8.71	CC-7	1.25	31.8	.259	6.6	15	2.6	.55	14	8.2	36	.55	13.9	0.042	1.1	13.0	SPR	CG	GI
0.343	8.71	11257	1.25	31.8	.259	6.6	18	3.2	.42	11	7.7	34	.46	11.7	0.042	1.1	10.0	SST	C	N
0.343	8.71	B2-40	1.25	31.8	.255	6.5	23	4.0	.39	9.9	8.8	39	.47	12.0	0.044	1.1	9.75	SST	C	N
0.343	8.71	3842	1.25	31.8	.159	4.0	724	127	.09	2.2	64	285	1.01	25.7	0.092	2.3	11.0	SPR	CG	GI
0.343	8.71	3505	1.28	32.5	.273	6.9	7.4	1.3	.83	21	6.1	27	.46	11.6	0.035	0.9	12.0	MW	C	Z
0.343	8.71	B9-23	1.31	33.3	.257	6.5	16	2.8	.55	14	8.8	39	.62	15.8	0.043	1.1	13.5	SPR	C	N
0.343	8.71	L-44	1.38	34.9	.295	7.5	1.6	.28	1.0	26	1.6	7.2	.26	6.7	0.024	0.6	10.0	SST	C	N
0.343	8.71	3884	1.38	34.9	.289	7.3	2.2	.39	1.0	25	2.2	9.8	.38	9.6	0.027	0.7	13.0	MW	C	Z
0.343	8.71	3457	1.38	34.9	.279	7.1	7.7	1.4	.70	18	5.4	24	.30	7.7	0.032	0.8	8.50	MW	C	Z
0.343	8.71	L-32	1.44	36.5	.293	7.4	1.4	.24	1.0	27	1.4	6.4	.39	9.9	0.025	0.6	14.6	MW	C	Z
0.343	8.71	2594	1.44	36.5	.249	6.3	27	4.7	.42	11	11	51	.56	14.3	0.047	1.2	12.0	HD	CG	Z
0.343	8.71	10519	1.47	37.3	.259	6.6	14	2.4	.59	15	8.2	36	.62	15.7	0.042	1.1	13.8	SPR	C	Z
0.343	8.71	S-3101	1.50	38.1	.293	7.4	1.4	.25	1.2	29	1.6	7.3	.34	8.7	0.025	0.6	12.8	SST	C	N
0.343	8.71	1951	1.50	38.1	.283	7.2	3.5	.60	1.1	27	3.7	17	.42	10.7	0.030	0.8	13.0	MW	C	Z
0.343	8.71	12630	1.50	38.1	.283	7.2	3.8	.66	1.1	28	4.2	19	.39	9.9	0.030	0.8	12.0	MW	C	Z
0.343	8.71	3890	1.50	38.1	.273	6.9	7.0	1.2	.68	17	4.8	21	.47	12.0	0.035	0.9	12.5	SPR	C	Z
0.343	8.71	UU-47	1.50	38.1	.269	6.8	6.3	1.1	.83	21	5.2	23	.67	16.9	0.037	0.9	17.0	SPR	C	Z
0.343	8.71	5	1.50	38.1	.249	6.3	23	3.9	.50	13	11	51	.71	17.9	0.047	1.2	14.0	HD	C	Z
0.343	8.71	S-879	1.50	38.1	.249	6.3	19	3.3	.57	15	11	47	.69	17.5	0.047	1.2	14.8	SST	CG	N
0.343	8.71	11453	1.50	38.1	.219	5.6	113	20	.21	5.3	24	105	.65	16.5	0.062	1.6	10.5	HD	CG	Z
0.343	8.71	B2-53	1.50	38.1	.213	5.4	96	17	.28	7.2	27	120	.94	24.0	0.065	1.7	14.5	SPR	CG	N
0.343	8.71	12405	1.53	38.9	.311	7.9	.35	.06	1.4	35	.47	2.1	.17	4.4	0.016	0.4	9.75	MW	C	Z
0.343	8.71	11546	1.53	38.9	.257	6.5	17	3.0	.51	13	8.8	39	.58	14.7	0.043	1.1	12.5	SPR	CG	Z
0.343	8.71	10188	1.56	39.7	.303	7.7	.49	.09	1.2	31	.60	2.7	.34	8.6	0.020	0.5	16.0	MW	C	Z
0.343	8.71	QQ-36	1.56	39.7	.271	6.9	5.6	.97	.91	23	5.1	23	.65	16.5	0.036	0.9	17.0	SPR	C	Z
0.343	8.71	S-1099	1.56	39.7	.247	6.3	18	3.1	.64	16	11	50	.79	20.1	0.048	1.2	16.5	SST	CG	N
0.343	8.71	A15-36	1.56	39.7	.241	6.1	23	4.0	.55	14	13	56	.87	22.0	0.051	1.3	17.0	SST	CG	N
0.343	8.71	S-210	1.59	40.5	.287	7.3	1.6	.27	1.1	27	1.7	7.4	.53	13.5	0.028	0.7	18.0	SST	C	N
0.343	8.71	S-452	1.63	41.3	.303	7.7	.20	.04	.98	25	.20	.87	.65	16.5	0.020	0.5	31.5	SST	C	N
0.343	8.71	S-15	1.63	41.3	.273	6.9	6.4	1.1	.70	18	4.5	20	.46	11.6	0.035	0.9	12.0	SST	C	N
0.343	8.71	HH-58	1.63	41.3	.263	6.7	9.4	1.7	.75	19	7.1	32	.64	16.3	0.040	1.0	16.0	SPR	CG	N
0.343	8.71	KK-73	1.63	41.3	.243	6.2	27	4.7	.47	12	13	57	.76	19.4	0.050	1.3	15.3	SPR	CG	Z
0.343	8.71	S-1384	1.75	44.5	.303	7.7	.46	.08	1.4	36	.65	2.9	.32	8.1	0.020	0.5	15.0	SST	C	N
0.343	8.71	S-1492	1.81	46.0	.247	6.3	14	2.5	.79	20	11	50	.96	24.4	0.048	1.2	20.0	SST	CG	N
0.343	8.71	2933	1.81	46.0	.227	5.8	40	7.0	.49	12	20	87	1.13	28.7	0.058	1.5	19.5	SPR	CG	Z
0.343	8.71	2683	1.91	48.4	.227	5.8	50	8.8	.39	9.9	20	87	.93	23.6	0.058	1.5	16.0	SPR	CG	Z
0.343	8.71	11199	2.00	50.8	.293	7.4	.70	.12	1.3	33	.91	4.0	.70	17.8	0.025	0.6	27.0	MW	C	Z
0.343	8.71	1819	2.00	50.8	.279	7.1	3.1	.55	1.4	35	4.4	19	.61	15.4	0.032	0.8	18.0	MW	C	Z
0.343	8.71	B14-27	2.00	50.8	.275	7.0	4.3	.76	1.1	27	4.6	21	.61	15.5	0.034	0.9	17.0	SPR	C	Z
0.343	8.71	M-10	2.00	50.8	.271	6.9	4.4	.77	1.2	30	5.2	23	.79	20.1	0.036	0.9	21.0	SPR	C	N
0.343	8.71	A-76	2.00	50.8	.263	6.7	7.8	1.4	.91	23	7.1	32	.76	19.3	0.040	1.0	19.0	SPR	CG	Z
0.343	8.71	CC-71	2.00	50.8	.263	6.7	9.4	1.7	.75	19	7.1	32	.68	17.3	0.040	1.0	16.0	SPR	C	N
0.343	8.71	3442	2.00	50.8	.209	5.3	73	13	.41	10	29	131	1.41	35.7	0.067	1.7	21.0	SPR	CG	Z
0.343	8.71	11466	2.13	54.0	.293	7.4	.69	.12	1.5	38	1.0	4.6	.64	16.2	0.025	0.6	24.5			




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.343	8.71	11880	3.00	76.2	.291	7.4	.76	.13	2.3	58	1.8	7.8	.70	17.8	0.026	0.7	26.0	SST	C	N
0.343	8.71	QQ-52	3.00	76.2	.253	6.4	6.9	1.2	1.4	34	9.4	42	1.40	35.4	0.045	1.1	30.0	SST	C	Z
0.343	8.71	10105	3.13	79.4	.289	7.3	.73	.13	2.2	55	1.6	7.0	.97	24.7	0.027	0.7	35.0	MW	C	Z
0.343	8.71	1723	3.13	79.4	.279	7.1	2.3	.40	1.7	43	3.9	17	.80	20.3	0.032	0.8	24.0	SPR	C	N
0.343	8.71	S-434	4.13	104.8	.253	6.4	6.8	1.2	1.4	35	9.4	42	1.41	35.9	0.045	1.1	30.3	SST	C	N
0.343	8.71	4113	4.75	120.7	.281	7.1	1.6	.27	3.1	79	4.9	22	.96	24.4	0.031	0.8	30.0	MW	C	Z
0.343	8.71	B8-55	4.88	123.8	.247	6.3	8.4	1.5	1.4	37	12	54	1.85	46.9	0.048	1.2	37.5	SPR	C	Z
0.343	8.71	10546	5.25	133.4	.243	6.2	8.5	1.5	1.5	38	13	57	2.25	57.2	0.050	1.3	44.0	SPR	C	Z
0.343	8.71	1912	5.75	146.1	.263	6.7	2.5	.44	2.8	72	7.1	32	2.23	56.6	0.040	1.0	54.8	SPR	C	GI
0.350	8.89	B4-63	.62	15.8	.286	7.3	4.3	.75	.21	5.2	.88	3.9	.42	10.6	0.032	0.8	13.0	MW	CG	BO
0.350	8.89	12705	1.30	32.9	.260	6.6	24	4.2	.38	9.7	9.2	41	.47	12.0	0.045	1.1	9.50	SST	C	N
0.350	8.89	12752	1.87	47.5	.308	7.8	.49	.09	1.5	37	.72	3.2	.40	10.1	0.021	0.5	18.0	MW	C	N
0.360	9.14	MM-63	.25	6.4	.340	8.6	.07	.01	.18	4.6	.01	.06	.07	1.8	0.010	0.3	6.00	SST	C	N
0.360	9.14	2899	.25	6.4	.330	8.4	.60	.10	.16	4.1	.10	.42	.09	2.3	0.015	0.4	5.00	MW	C	Z
0.360	9.14	I-27	.25	6.4	.296	7.5	43	7.5	.09	2.2	3.7	16	.13	3.3	0.032	0.8	3.00	HD	C	N
0.360	9.14	L-66	.25	6.4	.284	7.2	91	16	.06	1.6	5.8	26	.11	2.9	0.038	1.0	3.00	SPR	CG	Z
0.360	9.14	I-53	.25	6.4	.280	7.1	99	17	.06	1.6	6.4	28	.16	4.1	0.040	1.0	3.00	SST	C	N
0.360	9.14	AA-93	.25	6.4	.266	6.8	201	35	.05	1.3	10	45	.14	3.6	0.047	1.2	3.00	SST	CG	N
0.360	9.14	PP-39	.34	8.7	.320	8.1	1.3	.23	.22	5.7	.29	1.3	.12	3.0	0.020	0.5	6.00	SST	CG	N
0.360	9.14	HH-45	.34	8.7	.300	7.6	13	2.3	.21	5.3	2.7	12	.14	3.4	0.030	0.8	4.50	MW	CG	Z
0.360	9.14	B1-1	.38	9.5	.314	8.0	3.5	.62	.24	6.0	.84	3.7	.14	3.5	0.023	0.6	5.00	MW	C	Z
0.360	9.14	10849	.38	9.5	.296	7.5	25	4.3	.21	5.3	5.1	23	.12	3.0	0.032	0.8	3.75	MW	CG	Z
0.360	9.14	G-54	.38	9.5	.292	7.4	28	4.9	.16	4.0	4.4	20	.17	4.3	0.034	0.9	4.00	SPR	C	N
0.360	9.14	M-142	.38	9.5	.286	7.3	40	7.1	.13	3.4	5.4	24	.19	4.7	0.037	0.9	4.00	SPR	C	N
0.360	9.14	2502	.38	9.5	.256	6.5	182	32	.10	2.6	19	84	.21	5.3	0.052	1.3	4.00	MW	CG	Z
0.360	9.14	71064	.38	9.7	.296	7.5	25	4.4	.20	5.2	5.1	23	.12	3.0	0.032	0.8	3.75	MW	CG	N
0.360	9.14	71064S	.38	9.7	.296	7.5	21	3.7	.16	4.1	3.4	15	.12	3.0	0.032	0.8	3.75	SST	CG	N
0.360	9.14	NN-35	.41	10.3	.300	7.6	7.1	1.2	.23	5.7	1.6	7.1	.18	4.6	0.030	0.8	6.00	SST	CG	N
0.360	9.14	TT-33	.41	10.3	.288	7.3	19	3.3	.16	4.1	3.1	14	.24	6.2	0.036	0.9	5.75	SPR	C	Z
0.360	9.14	J-14	.41	10.3	.278	7.1	32	5.5	.12	3.0	3.8	17	.29	7.3	0.041	1.0	6.00	SPR	C	Z
0.360	9.14	LL-67	.41	10.3	.270	6.9	84	15	.11	2.7	9.0	40	.18	4.6	0.045	1.1	4.00	SST	CG	N
0.360	9.14	G-51	.41	10.3	.250	6.4	187	33	.09	2.2	16	71	.25	6.3	0.055	1.4	4.50	SPR	CG	Z
0.360	9.14	K-87	.41	10.3	.222	5.6	594	104	.05	1.3	31	137	.29	7.4	0.069	1.8	4.25	SPR	CG	Z
0.360	9.14	10956	.44	11.1	.314	8.0	4.7	.83	.32	8.1	1.5	6.6	.12	3.1	0.023	0.6	4.25	MW	C	N
0.360	9.14	II-83	.44	11.1	.298	7.6	5.5	.95	.16	4.0	.87	3.9	.28	7.1	0.031	0.8	8.00	SST	C	N
0.360	9.14	G-45	.44	11.1	.282	7.2	41	7.1	.16	3.9	6.3	28	.21	5.4	0.039	1.0	4.50	SPR	C	Z
0.360	9.14	I-15	.44	11.1	.280	7.1	45	7.9	.15	3.8	6.8	30	.18	4.6	0.040	1.0	4.50	SPR	CG	Z
0.360	9.14	FF-41	.44	11.1	.276	7.0	47	8.2	.17	4.3	7.8	35	.21	5.3	0.042	1.1	5.00	SPR	CG	Z
0.360	9.14	S-1505	.44	11.1	.266	6.8	67	12	.15	3.9	10	45	.24	6.0	0.047	1.2	5.00	SST	CG	N
0.360	9.14	S-1100	.44	11.1	.262	6.7	60	11	.14	3.7	8.7	39	.29	7.5	0.049	1.2	6.00	SST	CG	N
0.360	9.14	AA-95	.44	11.1	.262	6.7	93	16	.13	3.4	12	55	.25	6.2	0.049	1.2	5.00	SPR	CG	N
0.360	9.14	JJ-56	.44	11.1	.250	6.4	187	33	.09	2.2	16	71	.30	7.7	0.055	1.4	4.50	SPR	C	N
0.360	9.14	71027	.44	11.2	.308	7.8	10	1.8	.27	6.9	2.8	12	.10	2.5	0.026	0.7	3.75	MW	CG	N
0.360	9.14	71027S	.44	11.2	.308	7.8	8.7	1.5	.21	5.4	1.9	8.3	.10	2.5	0.026	0.7	3.75	SST	CG	N
0.360	9.14	71046	.44	11.2	.302	7.7	15	2.6	.26	6.7	3.8	17	.11	2.9	0.029	0.7	3.88	MW	CG	N
0.360	9.14	71046S	.44	11.2	.302	7.7	12	2.2	.21	5.2	2.6	11	.11	2.9	0.029	0.7	3.88	SST	CG	N
0.360	9.14	71065	.44	11.2	.296	7.5	21	3.6	.25	6.3	5.1	23	.13	3.3	0.032	0.8	4.00	MW	CG	N
0.360	9.14	71065S	.44	11.2	.296	7.5	18	3.1	.19	4.9	3.4	15	.13	3.3	0.032	0.8	4.00	SST	CG	N
0.360	9.14	71083	.44	11.2	.290	7.4	28	4.9	.23	5.7	6.3	28	.15	3.8	0.035	0.9	4.25	MW	CG	N
0.360	9.14	71083S	.44	11.2	.290	7.4	24	4.2	.18	4.6	4.3	19	.15	3.8	0.035	0.9	4.25	SST	CG	N
0.360	9.14	71101	.44	11.2	.284	7.2	38	6.6	.21	5.4	8.1	36	.17	4.2	0.038	1.0	4.38	MW	CG	N
0.360	9.14	71101S	.44	11.2	.284	7.2	32	5.6	.17	4.3	5.5	24	.17	4.2	0.038	1.0	4.38	SST	CG	N
0.360	9.14	71119	.44	11.2	.280	7.1	45	7.9	.21	5.3	9.4	42	.18	4.6	0.040	1.0	4.50	MW	CG	N
0.360	9.14	71119S	.44	11.2	.280	7.1	38	6.7	.17	4.2	6.4	28	.18	4.6	0.040	1.0	4.50	SST	CG	N
0.360	9.14	71137	.44	11.2	.276	7.0	57	10	.19	4.8	11	48	.19	4.8	0.042	1.1	4.50	MW	CG	N
0.360	9.14	71137S	.44	11.2	.276	7.0	48	8.5	.15	3.8	7.3	33	.19	4.8	0.042	1.1	4.50	SST	CG	N
0.360	9.14	71155	.44	11.2	.270	6.9	77	13	.17	4.4	13	59	.20	5.1	0.045	1.1	4.50	MW	CG	N
0.360	9.14	71155S	.44	11.2	.270	6.9	65	11	.14	3.5	9.0	40	.20	5.1	0.045	1.1	4.50	SST	CG	N
0.360	9.14	71174	.44	11.2	.266	6.8	93	16	.16	4.1	15	67	.21	5.4	0.047	1.2	4.50	MW	CG	N
0.360	9.14	71174S	.44	11.2	.266	6.8	79	14	.13	3.3	10	45	.21	5.4	0.047	1.2	4.50	SST	CG	N
0.360	9.14	71196	.44	11.2	.262	6.7	109	19	.16	4.0	17	76	.22	5.6	0.049	1.2	4.50	MW	CG	N
0.360	9.14	71196S	.44	11.2	.262	6.7	93	16	.12	3.2	12	51	.22	5.6	0.049	1.2	4.50	SST	CG	N
0.360	9.14	71218	.44	11.2	.258	6.6	127	22	.14	3.6	18	80	.24	6.0	0.051	1.3	4.63	MW	CG	N
0.360	9.14	71218S	.44	11.2	.258	6.6	108	19	.11	2.9	12	54	.24	6.0	0.051	1.3	4.63	SST	CG	N
0.360	9.14	71240	.44	11.2	.250	6.4	175	31	.13	3.2	22	99	.25	6.5	0.055	1.4	4.63	MW	CG	N
0.360	9.14	71240S	.44	11.2	.250	6.4	149	26	.10	2.6	15	67	.25	6.5	0.055	1.4	4.63	SST	CG	N
0.360	9.14	71262	.44	11.2	.242	6.1	238	42	.11	2.9	27	121	.27	6.9	0.059	1.5	4.63	MW	CG	N
0.360	9.14	71262S	.44	11.2	.242	6.1	202	35	.09	2.3	18	82	.27	6.9	0.059	1.5	4.63	SST	CG	N
0.360	9.14	M-71	.47	11.9	.286	7.3	27	4.7	.20	5.1	5.4	24	.19	4.7	0.037	0.9	5.00	SPR	CG	Z
0.360	9.14	EE-72	.47	11.9	.276	7.0	56	9.8	.14	3.5	7.8	35	.19	4.8	0.042	1.1	4.50	SPR	CG	Z

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.360	9.14	71047S	.50	12.7	.302	7.7	11	1.9	.24	6.1	2.6	11	.12	3.1	0.029	0.7	4.25	SST	CG	N
0.360	9.14	10073	.50	12.7	.298	7.6	13	2.2	.31	8.0	3.9	18	.19	4.7	0.031	0.8	5.00	MW	C	Z
0.360	9.14	3571	.50	12.7	.296	7.5	17	3.0	.30	7.5	5.1	23	.18	4.5	0.032	0.8	4.50	MW	C	Z
0.360	9.14	71066	.50	12.7	.296	7.5	18	3.1	.29	7.2	5.1	23	.14	3.6	0.032	0.8	4.38	MW	CG	N
0.360	9.14	71066S	.50	12.7	.296	7.5	15	2.7	.22	5.7	3.4	15	.14	3.6	0.032	0.8	4.38	SST	CG	N
0.360	9.14	71084	.50	12.7	.290	7.4	24	4.2	.26	6.7	6.3	28	.16	4.1	0.035	0.9	4.63	MW	CG	N
0.360	9.14	71084S	.50	12.7	.290	7.4	20	3.6	.21	5.3	4.3	19	.16	4.1	0.035	0.9	4.63	SST	CG	N
0.360	9.14	10122	.50	12.7	.285	7.2	27	4.7	.21	5.3	5.6	25	.19	4.7	0.037	0.9	5.00	SPR	CG	Z
0.360	9.14	K-79	.50	12.7	.284	7.2	32	5.5	.17	4.4	5.5	24	.21	5.3	0.038	1.0	4.50	SST	C	N
0.360	9.14	71102	.50	12.7	.284	7.2	33	5.8	.24	6.2	8.1	36	.18	4.6	0.038	1.0	4.75	MW	CG	N
0.360	9.14	71102S	.50	12.7	.284	7.2	28	4.9	.19	4.9	5.5	24	.18	4.6	0.038	1.0	4.75	SST	CG	N
0.360	9.14	71120	.50	12.7	.280	7.1	39	6.8	.24	6.2	9.4	42	.20	5.0	0.040	1.0	4.88	MW	CG	N
0.360	9.14	71120S	.50	12.7	.280	7.1	33	5.8	.19	4.9	6.4	28	.20	5.0	0.040	1.0	4.88	SST	CG	N
0.360	9.14	A10-7	.50	12.7	.278	7.1	37	6.5	.18	4.7	6.8	30	.21	5.2	0.041	1.0	5.00	SST	CG	N
0.360	9.14	VWV-67	.50	12.7	.278	7.1	28	4.9	.23	5.9	6.6	29	.27	6.8	0.041	1.0	6.50	SPR	CG	Z
0.360	9.14	B12-23	.50	12.7	.278	7.1	42	7.4	.17	4.4	7.3	32	.21	5.2	0.041	1.0	5.00	SPR	CG	N
0.360	9.14	B-45	.50	12.7	.276	7.0	35	6.1	.21	5.2	7.2	32	.29	7.5	0.042	1.1	6.00	SPR	C	Z
0.360	9.14	71138	.50	12.7	.276	7.0	47	8.3	.23	5.8	11	48	.21	5.3	0.042	1.1	5.00	MW	CG	N
0.360	9.14	71138S	.50	12.7	.276	7.0	40	7.0	.18	4.7	7.3	33	.21	5.3	0.042	1.1	5.00	SST	CG	N
0.360	9.14	L-70	.50	12.7	.270	6.9	56	9.9	.16	4.1	9.0	40	.23	5.7	0.045	1.1	5.00	SST	CG	N
0.360	9.14	71156	.50	12.7	.270	6.9	65	11	.20	5.2	13	59	.22	5.6	0.045	1.1	4.88	MW	CG	N
0.360	9.14	71156S	.50	12.7	.270	6.9	56	9.7	.16	4.1	9.0	40	.22	5.6	0.045	1.1	4.88	SST	CG	N
0.360	9.14	AA-96	.50	12.7	.266	6.8	66	12	.17	4.2	11	48	.26	6.6	0.047	1.2	5.50	SPR	CG	Z
0.360	9.14	71175	.50	12.7	.266	6.8	79	14	.19	4.9	15	67	.23	5.8	0.047	1.2	4.88	MW	CG	N
0.360	9.14	71175S	.50	12.7	.266	6.8	67	12	.15	3.9	10	45	.23	5.8	0.047	1.2	4.88	SST	CG	N
0.360	9.14	A13-16	.50	12.7	.266	6.8	77	13	.14	3.6	11	48	.24	6.0	0.047	1.2	5.00	SPR	CG	Z
0.360	9.14	71197	.50	12.7	.262	6.7	92	16	.18	4.7	17	76	.25	6.2	0.049	1.2	5.00	MW	CG	N
0.360	9.14	71197S	.50	12.7	.262	6.7	78	14	.15	3.7	12	51	.25	6.2	0.049	1.2	5.00	SST	CG	N
0.360	9.14	71219	.50	12.7	.258	6.6	108	19	.17	4.2	18	80	.26	6.5	0.051	1.3	5.00	MW	CG	N
0.360	9.14	71219S	.50	12.7	.258	6.6	92	16	.13	3.4	12	54	.26	6.5	0.051	1.3	5.00	SST	CG	N
0.360	9.14	71241	.50	12.7	.250	6.4	148	26	.15	3.8	22	99	.28	7.2	0.055	1.4	5.13	MW	CG	N
0.360	9.14	71241S	.50	12.7	.250	6.4	126	22	.12	3.1	15	67	.28	7.2	0.055	1.4	5.13	SST	CG	N
0.360	9.14	71263	.50	12.7	.242	6.1	201	35	.14	3.5	27	121	.30	7.7	0.059	1.5	5.13	MW	CG	N
0.360	9.14	71263S	.50	12.7	.242	6.1	171	30	.11	2.8	18	82	.30	7.7	0.059	1.5	5.13	SST	CG	N
0.360	9.14	3656	.50	12.7	.200	5.1	1084	190	.04	1.0	44	197	.36	9.1	0.080	2.0	4.50	SPR	CG	Z
0.360	9.14	B5-10	.53	13.5	.318	8.1	3.6	.63	.43	11	1.6	6.9	.08	2.1	0.021	0.5	4.00	MW	CG	N
0.360	9.14	M-82	.53	13.5	.300	7.6	7.3	1.3	.35	8.9	2.5	11	.18	4.6	0.030	0.8	6.00	SST	CG	N
0.360	9.14	A13-20	.53	13.5	.294	7.5	15	2.5	.26	6.6	3.8	17	.17	4.2	0.033	0.8	5.00	SST	CG	N
0.360	9.14	A13-14	.53	13.5	.268	6.8	56	9.8	.17	4.4	9.6	43	.25	6.4	0.046	1.2	5.33	SST	CG	N
0.360	9.14	Y-14	.53	13.5	.264	6.7	113	20	.10	2.6	12	52	.20	5.2	0.048	1.2	4.25	SPR	CG	N
0.360	9.14	KK-89	.53	13.5	.260	6.6	101	18	.11	2.9	11	51	.25	6.4	0.050	1.3	5.00	SST	CG	N
0.360	9.14	12622	.53	13.5	.260	6.6	101	18	.12	3.1	12	54	.25	6.4	0.050	1.3	5.00	SPR	CG	N
0.360	9.14	S-26	.53	13.5	.258	6.6	74	13	.16	4.2	12	54	.36	9.1	0.051	1.3	6.00	SST	C	N
0.360	9.14	12646	.55	13.9	.294	7.5	9.4	1.6	.33	8.4	3.1	14	.22	5.5	0.033	0.8	6.50	SST	CG	N
0.360	9.14	71029	.56	14.2	.308	7.8	8.1	1.4	.34	8.7	2.8	12	.11	2.7	0.026	0.7	4.13	MW	CG	N
0.360	9.14	71029S	.56	14.2	.308	7.8	6.9	1.2	.27	6.8	1.9	8.3	.11	2.7	0.026	0.7	4.13	SST	CG	N
0.360	9.14	71048	.56	14.2	.302	7.7	11	1.9	.35	8.8	3.8	17	.13	3.3	0.029	0.7	4.50	MW	CG	N
0.360	9.14	71048S	.56	14.2	.302	7.7	9.4	1.6	.27	6.9	2.6	11	.13	3.3	0.029	0.7	4.50	SST	CG	N
0.360	9.14	71067	.56	14.2	.296	7.5	16	2.8	.32	8.1	5.1	23	.15	3.8	0.032	0.8	4.63	MW	CG	N
0.360	9.14	71067S	.56	14.2	.296	7.5	14	2.4	.25	6.3	3.4	15	.15	3.8	0.032	0.8	4.63	SST	CG	N
0.360	9.14	71085	.56	14.2	.290	7.4	21	3.7	.30	7.7	6.3	28	.18	4.4	0.035	0.9	5.00	MW	CG	N
0.360	9.14	71085S	.56	14.2	.290	7.4	18	3.1	.24	6.2	4.3	19	.18	4.4	0.035	0.9	5.00	SST	CG	N
0.360	9.14	71103	.56	14.2	.284	7.2	28	5.0	.28	7.2	8.1	36	.19	4.9	0.038	1.0	5.13	MW	CG	N
0.360	9.14	71103S	.56	14.2	.284	7.2	24	4.2	.23	5.8	5.5	24	.19	4.9	0.038	1.0	5.13	SST	CG	N
0.360	9.14	71121	.56	14.2	.280	7.1	34	5.9	.28	7.1	9.4	42	.22	5.5	0.040	1.0	5.38	MW	CG	N
0.360	9.14	71121S	.56	14.2	.280	7.1	29	5.0	.22	5.6	6.4	28	.22	5.5	0.040	1.0	5.38	SST	CG	N
0.360	9.14	71139	.56	14.2	.276	7.0	42	7.3	.26	6.6	11	48	.23	5.7	0.042	1.1	5.38	MW	CG	N
0.360	9.14	71139S	.56	14.2	.276	7.0	35	6.2	.21	5.3	7.3	33	.23	5.7	0.042	1.1	5.38	SST	CG	N
0.360	9.14	71157	.56	14.2	.270	6.9	56	9.7	.24	6.1	13	59	.24	6.1	0.045	1.1	5.38	MW	CG	N
0.360	9.14	71157S	.56	14.2	.270	6.9	47	8.3	.19	4.8	9.0	40	.24	6.1	0.045	1.1	5.38	SST	CG	N
0.360	9.14	71176	.56	14.2	.266	6.8	69	12	.22	5.6	15	67	.25	6.4	0.047	1.2	5.38	MW	CG	N
0.360	9.14	71176S	.56	14.2	.266	6.8	58	10	.17	4.4	10	45	.25	6.4	0.047	1.2	5.38	SST	CG	N
0.360	9.14	71198	.56	14.2	.262	6.7	80	14	.21	5.4	17	76	.26	6.7	0.049	1.2	5.38	MW	CG	N
0.360	9.14	71198S	.56	14.2	.262	6.7	68	12	.17	4.3	12	51	.26	6.7	0.049	1.2	5.38	SST	CG	N
0.360	9.14	71220	.56	14.2	.258	6.6	94	16	.19	4.9	18	80	.28	7.1	0.051	1.3	5.50	MW	CG	N
0.360	9.14	71220S	.56	14.2	.258	6.6	80	14	.15	3.9	12	54	.28	7.1	0.051	1.3	5.50	SST	CG	N
0.360	9.14	71242	.56	14.2	.250	6.4	128	22	.17	4.4	22	99	.31	7.9	0.055	1.4	5.63	MW	CG	N
0.360	9.14	71242S	.56	14.2	.250	6.4	109	19	.14	3.5	15	67	.31	7.9	0.055	1.4	5.63	SST	CG	N
0.360	9.14	71264	.56	14.2	.242	6.1	173	30	.16	4.0	27	121	.33	8.4	0.059	1.5	5.63	MW	CG	N
0.360	9.14	71264S	.56	14.2	.242	6.1	147	26	.13	3.2										




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.360	9.14	KK-47	.59	15.1	.264	6.7	51	8.9	.23	5.8	12	52	.34	8.5	0.048	1.2	7.00	SPR	CG	N
0.360	9.14	N-88	.59	15.1	.180	4.6	1074	188	.05	1.3	54	241	.54	13.7	0.090	2.3	6.00	SST	CG	N
0.360	9.14	A12-5	.63	15.9	.322	8.2	1.4	.24	.50	13	.68	3.0	.12	3.1	0.019	0.5	5.50	MW	C	Z
0.360	9.14	G-65	.63	15.9	.318	8.1	3.2	.56	.48	12	1.6	6.9	.11	2.8	0.021	0.5	4.25	MW	C	N
0.360	9.14	S-923	.63	15.9	.312	7.9	2.0	.35	.42	11	.84	3.8	.20	5.2	0.024	0.6	7.50	SST	C	N
0.360	9.14	3859	.63	15.9	.310	7.9	2.0	.35	.36	9.2	.73	3.2	.26	6.7	0.025	0.6	9.50	MW	C	Z
0.360	9.14	B1-45	.63	15.9	.308	7.8	6.3	1.1	.29	7.5	1.9	8.3	.12	3.0	0.026	0.7	4.50	SST	CG	N
0.360	9.14	B12-28	.63	15.9	.308	7.8	7.1	1.2	.39	9.9	2.8	12	.12	3.0	0.026	0.7	4.50	MW	CG	N
0.360	9.14	FF-66	.63	15.9	.300	7.6	8.3	1.5	.34	8.7	2.8	13	.20	5.0	0.030	0.8	5.50	SST	C	N
0.360	9.14	10815	.63	15.9	.296	7.5	14	2.5	.26	6.5	3.7	16	.19	4.9	0.032	0.8	5.00	SPR	C	Z
0.360	9.14	3047	.63	15.9	.296	7.5	12	2.2	.42	11	5.1	23	.18	4.5	0.032	0.8	5.50	MW	CG	Z
0.360	9.14	4267	.63	15.9	.290	7.1	41	7.2	.16	4.2	6.8	30	.23	5.8	0.040	1.0	4.75	SPR	C	Z
0.360	9.14	GG-77	.63	15.9	.280	7.1	28	5.0	.24	6.1	6.8	30	.24	6.1	0.040	1.0	6.00	SPR	CG	N
0.360	9.14	L-99	.63	15.9	.280	7.1	18	3.1	.33	8.3	5.8	26	.30	7.6	0.040	1.0	7.50	SST	CG	N
0.360	9.14	K-65	.63	15.9	.280	7.1	15	2.7	.29	7.2	4.3	19	.34	8.6	0.040	1.0	8.50	SST	CG	N
0.360	9.14	S-1262	.63	15.9	.278	7.1	29	5.1	.23	5.9	6.8	30	.24	6.0	0.041	1.0	5.75	SST	CG	N
0.360	9.14	V-66	.63	15.9	.270	6.9	32	5.6	.27	6.7	8.4	37	.36	9.1	0.045	1.1	8.00	SPR	CG	N
0.360	9.14	A11-16	.63	15.9	.268	6.8	47	8.2	.21	5.2	9.6	43	.28	7.0	0.046	1.2	6.00	SST	CG	N
0.360	9.14	B7-4	.63	15.9	.268	6.8	49	8.6	.21	5.3	10	45	.29	7.3	0.046	1.2	6.25	SPR	CG	Z
0.360	9.14	10878	.63	15.9	.266	6.8	58	10	.19	4.8	11	48	.33	8.4	0.047	1.2	6.00	SPR	C	N
0.360	9.14	71030	.63	16.0	.308	7.8	7.2	1.3	.38	9.8	2.8	12	.12	3.0	0.026	0.7	4.50	MW	CG	N
0.360	9.14	71030S	.63	16.0	.308	7.8	6.1	1.1	.30	7.7	1.9	8.3	.12	3.0	0.026	0.7	4.50	SST	CG	N
0.360	9.14	71049	.63	16.0	.302	7.7	9.9	1.7	.39	9.8	3.8	17	.14	3.6	0.029	0.7	4.88	MW	CG	N
0.360	9.14	71049S	.63	16.0	.302	7.7	8.4	1.5	.30	7.7	2.6	11	.14	3.6	0.029	0.7	4.88	SST	CG	N
0.360	9.14	71068	.63	16.0	.296	7.5	15	2.6	.35	8.8	5.1	23	.16	4.0	0.032	0.8	4.88	MW	CG	N
0.360	9.14	71068S	.63	16.0	.296	7.5	12	2.2	.27	7.0	3.4	15	.16	4.0	0.032	0.8	4.88	SST	CG	N
0.360	9.14	71086	.63	16.0	.290	7.4	19	3.2	.34	8.7	6.3	28	.19	4.8	0.035	0.9	5.38	MW	CG	N
0.360	9.14	71086S	.63	16.0	.290	7.4	16	2.8	.27	6.9	4.3	19	.19	4.8	0.035	0.9	5.38	SST	CG	N
0.360	9.14	71104	.63	16.0	.284	7.2	25	4.4	.32	8.2	8.1	36	.21	5.4	0.038	1.0	5.63	MW	CG	N
0.360	9.14	71104S	.63	16.0	.284	7.2	21	3.7	.26	6.6	5.5	24	.21	5.4	0.038	1.0	5.63	SST	CG	N
0.360	9.14	71122	.63	16.0	.280	7.1	30	5.2	.32	8.1	9.4	42	.23	5.8	0.040	1.0	5.75	MW	CG	N
0.360	9.14	71122S	.63	16.0	.280	7.1	25	4.4	.25	6.4	6.4	28	.23	5.8	0.040	1.0	5.75	SST	CG	N
0.360	9.14	71140	.63	16.0	.276	7.0	38	6.6	.29	7.3	11	48	.24	6.0	0.042	1.1	5.63	MW	CG	N
0.360	9.14	71140S	.63	16.0	.276	7.0	32	5.6	.23	5.8	7.3	33	.24	6.0	0.042	1.1	5.63	SST	CG	N
0.360	9.14	71158	.63	16.0	.270	6.9	49	8.6	.27	6.9	13	59	.26	6.7	0.045	1.1	5.88	MW	CG	N
0.360	9.14	71158S	.63	16.0	.270	6.9	42	7.3	.22	5.5	9.0	40	.26	6.7	0.045	1.1	5.88	SST	CG	N
0.360	9.14	71177	.63	16.0	.266	6.8	61	11	.25	6.3	15	67	.27	6.9	0.047	1.2	5.75	MW	CG	N
0.360	9.14	71177S	.63	16.0	.266	6.8	52	9.1	.20	5.0	10	45	.27	6.9	0.047	1.2	5.75	SST	CG	N
0.360	9.14	71199	.63	16.0	.262	6.7	71	12	.24	6.1	17	76	.29	7.3	0.049	1.2	5.88	MW	CG	N
0.360	9.14	71199S	.63	16.0	.262	6.7	60	11	.19	4.9	12	51	.29	7.3	0.049	1.2	5.88	SST	CG	N
0.360	9.14	71221	.63	16.0	.258	6.6	83	14	.22	5.5	18	80	.31	7.8	0.051	1.3	6.00	MW	CG	N
0.360	9.14	71221S	.63	16.0	.258	6.6	70	12	.17	4.4	12	54	.31	7.8	0.051	1.3	6.00	SST	CG	N
0.360	9.14	71243	.63	16.0	.250	6.4	113	20	.20	5.0	22	99	.34	8.6	0.055	1.4	6.13	MW	CG	N
0.360	9.14	71243S	.63	16.0	.250	6.4	96	17	.16	4.0	15	67	.34	8.6	0.055	1.4	6.13	SST	CG	N
0.360	9.14	71265	.63	16.0	.242	6.1	153	27	.18	4.5	27	121	.36	9.2	0.059	1.5	6.13	MW	CG	N
0.360	9.14	71265S	.63	16.0	.242	6.1	130	23	.14	3.6	18	82	.36	9.2	0.059	1.5	6.13	SST	CG	N
0.360	9.14	JJ-53	.66	16.7	.284	7.2	23	4.0	.26	6.5	5.8	26	.23	5.8	0.038	1.0	6.00	SPR	CG	N
0.360	9.14	10954	.66	16.7	.266	6.8	42	7.4	.26	6.5	11	48	.40	10.2	0.047	1.2	7.50	SPR	C	N
0.360	9.14	12695	.67	17.1	.236	6.0	134	23	.18	4.5	24	105	.50	12.6	0.062	1.6	8.00	MW	CG	N
0.360	9.14	B5-16	.69	17.4	.314	8.0	4.2	.74	.48	12	2.0	9.1	.13	3.2	0.023	0.6	4.50	MW	C	N
0.360	9.14	B4-8	.69	17.4	.312	7.9	1.3	.22	.38	9.5	.47	2.1	.31	7.9	0.024	0.6	12.0	MW	C	T
0.360	9.14	J-25	.69	17.4	.310	7.9	5.5	.96	.45	11	2.5	11	.14	3.7	0.025	0.6	4.75	MW	C	Z
0.360	9.14	W-45	.69	17.4	.280	7.1	20	3.5	.32	8.2	6.4	28	.28	7.1	0.040	1.0	7.00	SST	CG	N
0.360	9.14	A13-11	.69	17.4	.274	7.0	32	5.6	.25	6.3	7.9	35	.27	6.9	0.043	1.1	6.25	SST	CG	N
0.360	9.14	N-68	.69	17.4	.270	6.9	24	4.2	.24	6.0	5.7	25	.45	11.4	0.045	1.1	9.00	SST	C	N
0.360	9.14	3668	.69	17.4	.268	6.8	52	9.2	.19	5.0	10	45	.32	8.2	0.046	1.2	6.00	SPR	C	Z
0.360	9.14	BB-79	.69	17.4	.250	6.4	62	11	.20	5.1	12	55	.49	12.3	0.055	1.4	9.00	SPR	CG	N
0.360	9.14	OO-37	.69	17.4	.240	6.1	100	17	.15	3.7	15	65	.54	13.7	0.060	1.5	9.00	SPR	CG	N
0.360	9.14	71031	.69	17.5	.308	7.8	6.6	1.2	.42	11	2.8	12	.12	3.1	0.026	0.7	4.63	MW	CG	N
0.360	9.14	71031S	.69	17.5	.308	7.8	5.6	.98	.33	8.4	1.9	8.3	.12	3.1	0.026	0.7	4.63	SST	CG	N
0.360	9.14	71050	.69	17.5	.302	7.7	8.6	1.5	.45	11	3.8	17	.15	3.9	0.029	0.7	5.25	MW	CG	N
0.360	9.14	71050S	.69	17.5	.302	7.7	7.3	1.3	.35	8.9	2.6	11	.15	3.9	0.029	0.7	5.25	SST	CG	N
0.360	9.14	71069	.69	17.5	.296	7.5	13	2.3	.40	10	5.1	23	.17	4.3	0.032	0.8	5.25	MW	CG	N
0.360	9.14	71069S	.69	17.5	.296	7.5	11	1.9	.31	7.9	3.4	15	.17	4.3	0.032	0.8	5.25	SST	CG	N
0.360	9.14	71087	.69	17.5	.290	7.4	16	2.9	.39	9.8	6.3	28	.21	5.2	0.035	0.9	5.88	MW	CG	N
0.360	9.14	71087S	.69	17.5	.290	7.4	14	2.4	.31	7.8	4.3	19	.21	5.2	0.035	0.9	5.88	SST	CG	N
0.360	9.14	71105	.69	17.5	.284	7.2	22	3.9	.37	9.3	8.1	36	.23	5.9	0.038	1.0	6.13	MW	CG	N
0.360	9.14	71105S	.69	17.5	.284	7.2	19	3.3	.29	7.4	5.5	24	.23	5.9	0.038	1.0	6.13	SST	CG	N
0.360	9.14	71123	.69	17.5	.280	7.1	27	4.7	.35	9.0	9.4	42	.25	6.4	0.040	1.0	6.25	MW	CG	N
0.360	9.14	71123S	.69	17.5	.280	7.1	23	4.0	.28	7.1	6.4									

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.360	9.14	71244	.69	17.5	.250	6.4	100	17	.22	5.7	22	99	.36	9.3	0.055	1.4	6.63	MW	CG	N
0.360	9.14	71244S	.69	17.5	.250	6.4	85	15	.18	4.5	15	67	.36	9.3	0.055	1.4	6.63	SST	CG	N
0.360	9.14	71266	.69	17.5	.242	6.1	134	23	.20	5.2	27	121	.40	10.1	0.059	1.5	6.75	MW	CG	N
0.360	9.14	71266S	.69	17.5	.242	6.1	114	20	.16	4.1	18	82	.40	10.1	0.059	1.5	6.75	SST	CG	N
0.360	9.14	11223	.72	18.2	.318	8.1	1.3 .23		.54	14	.71 3.2		.18	4.5	0.021	0.5	7.50	MW	C	N
0.360	9.14	B12-8	.72	18.2	.270	6.9	45	7.8	.21	5.4	9.6	43	.28	7.1	0.045	1.1	6.25	SPR	CG	GI
0.360	9.14	B7-54	.72	18.2	.268	6.8	49	8.6	.21	5.3	10	45	.33	8.5	0.046	1.2	6.25	SPR	C	N
0.360	9.14	3596	.72	18.2	.210	5.3	331	58	.11	2.8	37	164	.60	15.2	0.075	1.9	8.00	SPR	CG	Z
0.360	9.14	B12-18	.75	19.1	.316	8.0	2.9	.51	.61	15	1.8	8.0	.11	2.8	0.022	0.6	5.00	MW	CG	N
0.360	9.14	M-110	.75	19.1	.310	7.9	5.0	.88	.49	12	2.5	11	.15	3.8	0.025	0.6	5.00	MW	C	GI
0.360	9.14	71032	.75	19.1	.308	7.8	6.1	1.1	.46	12	2.8	12	.13	3.2	0.026	0.7	4.88	MW	CG	N
0.360	9.14	71032S	.75	19.1	.308	7.8	5.1	.90	.36	9.2	1.9	8.3	.13	3.2	0.026	0.7	4.88	SST	CG	N
0.360	9.14	B12-22	.75	19.1	.306	7.8	6.4	1.1	.48	12	3.1	14	.14	3.6	0.027	0.7	5.25	MW	CG	GI
0.360	9.14	71051	.75	19.1	.302	7.7	7.9	1.4	.48	12	3.8	17	.16	4.1	0.029	0.7	5.50	MW	CG	N
0.360	9.14	71051S	.75	19.1	.302	7.7	6.7	1.2	.38	9.7	2.6	11	.16	4.1	0.029	0.7	5.50	SST	CG	N
0.360	9.14	CC-50	.75	19.1	.300	7.6	7.1	1.2	.40	10	2.8	13	.21	5.3	0.030	0.8	6.00	SST	C	N
0.360	9.14	BB-71	.75	19.1	.300	7.6	3.6	.63	.45	11	1.6	7.3	.30	7.6	0.030	0.8	10.0	SST	CG	N
0.360	9.14	10014	.75	19.1	.296	7.5	11	1.9	.48	12	5.1	23	.19	4.9	0.032	0.8	6.00	MW	C	Z
0.360	9.14	71070	.75	19.1	.296	7.5	12	2.1	.43	11	5.1	23	.18	4.6	0.032	0.8	5.63	MW	CG	N
0.360	9.14	71070S	.75	19.1	.296	7.5	10	1.8	.34	8.6	3.4	15	.18	4.6	0.032	0.8	5.63	SST	CG	N
0.360	9.14	71088	.75	19.1	.290	7.4	15	2.6	.42	11	6.3	28	.21	5.4	0.035	0.9	6.13	MW	CG	N
0.360	9.14	71088S	.75	19.1	.290	7.4	13	2.2	.34	8.5	4.3	19	.21	5.4	0.035	0.9	6.13	SST	CG	N
0.360	9.14	B3-35	.75	19.1	.290	7.4	14	2.4	.45	12	6.3	28	.23	5.8	0.035	0.9	6.50	MW	CG	N
0.360	9.14	71106	.75	19.1	.284	7.2	21	3.7	.39	9.8	8.1	36	.24	6.0	0.038	1.0	6.25	MW	CG	N
0.360	9.14	71106S	.75	19.1	.284	7.2	18	3.1	.31	7.8	5.5	24	.24	6.0	0.038	1.0	6.25	SST	CG	N
0.360	9.14	S-1158	.75	19.1	.280	7.1	20	3.5	.32	8.2	6.4	28	.32	8.1	0.040	1.0	7.00	SST	C	N
0.360	9.14	71124	.75	19.1	.280	7.1	24	4.3	.39	9.8	9.4	42	.27	6.7	0.040	1.0	6.63	MW	CG	N
0.360	9.14	71124S	.75	19.1	.280	7.1	21	3.6	.31	7.8	6.4	28	.27	6.7	0.040	1.0	6.63	SST	CG	N
0.360	9.14	3785	.75	19.1	.276	7.0	28	4.9	.28	7.1	7.8	35	.34	8.5	0.042	1.1	7.00	SPR	C	Z
0.360	9.14	71142	.75	19.1	.276	7.0	31	5.4	.35	8.9	11	48	.27	6.9	0.042	1.1	6.50	MW	CG	N
0.360	9.14	71142S	.75	19.1	.276	7.0	26	4.6	.28	7.1	7.3	33	.27	6.9	0.042	1.1	6.50	SST	CG	N
0.360	9.14	A14-44	.75	19.1	.274	7.0	33	5.7	.26	6.5	8.4	37	.29	7.4	0.043	1.1	6.75	SPR	CG	Z
0.360	9.14	10027	.75	19.1	.270	6.9	38	6.7	.25	6.4	9.6	43	.32	8.0	0.045	1.1	7.00	SPR	CG	Z
0.360	9.14	G-22	.75	19.1	.270	6.9	18	3.2	.26	6.5	4.7	21	.50	12.6	0.045	1.1	11.0	SST	CG	N
0.360	9.14	H-29	.75	19.1	.270	6.9	33	5.8	.27	6.9	9.0	40	.32	8.0	0.045	1.1	7.00	SST	CG	N
0.360	9.14	71160	.75	19.1	.270	6.9	40	7.0	.33	8.5	13	59	.30	7.7	0.045	1.1	6.75	MW	CG	N
0.360	9.14	71160S	.75	19.1	.270	6.9	34	5.9	.27	6.8	9.0	40	.30	7.7	0.045	1.1	6.75	SST	CG	N
0.360	9.14	71179	.75	19.1	.266	6.8	39	6.9	.38	9.6	15	66	.37	9.4	0.047	1.2	7.88	MW	CG	N
0.360	9.14	71179S	.75	19.1	.266	6.8	33	5.8	.31	7.8	10	45	.37	9.4	0.047	1.2	7.88	SST	CG	N
0.360	9.14	AA-94	.75	19.1	.266	6.8	33	5.9	.30	7.7	10	45	.38	9.6	0.047	1.2	8.00	SST	CG	N
0.360	9.14	71201	.75	19.1	.262	6.7	57	10	.30	7.6	17	76	.34	8.6	0.049	1.2	6.88	MW	CG	N
0.360	9.14	71201S	.75	19.1	.262	6.7	48	8.5	.24	6.0	12	51	.34	8.6	0.049	1.2	6.88	SST	CG	N
0.360	9.14	2612	.75	19.1	.260	6.6	51	8.9	.24	6.1	12	54	.40	10.2	0.050	1.3	8.00	SPR	CG	Z
0.360	9.14	71223	.75	19.1	.258	6.6	66	12	.27	6.9	18	80	.36	9.1	0.051	1.3	7.00	MW	CG	N
0.360	9.14	71223S	.75	19.1	.258	6.6	56	9.8	.22	5.5	12	54	.36	9.1	0.051	1.3	7.00	SST	CG	N
0.360	9.14	DD-100	.75	19.1	.252	6.4	68	12	.21	5.3	14	64	.41	10.3	0.054	1.4	7.50	SST	CG	N
0.360	9.14	71245	.75	19.1	.250	6.4	90	16	.25	6.3	22	99	.39	10.0	0.055	1.4	7.13	MW	CG	N
0.360	9.14	71245S	.75	19.1	.250	6.4	77	13	.20	5.0	15	67	.39	10.0	0.055	1.4	7.13	SST	CG	N
0.360	9.14	M-107	.75	19.1	.242	6.1	117	21	.17	4.3	20	87	.44	11.2	0.059	1.5	7.50	SPR	CG	Z
0.360	9.14	71267	.75	19.1	.242	6.1	121	21	.22	5.7	27	121	.43	10.9	0.059	1.5	7.25	MW	CG	N
0.360	9.14	71267S	.75	19.1	.242	6.1	103	18	.18	4.6	18	82	.43	10.9	0.059	1.5	7.25	SST	CG	N
0.360	9.14	BB-52	.78	19.8	.300	7.6	9.7	1.7	.29	7.4	2.8	13	.15	3.8	0.030	0.8	5.00	SST	CG	N
0.360	9.14	B-85	.78	19.8	.298	7.6	8.3	1.5	.37	9.5	3.1	14	.22	5.5	0.031	0.8	6.00	SST	C	N
0.360	9.14	A13-17	.78	19.8	.292	7.4	14	2.4	.44	11	6.1	27	.20	5.2	0.034	0.9	6.00	MW	CG	N
0.360	9.14	S-1533	.78	19.8	.290	7.4	10	1.8	.43	11	4.3	19	.26	6.7	0.035	0.9	7.50	SST	CG	N
0.360	9.14	KK-49	.78	19.8	.260	6.6	51	8.9	.24	6.1	12	54	.40	10.2	0.050	1.3	8.00	SPR	CG	N
0.360	9.14	10447	.78	19.8	.258	6.6	67	12	.19	4.9	13	57	.41	10.4	0.051	1.3	7.00	SPR	C	Z
0.360	9.14	71033	.81	20.6	.308	7.8	5.6	.98	.49	13	2.8	12	.13	3.4	0.026	0.7	5.13	MW	CG	N
0.360	9.14	71033S	.81	20.6	.308	7.8	4.8	.83	.39	9.9	1.9	8.3	.13	3.4	0.026	0.7	5.13	SST	CG	N
0.360	9.14	71052	.81	20.6	.302	7.7	7.3	1.3	.52	13	3.8	17	.17	4.3	0.029	0.7	5.88	MW	CG	N
0.360	9.14	71052S	.81	20.6	.302	7.7	6.2	1.1	.41	10	2.6	11	.17	4.3	0.029	0.7	5.88	SST	CG	N
0.360	9.14	71071	.81	20.6	.296	7.5	11	1.9	.46	12	5.1	23	.19	4.8	0.032	0.8	5.88	MW	CG	N
0.360	9.14	71071S	.81	20.6	.296	7.5	9.4	1.7	.36	9.2	3.4	15	.19	4.8	0.032	0.8	5.88	SST	CG	N
0.360	9.14	71089	.81	20.6	.290	7.4	14	2.4	.46	12	6.3	28	.23	5.9	0.035	0.9	6.63	MW	CG	N
0.360	9.14	71089S	.81	20.6	.290	7.4	12	2.0	.37	9.3	4.3	19	.23	5.9	0.035	0.9	6.63	SST	CG	N
0.360	9.14	71107	.81	20.6	.284	7.2	19	3.3	.43	11	8.1	36	.26	6.5	0.038	1.0	6.75	MW	CG	N
0.360	9.14	71107S	.81	20.6	.284	7.2	16	2.8	.34	8.7	5.5	24	.26	6.5	0.038	1.0	6.75	SST	CG	N
0.360	9.14	71125	.81	20.6	.280	7.1	22	3.9	.42	11	9.4	42	.28	7.1	0.040	1.0	7.00	MW	CG	N
0.360	9.14	71125S	.81	20.6	.280	7.1	19	3.3	.33	8.5	6.4	28	.28	7.1	0.040	1.0	7.00	SST	CG	N
0.360	9.14	71143	.81	20.6	.276															




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.360	9.14	71246S	.81	20.6	.250	6.4	70	12	.22	5.5	15	67	.42	10.7	0.055	1.4	7.63	SST	CG	N
0.360	9.14	71268	.81	20.6	.242	6.1	111	19	.25	6.3	27	121	.46	11.6	0.059	1.5	7.75	MW	CG	N
0.360	9.14	71268S	.81	20.6	.242	6.1	94	16	.20	5.0	18	82	.46	11.6	0.059	1.5	7.75	SST	CG	N
0.360	9.14	B-73	.81	20.6	.308	7.8	5.3	.92	.35	9.0	1.9	8.3	.16	4.0	0.026	0.7	5.00	SST	C	N
0.360	9.14	J-51	.81	20.6	.308	7.8	5.9	1.0	.47	12	2.8	12	.16	4.0	0.026	0.7	5.00	MW	C	Z
0.360	9.14	B7-1	.81	20.6	.304	7.7	4.6	.81	.61	15	2.8	13	.20	5.2	0.028	0.7	7.25	MW	CG	Z
0.360	9.14	A13-26	.81	20.6	.294	7.5	10	1.8	.37	9.3	3.8	17	.21	5.2	0.033	0.8	6.25	SST	CG	N
0.360	9.14	H-64	.81	20.6	.290	7.4	12	2.0	.40	10	4.6	20	.26	6.7	0.035	0.9	7.50	SPR	CG	Z
0.360	9.14	4238	.81	20.6	.288	7.3	18	3.1	.28	7.1	5.0	22	.25	6.4	0.036	0.9	6.00	SPR	C	Z
0.360	9.14	B1-15	.81	20.6	.266	6.8	44	7.7	.25	6.3	11	48	.34	8.7	0.047	1.2	7.25	SPR	CG	GI
0.360	9.14	MM-48	.84	21.4	.304	7.7	6.1	1.1	.57	14	3.5	15	.20	5.0	0.028	0.7	6.00	MW	C	N
0.360	9.14	N-3	.84	21.4	.226	5.7	172	30	.15	3.9	27	118	.54	13.6	0.067	1.7	8.00	SST	CG	N
0.360	9.14	4279	.88	22.2	.310	7.9	4.3	.75	.57	15	2.5	11	.16	4.1	0.025	0.6	5.50	MW	C	Z
0.360	9.14	S-1279	.88	22.2	.310	7.9	3.3	.57	.50	13	1.7	7.3	.15	3.8	0.025	0.6	6.00	SST	CG	N
0.360	9.14	Z-55	.88	22.2	.310	7.9	3.7	.66	.44	11	1.7	7.3	.16	4.1	0.025	0.6	5.50	SST	C	N
0.360	9.14	XX-69	.88	22.2	.306	7.8	5.6	.97	.56	14	3.1	14	.18	4.6	0.027	0.7	5.75	MW	C	Z
0.360	9.14	J-11	.88	22.2	.302	7.7	4.0	.71	.59	15	2.4	11	.29	7.4	0.029	0.7	9.00	MW	C	Z
0.360	9.14	B17-133	.88	22.2	.300	7.6	5.9	1.0	.65	17	3.9	17	.23	5.7	0.030	0.8	7.50	MW	CG	Z
0.360	9.14	W-19	.88	22.2	.296	7.5	7.5	1.3	.46	12	3.4	15	.22	5.7	0.032	0.8	7.00	SST	CG	N
0.360	9.14	10095	.88	22.2	.294	7.5	9.8	1.7	.41	10	4.0	18	.26	6.7	0.033	0.8	7.00	SPR	C	Z
0.360	9.14	A13-49	.88	22.2	.294	7.5	11	1.9	.37	9.4	4.0	18	.21	5.4	0.033	0.8	6.50	SPR	CG	GI
0.360	9.14	O-93	.88	22.2	.290	7.4	16	2.8	.29	7.3	4.6	20	.21	5.3	0.035	0.9	6.00	SPR	C	GI
0.360	9.14	QQ-68	.88	22.2	.282	7.2	13	2.3	.45	11	5.9	26	.38	9.7	0.039	1.0	8.75	SST	C	N
0.360	9.14	GG-10	.88	22.2	.280	7.1	13	2.2	.48	12	6.0	27	.40	10.2	0.040	1.0	10.0	SST	CG	N
0.360	9.14	S-1257	.88	22.2	.278	7.1	19	3.3	.36	9.1	6.8	30	.32	8.1	0.041	1.0	7.75	SST	CG	N
0.360	9.14	A11-25	.88	22.2	.268	6.8	31	5.4	.31	7.8	9.6	43	.37	9.3	0.046	1.2	8.00	SST	CG	N
0.360	9.14	W-44	.88	22.2	.266	6.8	37	6.4	.28	7.1	10	45	.35	9.0	0.047	1.2	7.50	SST	CG	N
0.360	9.14	H-22	.88	22.2	.252	6.4	50	8.7	.29	7.3	14	64	.51	13.0	0.054	1.4	9.50	SST	CG	N
0.360	9.14	L-82	.88	22.2	.252	6.4	51	8.9	.30	7.6	15	68	.57	14.4	0.054	1.4	10.5	SPR	CG	Z
0.360	9.14	O-34	.88	22.2	.230	5.8	149	26	.16	4.2	24	109	.52	13.2	0.065	1.7	8.00	SPR	CG	N
0.360	9.14	71034	.88	22.4	.308	7.8	5.0	.87	.56	14	2.8	12	.15	3.7	0.026	0.7	5.63	MW	CG	N
0.360	9.14	71034S	.88	22.4	.308	7.8	4.2	.74	.44	11	1.9	8.3	.15	3.7	0.026	0.7	5.63	SST	CG	N
0.360	9.14	71053	.88	22.4	.302	7.7	6.7	1.2	.57	15	3.8	17	.18	4.5	0.029	0.7	6.13	MW	CG	N
0.360	9.14	71053S	.88	22.4	.302	7.7	5.7	1.0	.45	11	2.6	11	.18	4.5	0.029	0.7	6.13	SST	CG	N
0.360	9.14	71072	.88	22.4	.296	7.5	10	1.7	.51	13	5.1	23	.20	5.1	0.032	0.8	6.25	MW	CG	N
0.360	9.14	71072S	.88	22.4	.296	7.5	8.5	1.5	.41	10	3.4	15	.20	5.1	0.032	0.8	6.25	SST	CG	N
0.360	9.14	71090	.88	22.4	.290	7.4	13	2.2	.50	13	6.3	28	.24	6.1	0.035	0.9	6.88	MW	CG	N
0.360	9.14	71090S	.88	22.4	.290	7.4	11	1.9	.40	10	4.3	19	.24	6.1	0.035	0.9	6.88	SST	CG	N
0.360	9.14	71108	.88	22.4	.284	7.2	17	3.0	.48	12	8.1	36	.28	7.0	0.038	1.0	7.25	MW	CG	N
0.360	9.14	71108S	.88	22.4	.284	7.2	14	2.5	.38	9.6	5.5	24	.28	7.0	0.038	1.0	7.25	SST	CG	N
0.360	9.14	71126	.88	22.4	.280	7.1	20	3.6	.46	12	9.4	42	.30	7.6	0.040	1.0	7.50	MW	CG	N
0.360	9.14	71126S	.88	22.4	.280	7.1	17	3.0	.37	9.3	6.4	28	.30	7.6	0.040	1.0	7.50	SST	CG	N
0.360	9.14	71144	.88	22.4	.276	7.0	25	4.4	.43	11	11	48	.32	8.0	0.042	1.1	7.50	MW	CG	N
0.360	9.14	71144S	.88	22.4	.276	7.0	21	3.7	.34	8.7	7.3	33	.32	8.0	0.042	1.1	7.50	SST	CG	N
0.360	9.14	71162	.88	22.4	.270	6.9	33	5.8	.40	10	13	59	.35	8.9	0.045	1.1	7.75	MW	CG	N
0.360	9.14	71162S	.88	22.4	.270	6.9	28	4.9	.32	8.2	9.0	40	.35	8.9	0.045	1.1	7.75	SST	CG	N
0.360	9.14	71181	.88	22.4	.266	6.8	33	5.7	.46	12	15	66	.42	10.7	0.047	1.2	9.00	MW	CG	N
0.360	9.14	71181S	.88	22.4	.266	6.8	28	4.9	.37	9.3	10	45	.42	10.7	0.047	1.2	9.00	SST	CG	N
0.360	9.14	71203	.88	22.4	.262	6.7	48	8.3	.36	9.1	17	76	.38	9.6	0.049	1.2	7.75	MW	CG	N
0.360	9.14	71203S	.88	22.4	.262	6.7	41	7.1	.28	7.2	12	51	.38	9.6	0.049	1.2	7.75	SST	CG	N
0.360	9.14	71225	.88	22.4	.258	6.6	55	9.6	.32	8.3	18	80	.41	10.4	0.051	1.3	8.00	MW	CG	N
0.360	9.14	71225S	.88	22.4	.258	6.6	47	8.2	.26	6.6	12	54	.41	10.4	0.051	1.3	8.00	SST	CG	N
0.360	9.14	71247	.88	22.4	.250	6.4	75	13	.30	7.5	22	99	.45	11.4	0.055	1.4	8.13	MW	CG	N
0.360	9.14	71247S	.88	22.4	.250	6.4	64	11	.24	6.0	15	67	.45	11.4	0.055	1.4	8.13	SST	CG	N
0.360	9.14	71269	.88	22.4	.242	6.1	101	18	.27	6.9	27	121	.49	12.6	0.059	1.5	8.38	MW	CG	N
0.360	9.14	71269S	.88	22.4	.242	6.1	86	15	.22	5.5	18	82	.49	12.6	0.059	1.5	8.38	SST	CG	N
0.360	9.14	Y-24	.91	23.0	.290	7.4	9.1	1.6	.51	13	4.6	20	.32	8.0	0.035	0.9	9.00	SPR	CG	N
0.360	9.14	B2-14	.93	23.7	.258	6.6	6.3	1.1	.40	10	2.5	11	.54	13.6	0.051	1.3	9.50	MW	C	Z
0.360	9.14	M-133	.94	23.8	.330	8.4	.22	.04	.79	20	.17	.78	.15	3.8	0.015	0.4	9.00	SST	C	N
0.360	9.14	JJ-82	.94	23.8	.316	8.0	2.2	.39	.78	20	1.7	7.7	.15	3.9	0.022	0.6	6.00	MW	C	N
0.360	9.14	1929	.94	23.8	.310	7.9	3.9	.68	.63	16	2.5	11	.17	4.4	0.025	0.6	5.88	MW	C	Z
0.360	9.14	F-59	.94	23.8	.308	7.8	4.4	.78	.62	16	2.8	12	.18	4.6	0.026	0.7	6.00	MW	C	Z
0.360	9.14	A9-59	.94	23.8	.302	7.7	5.7	.99	.68	17	3.8	17	.20	5.2	0.029	0.7	7.00	MW	CG	N
0.360	9.14	S-179	.94	23.8	.298	7.6	5.6	.97	.56	14	3.1	14	.28	7.1	0.031	0.8	8.00	SST	C	N
0.360	9.14	KK-87	.94	23.8	.296	7.5	7.8	1.4	.65	17	5.1	23	.27	6.9	0.032	0.8	7.50	MW	C	N
0.360	9.14	F-60	.94	23.8	.270	6.9	32	5.6	.42	11	13	59	.41	10.3	0.045	1.1	8.00	MW	C	Z
0.360	9.14	S-373	.94	23.8	.150	3.8	1576	276	.05	1.3	81	361	.84	21.3	0.105	2.7	8.00	SST	CG	N
0.360	9.14	71035	.94	23.9	.308	7.8	4.6	.80	.61	15	2.8	12	.15	3.9	0.026	0.7	5.88	MW	CG	N
0.360	9.14	71035S	.94	23.9	.308	7.8	3.9	.68	.48	12	1.9	8.3	.15	3.9	0.026	0.7	5.88	SST	CG	N
0.360	9.14	71054	.94	23.9	.302	7.7	6.1	1.1	.63	16	3.8	17	.19	4.9	0.029</					

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.360	9.14	71145S	.94	23.9	.276	7.0	20	3.4	.37	9.5	7.3	33	.34	8.5	0.042	1.1	8.00	SST	CG	N
0.360	9.14	71163	.94	23.9	.270	6.9	30	5.3	.44	11	13	59	.37	9.4	0.045	1.1	8.25	MW	CG	N
0.360	9.14	71163S	.94	23.9	.270	6.9	26	4.5	.35	8.9	9.0	40	.37	9.4	0.045	1.1	8.25	SST	CG	N
0.360	9.14	71182	.94	23.9	.266	6.8	38	6.6	.40	10	15	67	.38	9.6	0.047	1.2	8.00	MW	CG	N
0.360	9.14	71182S	.94	23.9	.266	6.8	32	5.6	.32	8.0	10	45	.38	9.6	0.047	1.2	8.00	SST	CG	N
0.360	9.14	71204	.94	23.9	.262	6.7	44	7.7	.39	9.8	17	76	.40	10.3	0.049	1.2	8.25	MW	CG	N
0.360	9.14	71204S	.94	23.9	.262	6.7	38	6.6	.31	7.8	12	51	.40	10.3	0.049	1.2	8.25	SST	CG	N
0.360	9.14	71226	.94	23.9	.258	6.6	51	8.9	.35	8.9	18	80	.43	11.0	0.051	1.3	8.50	MW	CG	N
0.360	9.14	71226S	.94	23.9	.258	6.6	43	7.6	.28	7.1	12	54	.43	11.0	0.051	1.3	8.50	SST	CG	N
0.360	9.14	71248	.94	23.9	.250	6.4	70	12	.32	8.1	22	99	.47	12.0	0.055	1.4	8.63	MW	CG	N
0.360	9.14	71248S	.94	23.9	.250	6.4	59	10	.25	6.5	15	67	.47	12.0	0.055	1.4	8.63	SST	CG	N
0.360	9.14	71270	.94	23.9	.242	6.1	93	16	.29	7.4	27	121	.52	13.3	0.059	1.5	8.88	MW	CG	N
0.360	9.14	71270S	.94	23.9	.242	6.1	79	14	.23	5.9	18	82	.52	13.3	0.059	1.5	8.88	SST	CG	N
0.360	9.14	PP-49	.97	24.6	.280	7.1	10	1.8	.45	11	4.6	21	.52	13.2	0.040	1.0	13.0	SPR	CG	Z
0.360	9.14	I-8	.97	24.6	.224	5.7	178	31	.17	4.2	29	131	.68	17.3	0.068	1.7	9.00	SPR	C	N
0.360	9.14	NN-67	1.00	25.4	.328	8.3	.15	.03	.73	18	.11	.47	.27	6.9	0.016	0.4	16.0	SST	C	N
0.360	9.14	EE-64	1.00	25.4	.320	8.1	.98	.17	.82	21	.81	3.6	.18	4.6	0.020	0.5	8.00	MW	C	N
0.360	9.14	L-56	1.00	25.4	.318	8.1	2.1	.36	.75	19	1.6	6.9	.14	3.5	0.021	0.5	5.50	MW	C	N
0.360	9.14	10058	1.00	25.4	.316	8.0	2.2	.39	.81	21	1.8	8.0	.15	3.9	0.022	0.6	6.00	MW	C	GI
0.360	9.14	B5-43	1.00	25.4	.316	8.0	2.2	.39	.81	21	1.8	8.0	.13	3.4	0.022	0.6	6.00	MW	CG	N
0.360	9.14	2794	1.00	25.4	.308	7.8	1.4	.24	.58	15	.80	3.6	.42	10.6	0.026	0.7	15.0	MW	C	Z
0.360	9.14	71036	1.00	25.4	.308	7.8	4.1	.71	.68	17	2.8	12	.17	4.2	0.026	0.7	6.38	MW	CG	N
0.360	9.14	71036S	1.00	25.4	.308	7.8	3.4	.60	.54	14	1.9	8.3	.17	4.2	0.026	0.7	6.38	SST	CG	N
0.360	9.14	11735	1.00	25.4	.308	7.8	4.0	.69	.70	18	2.8	12	.20	5.0	0.026	0.7	6.50	MW	C	Z
0.360	9.14	10912	1.00	25.4	.306	7.8	5.2	.91	.59	15	3.1	14	.16	4.1	0.027	0.7	6.00	MW	CG	N
0.360	9.14	71055	1.00	25.4	.302	7.7	5.9	1.0	.65	16	3.8	17	.20	5.0	0.029	0.7	6.75	MW	CG	N
0.360	9.14	71055S	1.00	25.4	.302	7.7	5.0	.88	.51	13	2.6	11	.20	5.0	0.029	0.7	6.75	SST	CG	N
0.360	9.14	II-37	1.00	25.4	.300	7.6	3.6	.64	.64	16	2.3	10	.36	9.1	0.030	0.8	11.0	MW	C	N
0.360	9.14	PP-63	1.00	25.4	.300	7.6	5.8	1.0	.49	12	2.8	13	.21	5.3	0.030	0.8	7.00	SST	CG	N
0.360	9.14	71074	1.00	25.4	.296	7.5	8.5	1.5	.60	15	5.1	23	.22	5.7	0.032	0.8	7.00	MW	CG	N
0.360	9.14	71074S	1.00	25.4	.296	7.5	7.2	1.3	.47	12	3.4	15	.22	5.7	0.032	0.8	7.00	SST	CG	N
0.360	9.14	II-57	1.00	25.4	.290	7.4	11	1.9	.43	11	4.6	20	.28	7.1	0.035	0.9	8.00	SPR	C	Z
0.360	9.14	71092	1.00	25.4	.290	7.4	11	2.0	.57	14	6.3	28	.27	6.8	0.035	0.9	7.63	MW	CG	N
0.360	9.14	71092S	1.00	25.4	.290	7.4	9.5	1.7	.45	12	4.3	19	.27	6.8	0.035	0.9	7.63	SST	CG	N
0.360	9.14	71110	1.00	25.4	.284	7.2	15	2.6	.54	14	8.1	36	.30	7.7	0.038	1.0	8.00	MW	CG	N
0.360	9.14	71110S	1.00	25.4	.284	7.2	13	2.2	.43	11	5.5	24	.30	7.7	0.038	1.0	8.00	SST	CG	N
0.360	9.14	3446	1.00	25.4	.280	7.1	14	2.5	.48	12	6.8	30	.44	11.2	0.040	1.0	10.0	SPR	C	Z
0.360	9.14	71128	1.00	25.4	.280	7.1	18	3.1	.53	13	9.4	42	.34	8.5	0.040	1.0	8.38	MW	CG	N
0.360	9.14	71128S	1.00	25.4	.280	7.1	15	2.6	.42	11	6.4	28	.34	8.5	0.040	1.0	8.38	SST	CG	N
0.360	9.14	4281	1.00	25.4	.278	7.1	14	2.5	.51	13	7.1	32	.49	12.5	0.041	1.0	11.0	SPR	C	Z
0.360	9.14	Z-59	1.00	25.4	.278	7.1	13	2.3	.53	13	6.8	30	.43	10.9	0.041	1.0	10.5	SST	CG	N
0.360	9.14	B12-30	1.00	25.4	.278	7.1	19	3.4	.38	9.5	7.3	32	.35	8.9	0.041	1.0	8.50	SPR	CG	N
0.360	9.14	B1-63	1.00	25.4	.276	7.0	18	3.1	.41	10	7.3	33	.38	9.6	0.042	1.1	9.00	SST	CG	N
0.360	9.14	71146	1.00	25.4	.276	7.0	21	3.7	.51	13	11	48	.36	9.1	0.042	1.1	8.50	MW	CG	N
0.360	9.14	71146S	1.00	25.4	.276	7.0	18	3.2	.41	10	7.3	33	.36	9.1	0.042	1.1	8.50	SST	CG	N
0.360	9.14	XX-45	1.00	25.4	.272	6.9	27	4.6	.34	8.6	9.0	40	.37	9.5	0.044	1.1	8.50	SPR	CG	Z
0.360	9.14	10104	1.00	25.4	.270	6.9	27	4.8	.35	9.0	9.6	43	.45	11.4	0.045	1.1	9.00	SPR	C	Z
0.360	9.14	71164	1.00	25.4	.270	6.9	28	4.9	.47	12	13	59	.39	10.0	0.045	1.1	8.75	MW	CG	N
0.360	9.14	71164S	1.00	25.4	.270	6.9	24	4.2	.38	9.6	9.0	40	.39	10.0	0.045	1.1	8.75	SST	CG	N
0.360	9.14	1587	1.00	25.4	.268	6.8	26	4.6	.39	9.9	10	45	.46	11.7	0.046	1.2	10.0	SPR	CG	Z
0.360	9.14	71183	1.00	25.4	.266	6.8	35	6.2	.43	11	15	67	.40	10.1	0.047	1.2	8.50	MW	CG	N
0.360	9.14	71183S	1.00	25.4	.266	6.8	30	5.3	.34	8.6	10	45	.40	10.1	0.047	1.2	8.50	SST	CG	N
0.360	9.14	71205	1.00	25.4	.262	6.7	41	7.2	.41	11	17	76	.43	10.9	0.049	1.2	8.75	MW	CG	N
0.360	9.14	71205S	1.00	25.4	.262	6.7	35	6.1	.33	8.4	12	51	.43	10.9	0.049	1.2	8.75	SST	CG	N
0.360	9.14	71227	1.00	25.4	.258	6.6	48	8.4	.38	9.5	18	80	.45	11.5	0.051	1.3	8.88	MW	CG	N
0.360	9.14	71227S	1.00	25.4	.258	6.6	41	7.1	.30	7.6	12	54	.45	11.5	0.051	1.3	8.88	SST	CG	N
0.360	9.14	71249	1.00	25.4	.250	6.4	65	11	.34	8.7	22	99	.50	12.7	0.055	1.4	9.13	MW	CG	N
0.360	9.14	71249S	1.00	25.4	.250	6.4	55	9.6	.27	7.0	15	67	.50	12.7	0.055	1.4	9.13	SST	CG	N
0.360	9.14	2813	1.03	26.2	.270	6.9	27	4.8	.49	12	13	59	.41	10.3	0.045	1.1	9.00	MW	CG	Z
0.360	9.14	A13-34	1.03	26.2	.268	6.8	27	4.7	.36	9.1	9.6	43	.41	10.5	0.046	1.2	9.00	SST	CG	N
0.360	9.14	AA-24	1.03	26.2	.260	6.6	38	6.7	.32	8.1	12	54	.50	12.7	0.050	1.3	10.0	SPR	CG	N
0.360	9.14	S-1282	1.06	27.0	.310	7.9	2.6	.46	.63	16	1.7	7.3	.18	4.4	0.025	0.6	7.00	SST	CG	N
0.360	9.14	JJ-35	1.06	27.0	.278	7.1	11	1.9	.57	14	6.3	28	.49	12.5	0.041	1.0	12.0	SST	CG	N
0.360	9.14	KK-95	1.06	27.0	.266	6.8	29	5.1	.38	9.6	11	48	.47	11.9	0.047	1.2	10.0	SPR	CG	Z
0.360	9.14	12330	1.09	27.8	.294	7.5	7.9	1.4	.47	12	3.8	17	.28	7.1	0.033	0.8	7.50	SST	C	N
0.360	9.14	S-1582	1.09	27.8	.288	7.3	8.5	1.5	.55	14	4.7	21	.34	8.7	0.036	0.9	9.50	SST	CG	N
0.360	9.14	A14-29	1.09	27.8	.272	6.9	23	4.0	.39	9.9	9.0	40	.42	10.6	0.044	1.1	9.50	SPR	CG	GI
0.360	9.14	S-857	1.09	27.8	.266	6.8	19	3.3	.49	13	9.4	42	.60	15.2	0.047	1.2	12.8	SST	CG	N
0.360	9.14	10866	1.09	27.8	.248	6.3	44	7.7	.36	9.2	16	71	.69	17.4	0.056	1.4	12.3	SST	CG	N




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.360	9.14	S-1586	1.13	28.6	.242	6.1	64	11	.29	7.4	18	82	.65	16.5	0.059	1.5	11.0	SST	CG	N
0.360	9.14	3898	1.13	28.6	.236	6.0	101	18	.22	5.7	23	101	.62	15.7	0.062	1.6	10.0	HD	CG	Z
0.360	9.14	71037	1.13	28.7	.308	7.8	3.7	.65	.75	19	2.8	12	.18	4.5	0.026	0.7	6.75	MW	CG	N
0.360	9.14	71037S	1.13	28.7	.308	7.8	3.1	.55	.59	15	1.9	8.3	.18	4.5	0.026	0.7	6.75	SST	CG	N
0.360	9.14	71056	1.13	28.7	.302	7.7	5.2	.91	.74	19	3.8	17	.21	5.4	0.029	0.7	7.38	MW	CG	N
0.360	9.14	71056S	1.13	28.7	.302	7.7	4.4	.77	.58	15	2.6	11	.21	5.4	0.029	0.7	7.38	SST	CG	N
0.360	9.14	71075	1.13	28.7	.296	7.5	7.5	1.3	.68	17	5.1	23	.25	6.3	0.032	0.8	7.75	MW	CG	N
0.360	9.14	71075S	1.13	28.7	.296	7.5	6.4	1.1	.54	14	3.4	15	.25	6.3	0.032	0.8	7.75	SST	CG	N
0.360	9.14	71093	1.13	28.7	.290	7.4	9.8	1.7	.65	17	6.3	28	.30	7.6	0.035	0.9	8.50	MW	CG	N
0.360	9.14	71093S	1.13	28.7	.290	7.4	8.3	1.5	.52	13	4.3	19	.30	7.6	0.035	0.9	8.50	SST	CG	N
0.360	9.14	71111	1.13	28.7	.284	7.2	13	2.3	.62	16	8.1	36	.34	8.6	0.038	1.0	8.88	MW	CG	N
0.360	9.14	71111S	1.13	28.7	.284	7.2	11	1.9	.50	13	5.5	24	.34	8.6	0.038	1.0	8.88	SST	CG	N
0.360	9.14	71129	1.13	28.7	.280	7.1	16	2.7	.60	15	9.4	42	.37	9.3	0.040	1.0	9.13	MW	CG	N
0.360	9.14	71129S	1.13	28.7	.280	7.1	13	2.3	.48	12	6.4	28	.37	9.3	0.040	1.0	9.13	SST	CG	N
0.360	9.14	71147	1.13	28.7	.276	7.0	19	3.3	.58	15	11	48	.39	10.0	0.042	1.1	9.38	MW	CG	N
0.360	9.14	71147S	1.13	28.7	.276	7.0	16	2.8	.46	12	7.3	33	.39	10.0	0.042	1.1	9.38	SST	CG	N
0.360	9.14	71165	1.13	28.7	.270	6.9	25	4.3	.54	14	13	59	.43	11.0	0.045	1.1	9.63	MW	CG	N
0.360	9.14	71165S	1.13	28.7	.270	6.9	21	3.7	.43	11	9.0	40	.43	11.0	0.045	1.1	9.63	SST	CG	N
0.360	9.14	71184	1.13	28.7	.266	6.8	31	5.5	.48	12	15	67	.44	11.2	0.047	1.2	9.38	MW	CG	N
0.360	9.14	71184S	1.13	28.7	.266	6.8	27	4.6	.38	9.8	10	45	.44	11.2	0.047	1.2	9.38	SST	CG	N
0.360	9.14	71206	1.13	28.7	.262	6.7	36	6.3	.47	12	17	76	.47	12.0	0.049	1.2	9.63	MW	CG	N
0.360	9.14	71206S	1.13	28.7	.262	6.7	31	5.4	.37	9.5	12	51	.47	12.0	0.049	1.2	9.63	SST	CG	N
0.360	9.14	71228	1.13	28.7	.258	6.6	42	7.4	.43	11	18	80	.50	12.8	0.051	1.3	9.88	MW	CG	N
0.360	9.14	71228S	1.13	28.7	.258	6.6	36	6.3	.34	8.6	12	54	.50	12.8	0.051	1.3	9.88	SST	CG	N
0.360	9.14	71250	1.13	28.7	.250	6.4	57	10	.39	9.9	22	99	.56	14.1	0.055	1.4	10.1	MW	CG	N
0.360	9.14	71250S	1.13	28.7	.250	6.4	48	8.5	.31	7.9	15	67	.56	14.1	0.055	1.4	10.1	SST	CG	N
0.360	9.14	71271	1.13	28.7	.242	6.1	77	13	.36	9.1	27	121	.61	15.5	0.059	1.5	10.4	MW	CG	N
0.360	9.14	71271S	1.13	28.7	.242	6.1	65	11	.28	7.2	18	82	.61	15.5	0.059	1.5	10.4	SST	CG	N
0.360	9.14	PP-77	1.16	29.4	.300	7.6	4.7	.83	.60	15	2.8	13	.24	6.1	0.030	0.8	8.00	SST	CG	N
0.360	9.14	F-35	1.19	30.2	.308	7.8	3.6	.62	.78	20	2.8	12	.21	5.3	0.026	0.7	7.00	MW	C	Z
0.360	9.14	YY-43	1.19	30.2	.292	7.4	5.1	.89	.71	18	3.6	16	.48	12.1	0.034	0.9	13.0	SPR	C	Z
0.360	9.14	3664	1.19	30.2	.270	6.9	15	2.6	.47	12	6.9	30	.72	18.3	0.045	1.1	15.0	SPR	C	Z
0.360	9.14	71038	1.25	31.8	.308	7.8	3.3	.57	.85	22	2.8	12	.19	4.9	0.026	0.7	7.38	MW	CG	N
0.360	9.14	71038S	1.25	31.8	.308	7.8	2.8	.48	.67	17	1.9	8.3	.19	4.9	0.026	0.7	7.38	SST	CG	N
0.360	9.14	S-1272	1.25	31.8	.302	7.7	4.5	.78	.57	15	2.6	11	.25	6.3	0.029	0.7	7.50	SST	C	N
0.360	9.14	71057	1.25	31.8	.302	7.7	4.6	.81	.83	21	3.8	17	.24	6.0	0.029	0.7	8.13	MW	CG	N
0.360	9.14	71057S	1.25	31.8	.302	7.7	3.9	.68	.66	17	2.6	11	.24	6.0	0.029	0.7	8.13	SST	CG	N
0.360	9.14	NN-46	1.25	31.8	.300	7.6	5.8	1.0	.49	12	2.8	13	.21	5.3	0.030	0.8	7.00	SST	CG	N
0.360	9.14	71076	1.25	31.8	.296	7.5	6.8	1.2	.75	19	5.1	23	.26	6.7	0.032	0.8	8.25	MW	CG	N
0.360	9.14	71076S	1.25	31.8	.296	7.5	5.8	1.0	.59	15	3.4	15	.26	6.7	0.032	0.8	8.25	SST	CG	N
0.360	9.14	12502	1.25	31.8	.292	7.4	8.0	1.4	.51	13	4.1	18	.31	7.8	0.034	0.9	8.00	SST	C	N
0.360	9.14	71094	1.25	31.8	.290	7.4	8.8	1.5	.73	18	6.3	28	.32	8.1	0.035	0.9	9.13	MW	CG	N
0.360	9.14	71094S	1.25	31.8	.290	7.4	7.4	1.3	.58	15	4.3	19	.32	8.1	0.035	0.9	9.13	SST	CG	N
0.360	9.14	S-1281	1.25	31.8	.286	7.3	9.4	1.6	.54	14	5.1	23	.35	8.9	0.037	0.9	9.50	SST	CG	N
0.360	9.14	TT-38	1.25	31.8	.284	7.2	9.1	1.6	.64	16	5.8	26	.49	12.5	0.038	1.0	12.0	SPR	C	Z
0.360	9.14	71112	1.25	31.8	.284	7.2	12	2.1	.68	17	8.1	36	.37	9.3	0.038	1.0	9.63	MW	CG	N
0.360	9.14	71112S	1.25	31.8	.284	7.2	10	1.8	.54	14	5.5	24	.37	9.3	0.038	1.0	9.63	SST	CG	N
0.360	9.14	71130	1.25	31.8	.280	7.1	14	2.4	.67	17	9.4	42	.40	10.2	0.040	1.0	10.0	MW	CG	N
0.360	9.14	71130S	1.25	31.8	.280	7.1	12	2.1	.54	14	6.4	28	.40	10.2	0.040	1.0	10.0	SST	CG	N
0.360	9.14	71148	1.25	31.8	.276	7.0	17	3.0	.64	16	11	48	.43	10.8	0.042	1.1	10.1	MW	CG	N
0.360	9.14	71148S	1.25	31.8	.276	7.0	14	2.5	.51	13	7.3	33	.43	10.8	0.042	1.1	10.1	SST	CG	N
0.360	9.14	71166	1.25	31.8	.270	6.9	22	3.8	.60	15	13	59	.48	12.1	0.045	1.1	10.6	MW	CG	N
0.360	9.14	71166S	1.25	31.8	.270	6.9	19	3.3	.48	12	9.0	40	.48	12.1	0.045	1.1	10.6	SST	CG	N
0.360	9.14	71185	1.25	31.8	.266	6.8	28	4.9	.54	14	15	67	.48	12.2	0.047	1.2	10.3	MW	CG	N
0.360	9.14	71185S	1.25	31.8	.266	6.8	24	4.1	.43	11	10	45	.48	12.2	0.047	1.2	10.3	SST	CG	N
0.360	9.14	71207	1.25	31.8	.262	6.7	32	5.6	.53	13	17	76	.51	13.1	0.049	1.2	10.5	MW	CG	N
0.360	9.14	71207S	1.25	31.8	.262	6.7	27	4.8	.42	11	12	51	.51	13.1	0.049	1.2	10.5	SST	CG	N
0.360	9.14	71229	1.25	31.8	.258	6.6	37	6.5	.48	12	18	80	.55	14.1	0.051	1.3	10.9	MW	CG	N
0.360	9.14	71229S	1.25	31.8	.258	6.6	32	5.6	.38	9.7	12	54	.55	14.1	0.051	1.3	10.9	SST	CG	N
0.360	9.14	71251	1.25	31.8	.250	6.4	51	8.9	.44	11	22	99	.61	15.5	0.055	1.4	11.1	MW	CG	N
0.360	9.14	71251S	1.25	31.8	.250	6.4	43	7.5	.35	8.9	15	67	.61	15.5	0.055	1.4	11.1	SST	CG	N
0.360	9.14	71272	1.25	31.8	.242	6.1	68	12	.40	10	27	121	.67	17.0	0.059	1.5	11.4	MW	CG	N
0.360	9.14	71272S	1.25	31.8	.242	6.1	58	10	.32	8.2	18	82	.67	17.0	0.059	1.5	11.4	SST	CG	N
0.360	9.14	10450	1.28	32.5	.302	7.7	2.6	.45	.88	22	2.3	10	.41	10.3	0.029	0.7	13.0	MW	C	T
0.360	9.14	HH-85	1.31	33.3	.328	8.3	.18	.03	1.1	28	.20	.89	.22	5.7	0.016	0.4	13.0	SST	C	N
0.360	9.14	S-1270	1.31	33.3	.278	7.1	10	1.7	.68	17	6.8	30	.53	13.5	0.041	1.0	13.0	SST	CG	N
0.360	9.14	MM-83	1.31	33.3	.276	7.0	17	3.0	.46	12	7.8	35	.47	12.0	0.042	1.1	10.3	SPR	C	GI
0.360	9.14	3265	1.31	33.3	.274	7.0	18	3.2	.46	12	8.4	37	.45	11.5	0.043	1.1	10.5	SPR	CG	Z
0.360	9.14	F-62	1.31	33.3	.270	6.9	23	4.0	.42	11	9.6	43	.51	13.0	0					

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	END S	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.360	9.14	71040S	1.38	35.1	.308	7.8	2.6	.45	.73	18	1.9	8.3	.20	5.2	0.026	0.7	7.88	SST	CG	N
0.360	9.14	71058	1.38	35.1	.302	7.7	4.2	.73	.92	23	3.8	17	.25	6.4	0.029	0.7	8.75	MW	CG	N
0.360	9.14	71058S	1.38	35.1	.302	7.7	3.5	.62	.73	18	2.6	11	.25	6.4	0.029	0.7	8.75	SST	CG	N
0.360	9.14	71077	1.38	35.1	.296	7.5	6.3	1.1	.82	21	5.1	23	.28	7.2	0.032	0.8	8.88	MW	CG	N
0.360	9.14	71077S	1.38	35.1	.296	7.5	5.3	.93	.65	16	3.4	15	.28	7.2	0.032	0.8	8.88	SST	CG	N
0.360	9.14	71095	1.38	35.1	.290	7.4	7.9	1.4	.81	21	6.3	28	.35	8.9	0.035	0.9	10.0	MW	CG	N
0.360	9.14	71095S	1.38	35.1	.290	7.4	6.7	1.2	.64	16	4.3	19	.35	8.9	0.035	0.9	10.0	SST	CG	N
0.360	9.14	71113	1.38	35.1	.284	7.2	10	1.8	.79	20	8.1	36	.41	10.4	0.038	1.0	10.8	MW	CG	N
0.360	9.14	71113S	1.38	35.1	.284	7.2	8.7	1.5	.63	16	5.5	24	.41	10.4	0.038	1.0	10.8	SST	CG	N
0.360	9.14	71131	1.38	35.1	.280	7.1	13	2.2	.75	19	9.4	42	.44	11.2	0.040	1.0	11.0	MW	CG	N
0.360	9.14	71131S	1.38	35.1	.280	7.1	11	1.9	.60	15	6.4	28	.44	11.2	0.040	1.0	11.0	SST	CG	N
0.360	9.14	71149	1.38	35.1	.276	7.0	16	2.8	.69	17	11	48	.45	11.5	0.042	1.1	10.8	MW	CG	N
0.360	9.14	71149S	1.38	35.1	.276	7.0	13	2.4	.55	14	7.3	33	.45	11.5	0.042	1.1	10.8	SST	CG	N
0.360	9.14	71167	1.38	35.1	.270	6.9	20	3.5	.67	17	13	59	.52	13.1	0.045	1.1	11.5	MW	CG	N
0.360	9.14	71167S	1.38	35.1	.270	6.9	17	3.0	.53	14	9.0	40	.52	13.1	0.045	1.1	11.5	SST	CG	N
0.360	9.14	71186	1.38	35.1	.266	6.8	25	4.4	.61	15	15	67	.53	13.4	0.047	1.2	11.3	MW	CG	N
0.360	9.14	71186S	1.38	35.1	.266	6.8	21	3.7	.48	12	10	45	.53	13.4	0.047	1.2	11.3	SST	CG	N
0.360	9.14	71208	1.38	35.1	.262	6.7	29	5.1	.59	15	17	76	.56	14.3	0.049	1.2	11.5	MW	CG	N
0.360	9.14	71208S	1.38	35.1	.262	6.7	25	4.3	.47	12	12	51	.56	14.3	0.049	1.2	11.5	SST	CG	N
0.360	9.14	71230	1.38	35.1	.258	6.6	34	5.9	.53	14	18	80	.61	15.4	0.051	1.3	11.9	MW	CG	N
0.360	9.14	71230S	1.38	35.1	.258	6.6	28	5.0	.43	11	12	54	.61	15.4	0.051	1.3	11.9	SST	CG	N
0.360	9.14	71252	1.38	35.1	.250	6.4	45	8.0	.49	12	22	99	.67	17.1	0.055	1.4	12.3	MW	CG	N
0.360	9.14	71252S	1.38	35.1	.250	6.4	39	6.8	.39	9.9	15	67	.67	17.1	0.055	1.4	12.3	SST	CG	N
0.360	9.14	71273	1.38	35.1	.242	6.1	61	11	.45	11	27	121	.74	18.7	0.059	1.5	12.5	MW	CG	N
0.360	9.14	71273S	1.38	35.1	.242	6.1	52	9.0	.36	9.1	18	82	.74	18.7	0.059	1.5	12.5	SST	CG	N
0.360	9.14	S-827	1.41	35.7	.294	7.5	5.4	.94	.70	18	3.8	17	.37	9.3	0.033	0.8	10.0	SST	C	N
0.360	9.14	A14-43	1.44	36.5	.294	7.5	5.2	.92	.72	18	3.8	17	.34	8.6	0.033	0.8	10.3	SST	CG	N
0.360	9.14	S-1284	1.44	36.5	.286	7.3	8.5	1.5	.59	15	5.1	23	.38	9.6	0.037	0.9	10.3	SST	CG	N
0.360	9.14	2802	1.44	36.5	.270	6.9	17	3.0	.77	19	13	59	.63	16.0	0.045	1.1	13.0	MW	C	Z
0.360	9.14	3742	1.44	36.5	.256	6.5	28	4.9	.49	12	14	61	.78	19.8	0.052	1.3	15.0	SPR	CG	Z
0.360	9.14	N-52	1.44	36.5	.246	6.2	73	13	.24	6.2	18	79	.60	15.2	0.057	1.4	9.50	SPR	C	N
0.360	9.14	10724	1.47	37.3	.278	7.1	11	1.9	.68	17	7.3	32	.61	15.4	0.041	1.0	13.8	SPR	C	Z
0.360	9.14	N-47	1.47	37.3	.236	6.0	68	12	.34	8.5	23	101	.87	22.0	0.062	1.6	14.0	SPR	CG	Z
0.360	9.14	HH-12	1.50	38.1	.312	7.9	1.3	.22	1.2	30	1.5	6.7	.31	7.9	0.024	0.6	12.0	MW	C	N
0.360	9.14	71041	1.50	38.1	.308	7.8	2.8	.48	1.0	26	2.8	12	.22	5.5	0.026	0.7	8.38	MW	CG	N
0.360	9.14	71041S	1.50	38.1	.308	7.8	2.3	.41	.79	20	1.9	8.3	.22	5.5	0.026	0.7	8.38	SST	CG	N
0.360	9.14	71059	1.50	38.1	.302	7.7	3.8	.67	1.0	25	3.8	17	.27	6.9	0.029	0.7	9.38	MW	CG	N
0.360	9.14	71059S	1.50	38.1	.302	7.7	3.3	.57	.79	20	2.6	11	.27	6.9	0.029	0.7	9.38	SST	CG	N
0.360	9.14	HH-87	1.50	38.1	.300	7.6	2.6	.45	1.1	27	2.8	12	.42	10.7	0.030	0.8	13.0	SST	C	N
0.360	9.14	S-1286	1.50	38.1	.298	7.6	4.0	.69	.79	20	3.1	14	.32	8.1	0.031	0.8	10.3	SST	CG	N
0.360	9.14	1597	1.50	38.1	.296	7.5	5.1	.89	1.0	26	5.1	23	.37	9.3	0.032	0.8	10.5	MW	C	Z
0.360	9.14	71078	1.50	38.1	.296	7.5	5.5	.95	.94	24	5.1	23	.32	8.0	0.032	0.8	9.88	MW	CG	N
0.360	9.14	71078S	1.50	38.1	.296	7.5	4.6	.81	.74	19	3.4	15	.32	8.0	0.032	0.8	9.88	SST	CG	N
0.360	9.14	K-26	1.50	38.1	.294	7.5	3.5	.60	.96	24	3.3	15	.54	13.6	0.033	0.8	16.3	SPR	CG	GI
0.360	9.14	S-1567	1.50	38.1	.292	7.4	4.7	.83	.87	22	4.1	18	.43	10.8	0.034	0.9	12.5	SST	CG	N
0.360	9.14	71096	1.50	38.1	.290	7.4	7.2	1.3	.89	23	6.3	28	.38	9.6	0.035	0.9	10.8	MW	CG	N
0.360	9.14	71096S	1.50	38.1	.290	7.4	6.1	1.1	.71	18	4.3	19	.38	9.6	0.035	0.9	10.8	SST	CG	N
0.360	9.14	G-88	1.50	38.1	.286	7.3	8.3	1.4	.61	16	5.1	23	.39	9.9	0.037	0.9	10.5	SST	CG	N
0.360	9.14	B3-67	1.50	38.1	.286	7.3	6.0	1.1	.84	21	5.1	23	.54	13.6	0.037	0.9	13.5	SST	C	N
0.360	9.14	71114	1.50	38.1	.284	7.2	9.3	1.6	.87	22	8.1	36	.44	11.2	0.038	1.0	11.6	MW	CG	N
0.360	9.14	71114S	1.50	38.1	.284	7.2	7.9	1.4	.69	18	5.5	24	.44	11.2	0.038	1.0	11.6	SST	CG	N
0.360	9.14	A13-4	1.50	38.1	.284	7.2	9.8	1.7	.60	15	5.8	26	.43	10.9	0.038	1.0	11.3	SPR	CG	GI
0.360	9.14	GG-85	1.50	38.1	.280	7.1	9.0	1.6	.71	18	6.4	28	.52	13.2	0.040	1.0	13.0	SST	CG	N
0.360	9.14	71132	1.50	38.1	.280	7.1	12	2.0	.81	21	9.4	42	.47	11.8	0.040	1.0	11.6	MW	CG	N
0.360	9.14	71132S	1.50	38.1	.280	7.1	9.9	1.7	.65	16	6.4	28	.47	11.8	0.040	1.0	11.6	SST	CG	N
0.360	9.14	71150	1.50	38.1	.276	7.0	15	2.5	.75	19	11	48	.49	12.4	0.042	1.1	11.6	MW	CG	N
0.360	9.14	71150S	1.50	38.1	.276	7.0	12	2.2	.60	15	7.3	33	.49	12.4	0.042	1.1	11.6	SST	CG	N
0.360	9.14	S-1308	1.50	38.1	.272	6.9	14	2.4	.62	16	8.4	37	.57	14.5	0.044	1.1	13.0	SST	CG	N
0.360	9.14	71168	1.50	38.1	.270	6.9	18	3.1	.74	19	13	59	.56	14.3	0.045	1.1	12.5	MW	CG	N
0.360	9.14	71168S	1.50	38.1	.270	6.9	15	2.7	.59	15	9.0	40	.56	14.3	0.045	1.1	12.5	SST	CG	N
0.360	9.14	2615	1.50	38.1	.268	6.8	20	3.5	.71	18	14	63	.58	14.6	0.046	1.2	12.5	MW	CG	Z
0.360	9.14	71187	1.50	38.1	.266	6.8	23	4.0	.66	17	15	67	.56	14.3	0.047	1.2	12.0	MW	CG	N
0.360	9.14	71187S	1.50	38.1	.266	6.8	19	3.4	.53	13	10	45	.56	14.3	0.047	1.2	12.0	SST	CG	N
0.360	9.14	71209	1.50	38.1	.262	6.7	27	4.6	.64	16	17	76	.61	15.4	0.049	1.2	12.4	MW	CG	N
0.360	9.14	71209S	1.50	38.1	.262	6.7	23	3.9	.51	13	12	51	.61	15.4	0.049	1.2	12.4	SST	CG	N
0.360	9.14	71231	1.50	38.1	.258	6.6	31	5.4	.58	15	18	80	.65	16.5	0.051	1.3	12.8	MW	CG	N
0.360	9.14	71231S	1.50	38.1	.258	6.6	26	4.6	.46	12	12	54	.65	16.5	0.051	1.3	12.8	SST	CG	N
0.360	9.14	71253	1.50	38.1	.250	6.4	42	7.3	.54	14	22	99	.72	18.3	0.055	1.4	13.1	MW	CG	N
0.360	9.14	71253S	1.50	38.1	.250	6.4	35	6.2	.43	11	15	67	.72	18.						




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH	
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm					
0.360	9.14	B8-56	1.69	42.8	.268	6.8	14	2.5	.73	19	10	45	.78	19.9	0.046	1.2	17.0	SPR	CG	N	
0.360	9.14	10245	1.69	42.8	.266	6.8	29	5.1	.38	9.6	11	48	.52	13.1	0.047	1.2	10.0	SPR	C	Z	
0.360	9.14	10623	1.75	44.5	.324	8.2		.38	.07	1.6	39		.58	2.6	0.018	0.5	11.0	SST	CG	N	
0.360	9.14	FF-96	1.75	44.5	.310	7.9	1.4	.25	1.4	36	2.0	9.0	.34	8.6	0.025	0.6	12.5	MW	C	T	
0.360	9.14	71042	1.75	44.5	.308	7.8	2.4	.42	1.2	29	2.8	12	.24	6.2	0.026	0.7	9.38	MW	CG	N	
0.360	9.14	71042S	1.75	44.5	.308	7.8	2.0	.36	.91	23	1.9	8.3	.24	6.2	0.026	0.7	9.38	SST	CG	N	
0.360	9.14	71060	1.75	44.5	.302	7.7	3.3	.57	1.2	30	3.8	17	.30	7.7	0.029	0.7	10.5	MW	CG	N	
0.360	9.14	71060S	1.75	44.5	.302	7.7	2.8	.49	.92	23	2.6	11	.30	7.7	0.029	0.7	10.5	SST	CG	N	
0.360	9.14	71079	1.75	44.5	.296	7.5	4.6	.81	1.1	28	5.1	23	.36	9.1	0.032	0.8	11.3	MW	CG	N	
0.360	9.14	71079S	1.75	44.5	.296	7.5	3.9	.68	.88	22	3.4	15	.36	9.1	0.032	0.8	11.3	SST	CG	N	
0.360	9.14	71097	1.75	44.5	.290	7.4	6.2	1.1	1.0	26	6.3	28	.42	10.8	0.035	0.9	12.1	MW	CG	N	
0.360	9.14	71097S	1.75	44.5	.290	7.4	5.3	.92	.81	21	4.3	19	.42	10.8	0.035	0.9	12.1	SST	CG	N	
0.360	9.14	71115	1.75	44.5	.284	7.2	8.3	1.4	.98	25	8.1	36	.49	12.4	0.038	1.0	12.9	MW	CG	N	
0.360	9.14	71115S	1.75	44.5	.284	7.2	7.0	1.2	.78	20	5.5	24	.49	12.4	0.038	1.0	12.9	SST	CG	N	
0.360	9.14	71133	1.75	44.5	.280	7.1	9.8	1.7	.96	24	9.4	42	.54	13.7	0.040	1.0	13.5	MW	CG	N	
0.360	9.14	71133S	1.75	44.5	.280	7.1	8.3	1.5	.76	19	6.4	28	.54	13.7	0.040	1.0	13.5	SST	CG	N	
0.360	9.14	71151	1.75	44.5	.276	7.0	12	2.1	.91	23	11	48	.58	14.7	0.042	1.1	13.8	MW	CG	N	
0.360	9.14	71151S	1.75	44.5	.276	7.0	10	1.8	.73	18	7.3	33	.58	14.7	0.042	1.1	13.8	SST	CG	N	
0.360	9.14	71169	1.75	44.5	.270	6.9	15	2.7	.86	22	13	59	.64	16.3	0.045	1.1	14.3	MW	CG	N	
0.360	9.14	71169S	1.75	44.5	.270	6.9	13	2.3	.69	17	9.0	40	.64	16.3	0.045	1.1	14.3	SST	CG	N	
0.360	9.14	HH-89	1.75	44.5	.268	6.8	12	2.1	.81	20	9.7	43	.94	24.0	0.046	1.2	19.5	SPR	C	Z	
0.360	9.14	71188	1.75	44.5	.266	6.8	19	3.4	.78	20	15	67	.65	16.6	0.047	1.2	13.9	MW	CG	N	
0.360	9.14	71188S	1.75	44.5	.266	6.8	16	2.9	.62	16	10	45	.65	16.6	0.047	1.2	13.9	SST	CG	N	
0.360	9.14	K-45	1.75	44.5	.264	6.7	16	2.8	.73	19	12	52	.91	23.2	0.048	1.2	18.0	SPR	C	GI	
0.360	9.14	71210	1.75	44.5	.262	6.7	22	3.9	.76	19	17	76	.70	17.7	0.049	1.2	14.3	MW	CG	N	
0.360	9.14	71210S	1.75	44.5	.262	6.7	19	3.3	.60	15	12	51	.70	17.7	0.049	1.2	14.3	SST	CG	N	
0.360	9.14	71232	1.75	44.5	.258	6.6	26	4.6	.69	17	18	80	.75	18.9	0.051	1.3	14.6	MW	CG	N	
0.360	9.14	71232S	1.75	44.5	.258	6.6	22	3.9	.55	14	12	54	.75	18.9	0.051	1.3	14.6	SST	CG	N	
0.360	9.14	71254	1.75	44.5	.250	6.4	35	6.2	.63	16	22	99	.84	21.3	0.055	1.4	15.3	MW	CG	N	
0.360	9.14	71254S	1.75	44.5	.250	6.4	30	5.2	.51	13	15	67	.84	21.3	0.055	1.4	15.3	SST	CG	N	
0.360	9.14	71275	1.75	44.5	.242	6.1	47	8.2	.58	15	27	121	.92	23.4	0.059	1.5	15.6	MW	CG	N	
0.360	9.14	71275S	1.75	44.5	.242	6.1	40	7.0	.46	12	18	82	.92	23.4	0.059	1.5	15.6	SST	CG	N	
0.360	9.14	2629	1.78	45.2	.290	7.4	5.0	.87	.92	23	4.6	20	.55	14.0	0.035	0.9	14.8	SPR	C	Z	
0.360	9.14	11571	1.81	46.0	.280	7.1	11	2.0	.60	15	6.8	30	.52	13.2	0.040	1.0	12.0	SPR	C	N	
0.360	9.14	S-852	1.88	47.6	.312	7.9		.59	.10	1.4		.82	3.6	.50	12.6	0.024	0.6	20.5	SST	CG	N
0.360	9.14	S-100	1.88	47.6	.260	6.6	15	2.6	.78	20	11	51	1.00	25.4	0.050	1.3	20.0	SST	CG	N	
0.360	9.14	B14-21	1.88	47.6	.250	6.4	26	4.6	.61	15	16	71	1.09	27.6	0.055	1.4	19.8	SPR	CG	Z	
0.360	9.14	A-61	1.94	49.2	.288	7.3	3.8	.66	1.2	30	4.5	20	.76	19.2	0.036	0.9	21.0	SPR	CG	Z	
0.360	9.14	10110	2.00	50.8	.310	7.9		.63	.11	1.3	.83	3.7	.68	17.1	0.025	0.6	26.0	MW	C	Z	
0.360	9.14	71043	2.00	50.8	.308	7.8	2.1	.37	1.3	34	2.8	12	.27	6.9	0.026	0.7	10.4	MW	CG	N	
0.360	9.14	71043S	2.00	50.8	.308	7.8	1.8	.31	1.0	26	1.9	8.3	.27	6.9	0.026	0.7	10.4	SST	CG	N	
0.360	9.14	71061	2.00	50.8	.302	7.7	2.8	.49	1.4	35	3.8	17	.35	8.8	0.029	0.7	12.0	MW	CG	N	
0.360	9.14	71061S	2.00	50.8	.302	7.7	2.4	.42	1.1	27	2.6	11	.35	8.8	0.029	0.7	12.0	SST	CG	N	
0.360	9.14	11884	2.00	50.8	.302	7.7	1.8	.31	1.4	37	2.6	11	.55	14.0	0.029	0.7	18.0	MW	C	N	
0.360	9.14	10185	2.00	50.8	.296	7.5	2.7	.47	1.4	35	3.8	17	.61	15.4	0.032	0.8	18.0	MW	C	Z	
0.360	9.14	71080	2.00	50.8	.296	7.5	4.0	.70	1.3	33	5.1	23	.40	10.3	0.032	0.8	12.6	MW	CG	N	
0.360	9.14	71080S	2.00	50.8	.296	7.5	3.4	.60	1.0	26	3.4	15	.40	10.3	0.032	0.8	12.6	SST	CG	N	
0.360	9.14	71098	2.00	50.8	.290	7.4	5.3	.93	1.2	30	6.3	28	.49	12.3	0.035	0.9	13.9	MW	CG	N	
0.360	9.14	71098S	2.00	50.8	.290	7.4	4.5	.79	.95	24	4.3	19	.49	12.3	0.035	0.9	13.9	SST	CG	N	
0.360	9.14	71116	2.00	50.8	.284	7.2	7.4	1.3	1.1	28	8.1	36	.54	13.8	0.038	1.0	14.3	MW	CG	N	
0.360	9.14	71116S	2.00	50.8	.284	7.2	6.2	1.1	.88	22	5.5	24	.54	13.8	0.038	1.0	14.3	SST	CG	N	
0.360	9.14	71134	2.00	50.8	.280	7.1	8.6	1.5	1.1	28	9.4	42	.60	15.2	0.040	1.0	15.0	MW	CG	N	
0.360	9.14	71134S	2.00	50.8	.280	7.1	7.3	1.3	.87	22	6.4	28	.60	15.2	0.040	1.0	15.0	SST	CG	N	
0.360	9.14	HH-14	2.00	50.8	.280	7.1	5.3	.93	1.2	29	6.1	27	.84	21.3	0.040	1.0	21.0	SST	CG	N	
0.360	9.14	71152	2.00	50.8	.276	7.0	10	1.8	1.0	26	11	48	.65	16.4	0.042	1.1	15.4	MW	CG	N	
0.360	9.14	71152S	2.00	50.8	.276	7.0	8.8	1.5	.83	21	7.3	33	.65	16.4	0.042	1.1	15.4	SST	CG	N	
0.360	9.14	71170	2.00	50.8	.270	6.9	13	2.3	1.0	25	13	59	.73	18.6	0.045	1.1	16.3	MW	CG	N	
0.360	9.14	71170S	2.00	50.8	.270	6.9	11	2.0	.80	20	9.0	40	.73	18.6	0.045	1.1	16.3	SST	CG	N	
0.360	9.14	H-40	2.00	50.8	.266	6.8	12	2.1	.86	22	10	45	.89	22.7	0.047	1.2	19.0	SST	CG	N	
0.360	9.14	71189	2.00	50.8	.266	6.8	17	2.9	.90	23	15	67	.73	18.7	0.047	1.2	15.6	MW	CG	N	
0.360	9.14	71189S	2.00	50.8	.266	6.8	14	2.5	.71	18	10	45	.73	18.7	0.047	1.2	15.6	SST	CG	N	
0.360	9.14	71211	2.00	50.8	.262	6.7	20	3.4	.87	22	17	76	.79	20.1	0.049	1.2	16.1	MW	CG	N	
0.360	9.14	71211S	2.00	50.8	.262	6.7	17	2.9	.69	18	12	51	.79	20.1	0.049	1.2	16.1	SST	CG	N	
0.360	9.14	71233	2.00	50.8	.258	6.6	23	4.0	.79	20	18	80	.85	21.5	0.051	1.3	16.6	MW	CG	N	
0.360	9.14	71233S	2.00	50.8	.258	6.6	19	3.4	.63	16	12	54	.85	21.5	0.051	1.3	16.6	SST	CG	N	
0.360	9.14	71255	2.00	50.8	.250	6.4	31	5.3	.73	19	22	99	.95	24.1	0.055	1.4	17.3	MW	CG	N	
0.360	9.14	71255S	2.00	50.8	.250	6.4	26	4.5	.58	15	15	67	.95	24.1	0.055	1.4	17.3	SST	CG	N	
0.360	9.14	71276	2.00	50.8	.242	6.1	41	7.1	.67	17	27	121	1.05	26.6	0.059	1.5	17.8	MW	CG	N	
0.360	9.14	71276S	2.00	50.8	.242	6.1	35	6.1	.53	14	18	82	1.05	26.6	0.059	1.5	17.8	SST	CG	N	

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.360	9.14	71099S	2.25	57.2	.290	7.4	4.0	.70	1.1	27	4.3	19	.54	13.7	0.035	0.9	15.4	SST	CG	N
0.360	9.14	71117	2.25	57.2	.284	7.2	6.5	1.1	1.3	32	8.1	36	.60	15.3	0.038	1.0	15.9	MW	CG	N
0.360	9.14	71117S	2.25	57.2	.284	7.2	5.5	.96	1.0	25	5.5	24	.60	15.3	0.038	1.0	15.9	SST	CG	N
0.360	9.14	71135	2.25	57.2	.280	7.1	7.6	1.3	1.2	32	9.4	42	.68	17.1	0.040	1.0	16.9	MW	CG	N
0.360	9.14	71135S	2.25	57.2	.280	7.1	6.4	1.1	.99	25	6.4	28	.68	17.1	0.040	1.0	16.9	SST	CG	N
0.360	9.14	71153	2.25	57.2	.276	7.0	9.1	1.6	1.2	30	11	48	.73	18.5	0.042	1.1	17.4	MW	CG	N
0.360	9.14	71153S	2.25	57.2	.276	7.0	7.7	1.3	.95	24	7.3	33	.73	18.5	0.042	1.1	17.4	SST	CG	N
0.360	9.14	71171	2.25	57.2	.270	6.9	12	2.1	1.1	29	13	59	.81	20.6	0.045	1.1	18.0	MW	CG	N
0.360	9.14	71171S	2.25	57.2	.270	6.9	10	1.7	.90	23	9.0	40	.81	20.6	0.045	1.1	18.0	SST	CG	N
0.360	9.14	71190	2.25	57.2	.266	6.8	15	2.6	1.0	26	15	67	.82	20.7	0.047	1.2	17.4	MW	CG	N
0.360	9.14	71190S	2.25	57.2	.266	6.8	13	2.2	.81	20	10	45	.82	20.7	0.047	1.2	17.4	SST	CG	N
0.360	9.14	10347	2.25	57.2	.264	6.7	22	3.9	.52	13	12	52	.65	16.5	0.048	1.2	13.5	SPR	CG	Z
0.360	9.14	71212	2.25	57.2	.262	6.7	17	3.0	.99	25	17	76	.88	22.4	0.049	1.2	18.0	MW	CG	N
0.360	9.14	71212S	2.25	57.2	.262	6.7	15	2.6	.79	20	12	51	.88	22.4	0.049	1.2	18.0	SST	CG	N
0.360	9.14	71234	2.25	57.2	.258	6.6	20	3.5	.90	23	18	80	.95	24.1	0.051	1.3	18.6	MW	CG	N
0.360	9.14	71234S	2.25	57.2	.258	6.6	17	3.0	.72	18	12	54	.95	24.1	0.051	1.3	18.6	SST	CG	N
0.360	9.14	71256	2.25	57.2	.250	6.4	27	4.7	.83	21	22	99	1.06	26.9	0.055	1.4	19.3	MW	CG	N
0.360	9.14	71256S	2.25	57.2	.250	6.4	23	4.0	.66	17	15	67	1.06	26.9	0.055	1.4	19.3	SST	CG	N
0.360	9.14	71277	2.25	57.2	.242	6.1	36	6.3	.76	19	27	121	1.17	29.6	0.059	1.5	19.8	MW	CG	N
0.360	9.14	71277S	2.25	57.2	.242	6.1	31	5.4	.60	15	18	82	1.17	29.6	0.059	1.5	19.8	SST	CG	N
0.360	9.14	U-61A	2.28	57.9	.272	6.9	10	1.8	.89	22	9.0	40	.88	22.4	0.044	1.1	19.0	SPR	C	Z
0.360	9.14	12229	2.34	59.5	.304	7.7	1.7	.30	1.9	48	3.3	15	.45	11.4	0.028	0.7	16.0	MW	CG	GI
0.360	9.14	S-1589	2.34	59.5	.284	7.2	3.7	.64	1.4	36	5.2	23	.91	23.2	0.038	1.0	24.0	SST	CG	N
0.360	9.14	71082	2.50	63.5	.296	7.5	3.3	.58	1.5	39	5.1	23	.48	12.1	0.032	0.8	14.9	MW	CG	N
0.360	9.14	71082S	2.50	63.5	.296	7.5	2.8	.49	1.2	31	3.4	15	.48	12.1	0.032	0.8	14.9	SST	CG	N
0.360	9.14	71100	2.50	63.5	.290	7.4	4.2	.74	1.5	38	6.3	28	.60	15.1	0.035	0.9	17.0	MW	CG	N
0.360	9.14	71100S	2.50	63.5	.290	7.4	3.6	.63	1.2	31	4.3	19	.60	15.1	0.035	0.9	17.0	SST	CG	N
0.360	9.14	71118	2.50	63.5	.284	7.2	5.8	1.0	1.4	36	8.1	36	.67	17.0	0.038	1.0	17.6	MW	CG	N
0.360	9.14	71118S	2.50	63.5	.284	7.2	4.9	.86	1.1	28	5.5	24	.67	17.0	0.038	1.0	17.6	SST	CG	N
0.360	9.14	71136	2.50	63.5	.280	7.1	6.7	1.2	1.4	36	9.4	42	.75	19.1	0.040	1.0	18.8	MW	CG	N
0.360	9.14	71136S	2.50	63.5	.280	7.1	5.7	1.0	1.1	28	6.4	28	.75	19.1	0.040	1.0	18.8	SST	CG	N
0.360	9.14	71154	2.50	63.5	.276	7.0	8.2	1.4	1.3	34	11	48	.80	20.3	0.042	1.1	19.0	MW	CG	N
0.360	9.14	71154S	2.50	63.5	.276	7.0	6.9	1.2	1.1	27	7.3	33	.80	20.3	0.042	1.1	19.0	SST	CG	N
0.360	9.14	3600	2.50	63.5	.270	6.9	10	1.8	1.3	34	13	59	.99	25.1	0.045	1.1	21.0	MW	C	Z
0.360	9.14	71172	2.50	63.5	.270	6.9	11	1.8	1.3	32	13	59	.89	22.7	0.045	1.1	19.9	MW	CG	N
0.360	9.14	71172S	2.50	63.5	.270	6.9	9.0	1.6	1.0	25	9.0	40	.89	22.7	0.045	1.1	19.9	SST	CG	N
0.360	9.14	71191	2.50	63.5	.266	6.8	13	2.3	1.1	29	15	67	.90	23.0	0.047	1.2	19.3	MW	CG	N
0.360	9.14	71191S	2.50	63.5	.266	6.8	11	2.0	.90	23	10	45	.90	23.0	0.047	1.2	19.3	SST	CG	N
0.360	9.14	3788	2.50	63.5	.264	6.7	10	1.8	1.1	29	12	52	1.30	32.9	0.048	1.2	20.7	SPR	CG	Z
0.360	9.14	71213	2.50	63.5	.262	6.7	15	2.7	1.1	28	17	76	.97	24.7	0.049	1.2	19.9	MW	CG	N
0.360	9.14	71213S	2.50	63.5	.262	6.7	13	2.3	.88	22	12	51	.97	24.7	0.049	1.2	19.9	SST	CG	N
0.360	9.14	12473	2.50	63.5	.260	6.6	15	2.7	.80	20	12	54	1.10	27.9	0.050	1.3	22.0	SPR	CG	Z
0.360	9.14	71235	2.50	63.5	.258	6.6	18	3.1	1.0	25	18	80	1.04	26.4	0.051	1.3	20.4	MW	CG	N
0.360	9.14	71235S	2.50	63.5	.258	6.6	15	2.7	.80	20	12	54	1.04	26.4	0.051	1.3	20.4	SST	CG	N
0.360	9.14	71257	2.50	63.5	.250	6.4	24	4.2	.92	23	22	99	1.17	29.7	0.055	1.4	21.3	MW	CG	N
0.360	9.14	71257S	2.50	63.5	.250	6.4	20	3.6	.74	19	15	67	1.17	29.7	0.055	1.4	21.3	SST	CG	N
0.360	9.14	71278	2.50	63.5	.242	6.1	32	5.6	.85	22	27	121	1.29	32.8	0.059	1.5	21.9	MW	CG	N
0.360	9.14	71278S	2.50	63.5	.242	6.1	27	4.8	.68	17	18	82	1.29	32.8	0.059	1.5	21.9	SST	CG	N
0.360	9.14	LL-12	2.63	66.7	.180	4.6	262	46	.22	5.7	59	260	1.85	46.9	0.090	2.3	20.5	SPR	CG	Z
0.360	9.14	B10-53	2.69	68.2	.274	7.0	9.7	1.7	.86	22	8.4	37	.82	20.8	0.043	1.1	18.0	SPR	C	BO
0.360	9.14	3940	2.69	68.2	.252	6.4	21	3.7	.72	18	15	68	1.20	30.5	0.054	1.4	22.3	SPR	CG	Z
0.360	9.14	71173	2.75	69.9	.270	6.9	9.6	1.7	1.4	35	13	59	.97	24.7	0.045	1.1	21.6	MW	CG	N
0.360	9.14	71173S	2.75	69.9	.270	6.9	8.2	1.4	1.1	28	9.0	40	.97	24.7	0.045	1.1	21.6	SST	CG	N
0.360	9.14	71192	2.75	69.9	.266	6.8	12	2.1	1.2	32	15	67	.98	24.9	0.047	1.2	20.9	MW	CG	N
0.360	9.14	71192S	2.75	69.9	.266	6.8	10	1.8	.99	25	10	45	.98	24.9	0.047	1.2	20.9	SST	CG	N
0.360	9.14	71214	2.75	69.9	.262	6.7	14	2.5	1.2	31	17	76	1.06	26.9	0.049	1.2	21.6	MW	CG	N
0.360	9.14	71214S	2.75	69.9	.262	6.7	12	2.1	.97	25	12	51	1.06	26.9	0.049	1.2	21.6	SST	CG	N
0.360	9.14	71236	2.75	69.9	.258	6.6	16	2.8	1.1	28	18	80	1.14	29.0	0.051	1.3	22.4	MW	CG	N
0.360	9.14	71236S	2.75	69.9	.258	6.6	14	2.4	.88	22	12	54	1.14	29.0	0.051	1.3	22.4	SST	CG	N
0.360	9.14	71258	2.75	69.9	.250	6.4	22	3.8	1.0	26	22	99	1.28	32.5	0.055	1.4	23.3	MW	CG	N
0.360	9.14	71258S	2.75	69.9	.250	6.4	19	3.3	.81	21	15	67	1.28	32.5	0.055	1.4	23.3	SST	CG	N
0.360	9.14	71279	2.75	69.9	.242	6.1	29	5.1	.94	24	27	121	1.42	36.0	0.059	1.5	24.0	MW	CG	N
0.360	9.14	71279S	2.75	69.9	.242	6.1	25	4.3	.75	19	18	82	1.42	36.0	0.059	1.5	24.0	SST	CG	N
0.360	9.14	4318	2.81	71.4	.272	6.9	7.4	1.3	1.2	31	9.0	40	1.16	29.3	0.044	1.1	25.3	SPR	C	Z
0.360	9.14	10642	2.88	73.0	.270	6.9	7.6	1.3	1.3	32	9.6	43	1.26	32.0	0.045	1.1	27.0	SPR	C	Z
0.360	9.14	LL-32	2.88	73.0	.240	6.1	25	4.3	.78	20	19	86	1.62	41.1	0.060	1.5	27.0	SST	CG	N
0.360	9.14	12154	3.00	76.2	.274	7.0	5.8	1.0	1.5	37	8.4	37	1.25	31.7	0.043	1.1	29.0	SPR	CG	Z
0.360	9.14	71193	3.00	76.2	.266	6.8	11	1.9	1.4	35	15	67	1.07	27.2	0.047	1.2	22.8	MW	CG	N
0.3																				




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.360	9.14	71216	3.25	82.6	.262	6.7	12	2.1	1.4	37	17	76	1.24	31.6	0.049	1.2	25.4	MW	CG	N
0.360	9.14	71216S	3.25	82.6	.262	6.7	10	1.8	1.1	29	12	51	1.24	31.6	0.049	1.2	25.4	SST	CG	N
0.360	9.14	71238	3.25	82.6	.258	6.6	14	2.4	1.3	33	18	80	1.34	34.0	0.051	1.3	26.3	MW	CG	N
0.360	9.14	71238S	3.25	82.6	.258	6.6	12	2.0	1.0	27	12	54	1.34	34.0	0.051	1.3	26.3	SST	CG	N
0.360	9.14	71260	3.25	82.6	.250	6.4	19	3.2	1.2	31	22	99	1.49	37.7	0.055	1.4	27.0	MW	CG	N
0.360	9.14	71260S	3.25	82.6	.250	6.4	16	2.8	.96	24	15	67	1.49	37.7	0.055	1.4	27.0	SST	CG	N
0.360	9.14	71281	3.25	82.6	.242	6.1	25	4.3	1.1	28	27	121	1.66	42.1	0.059	1.5	28.1	MW	CG	N
0.360	9.14	71281S	3.25	82.6	.242	6.1	21	3.6	.89	23	18	82	1.66	42.1	0.059	1.5	28.1	SST	CG	N
0.360	9.14	10850	3.50	88.9	.280	7.1	5.0	.88	1.3	32	6.4	28	.88	22.4	0.040	1.0	22.0	SST	CG	N
0.360	9.14	71195	3.50	88.9	.266	6.8	9.4	1.6	1.6	41	15	67	1.24	31.5	0.047	1.2	26.4	MW	CG	N
0.360	9.14	71195S	3.50	88.9	.266	6.8	8.0	1.4	1.3	32	10	45	1.24	31.5	0.047	1.2	26.4	SST	CG	N
0.360	9.14	71217	3.50	88.9	.262	6.7	11	1.9	1.6	40	17	76	1.34	33.9	0.049	1.2	27.3	MW	CG	N
0.360	9.14	71217S	3.50	88.9	.262	6.7	9.3	1.6	1.2	32	12	51	1.34	33.9	0.049	1.2	27.3	SST	CG	N
0.360	9.14	71239	3.50	88.9	.258	6.6	13	2.2	1.4	36	18	80	1.43	36.4	0.051	1.3	28.1	MW	CG	N
0.360	9.14	71239S	3.50	88.9	.258	6.6	11	1.9	1.1	29	12	54	1.43	36.4	0.051	1.3	28.1	SST	CG	N
0.360	9.14	71261	3.50	88.9	.250	6.4	17	3.0	1.3	33	22	99	1.60	40.7	0.055	1.4	29.1	MW	CG	N
0.360	9.14	71261S	3.50	88.9	.250	6.4	15	2.5	1.0	26	15	67	1.60	40.7	0.055	1.4	29.1	SST	CG	N
0.360	9.14	71282	3.50	88.9	.242	6.1	23	4.0	1.2	31	27	121	1.78	45.1	0.059	1.5	30.1	MW	CG	N
0.360	9.14	71282S	3.50	88.9	.242	6.1	19	3.4	.96	24	18	82	1.78	45.1	0.059	1.5	30.1	SST	CG	N
0.360	9.14	UU-54	3.75	95.3	.290	7.4	2.0	.35	2.3	59	4.6	20	1.23	31.1	0.035	0.9	34.0	SPR	C	Z
0.360	9.14	2907	4.00	101.6	.180	4.6	148	26	.40	10	59	260	3.13	79.4	0.090	2.3	34.8	SPR	CG	Z
0.360	9.14	L-33	4.13	104.8	.266	6.8	6.1	1.1	1.8	46	11	48	1.88	47.8	0.047	1.2	40.0	SPR	CG	Z
0.360	9.14	11422	4.38	111.1	.300	7.6	.91	.16	3.2	81	2.9	13	1.17	29.7	0.030	0.8	38.0	MW	C	Z
0.360	9.14	11515	4.81	122.2	.292	7.4	1.7	.31	2.5	64	4.4	20	1.19	30.2	0.034	0.9	34.0	SPR	C	Z
0.360	9.14	3053	4.88	123.8	.266	6.8	5.4	.94	2.0	51	11	48	2.12	53.7	0.047	1.2	45.0	HD	CG	Z
0.360	9.14	12265	5.25	133.4	.236	6.0	32	5.7	.70	18	23	101	1.67	42.5	0.062	1.6	27.0	SPR	CG	GI
0.360	9.14	12117	6.25	158.8	.282	7.2	2.1	.37	3.0	76	6.3	28	1.99	50.5	0.039	1.0	50.0	SPR	C	Z
0.360	9.14	2623	6.50	165.1	.284	7.2	2.0	.36	2.9	73	5.8	26	1.81	45.8	0.038	1.0	46.5	SPR	C	Z
0.360	9.14	12202	7.63	193.7	.264	6.7	3.8	.66	3.1	78	12	52	3.36	85.3	0.048	1.2	69.0	SPR	C	Z
0.362	9.19	12745	1.19	30.1	.290	7.4	7.7	1.4	.76	19	5.8	26	.43	11.0	0.036	0.9	11.0	MW	C	N
0.364	9.25	12694	2.25	57.2	.264	6.7	18	3.2	.92	23	17	74	.95	24.1	0.050	1.3	18.0	MW	C	BO
0.370	9.40	B4-61	.88	22.2	.314	8.0	5.5	.96	.41	10	2.3	10	.18	4.6	0.028	0.7	5.50	SST	C	N
0.375	9.53	BB-89	.19	4.8	.335	8.5	8.9	1.6	.10	2.4	.86	3.8	.07	1.8	0.020	0.5	2.50	SST	C	N
0.375	9.53	4104	.25	6.4	.291	7.4	121	21	.06	1.6	7.5	34	.13	3.2	0.042	1.1	3.00	SPR	CG	Z
0.375	9.53	3289	.28	7.1	.299	7.6	39	6.9	.09	2.3	3.6	16	.19	4.8	0.038	1.0	4.00	SPR	C	Z
0.375	9.53	10183	.31	7.9	.347	8.8	.78	.14	.25	6.3	.19	.87	.06	1.6	0.014	0.4	3.50	MW	C	T
0.375	9.53	S-1315	.38	9.5	.315	8.0	25	4.3	.11	2.8	2.7	12	.12	3.0	0.030	0.8	3.00	SST	C	N
0.375	9.53	K-20	.38	9.5	.305	7.7	27	4.8	.16	4.1	4.4	20	.18	4.4	0.035	0.9	4.00	SPR	C	GI
0.375	9.53	K-69	.38	9.5	.293	7.4	32	5.5	.17	4.3	5.4	24	.21	5.2	0.041	1.0	5.00	SST	CG	N
0.375	9.53	A-32	.38	9.5	.285	7.2	66	11	.14	3.6	9.2	41	.20	5.1	0.045	1.1	4.50	SPR	CG	N
0.375	9.53	A10-38	.38	9.5	.273	6.9	127	22	.09	2.3	12	52	.20	5.2	0.051	1.3	4.00	SST	CG	N
0.375	9.53	S-166	.38	9.5	.265	6.7	116	20	.10	2.5	12	52	.28	7.0	0.055	1.4	5.00	SST	CG	N
0.375	9.53	10634	.41	10.3	.315	8.0	20	3.5	.14	3.4	2.7	12	.13	3.3	0.030	0.8	3.25	SST	C	N
0.375	9.53	B2-47	.42	10.7	.279	7.1	87	15	.13	3.2	11	50	.26	6.7	0.048	1.2	4.50	SPR	C	N
0.375	9.53	H-4	.44	11.1	.291	7.4	42	7.4	.17	4.3	7.1	31	.19	4.8	0.042	1.1	4.50	SST	CG	N
0.375	9.53	10132	.44	11.1	.285	7.2	66	11	.14	3.6	9.2	41	.20	5.2	0.045	1.1	4.50	SPR	CG	Z
0.375	9.53	V-38	.44	11.1	.285	7.2	82	14	.11	2.9	9.2	41	.18	4.6	0.045	1.1	4.00	SPR	CG	Z
0.375	9.53	B4-17	.44	11.1	.279	7.1	87	15	.13	3.2	11	50	.26	6.7	0.048	1.2	4.50	SPR	C	N
0.375	9.53	3666	.47	11.9	.327	8.3	3.3	.58	.34	8.6	1.1	5.0	.13	3.2	0.024	0.6	5.33	MW	C	Z
0.375	9.53	AA-66	.47	11.9	.305	7.7	16	2.8	.25	6.5	4.1	18	.21	5.3	0.035	0.9	5.00	SST	C	N
0.375	9.53	O-61	.47	11.9	.295	7.5	33	5.7	.20	5.1	6.5	29	.24	6.1	0.040	1.0	5.00	SPR	C	N
0.375	9.53	F-33	.47	11.9	.285	7.2	94	16	.10	2.5	9.2	41	.21	5.4	0.045	1.1	4.75	SPR	C	Z
0.375	9.53	TT-36	.47	11.9	.283	7.2	52	9.0	.19	4.8	9.8	44	.25	6.4	0.046	1.2	5.50	SPR	CG	Z
0.375	9.53	A-20	.47	11.9	.275	7.0	58	10	.17	4.3	9.7	43	.30	7.6	0.050	1.3	6.00	SST	CG	N
0.375	9.53	2583	.50	12.7	.335	8.5	2.1	.36	.39	9.9	.80	3.6	.11	2.8	0.020	0.5	4.50	MW	C	Z
0.375	9.53	N-36	.50	12.7	.335	8.5	1.8	.31	.39	9.9	.70	3.1	.11	2.8	0.020	0.5	4.50	SST	C	N
0.375	9.53	PP-71	.50	12.7	.335	8.5	.82	.14	.32	8.0	.26	1.2	.19	4.7	0.020	0.5	8.25	MW	C	BO
0.375	9.53	NN-38	.50	12.7	.333	8.5	.90	.16	.29	7.4	.26	1.2	.21	5.3	0.021	0.5	9.00	MW	C	N
0.375	9.53	B12-33	.50	12.7	.331	8.4	1.9	.34	.37	9.3	.70	3.1	.13	3.4	0.022	0.6	6.00	MW	CG	N
0.375	9.53	4254	.50	12.7	.329	8.4	1.7	.29	.30	7.7	.51	2.3	.20	5.0	0.023	0.6	7.50	MW	C	T
0.375	9.53	K-5	.50	12.7	.323	8.2	2.6	.45	.27	6.8	.69	3.0	.23	5.9	0.026	0.7	8.00	MW	C	Z
0.375	9.53	CC-46	.50	12.7	.311	7.9	8.1	1.4	.28	7.0	2.2	10	.22	5.7	0.032	0.8	6.00	SST	C	N
0.375	9.53	S-1184	.50	12.7	.303	7.7	20	3.4	.23	5.8	4.5	20	.17	4.3	0.036	0.9	4.75	SST	CG	N
0.375	9.53	BB-6	.50	12.7	.301	7.6	17	3.0	.26	6.6	4.5	20	.24	6.1	0.037	0.9	5.50	SST	C	N
0.375	9.53	10153	.50	12.7	.293	7.4	31	5.5	.23	5.7	7.0	31	.23	5.7	0.041	1.0	5.50	SPR	CG	Z
0.375	9.53	S-837	.50	12.7	.293	7.4	32	5.5	.21	5.3	6.6	29	.21	5.2	0.041	1.0	5.00	SST	CG	N
0.375	9.53	EE-50	.50	12.7	.293	7.4	44	7.6	.16	4.1	7.0	31	.23	5.7	0.041	1.0	4.50	SPR	C	N
0.375	9.53	938	.50	12.7	.281	7.1	99	17	.11	2.7	10	47	.24	6.0	0.047	1.2	4.00	HD	C	Z
0.375	9.53	K-96	.50	12.7	.281	7.1	57	9.9	.18	4.7	10	47	.26	6.6	0.047	1.2	5.50	SPR	CG	N
0.375	9.53	MM-77	.50	12.7	.275	7.0	65	11	.1											

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	END S	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.375	9.53	Z-58	.53	13.5	.303	7.7	21	3.6	.23	5.9	4.8	21	.18	4.6	0.036	0.9	5.00	SPR	CG	Z
0.375	9.53	F-28	.53	13.5	.285	7.2	55	9.6	.17	4.3	9.2	41	.27	6.9	0.045	1.1	5.00	HD	C	Z
0.375	9.53	UU-62	.53	13.5	.281	7.1	66	12	.16	4.0	10	47	.28	7.2	0.047	1.2	5.00	SPR	C	Z
0.375	9.53	10136	.53	13.5	.215	5.5	765	134	.06	1.4	43	190	.40	10.2	0.080	2.0	5.00	SPR	CG	N
0.375	9.53	10613	.53	13.5	.215	5.5	706	124	.06	1.5	43	190	.42	10.7	0.080	2.0	5.25	SPR	CG	N
0.375	9.53	BB-37	.56	14.3	.345	8.8		.45	.08		.21	.95	.09	2.3	0.015	0.4	5.00	SST	C	N
0.375	9.53	F-45	.56	14.3	.323	8.2	7.7	1.4	.34	8.8	2.7	12	.13	3.3	0.026	0.7	4.00	MW	C	Z
0.375	9.53	10581	.56	14.3	.317	8.1	7.6	1.3	.41	10	3.1	14	.15	3.9	0.029	0.7	5.25	MW	CG	Z
0.375	9.53	2654	.56	14.3	.299	7.6	26	4.6	.22	5.5	5.6	25	.19	4.8	0.038	1.0	5.00	SPR	CG	Z
0.375	9.53	1891	.56	14.3	.285	7.2	41	7.2	.23	5.7	9.2	41	.27	6.9	0.045	1.1	6.00	SPR	CG	Z
0.375	9.53	O-75	.56	14.3	.283	7.2	45	7.9	.22	5.5	9.8	44	.28	7.0	0.046	1.2	6.00	SPR	CG	N
0.375	9.53	J-56	.56	14.3	.281	7.1	50	8.8	.19	5.0	9.8	44	.31	7.8	0.047	1.2	5.50	SST	C	N
0.375	9.53	I-33	.56	14.3	.277	7.0	80	14	.15	3.8	12	53	.29	7.5	0.049	1.2	5.00	SPR	C	N
0.375	9.53	B15-17	.56	14.3	.211	5.4	646	113	.07	1.8	45	201	.49	12.5	0.082	2.1	6.00	SPR	CG	N
0.375	9.53	W-15	.59	15.1	.323	8.2	2.4	.42	.35	8.8	.82	3.7	.25	6.3	0.026	0.7	8.50	MW	C	N
0.375	9.53	S-908	.59	15.1	.301	7.6	15	2.7	.31	8.0	4.9	22	.22	5.6	0.037	0.9	6.00	SST	CG	N
0.375	9.53	B14-7	.59	15.1	.289	7.3	38	6.7	.21	5.4	8.1	36	.24	6.0	0.043	1.1	5.50	SPR	CG	N
0.375	9.53	B12-48	.63	15.9	.347	8.8		.59	.10		.33	1.4	.07	1.8	0.014	0.4	4.00	MW	C	N
0.375	9.53	OO-63	.63	15.9	.335	8.5	1.5	.26	.51	13	.75	3.3	.12	3.0	0.020	0.5	5.00	SST	C	N
0.375	9.53	HH-80	.63	15.9	.331	8.4	1.7	.30	.46	12	.78	3.5	.17	4.2	0.022	0.6	6.50	MW	C	N
0.375	9.53	O-90	.63	15.9	.327	8.3	1.6	.28	.41	10	.65	2.9	.22	5.5	0.024	0.6	8.00	SST	C	N
0.375	9.53	12433	.63	15.9	.323	8.2	5.2	.90	.47	12	2.4	11	.16	4.0	0.026	0.7	5.00	MW	C	GI
0.375	9.53	G-95	.63	15.9	.323	8.2	2.4	.42	.40	10	.96	4.3	.22	5.6	0.026	0.7	8.50	MW	CG	N
0.375	9.53	10305	.63	15.9	.317	8.1	3.5	.61	.34	8.5	1.2	5.2	.29	7.4	0.029	0.7	9.00	MW	CG	Z
0.375	9.53	Z-8	.63	15.9	.315	8.0	4.7	.83	.39	9.8	1.8	8.1	.24	6.1	0.030	0.8	8.00	MW	CG	Z
0.375	9.53	2603	.63	15.9	.303	7.7	15	2.7	.37	9.5	5.8	26	.25	6.4	0.036	0.9	6.00	MW	C	Z
0.375	9.53	KK-38	.63	15.9	.295	7.5	17	2.9	.34	8.5	5.5	25	.29	7.4	0.040	1.0	7.25	SST	CG	N
0.375	9.53	BB-54	.63	15.9	.289	7.3	34	5.9	.24	6.1	8.1	36	.26	6.6	0.043	1.1	6.00	SPR	CG	Z
0.375	9.53	516	.63	15.9	.281	7.1	46	8.0	.23	5.8	10	47	.34	8.8	0.047	1.2	6.33	HD	C	Z
0.375	9.53	H-60-A	.63	15.9	.281	7.1	36	6.3	.27	6.9	9.8	44	.35	9.0	0.047	1.2	7.50	SPR	CG	Z
0.375	9.53	S-3027	.63	15.9	.273	6.9	68	12	.17	4.4	12	52	.34	8.7	0.051	1.3	5.75	SST	C	N
0.375	9.53	G-97	.63	15.9	.263	6.7	145	25	.11	2.9	16	73	.34	8.5	0.056	1.4	5.00	SPR	C	N
0.375	9.53	RR-12	.63	15.9	.255	6.5	119	21	.15	3.7	17	77	.48	12.2	0.060	1.5	7.00	MW	C	N
0.375	9.53	507	.63	15.9	.251	6.4	160	28	.14	3.5	22	97	.45	11.5	0.062	1.6	6.33	HD	C	Z
0.375	9.53	F-46	.63	15.9	.249	6.3	186	33	.12	3.1	23	102	.38	9.6	0.063	1.6	6.00	HD	CG	N
0.375	9.53	K-70	.63	15.9	.231	5.9	278	49	.11	2.9	32	142	.50	12.8	0.072	1.8	7.00	SPR	CG	N
0.375	9.53	11311	.63	15.9	.225	5.7	421	74	.08	2.2	36	159	.45	11.4	0.075	1.9	6.00	SPR	CG	Z
0.375	9.53	S-1689	.64	16.3	.325	8.3	5.7	1.0	.28	7.1	1.6	7.1	.13	3.2	0.025	0.6	4.00	SST	C	N
0.375	9.53	1785	.66	16.7	.323	8.2	5.2	.90	.50	13	2.6	11	.16	4.0	0.026	0.7	5.00	MW	C	Z
0.375	9.53	12655	.66	16.7	.323	8.2	5.6	.98	.47	12	2.7	12	.15	3.8	0.026	0.7	4.75	MW	C	N
0.375	9.53	2769	.66	16.7	.211	5.4	704	123	.09	2.3	64	285	.55	13.9	0.082	2.1	5.67	MW	C	Z
0.375	9.53	12429	.69	17.4	.327	8.3	3.7	.64	.54	14	2.0	8.9	.14	3.7	0.024	0.6	5.00	MW	C	GI
0.375	9.53	12421	.69	17.4	.321	8.2	6.0	1.1	.49	13	3.0	13	.16	4.1	0.027	0.7	5.00	MW	C	N
0.375	9.53	S-892	.69	17.4	.311	7.9	4.1	.71	.34	8.5	1.4	6.0	.35	8.9	0.032	0.8	10.0	SST	C	N
0.375	9.53	3637	.69	17.4	.305	7.7	11	1.9	.40	10	4.4	20	.28	7.1	0.035	0.9	7.00	SPR	C	Z
0.375	9.53	B12-26	.69	17.4	.305	7.7	14	2.4	.32	8.2	4.4	20	.21	5.3	0.035	0.9	6.00	SPR	CG	N
0.375	9.53	A15-3	.69	17.4	.297	7.5	21	3.6	.29	7.5	6.1	27	.24	6.2	0.039	1.0	6.25	SPR	CG	N
0.375	9.53	I-85	.69	17.4	.283	7.2	28	4.9	.25	6.4	7.0	31	.44	11.1	0.046	1.2	8.50	SPR	C	N
0.375	9.53	KK-8	.69	17.4	.271	6.9	62	11	.21	5.4	13	58	.36	9.2	0.052	1.3	7.00	SPR	CG	Z
0.375	9.53	H-11	.69	17.4	.251	6.4	173	30	.13	3.2	22	97	.37	9.4	0.062	1.6	6.00	SPR	CG	Z
0.375	9.53	A12-15	.70	17.9	.333	8.5		.55	.10		.22	.97	.31	7.7	0.021	0.5	13.5	MW	C	N
0.375	9.53	4252	.75	19.1	.343	8.7	.34	.06	.61	15	.21	.91	.14	3.7	0.016	0.4	8.00	MW	C	T
0.375	9.53	FF-52	.75	19.1	.341	8.7	.24	.04	.54	14	.13	.57	.21	5.4	0.017	0.4	11.5	SST	C	N
0.375	9.53	S-7	.75	19.1	.335	8.5	.75	.13	.57	14	.42	1.9	.18	4.6	0.020	0.5	8.00	SST	C	N
0.375	9.53	B2-7	.75	19.1	.333	8.5	.55	.10	.45	11	.24	1.1	.31	7.7	0.021	0.5	13.5	MW	CL	N
0.375	9.53	GG-99	.75	19.1	.325	8.3	2.8	.50	.56	14	1.6	7.1	.18	4.4	0.025	0.6	6.00	SST	C	N
0.375	9.53	G-99	.75	19.1	.323	8.2	5.2	.90	.52	13	2.7	12	.16	4.0	0.026	0.7	5.00	MW	C	N
0.375	9.53	A-51	.75	19.1	.319	8.1	3.7	.64	.55	14	2.0	9.1	.20	5.0	0.028	0.7	7.00	SST	CG	N
0.375	9.53	526	.75	19.1	.313	8.0	7.7	1.3	.42	11	3.2	14	.22	5.7	0.031	0.8	6.25	HD	C	Z
0.375	9.53	A-70	.75	19.1	.297	7.5	17	3.0	.34	8.5	5.7	25	.25	6.4	0.039	1.0	6.50	SST	CG	N
0.375	9.53	I-12	.75	19.1	.295	7.5	24	4.3	.27	6.8	6.5	29	.24	6.1	0.040	1.0	6.00	SPR	CG	GI
0.375	9.53	B2-70	.75	19.1	.295	7.5	24	4.3	.37	9.4	9.0	40	.28	7.1	0.040	1.0	6.00	MW	C	N
0.375	9.53	291	.75	19.1	.293	7.4	23	4.0	.31	7.8	7.0	31	.32	8.1	0.041	1.0	6.75	HD	C	Z
0.375	9.53	S-740	.75	19.1	.291	7.4	22	3.9	.32	8.1	7.1	31	.33	8.3	0.042	1.1	6.75	SST	C	N
0.375	9.53	12234	.75	19.1	.291	7.4	24	4.2	.31	7.9	7.5	34	.34	8.5	0.042	1.1	7.00	SPR	C	Z
0.375	9.53	B15-61	.75	19.1	.285	7.2	30	5.2	.31	7.9	9.2	41	.38	9.7	0.045	1.1	7.50	SPR	C	N
0.375	9.53	F-37	.75	19.1	.283	7.2	36	6.3	.27	6.9	9.8	44	.37	9.3	0.046	1.2	7.00	HD	C	Z
0.375	9.53	II-79	.75	19.1	.281	7.1	31	5.4	.30	7.7	9.3	41	.45	11.3	0.047	1.2	8.50	SPR	C	Z
0.375	9.53	2557	.75	19.1	.279	7.1	35	6.1	.35	9.0	12	55	.40	10.1	0.048	1.2	8.25	MW	CG	Z
0.375	9.53	4358	.75	19.1	.275	7.0	65	11	.18	4.6	12	52	.35	8.9	0.050	1.3	6.00	SPR	C	Z
0.375	9.53	367	.75</																	




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.375	9.53	I-64	.81	20.6	.297	7.5	13	2.3	.47	12	6.1	27	.34	8.7	0.039	1.0	8.75	SPR	CG	Z
0.375	9.53	S-1450	.81	20.6	.267	6.8	32	5.6	.16	4.2	5.3	23	.65	16.5	0.054	1.4	12.0	SST	CG	N
0.375	9.53	QQ-15	.84	21.4	.289	7.3	27	4.7	.30	7.6	8.1	36	.34	8.7	0.043	1.1	7.00	SPR	C	Z
0.375	9.53	F-52	.84	21.4	.285	7.2	30	5.2	.31	7.9	9.2	41	.38	9.7	0.045	1.1	7.50	SPR	C	Z
0.375	9.53	JJ-81	.88	22.2	.335	8.5	.89	.16	.72	18	.64	2.8	.16	4.1	0.020	0.5	7.00	SST	C	N
0.375	9.53	363	.88	22.2	.329	8.4	2.6	.46	.73	18	1.9	8.5	.15	3.8	0.023	0.6	5.50	MW	C	Z
0.375	9.53	11288	.88	22.2	.325	8.3	2.7	.48	.58	15	1.6	7.1	.18	4.6	0.025	0.6	6.25	SST	C	N
0.375	9.53	3093	.88	22.2	.319	8.1	3.6	.63	.63	16	2.3	10	.25	6.3	0.028	0.7	7.75	MW	C	Z
0.375	9.53	S-46	.88	22.2	.317	8.1	1.4	.25	.35	9.0	.50	2.2	.52	13.3	0.029	0.7	17.0	SST	C	N
0.375	9.53	I-89	.88	22.2	.315	8.0	4.1	.71	.61	15	2.5	11	.27	6.9	0.030	0.8	9.00	MW	CG	Z
0.375	9.53	DD-90	.88	22.2	.315	8.0	3.9	.68	.59	15	2.3	10	.29	7.2	0.030	0.8	8.50	SST	C	N
0.375	9.53	2571	.88	22.2	.313	8.0	3.3	.57	.47	12	1.5	6.8	.40	10.2	0.031	0.8	12.0	MW	C	Z
0.375	9.53	S-736	.88	22.2	.311	7.9	7.2	1.3	.46	12	3.3	15	.24	6.1	0.032	0.8	6.50	SST	C	N
0.375	9.53	N-95	.88	22.2	.305	7.7	4.8	.84	.46	12	2.2	9.7	.42	10.7	0.035	0.9	12.0	SST	CG	N
0.375	9.53	UU-33	.88	22.2	.297	7.5	16	2.8	.38	9.7	6.1	27	.33	8.4	0.039	1.0	7.50	SPR	C	Z
0.375	9.53	S-741	.88	22.2	.291	7.4	19	3.4	.37	9.4	7.1	31	.36	9.1	0.042	1.1	7.50	SST	C	N
0.375	9.53	3616	.88	22.2	.281	7.1	33	5.8	.32	8.0	10	47	.42	10.7	0.047	1.2	8.00	HD	C	Z
0.375	9.53	B14-59	.88	22.2	.271	6.9	69	12	.19	4.8	13	58	.39	9.9	0.052	1.3	6.50	SPR	C	Z
0.375	9.53	Y-25	.88	22.2	.255	6.5	86	15	.22	5.5	19	83	.48	12.2	0.060	1.5	8.00	SST	CG	N
0.375	9.53	885	.88	22.2	.215	5.5	328	57	.13	3.3	43	190	.72	18.3	0.080	2.0	9.00	HD	CG	Z
0.375	9.53	B9-15	.91	23.0	.317	8.1	4.6	.81	.69	18	3.2	14	.21	5.4	0.029	0.7	7.33	MW	CG	GI
0.375	9.53	S-492	.91	23.0	.305	7.7	6.0	1.0	.56	14	3.3	15	.35	8.9	0.035	0.9	10.0	SST	CG	N
0.375	9.53	B3-38	.91	23.0	.269	6.8	52	9.2	.27	6.8	14	62	.45	11.4	0.053	1.3	8.50	SPR	CG	N
0.375	9.53	K-42	.94	23.8	.335	8.5	1.1	.20	.77	20	.86	3.8	.14	3.6	0.020	0.5	6.00	SST	C	N
0.375	9.53	10263	.94	23.8	.325	8.3	4.8	.83	.50	13	2.4	11	.14	3.7	0.025	0.6	4.75	MW	C	Z
0.375	9.53	A11-58	.94	23.8	.315	8.0	5.4	.95	.73	18	4.0	18	.21	5.3	0.030	0.8	7.00	MW	CG	N
0.375	9.53	F-38	.94	23.8	.285	7.2	23	4.1	.39	10	9.2	41	.45	11.4	0.045	1.1	9.00	SPR	C	Z
0.375	9.53	O-45	.94	23.8	.281	7.1	33	5.8	.32	8.0	10	47	.42	10.7	0.047	1.2	8.00	SPR	C	Z
0.375	9.53	12310	.94	23.8	.279	7.1	36	6.4	.31	7.8	11	50	.43	11.0	0.048	1.2	8.00	SPR	C	Z
0.375	9.53	S-1008	.94	23.8	.273	6.9	38	6.6	.31	7.9	12	52	.45	11.3	0.051	1.3	8.75	SST	CG	N
0.375	9.53	2928	.94	23.8	.251	6.4	77	13	.26	6.5	20	88	.68	17.3	0.062	1.6	11.0	HD	CG	GI
0.375	9.53	B11-36	.97	24.6	.319	8.1	2.1	.37	.63	16	1.3	5.9	.34	8.5	0.028	0.7	12.0	MW	CG	N
0.375	9.53	A-78	1.00	25.4	.335	8.5	.48	.08	.76	19	.36	1.6	.25	6.2	0.020	0.5	11.3	SST	C	N
0.375	9.53	H-7	1.00	25.4	.327	8.3	1.2	.21	.74	19	.88	3.9	.26	6.7	0.024	0.6	10.0	SST	C	N
0.375	9.53	3230	1.00	25.4	.315	8.0	4.4	.76	.72	18	3.1	14	.29	7.2	0.030	0.8	8.50	MW	C	Z
0.375	9.53	HH-74	1.00	25.4	.315	8.0	5.0	.88	.54	14	2.7	12	.24	6.1	0.030	0.8	7.00	SST	C	N
0.375	9.53	U-26	1.00	25.4	.315	8.0	3.0	.52	.63	16	1.9	8.3	.38	9.5	0.030	0.8	11.5	MW	C	N
0.375	9.53	S-737	1.00	25.4	.311	7.9	6.2	1.1	.53	14	3.3	15	.26	6.7	0.032	0.8	7.25	SST	C	N
0.375	9.53	10763	1.00	25.4	.305	7.7	5.4	.95	.58	15	3.1	14	.42	10.7	0.035	0.9	11.0	SST	C	N
0.375	9.53	O-156	1.00	25.4	.297	7.5	11	1.9	.55	14	6.1	27	.43	10.9	0.039	1.0	10.0	SPR	C	GI
0.375	9.53	3577	1.00	25.4	.293	7.4	14	2.4	.55	14	7.5	33	.45	11.5	0.041	1.0	10.0	MW	C	GI
0.375	9.53	3595	1.00	25.4	.291	7.4	17	3.0	.57	15	9.8	43	.43	10.8	0.042	1.1	9.00	MW	C	GI
0.375	9.53	S-742	1.00	25.4	.291	7.4	16	2.8	.44	11	7.1	31	.40	10.1	0.042	1.1	8.50	SST	C	N
0.375	9.53	XX-64	1.00	25.4	.289	7.3	17	2.9	.48	12	8.1	36	.47	12.0	0.043	1.1	10.0	SPR	C	Z
0.375	9.53	TT-58	1.00	25.4	.285	7.2	18	3.2	.46	12	8.4	37	.54	13.7	0.045	1.1	11.0	SPR	C	GI
0.375	9.53	B15-39	1.00	25.4	.285	7.2	18	3.2	.48	12	8.6	38	.50	12.6	0.045	1.1	10.0	SST	C	N
0.375	9.53	200	1.00	25.4	.281	7.1	27	4.6	.40	10	10	47	.49	12.5	0.047	1.2	9.50	HD	C	Z
0.375	9.53	Z-37	1.00	25.4	.281	7.1	22	3.8	.45	12	9.8	44	.47	11.9	0.047	1.2	10.0	SST	CG	N
0.375	9.53	L-10	1.00	25.4	.249	6.3	166	29	.14	3.5	23	102	.41	10.4	0.063	1.6	6.50	SPR	CG	N
0.375	9.53	10220	1.00	25.4	.231	5.9	174	30	.18	4.7	32	142	.72	18.3	0.072	1.8	10.0	SPR	CG	GI
0.375	9.53	B3-42	1.00	25.4	.215	5.5	353	62	.12	3.1	43	190	.76	19.3	0.080	2.0	8.50	SPR	C	N
0.375	9.53	4290	1.03	26.2	.313	8.0	4.7	.82	.75	19	3.5	16	.28	7.1	0.031	0.8	9.00	MW	CG	Z
0.375	9.53	10067	1.06	27.0	.321	8.2	1.4	.24	.63	16	.88	3.9	.43	11.0	0.027	0.7	15.0	MW	C	Z
0.375	9.53	GG-92	1.06	27.0	.307	7.8	7.7	1.3	.52	13	3.9	18	.29	7.3	0.034	0.9	7.50	SST	C	N
0.375	9.53	Z-48	1.06	27.0	.297	7.5	12	2.0	.52	13	6.1	27	.37	9.4	0.039	1.0	9.50	SPR	CG	GI
0.375	9.53	2542	1.06	27.0	.285	7.2	23	4.1	.39	10	9.2	41	.41	10.3	0.045	1.1	9.00	SPR	CG	Z
0.375	9.53	10038	1.06	27.0	.281	7.1	25	4.4	.42	11	10	47	.52	13.1	0.047	1.2	10.0	SPR	C	Z
0.375	9.53	B11-61	1.09	27.8	.325	8.3	3.3	.57	.72	18	2.4	11	.18	4.4	0.025	0.6	6.00	MW	C	Z
0.375	9.53	11871	1.09	27.8	.323	8.2	1.2	.22	.73	19	.91	4.0	.36	9.2	0.026	0.7	13.0	SST	C	N
0.375	9.53	A10-70	1.09	27.8	.265	6.7	50	8.8	.31	7.8	15	69	.55	14.0	0.055	1.4	10.0	SPR	CG	Z
0.375	9.53	S-913	1.09	27.8	.249	6.3	84	15	.26	6.5	22	96	.61	15.6	0.063	1.6	9.75	SST	CG	N
0.375	9.53	S-3039	1.13	28.6	.327	8.3	.66	.12	.71	18	.47	2.1	.42	10.7	0.024	0.6	16.5	SST	C	N
0.375	9.53	B11-22	1.13	28.6	.315	8.0	3.5	.62	.80	20	2.8	13	.33	8.4	0.030	0.8	10.0	MW	C	N
0.375	9.53	U-3	1.13	28.6	.309	7.8	5.3	.93	.73	19	3.9	17	.36	9.2	0.033	0.8	10.0	SPR	C	Z
0.375	9.53	11755	1.13	28.6	.307	7.8	7.5	1.3	.57	14	4.2	19	.29	7.3	0.034	0.9	8.50	SPR	CG	Z
0.375	9.53	519	1.13	28.6	.293	7.4	13	2.3	.53	14	7.0	31	.46	11.7	0.041	1.0	10.3	HD	C	Z
0.375	9.53	F-44	1.13	28.6	.285	7.2	21	3.6	.45	11	9.2	41	.50	12.6	0.045	1.1	10.0	SPR	C	Z
0.375	9.53	10078	1.13	28.6	.279	7.1	26	4.5	.43	11	11	50	.50	12.8	0.048	1.2	10.5	SPR	CG	Z
0.375	9.53	FF-90	1.13	28.6	.265	6.7	44	7.6	.33	8.5	15	65	.55	14.0	0.055	1.4	10.0	SST	CG	N
0.375	9.53	N-111	1.13	28.6	.251	6.4	75	13	.27	6.9	21	92	.62	15.7	0.062	1.6	10.0	SST	CG	N

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.375	9.53	10017	1.25	31.8	.307	7.8	4.8	.85	.81	21	3.9	17	.44	11.2	0.034	0.9	12.0	SPR	C	Z
0.375	9.53	3677	1.25	31.8	.293	7.4	14	2.4	.52	13	7.0	31	.45	11.5	0.041	1.0	10.0	SPR	C	Z
0.375	9.53	S-743	1.25	31.8	.291	7.4	12	2.2	.57	14	7.1	31	.48	12.3	0.042	1.1	10.5	SST	C	N
0.375	9.53	3847	1.25	31.8	.281	7.1	23	4.1	.45	11	10	47	.54	13.7	0.047	1.2	10.5	SPR	C	Z
0.375	9.53	10797	1.25	31.8	.279	7.1	22	3.8	.49	12	10	46	.53	13.4	0.048	1.2	11.0	SST	CG	N
0.375	9.53	GG-11	1.25	31.8	.275	7.0	28	5.0	.41	11	12	52	.56	14.3	0.050	1.3	11.3	SPR	CG	Z
0.375	9.53	LL-61	1.28	32.5	.275	7.0	19	3.4	.57	14	11	49	.70	17.8	0.050	1.3	14.0	SST	CG	N
0.375	9.53	B-11	1.28	32.5	.263	6.7	29	5.1	.33	8.4	9.6	42	.95	24.2	0.056	1.4	17.0	HD	CG	GI
0.375	9.53	V-60	1.31	33.3	.305	7.7	4.3	.76	.86	22	3.7	17	.46	11.6	0.035	0.9	13.0	SST	CG	N
0.375	9.53	10032	1.31	33.3	.285	7.2	15	2.6	.62	16	9.2	41	.63	16.0	0.045	1.1	13.0	SPR	C	Z
0.375	9.53	12400	1.38	34.9	.341	8.7	.22	.04	1.1	28	.24	1.1	.26	6.5	0.017	0.4	14.0	MW	C	N
0.375	9.53	UU-68	1.38	34.9	.327	8.3	.96	.17	1.1	27	1.0	4.5	.31	7.9	0.024	0.6	12.0	SST	C	N
0.375	9.53	3507	1.38	34.9	.315	8.0	3.7	.64	1.1	27	3.9	17	.32	8.2	0.030	0.8	9.75	MW	C	Z
0.375	9.53	S-207	1.38	34.9	.293	7.4	8.6	1.5	.76	19	6.6	29	.57	14.6	0.041	1.0	13.0	SST	C	N
0.375	9.53	S-282	1.38	34.9	.257	6.5	51	8.8	.35	9.0	18	79	.68	17.2	0.059	1.5	11.5	SST	CG	N
0.375	9.53	H-44	1.38	34.9	.247	6.3	68	12	.35	8.9	24	107	.88	22.4	0.064	1.6	13.8	SPR	CG	GI
0.375	9.53	S-1067	1.38	34.9	.231	5.9	142	25	.21	5.3	30	133	.76	19.2	0.072	1.8	10.5	SST	CG	N
0.375	9.53	12712	1.39	35.3	.307	7.8	6.1	1.1	.97	25	5.9	26	.37	9.5	0.034	0.9	10.0	MW	C	N
0.375	9.53	10579	1.41	35.7	.335	8.5	.51	.09	1.1	29	.59	2.6	.26	6.6	0.020	0.5	12.0	MW	C	Z
0.375	9.53	3936	1.41	35.7	.313	8.0	5.4	.95	.82	21	4.5	20	.28	7.1	0.031	0.8	8.00	MW	C	Z
0.375	9.53	N-125	1.44	36.5	.315	8.0	3.1	.54	.88	22	2.7	12	.33	8.4	0.030	0.8	10.0	SST	C	N
0.375	9.53	FF-87	1.44	36.5	.315	8.0	3.8	.66	.72	18	2.7	12	.29	7.2	0.030	0.8	8.50	SST	C	N
0.375	9.53	FF-94	1.44	36.5	.281	7.1	13	2.3	.64	16	8.5	38	.80	20.3	0.047	1.2	17.0	SPR	CG	GI
0.375	9.53	4183	1.50	38.1	.341	8.7	.19	.03	1.2	31	.23	1.0	.28	7.2	0.017	0.4	15.8	MW	C	N
0.375	9.53	111	1.50	38.1	.325	8.3	1.7	.31	1.2	31	2.2	9.6	.26	6.7	0.025	0.6	9.50	MW	C	Z
0.375	9.53	S-1421	1.50	38.1	.321	8.2	3.0	.53	.66	17	2.0	8.9	.22	5.7	0.027	0.7	7.25	SST	C	N
0.375	9.53	30	1.50	38.1	.319	8.1	2.6	.46	1.2	30	3.2	14	.31	7.8	0.028	0.7	10.0	MW	C	Z
0.375	9.53	S-14	1.50	38.1	.317	8.1	2.1	.37	1.1	29	2.4	11	.38	9.6	0.029	0.7	12.0	SST	C	N
0.375	9.53	2551	1.50	38.1	.315	8.0	2.6	.45	1.1	27	2.8	12	.42	10.7	0.030	0.8	13.0	MW	C	Z
0.375	9.53	S-739	1.50	38.1	.311	7.9	3.9	.69	.84	21	3.3	15	.36	9.1	0.032	0.8	10.3	SST	C	N
0.375	9.53	3820	1.50	38.1	.299	7.6	8.2	1.4	.68	17	5.6	25	.44	11.1	0.038	1.0	11.5	SPR	CG	Z
0.375	9.53	G-73	1.50	38.1	.293	7.4	9.7	1.7	.68	17	6.6	29	.49	12.5	0.041	1.0	12.0	SST	CG	N
0.375	9.53	S-744	1.50	38.1	.291	7.4	10	1.8	.69	17	7.1	31	.56	14.1	0.042	1.1	12.3	SST	C	N
0.375	9.53	S-1216	1.50	38.1	.287	7.3	16	2.8	.50	13	8.1	36	.48	12.3	0.044	1.1	10.0	SST	C	N
0.375	9.53	2554	1.50	38.1	.285	7.2	16	2.7	.59	15	9.2	41	.61	15.4	0.045	1.1	12.5	SPR	C	Z
0.375	9.53	J-50	1.50	38.1	.285	7.2	12	2.1	.73	18	8.6	38	.63	16.0	0.045	1.1	14.0	SST	CG	N
0.375	9.53	10001	1.50	38.1	.281	7.1	20	3.5	.73	19	15	65	.61	15.5	0.047	1.2	12.0	MW	C	Z
0.375	9.53	MM-42	1.50	38.1	.275	7.0	24	4.3	.45	11	11	49	.58	14.6	0.050	1.3	11.5	SST	CG	N
0.375	9.53	3712	1.50	38.1	.263	6.7	33	5.9	.49	12	16	73	.84	21.3	0.056	1.4	15.0	SPR	CG	Z
0.375	9.53	YY-56	1.50	38.1	.245	6.2	78	14	.44	11	35	155	.85	21.5	0.065	1.7	13.0	MW	CG	Z
0.375	9.53	B2-46	1.50	38.1	.213	5.4	325	57	.14	3.5	44	197	.77	19.6	0.081	2.1	9.50	SPR	CG	N
0.375	9.53	4268	1.56	39.7	.335	8.5	.49	.09	1.3	33	.63	2.8	.27	6.9	0.020	0.5	12.5	MW	C	BO
0.375	9.53	2650	1.56	39.7	.299	7.6	7.3	1.3	.77	20	5.6	25	.52	13.3	0.038	1.0	12.8	SPR	C	Z
0.375	9.53	L-46	1.56	39.7	.295	7.5	8.5	1.5	.77	20	6.5	29	.58	14.7	0.040	1.0	13.5	SPR	C	N
0.375	9.53	10998	1.56	39.7	.275	7.0	27	4.7	.44	11	12	52	.64	16.2	0.050	1.3	11.8	HD	C	Z
0.375	9.53	10167	1.59	40.5	.319	8.1	2.6	.46	1.3	32	3.3	15	.31	7.8	0.028	0.7	10.0	MW	C	Z
0.375	9.53	UU-59	1.69	42.8	.231	5.9	93	16	.34	8.7	32	142	1.22	31.1	0.072	1.8	17.0	HD	CG	Z
0.375	9.53	S-1442	1.69	42.8	.215	5.5	166	29	.24	6.1	40	178	1.20	30.5	0.080	2.0	14.0	SST	C	N
0.375	9.53	3904	1.75	44.5	.335	8.5	.57	.10	1.5	38	.86	3.8	.24	6.1	0.020	0.5	11.0	MW	C	T
0.375	9.53	3316	1.75	44.5	.325	8.3	1.0	.18	1.4	34	1.4	6.0	.40	10.2	0.025	0.6	15.0	MW	C	Z
0.375	9.53	TT-63	1.75	44.5	.325	8.3	.84	.15	1.3	33	1.1	4.8	.46	11.7	0.025	0.6	17.5	MW	C	Z
0.375	9.53	525	1.75	44.5	.307	7.8	3.7	.65	1.1	29	4.2	19	.54	13.8	0.034	0.9	15.0	HD	C	Z
0.375	9.53	12480	1.75	44.5	.305	7.7	3.7	.64	1.1	29	4.1	18	.53	13.3	0.035	0.9	15.0	SST	CG	N
0.375	9.53	114	1.75	44.5	.293	7.4	8.2	1.4	.85	22	7.0	31	.67	16.9	0.041	1.0	15.3	HD	C	Z
0.375	9.53	12293	1.75	44.5	.281	7.1	15	2.6	.71	18	10	47	.73	18.5	0.047	1.2	15.5	SPR	CG	GI
0.375	9.53	3037	1.78	45.2	.287	7.3	11	1.9	.79	20	8.6	38	.68	17.3	0.044	1.1	15.5	SPR	CG	GI
0.375	9.53	3941	1.78	45.2	.251	6.4	46	8.1	.47	12	22	97	1.05	26.8	0.062	1.6	17.0	SPR	CG	Z
0.375	9.53	11587	1.81	46.0	.287	7.3	11	2.0	.76	19	8.6	38	.70	17.9	0.044	1.1	15.0	SPR	CG	N
0.375	9.53	CC-94	1.81	46.0	.285	7.2	11	1.9	.79	20	8.6	38	.68	17.1	0.045	1.1	15.0	SST	CG	N
0.375	9.53	4363	1.88	47.6	.281	7.1	19	3.3	.55	14	10	47	.59	14.9	0.047	1.2	12.5	SPR	CG	Z
0.375	9.53	S-1382	2.00	50.8	.335	8.5	.56	.10	1.5	39	.86	3.8	.22	5.6	0.020	0.5	10.0	SST	C	N
0.375	9.53	10192	2.00	50.8	.319	8.1	1.5	.26	1.6	39	2.3	10	.45	11.4	0.028	0.7	16.0	MW	CG	Z
0.375	9.53	10284	2.00	50.8	.315	8.0	2.0	.35	1.5	38	3.0	13	.51	13.0	0.030	0.8	16.0	MW	C	Z
0.375	9.53	S-442	2.00	50.8	.311	7.9	2.0	.36	1.4	36	2.9	13	.58	14.6	0.032	0.8	18.0	SST	CG	N
0.375	9.53	OO-91	2.00	50.8	.295	7.5	5.8	1.0	1.1	29	6.5	29	.76	19.3	0.040	1.0	19.0	SPR	CG	N
0.375	9.53	384	2.00	50.8	.293	7.4	7.1	1.3	.98	25	7.0	31	.75	19.0	0.041	1.0	17.3	HD	C	Z
0.375	9.53	3605	2.00	50.8	.285	7.2	11	1.9	1.2	30	13	57	.81	20.6	0.045	1.1	17.0	MW	C	Z
0.375	9.53	17	2.00	50.8	.281	7.1	12	2.1	.88	22	10	47	.93	23.6	0.047	1.2	18.8	HD	C	Z
0.375	9.53	II-77	2.00	50.8	.281	7.1	10	1.8	.94	24	9.8	44	.87	22.1	0.047	1.2	18.5	SST	CG	N
0.3																				




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.375	9.53	4180	2.25	57.2	.247	6.3	45	7.8	.54	14	24	107	1.34	34.1	0.064	1.6	20.0	SPR	C	Z
0.375	9.53	K-57	2.38	60.3	.327	8.3	1.0	.18	2.0	52	2.0	9.1	.34	8.5	0.024	0.6	13.0	MW	C	GI
0.375	9.53	3928	2.38	60.3	.307	7.8	2.7	.47	1.6	40	4.2	19	.71	18.1	0.034	0.9	20.0	SPR	C	Z
0.375	9.53	3557	2.38	60.3	.293	7.4	5.5	.95	1.5	37	8.0	36	.90	22.9	0.041	1.0	22.0	MW	CG	Z
0.375	9.53	12471	2.38	60.3	.275	7.0	14	2.4	.85	22	12	52	1.05	26.7	0.050	1.3	21.0	SPR	CG	Z
0.375	9.53	S-1122	2.50	63.5	.251	6.4	23	4.1	.76	19	18	79	1.74	44.1	0.062	1.6	28.0	SST	CG	N
0.375	9.53	S-1621	2.53	64.3	.285	7.2	7.9	1.4	1.1	28	8.6	38	.97	24.6	0.045	1.1	20.5	SST	C	N
0.375	9.53	11733	2.59	65.9	.250	6.4	33	5.7	.69	17	22	100	1.56	39.7	0.063	1.6	24.0	SPR	CG	Z
0.375	9.53	I-48	2.63	66.7	.295	7.5	5.8	1.0	1.1	28	6.5	29	.79	20.1	0.040	1.0	18.8	SPR	C	N
0.375	9.53	11981	2.66	67.5	.295	7.5	6.1	1.1	1.1	27	6.5	29	.76	19.3	0.040	1.0	18.0	SPR	C	Z
0.375	9.53	B2-49	2.75	69.9	.291	7.4	6.4	1.1	1.1	28	7.1	31	.78	19.7	0.042	1.1	18.5	SST	CG	N
0.375	9.53	12537	2.91	73.9	.231	5.9	56	9.7	.57	15	32	142	2.02	51.2	0.072	1.8	27.0	SPR	C	N
0.375	9.53	12201	3.00	76.2	.313	8.0	1.5	.26	2.2	57	3.3	15	.78	19.7	0.031	0.8	24.0	MW	C	Z
0.375	9.53	12257	3.00	76.2	.291	7.4	6.5	1.1	1.2	29	7.5	34	.90	22.9	0.042	1.1	20.5	SPR	C	Z
0.375	9.53	10002	3.00	76.2	.281	7.1	10	1.8	1.0	26	10	47	1.06	26.9	0.047	1.2	21.5	SPR	C	Z
0.375	9.53	B17-177	3.19	81.0	.281	7.1	6.6	1.2	1.6	40	10	47	1.50	38.2	0.047	1.2	32.0	SPR	CG	Z
0.375	9.53	1713	3.34	84.9	.299	7.6	2.7	.47	2.1	53	5.6	25	1.23	31.2	0.038	1.0	31.3	SPR	C	Z
0.375	9.53	10921	3.38	85.7	.273	6.9	11	2.0	1.1	28	12	55	1.43	36.3	0.051	1.3	27.0	SPR	C	Z
0.375	9.53	3134	3.47	88.1	.267	6.8	13	2.4	1.1	28	15	65	1.65	41.8	0.054	1.4	29.5	SPR	C	Z
0.375	9.53	S-1335	3.50	88.9	.313	8.0	1.4	.25	2.1	54	3.0	13	.71	18.1	0.031	0.8	22.0	SST	C	N
0.375	9.53	12007	3.50	88.9	.295	7.5	4.7	.82	1.4	36	6.5	29	.96	24.4	0.040	1.0	23.0	SPR	C	Z
0.375	9.53	2545	3.50	88.9	.263	6.7	16	2.8	1.0	26	16	73	1.72	43.6	0.056	1.4	29.7	SPR	C	Z
0.375	9.53	2947	3.63	92.1	.293	7.4	3.2	.56	2.1	54	6.8	30	1.52	38.5	0.041	1.0	36.0	SPR	C	Z
0.375	9.53	3921	3.75	95.3	.247	6.3	22	3.8	1.1	28	24	107	2.50	63.4	0.064	1.6	39.0	SPR	CG	Z
0.375	9.53	12210	3.75	95.3	.245	6.2	23	4.1	1.1	27	25	111	2.54	64.4	0.065	1.7	39.0	SPR	CG	N
0.375	9.53	4301	3.75	95.3	.231	5.9	40	6.9	.80	20	32	142	2.66	67.7	0.072	1.8	37.0	SPR	CG	Z
0.375	9.53	B4-7	4.00	101.6	.329	8.4	3.7	.65	.53	14	2.0	8.7	.13	3.2	0.023	0.6	4.50	MW	C	N
0.375	9.53	10600	4.00	101.6	.275	7.0	6.2	1.1	1.8	46	11	50	2.20	55.9	0.050	1.3	44.0	SPR	CG	Z
0.375	9.53	10173	4.50	114.3	.275	7.0	6.9	1.2	1.7	43	12	52	2.00	50.8	0.050	1.3	40.0	SPR	CG	Z
0.375	9.53	3103	7.50	190.5	.251	6.4	12	2.0	1.9	48	22	97	3.91	99.2	0.062	1.6	62.0	SPR	C	Z
0.375	9.53	517	9.00	228.6	.281	7.1	2.5	.44	4.2	107	10	47	3.88	98.5	0.047	1.2	81.5	HD	C	Z
0.375	9.53	12649	10.5	266.7	.299	7.6	1.1	.19	5.1	129	5.6	25	2.74	69.5	0.038	1.0	71.0	SPR	O	N
0.375	9.53	508	12.0	304.8	.251	6.4	5.9	1.0	3.7	94	22	97	7.44	189.0	0.062	1.6	119.0	HD	C	Z
0.380	9.65	A12-31	1.00	25.4	.338	8.6	1.1	.19	.82	21	.90	4.0	.18	4.5	0.021	0.5	7.50	MW	C	Z
0.390	9.91	K-73	.25	6.4	.310	7.9	75	13	.08	2.0	5.9	26	.12	3.0	0.040	1.0	3.00	SST	CG	N
0.390	9.91	10472	.31	7.9	.346	8.8	1.2	.22	.13	3.2	.15	68	.19	4.7	0.022	0.6	7.50	MW	C	Z
0.390	9.91	FF-12	.34	8.7	.290	7.4	114	20	.09	2.4	11	47	.19	4.8	0.050	1.3	3.75	SST	CG	N
0.390	9.91	A13-57	.38	9.5	.320	8.1	28	4.8	.15	3.9	4.3	19	.13	3.3	0.035	0.9	3.75	SPR	CG	N
0.390	9.91	DD-61	.38	9.5	.286	7.3	118	21	.10	2.6	12	53	.21	5.3	0.052	1.3	4.00	SST	CG	N
0.390	9.91	DD-79	.41	10.3	.320	8.1	21	3.8	.20	5.0	4.3	19	.15	3.8	0.035	0.9	4.25	SPR	CG	N
0.390	9.91	O-49	.44	11.1	.326	8.3	7.3	1.3	.25	6.2	1.8	8.0	.19	4.9	0.032	0.8	6.00	SST	CG	N
0.390	9.91	MM-30	.44	11.1	.310	7.9	25	4.3	.22	5.5	5.3	24	.22	5.6	0.040	1.0	5.50	SPR	CG	Z
0.390	9.91	10946	.47	11.9	.340	8.6	4.1	.72	.33	8.4	1.4	6.0	.14	3.5	0.025	0.6	4.50	SST	C	N
0.390	9.91	O-77	.50	12.7	.330	8.4	6.2	1.1	.29	7.4	1.8	8.0	.21	5.3	0.030	0.8	6.00	MW	C	N
0.390	9.91	W-8	.50	12.7	.324	8.2	9.4	1.6	.27	6.8	2.5	11	.23	5.9	0.033	0.8	6.00	SPR	C	GI
0.390	9.91	G-79	.50	12.7	.316	8.0	15	2.7	.28	7.1	4.3	19	.22	5.6	0.037	0.9	6.00	SPR	CG	N
0.390	9.91	H-84	.50	12.7	.310	7.9	25	4.4	.24	6.0	5.9	26	.20	5.1	0.040	1.0	5.00	SST	CG	N
0.390	9.91	71283	.50	12.7	.304	7.7	42	7.3	.26	6.6	11	48	.21	5.3	0.043	1.1	4.88	MW	CG	N
0.390	9.91	71283S	.50	12.7	.304	7.7	35	6.2	.21	5.2	7.3	32	.21	5.3	0.043	1.1	4.88	SST	CG	N
0.390	9.91	71298	.50	12.7	.296	7.5	59	10	.24	6.0	14	62	.24	6.0	0.047	1.2	5.00	MW	CG	N
0.390	9.91	71298S	.50	12.7	.296	7.5	50	8.8	.19	4.8	9.5	42	.24	6.0	0.047	1.2	5.00	SST	CG	N
0.390	9.91	S-144	.50	12.7	.220	5.6	920	161	.05	1.3	46	205	.38	9.7	0.085	2.2	4.50	SST	CG	N
0.390	9.91	71284	.56	14.2	.304	7.7	36	6.4	.30	7.5	11	48	.23	5.7	0.043	1.1	5.25	MW	CG	N
0.390	9.91	71284S	.56	14.2	.304	7.7	31	5.4	.24	6.0	7.3	32	.23	5.7	0.043	1.1	5.25	SST	CG	N
0.390	9.91	71299	.56	14.2	.296	7.5	51	9.0	.27	6.9	14	62	.25	6.4	0.047	1.2	5.38	MW	CG	N
0.390	9.91	71299S	.56	14.2	.296	7.5	44	7.6	.22	5.5	9.5	42	.25	6.4	0.047	1.2	5.38	SST	CG	N
0.390	9.91	K-64	.56	14.3	.336	8.5	3.2	.56	.35	8.8	1.1	4.9	.22	5.5	0.027	0.7	7.00	MW	C	Z
0.390	9.91	10331	.59	15.1	.328	8.3	14	2.5	.30	7.6	4.3	19	.12	3.1	0.031	0.8	4.00	MW	CG	Z
0.390	9.91	VW-8	.63	15.9	.360	9.1	.48	.08	.54	14	.26	1.2	.08	2.1	0.015	0.4	4.50	SST	C	N
0.390	9.91	M-84	.63	15.9	.344	8.7	1.4	.24	.44	11	.60	2.7	.18	4.7	0.023	0.6	8.00	MW	C	BO
0.390	9.91	FF-99	.63	15.9	.270	6.9	148	26	.13	3.3	19	85	.39	9.9	0.060	1.5	5.50	SPR	C	N
0.390	9.91	S-47	.63	15.9	.266	6.8	105	18	.19	4.8	20	88	.43	11.0	0.062	1.6	7.00	SST	CG	N
0.390	9.91	71285	.63	16.0	.304	7.7	32	5.6	.34	8.6	11	48	.25	6.3	0.043	1.1	5.75	MW	CG	N
0.390	9.91	71285S	.63	16.0	.304	7.7	27	4.7	.27	6.9	7.3	32	.25	6.3	0.043	1.1	5.75	SST	CG	N
0.390	9.91	71300	.63	16.0	.296	7.5	45	8.0	.31	7.8	14	62	.28	7.0	0.047	1.2	5.88	MW	CG	N
0.390	9.91	71300S	.63	16.0	.296	7.5	39	6.8	.25	6.2	9.5	42	.28	7.0	0.047	1.2	5.88	SST	CG	N
0.390	9.91	I-23	.69	17.4	.328	8.3	8.2	1.4	.49	12	4.0	18	.20	5.1	0.031	0.8	5.50	MW	C	N
0.390	9.91	AA-28	.69	17.4	.310	7.9	19	3.3	.31	7.9	5.9	26	.24	6.1	0.040	1.0	6.00	SST	CG	N
0.390	9.91	71286	.69	17.5	.304	7.7	29	5.0	.38	9.6	11	48	.26	6.7	0.043	1.1	6.13	MW	CG	N
0.390	9.91	71286S	.69	17.5	.304															

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.390	9.91	3604	.75	19.1	.272	6.9	120	21	.21	5.4	25	113	.35	9.0	0.059	1.5	6.00	MW	CG	Z
0.390	9.91	K-82	.75	19.1	.266	6.8	150	26	.14	3.6	21	94	.37	9.4	0.062	1.6	6.00	HD	CG	N
0.390	9.91	71288	.81	20.6	.304	7.7	24	4.2	.45	11	11	48	.30	7.5	0.043	1.1	6.88	MW	CG	N
0.390	9.91	71288S	.81	20.6	.304	7.7	20	3.6	.36	9.1	7.3	32	.30	7.5	0.043	1.1	6.88	SST	CG	N
0.390	9.91	71303	.81	20.6	.296	7.5	34	5.9	.42	11	14	62	.33	8.5	0.047	1.2	7.13	MW	CG	N
0.390	9.91	71303S	.81	20.6	.296	7.5	29	5.0	.33	8.4	9.5	42	.33	8.5	0.047	1.2	7.13	SST	CG	N
0.390	9.91	11290	.81	20.6	.348	8.8	1.2	.22	.67	17	.82	3.6	.15	3.7	0.021	0.5	6.00	SST	C	N
0.390	9.91	NN-47	.81	20.6	.334	8.5	2.8	.49	.57	14	1.6	7.1	.25	6.2	0.028	0.7	7.75	SST	C	N
0.390	9.91	HH-18	.81	20.6	.326	8.3	6.3	1.1	.50	13	3.2	14	.24	6.1	0.032	0.8	6.50	SST	C	N
0.390	9.91	A-91	.88	22.2	.342	8.7	1.6	.28	.66	17	1.1	4.8	.22	5.5	0.024	0.6	8.00	MW	C	N
0.390	9.91	CC-78	.88	22.2	.340	8.6	2.7	.47	.57	14	1.5	6.8	.17	4.3	0.025	0.6	5.75	SST	C	N
0.390	9.91	11448	.88	22.2	.332	8.4	4.8	.84	.50	13	2.4	11	.20	5.2	0.029	0.7	6.00	SST	C	N
0.390	9.91	10919	.88	22.2	.330	8.4	5.5	.97	.47	12	2.6	12	.21	5.3	0.030	0.8	6.00	SST	C	N
0.390	9.91	B10-16	.88	22.2	.322	8.2	14	2.5	.29	7.3	4.1	18	.20	5.2	0.034	0.9	5.00	SPR	C	N
0.390	9.91	H-31	.88	22.2	.320	8.1	6.0	1.0	.56	14	3.4	15	.32	8.0	0.035	0.9	9.00	SST	CG	N
0.390	9.91	3845	.88	22.2	.310	7.9	17	3.0	.37	9.3	6.3	28	.28	7.1	0.040	1.0	7.00	SPR	CG	Z
0.390	9.91	B15-34	.88	22.2	.310	7.9	13	2.2	.47	12	5.9	26	.32	8.1	0.040	1.0	8.00	SST	CG	N
0.390	9.91	AA-44	.88	22.2	.290	7.4	34	5.9	.32	8.0	11	47	.40	10.2	0.050	1.3	8.00	SST	CG	N
0.390	9.91	3781	.88	22.2	.266	6.8	100	18	.21	5.3	21	94	.50	12.6	0.062	1.6	8.00	HD	CG	Z
0.390	9.91	71289	.88	22.4	.304	7.7	22	3.8	.49	13	11	48	.32	8.1	0.043	1.1	7.38	MW	CG	N
0.390	9.91	71289S	.88	22.4	.304	7.7	19	3.2	.39	10	7.3	32	.32	8.1	0.043	1.1	7.38	SST	CG	N
0.390	9.91	71304	.88	22.4	.296	7.5	29	5.0	.49	12	14	62	.38	9.7	0.047	1.2	8.13	MW	CG	N
0.390	9.91	71304S	.88	22.4	.296	7.5	24	4.2	.39	9.9	9.5	42	.38	9.7	0.047	1.2	8.13	SST	CG	N
0.390	9.91	S-1694	.91	23.0	.334	8.5	4.0	.71	.53	13	2.1	9.5	.20	5.0	0.028	0.7	6.00	SST	C	N
0.390	9.91	3576	.91	23.0	.320	8.1	4.7	.82	.48	12	2.2	10	.43	10.9	0.035	0.9	12.3	HD	CG	GI
0.390	9.91	A10-26	.91	23.0	.306	7.8	15	2.6	.45	11	6.8	30	.35	8.8	0.042	1.1	8.25	SST	CG	N
0.390	9.91	BB-8	.94	23.8	.350	8.9	.75	.13	.77	20	.58	2.6	.17	4.2	0.020	0.5	7.25	SST	C	N
0.390	9.91	MM-43	.94	23.8	.230	5.8	395	69	.10	2.7	41	185	.56	14.2	0.080	2.0	7.00	SPR	CG	BO
0.390	9.91	71290	.94	23.9	.304	7.7	20	3.5	.53	14	11	48	.34	8.6	0.043	1.1	7.88	MW	CG	N
0.390	9.91	71290S	.94	23.9	.304	7.7	17	3.0	.43	11	7.3	32	.34	8.6	0.043	1.1	7.88	SST	CG	N
0.390	9.91	71305	.94	23.9	.296	7.5	28	5.0	.49	13	14	62	.38	9.7	0.047	1.2	8.13	MW	CG	N
0.390	9.91	71305S	.94	23.9	.296	7.5	24	4.2	.39	9.9	9.5	42	.38	9.7	0.047	1.2	8.13	SST	CG	N
0.390	9.91	10955	.97	24.6	.344	8.7	1.5	.26	.77	20	1.1	5.1	.20	5.0	0.023	0.6	7.50	MW	C	Z
0.390	9.91	S-912	.97	24.6	.308	7.8	12	2.1	.53	14	6.3	28	.37	9.4	0.041	1.0	9.00	SST	CG	N
0.390	9.91	U-30	.97	24.6	.262	6.7	73	13	.30	7.5	22	97	.66	16.7	0.064	1.6	10.3	SST	CG	N
0.390	9.91	A12-14	.97	24.6	.346	8.8	1.2	.22	.78	20	.96	4.3	.19	4.7	0.022	0.6	7.50	MW	C	Z
0.390	9.91	EE-98	1.00	25.4	.344	8.7	.49	.09	.55	14	.27	1.2	.45	11.4	0.023	0.6	18.5	MW	C	Z
0.390	9.91	A-82	1.00	25.4	.320	8.1	8.8	1.5	.48	12	4.3	19	.30	7.6	0.035	0.9	7.50	SPR	C	Z
0.390	9.91	O-154	1.00	25.4	.308	7.8	13	2.2	.53	14	6.8	30	.43	10.9	0.041	1.0	9.50	SPR	C	GI
0.390	9.91	71291	1.00	25.4	.304	7.7	19	3.3	.58	15	11	48	.35	9.0	0.043	1.1	8.25	MW	CG	N
0.390	9.91	71291S	1.00	25.4	.304	7.7	16	2.8	.46	12	7.3	32	.35	9.0	0.043	1.1	8.25	SST	CG	N
0.390	9.91	71306	1.00	25.4	.296	7.5	27	4.7	.52	13	14	62	.40	10.1	0.047	1.2	8.50	MW	CG	N
0.390	9.91	71306S	1.00	25.4	.296	7.5	23	4.0	.42	11	9.5	42	.40	10.1	0.047	1.2	8.50	SST	CG	N
0.390	9.91	PP-6	1.00	25.4	.290	7.4	24	4.2	.45	11	11	47	.53	13.3	0.050	1.3	10.5	SST	CG	N
0.390	9.91	B9-28	1.00	25.4	.272	6.9	84	15	.22	5.6	18	81	.46	11.6	0.059	1.5	7.75	SPR	CG	Z
0.390	9.91	B10-23	1.06	27.0	.274	7.0	54	9.5	.30	7.7	16	73	.54	13.6	0.058	1.5	9.25	SST	CG	N
0.390	9.91	H-61	1.06	27.0	.262	6.7	99	17	.23	5.9	23	103	.58	14.6	0.064	1.6	9.00	SPR	CG	Z
0.390	9.91	S-1130	1.13	28.6	.360	9.1	.15	.03	.96	24	.14	.64	.17	4.2	0.015	0.4	10.0	SST	C	N
0.390	9.91	4134	1.13	28.6	.260	6.6	107	19	.23	5.8	24	108	.65	16.5	0.065	1.7	9.00	SPR	C	Z
0.390	9.91	71292	1.13	28.7	.304	7.7	17	2.9	.65	17	11	48	.39	10.0	0.043	1.1	9.13	MW	CG	N
0.390	9.91	71292S	1.13	28.7	.304	7.7	14	2.5	.52	13	7.3	32	.39	10.0	0.043	1.1	9.13	SST	CG	N
0.390	9.91	71307	1.13	28.7	.296	7.5	24	4.1	.59	15	14	62	.44	11.2	0.047	1.2	9.38	MW	CG	N
0.390	9.91	71307S	1.13	28.7	.296	7.5	20	3.5	.47	12	9.5	42	.44	11.2	0.047	1.2	9.38	SST	CG	N
0.390	9.91	K-7	1.19	30.2	.316	8.0	7.2	1.3	.65	16	4.7	21	.39	9.9	0.037	0.9	9.50	SST	C	N
0.390	9.91	G-55	1.19	30.2	.308	7.8	9.8	1.7	.65	16	6.3	28	.47	12.0	0.041	1.0	10.5	SST	C	N
0.390	9.91	3243	1.19	30.2	.290	7.4	23	4.1	.48	12	11	50	.64	16.2	0.050	1.3	11.8	SPR	C	Z
0.390	9.91	A-90	1.19	30.2	.262	6.7	103	18	.22	5.7	23	103	.56	14.2	0.064	1.6	8.75	HD	CG	N
0.390	9.91	A10-5	1.22	31.0	.340	8.6	1.9	.33	.82	21	1.5	6.8	.19	4.8	0.025	0.6	7.50	SST	CG	N
0.390	9.91	YY-67	1.25	31.8	.346	8.8	.68	.12	.96	24	.65	2.9	.29	7.3	0.022	0.6	12.0	MW	C	Z
0.390	9.91	B4-19	1.25	31.8	.344	8.7	1.1	.20	1.0	26	1.1	5.1	.24	6.0	0.023	0.6	9.25	MW	C	N
0.390	9.91	71293	1.25	31.8	.304	7.7	15	2.6	.73	19	11	48	.43	10.9	0.043	1.1	10.0	MW	CG	N
0.390	9.91	71293S	1.25	31.8	.304	7.7	13	2.2	.58	15	7.3	32	.43	10.9	0.043	1.1	10.0	SST	CG	N
0.390	9.91	71308	1.25	31.8	.296	7.5	21	3.6	.67	17	14	62	.49	12.4	0.047	1.2	10.4	MW	CG	N
0.390	9.91	71308S	1.25	31.8	.296	7.5	18	3.1	.54	14	9.5	42	.49	12.4	0.047	1.2	10.4	SST	CG	N
0.390	9.91	S-304	1.25	31.8	.266	6.8	43	7.5	.35	8.9	15	67	.90	22.8	0.062	1.6	14.5	SST	CG	N
0.390	9.91	3002	1.25	31.8	.264	6.7	76	13	.29	7.4	22	98	.66	16.8	0.063	1.6	10.5	SPR	CG	Z
0.390	9.91	U-56	1.25	31.8	.264	6.7	79	14	.28	7.2	22	98	.71	18.0	0.063	1.6	10.3	SPR	C	Z
0.390	9.91	12132	1.28	32.5	.262	6.7	82	14	.28	7.2	23	103	.74	18.7	0.064	1.6	10.5	SPR	C	Z
0.390	9.91	S-894	1.28	32.5	.260	6.6	52	9.1	.34	8.6	18	78	.94	23.9	0.065	1.7	14.5	SST	CG	N
0.390	9.91	QQ-54	1.34	34.1	.318	8.1	6.8	1.2	.94</											




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.390	9.91	MM-84	1.50	38.1	.308	7.8	8.1	1.4	.83	21	6.8	30	.60	15.4	0.041	1.0	13.8	SPR	C	BO
0.390	9.91	71295	1.50	38.1	.304	7.7	12	2.1	.88	22	11	48	.50	12.7	0.043	1.1	11.6	MW	CG	N
0.390	9.91	71295S	1.50	38.1	.304	7.7	10	1.8	.70	18	7.3	32	.50	12.7	0.043	1.1	11.6	SST	CG	N
0.390	9.91	71310	1.50	38.1	.296	7.5	17	3.0	.82	21	14	62	.57	14.5	0.047	1.2	12.1	MW	CG	N
0.390	9.91	71310S	1.50	38.1	.296	7.5	15	2.6	.65	17	9.5	42	.57	14.5	0.047	1.2	12.1	SST	CG	N
0.390	9.91	3073	1.53	38.9	.296	7.5	13	2.3	.76	19	10	45	.71	17.9	0.047	1.2	15.0	SPR	CG	Z
0.390	9.91	12638	1.69	42.8	.312	7.9	6.1	1.1	.90	23	5.5	24	.55	13.9	0.039	1.0	13.0	SST	C	N
0.390	9.91	L-34	1.75	44.5	.350	8.9	.33	.06	1.4	36	.46	2.1	.34	8.6	0.020	0.5	16.0	MW	C	T
0.390	9.91	BB-76	1.75	44.5	.346	8.8	.53	.09	1.4	37	.77	3.4	.31	7.8	0.022	0.6	13.0	SST	C	N
0.390	9.91	71296	1.75	44.5	.304	7.7	10	1.8	1.0	26	11	48	.57	14.5	0.043	1.1	13.3	MW	CG	N
0.390	9.91	71296S	1.75	44.5	.304	7.7	8.9	1.6	.82	21	7.3	32	.57	14.5	0.043	1.1	13.3	SST	CG	N
0.390	9.91	71311	1.75	44.5	.296	7.5	15	2.5	.96	24	14	62	.66	16.7	0.047	1.2	14.0	MW	CG	N
0.390	9.91	71311S	1.75	44.5	.296	7.5	12	2.2	.77	19	9.5	42	.66	16.7	0.047	1.2	14.0	SST	CG	N
0.390	9.91	2922	1.81	46.0	.348	8.8	.40	.07	1.5	37	.58	2.6	.36	9.1	0.021	0.5	16.0	MW	C	Z
0.390	9.91	H-86	1.88	47.6	.350	8.9	.35	.06	1.6	39	.54	2.4	.32	8.1	0.020	0.5	15.0	MW	C	T
0.390	9.91	3314	1.88	47.6	.296	7.5	17	3.0	.58	15	10	45	.61	15.5	0.047	1.2	12.0	HD	C	Z
0.390	9.91	TT-29	1.88	47.6	.290	7.4	14	2.5	.75	19	11	47	.80	20.3	0.050	1.3	16.0	SST	CG	N
0.390	9.91	I-50	1.88	47.6	.276	7.0	28	5.0	.58	15	17	74	.94	23.9	0.057	1.4	16.5	SPR	CG	GI
0.390	9.91	10086	2.00	50.8	.310	7.9	5.1	.90	1.2	31	6.3	28	.75	19.1	0.040	1.0	18.8	SPR	CG	N
0.390	9.91	2607	2.00	50.8	.308	7.8	6.4	1.1	1.3	32	8.0	36	.74	18.7	0.041	1.0	17.0	MW	C	GI
0.390	9.91	71297	2.00	50.8	.304	7.7	9.8	1.7	1.1	28	11	48	.60	15.3	0.043	1.1	14.0	MW	CG	N
0.390	9.91	71297S	2.00	50.8	.304	7.7	8.3	1.5	.88	22	7.3	32	.60	15.3	0.043	1.1	14.0	SST	CG	N
0.390	9.91	71312	2.00	50.8	.296	7.5	13	2.2	1.1	28	14	62	.74	18.8	0.047	1.2	15.8	MW	CG	N
0.390	9.91	71312S	2.00	50.8	.296	7.5	11	1.9	.88	22	9.5	42	.74	18.8	0.047	1.2	15.8	SST	CG	N
0.390	9.91	2764	2.00	50.8	.296	7.5	9.7	1.7	1.0	27	10	45	.94	23.9	0.047	1.2	20.0	HD	CG	Z
0.390	9.91	2943	2.03	51.6	.338	8.6	1.5	.27	1.7	43	2.6	11	.29	7.3	0.026	0.7	11.0	MW	CG	Z
0.390	9.91	2883	2.13	54.0	.296	7.5	11	1.9	.95	24	10	45	.86	21.9	0.047	1.2	18.3	SPR	CG	Z
0.390	9.91	GG-86	2.25	57.2	.326	8.3	2.0	.36	1.6	40	3.2	14	.54	13.8	0.032	0.8	16.0	SST	C	N
0.390	9.91	EE-96	2.50	63.5	.210	5.3	184	32	.30	7.6	55	246	1.89	48.0	0.090	2.3	21.0	SPR	CG	N
0.390	9.91	11396	2.69	68.2	.282	7.2	17	3.0	.83	21	14	63	1.19	30.2	0.054	1.4	21.0	HD	C	Z
0.390	9.91	S-1337	3.25	82.6	.288	7.3	10	1.8	1.1	28	11	50	1.25	31.7	0.051	1.3	23.5	SST	C	N
0.390	9.91	3392	3.38	85.7	.298	7.6	7.5	1.3	1.3	32	9.5	42	1.10	28.0	0.046	1.2	23.0	SPR	C	Z
0.390	9.91	10901	3.50	88.9	.314	8.0	3.8	.67	1.4	36	5.4	24	.76	19.3	0.038	1.0	20.0	SPR	CG	N
0.390	9.91	11465	4.75	120.7	.326	8.3	1.8	.32	1.7	44	3.2	14	.83	21.1	0.032	0.8	25.0	SST	C	N
0.406	10.31	BB-78	.38	9.5	.368	9.3	.94	.16	.28	7.1	.26	1.2	.10	2.4	0.019	0.5	5.00	SST	C	N
0.406	10.31	B-62	.38	9.5	.336	8.5	21	3.7	.19	4.9	4.1	18	.14	3.6	0.035	0.9	4.00	SPR	CG	Z
0.406	10.31	12533	.41	10.3	.370	9.4	1.5	.26	.33	8.3	.49	2.2	.08	2.1	0.018	0.5	3.50	SST	C	N
0.406	10.31	J-41	.41	10.3	.370	9.4	.86	.15	.30	7.6	.26	1.1	.11	2.7	0.018	0.5	5.00	MW	C	N
0.406	10.31	A-66	.41	10.3	.348	8.8	6.3	1.1	.26	6.6	1.7	7.3	.15	3.7	0.029	0.7	5.00	MW	CG	N
0.406	10.31	M-24	.41	10.3	.306	7.8	72	13	.15	3.8	11	48	.24	6.0	0.050	1.3	4.75	SPR	CG	N
0.406	10.31	S-1096	.44	11.1	.356	9.0	2.2	.39	.26	6.7	.58	2.6	.18	4.4	0.025	0.6	6.00	SST	C	N
0.406	10.31	W-28	.44	11.1	.350	8.9	7.3	1.3	.28	7.2	2.1	9.2	.14	3.6	0.028	0.7	4.00	SST	C	N
0.406	10.31	BB-42	.44	11.1	.306	7.8	66	12	.16	4.2	11	48	.25	6.4	0.050	1.3	5.00	SPR	CG	N
0.406	10.31	JJ-12	.50	12.7	.358	9.1	1.9	.33	.36	9.0	.66	2.9	.14	3.7	0.024	0.6	6.00	SST	CG	N
0.406	10.31	EE-89	.50	12.7	.348	8.8	6.3	1.1	.33	8.3	2.1	9.2	.17	4.4	0.029	0.7	5.00	MW	C	Z
0.406	10.31	N-63	.50	12.7	.334	8.5	16	2.8	.28	7.1	4.4	20	.18	4.6	0.036	0.9	5.00	SPR	CG	Z
0.406	10.31	A10-55	.50	12.7	.332	8.4	15	2.7	.30	7.5	4.5	20	.20	5.2	0.037	0.9	5.50	SPR	CG	N
0.406	10.31	GG-69	.50	12.7	.326	8.3	25	4.4	.24	6.2	6.1	27	.20	5.1	0.040	1.0	5.00	SPR	CG	Z
0.406	10.31	K-95	.50	12.7	.282	7.2	161	28	.13	3.2	20	91	.33	8.3	0.062	1.6	5.25	HD	CG	Z
0.406	10.31	J-17	.50	12.7	.272	6.9	297	52	.09	2.2	25	113	.30	7.7	0.067	1.7	4.50	SPR	CG	GI
0.406	10.31	I-98	.50	12.7	.242	6.1	678	119	.06	1.5	40	179	.37	9.4	0.082	2.1	4.50	SST	CG	N
0.406	10.31	B7-22	.53	13.5	.328	8.3	27	4.7	.21	5.3	5.6	25	.18	4.5	0.039	1.0	4.50	SPR	CG	Z
0.406	10.31	10843	.53	13.5	.278	7.1	172	30	.13	3.3	22	99	.35	8.9	0.064	1.6	5.50	SPR	CG	N
0.406	10.31	3629	.53	13.5	.232	5.9	846	148	.06	1.5	51	226	.44	11.0	0.087	2.2	5.00	SPR	CG	GI
0.406	10.31	A12-13	.54	13.7	.364	9.2	2.1	.37	.43	11	.92	4.1	.11	2.7	0.021	0.5	4.00	SST	C	N
0.406	10.31	B11-32	.56	14.3	.360	9.1	1.8	.31	.42	11	.76	3.4	.14	3.5	0.023	0.6	6.00	MW	CG	N
0.406	10.31	H-1	.56	14.3	.354	9.0	2.6	.46	.38	9.7	.99	4.4	.18	4.6	0.026	0.7	6.00	SST	C	N
0.406	10.31	XX-35	.56	14.3	.352	8.9	4.9	.85	.38	9.6	1.8	8.2	.15	3.8	0.027	0.7	4.50	SST	C	N
0.406	10.31	XX-47	.56	14.3	.350	8.9	3.3	.57	.34	8.6	1.1	4.9	.22	5.7	0.028	0.7	7.00	MW	C	Z
0.406	10.31	OO-45	.56	14.3	.346	8.8	4.4	.77	.35	8.9	1.5	6.9	.21	5.3	0.030	0.8	7.00	MW	CG	N
0.406	10.31	3718	.56	14.3	.324	8.2	17	2.9	.28	7.0	4.6	20	.29	7.3	0.041	1.0	7.00	SPR	CG	Z
0.406	10.31	J-4	.56	14.3	.316	8.0	56	9.8	.15	3.9	8.6	38	.19	4.9	0.045	1.1	4.25	SPR	CG	Z
0.406	10.31	I-55	.59	15.1	.358	9.1	1.4	.25	.38	9.6	.54	2.4	.22	5.5	0.024	0.6	8.00	MW	C	BO
0.406	10.31	A-2	.59	15.1	.358	9.1	1.4	.25	.40	10	.57	2.5	.19	4.9	0.024	0.6	8.00	MW	CG	N
0.406	10.31	S-1480	.59	15.1	.350	8.9	4.7	.83	.43	11	2.0	9.0	.17	4.3	0.028	0.7	5.00	SST	C	N
0.406	10.31	O-2	.59	15.1	.346	8.8	5.5	.96	.41	10	2.3	10	.18	4.6	0.030	0.8	6.00	MW	CG	N
0.406	10.31	10798	.59	15.1	.330	8.4	16	2.8	.33	8.3	5.2	23	.22	5.6	0.038	1.0	5.75	SPR	CG	BO
0.406	10.31	11086	.59	15.1	.308	7.8	31	5.4	.24	6.0	7.3	33	.36	9.0	0.049	1.2	7.25	SST	CG	N
0.406	10.31	Q-39	.63	15.9	.358	9.1	3.4	.60	.49	13	1.7	7.5	.13	3.4	0.024	0.6	4.50	MW	C	N
0.406	10.31	S-865	.63	15.9	.344	8.7	2.8	.49	.28											

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.406	10.31	PP-3	.72	18.2	.326	8.3	16	2.7	.36	9.2	5.7	25	.25	6.4	0.040	1.0	6.25	SST	CG	N
0.406	10.31	V-7	.75	19.1	.352	8.9	1.8	.31	.48	12	.84	3.7	.27	6.9	0.027	0.7	10.0	MW	CG	N
0.406	10.31	NN-88	.75	19.1	.346	8.8	3.1	.55	.45	11	1.4	6.3	.30	7.6	0.030	0.8	9.00	MW	C	Z
0.406	10.31	S-16	.75	19.1	.344	8.7	2.4	.43	.38	9.6	.92	4.1	.37	9.4	0.031	0.8	11.0	SST	C	N
0.406	10.31	II-89	.75	19.1	.332	8.4	9.3	1.6	.45	12	4.2	19	.30	7.5	0.037	0.9	7.00	SST	C	N
0.406	10.31	FF-8	.75	19.1	.326	8.3	11	1.9	.43	11	4.8	21	.32	8.1	0.040	1.0	8.00	SST	CG	N
0.406	10.31	10857	.75	19.1	.298	7.6	51	8.9	.27	6.8	14	61	.41	10.3	0.054	1.4	7.50	SPR	CG	GI
0.406	10.31	4327	.75	19.1	.282	7.2	116	20	.18	4.5	20	91	.40	10.2	0.062	1.6	6.50	SPR	CG	Z
0.406	10.31	K-81	.75	19.1	.278	7.1	151	26	.15	3.8	22	99	.38	9.8	0.064	1.6	6.00	SPR	CG	Z
0.406	10.31	A12-27	.80	20.3	.364	9.2	.49	.09	.53	13	.26	1.1	.27	6.9	0.021	0.5	12.0	MW	C	N
0.406	10.31	10811	.81	20.6	.382	9.7	.09	.02	.72	18	.06	.28	.10	2.4	0.012	0.3	7.00	SST	C	N
0.406	10.31	S-1323	.81	20.6	.370	9.4	.28	.05	.63	16	.18	.79	.18	4.6	0.018	0.5	10.0	SST	CG	N
0.406	10.31	10155	.81	20.6	.366	9.3	.53	.09	.60	15	.32	1.4	.21	5.3	0.020	0.5	9.50	MW	C	Z
0.406	10.31	A-53	.81	20.6	.324	8.2	15	2.7	.43	11	6.5	29	.31	7.8	0.041	1.0	7.50	SPR	CG	GI
0.406	10.31	A10-30	.81	20.6	.304	7.7	35	6.1	.33	8.4	12	51	.42	10.7	0.051	1.3	8.25	SPR	CG	GI
0.406	10.31	N-49	.81	20.6	.286	7.3	78	14	.22	5.7	17	78	.42	10.7	0.060	1.5	7.00	SST	CG	N
0.406	10.31	PP-96	.81	20.6	.286	7.3	62	11	.26	6.5	16	71	.56	14.1	0.060	1.5	9.25	SPR	CG	Z
0.406	10.31	2865	.88	22.2	.382	9.7	.07	.01	.76	19	.05	.23	.12	3.0	0.012	0.3	9.00	MW	C	Z
0.406	10.31	1559	.88	22.2	.364	9.2	.78	.14	.68	17	.53	2.4	.19	4.9	0.021	0.5	8.25	MW	C	Z
0.406	10.31	V-52	.88	22.2	.356	9.0	1.3	.22	.63	16	.79	3.5	.25	6.4	0.025	0.6	9.00	SST	C	N
0.406	10.31	10125	.88	22.2	.336	8.5	11	1.8	.39	9.8	4.1	18	.25	6.2	0.035	0.9	6.00	SPR	C	GI
0.406	10.31	PP-73	.88	22.2	.326	8.3	11	1.9	.51	13	5.7	25	.32	8.1	0.040	1.0	8.00	SST	CG	N
0.406	10.31	GG-82	.88	22.2	.324	8.2	10	1.8	.51	13	5.3	23	.37	9.4	0.041	1.0	9.00	SST	CG	N
0.406	10.31	I-96	.88	22.2	.310	7.9	24	4.2	.44	11	10	46	.43	11.0	0.048	1.2	9.00	SPR	CG	Z
0.406	10.31	GG-90	.88	22.2	.288	7.3	66	12	.25	6.4	17	74	.50	12.7	0.059	1.5	7.50	SST	C	N
0.406	10.31	S-134	.88	22.2	.262	6.7	150	26	.19	4.7	28	124	.58	14.6	0.072	1.8	8.00	SST	CG	N
0.406	10.31	3745	.88	22.2	.246	6.2	283	50	.14	3.6	40	179	.64	16.3	0.080	2.0	8.00	SPR	CG	Z
0.406	10.31	10539	.91	23.0	.322	8.2	14	2.4	.48	12	6.6	29	.34	8.5	0.042	1.1	8.00	SST	CG	N
0.406	10.31	1545	.94	23.8	.362	9.2	1.0	.18	.74	19	.74	3.3	.20	5.0	0.022	0.6	8.00	MW	C	Z
0.406	10.31	U-11	.94	23.8	.354	9.0	1.7	.30	.70	18	1.2	5.4	.23	5.9	0.026	0.7	8.00	SST	C	N
0.406	10.31	B-4	.94	23.8	.330	8.4	8.6	1.5	.60	15	5.1	23	.34	8.7	0.038	1.0	9.00	HD	CG	Z
0.406	10.31	2863	.94	23.8	.324	8.2	19	3.3	.35	8.9	6.5	29	.31	7.8	0.041	1.0	6.50	SPR	C	Z
0.406	10.31	L-58	.94	23.8	.302	7.7	39	6.9	.31	7.9	12	54	.42	10.6	0.052	1.3	8.00	SPR	CG	Z
0.406	10.31	G-64	.97	24.6	.356	9.0	1.5	.26	.74	19	1.1	5.0	.23	5.7	0.025	0.6	8.00	SST	C	N
0.406	10.31	W-3	.97	24.6	.344	8.7	4.5	.78	.62	16	2.8	12	.22	5.5	0.031	0.8	7.00	SST	CG	N
0.406	10.31	10963	.98	25.0	.262	6.7	230	40	.13	3.3	30	132	.54	13.7	0.072	1.8	6.50	HD	C	Z
0.406	10.31	U-86	1.00	25.4	.372	9.4	.26	.05	.85	22	.22	.97	.15	3.9	0.017	0.4	9.00	SST	CG	N
0.406	10.31	S-1152	1.00	25.4	.368	9.3	.70	.12	.87	22	.61	2.7	.13	3.4	0.019	0.5	6.00	SST	C	N
0.406	10.31	S-265	1.00	25.4	.362	9.2	1.1	.20	.84	21	.96	4.3	.17	4.2	0.022	0.6	6.50	SST	C	N
0.406	10.31	S-477	1.00	25.4	.358	9.1	.46	.08	.54	14	.25	1.1	.46	11.6	0.024	0.6	18.0	SST	C	N
0.406	10.31	S-1046	1.00	25.4	.354	9.0	.65	.11	.51	13	.33	1.5	.49	12.5	0.026	0.7	18.0	SST	C	N
0.406	10.31	V-65	1.00	25.4	.342	8.7	3.6	.63	.68	17	2.4	11	.32	8.1	0.032	0.8	9.00	SST	C	N
0.406	10.31	3607	1.00	25.4	.338	8.6	7.5	1.3	.73	18	5.4	24	.27	6.9	0.034	0.9	7.00	MW	C	GI
0.406	10.31	3624	1.00	25.4	.326	8.3	10	1.8	.61	15	6.1	27	.38	9.7	0.040	1.0	9.50	SPR	CG	Z
0.406	10.31	3919	1.00	25.4	.322	8.2	11	1.9	.56	14	6.1	27	.44	11.2	0.042	1.1	10.5	SPR	CG	Z
0.406	10.31	941	1.00	25.4	.306	7.8	28	5.0	.50	13	14	63	.50	12.7	0.050	1.3	9.00	MW	C	Z
0.406	10.31	A-49	1.00	25.4	.282	7.2	95	17	.21	5.5	20	91	.53	13.4	0.062	1.6	7.50	SPR	C	Z
0.406	10.31	3901	1.00	25.4	.278	7.1	67	12	.30	7.5	20	88	.70	17.9	0.064	1.6	11.0	SPR	CG	Z
0.406	10.31	QQ-39	1.00	25.4	.278	7.1	93	16	.33	8.5	31	138	.54	13.8	0.064	1.6	8.50	MW	CG	Z
0.406	10.31	EE-55	1.03	26.2	.306	7.8	27	4.8	.40	10	11	48	.46	11.7	0.050	1.3	9.25	SPR	CG	N
0.406	10.31	M-108	1.06	27.0	.356	9.0	1.1	.19	.81	21	.90	4.0	.25	6.4	0.025	0.6	10.0	SST	CG	N
0.406	10.31	JJ-96	1.06	27.0	.342	8.7	5.8	1.0	.57	14	3.3	15	.26	6.5	0.032	0.8	7.00	HD	C	GI
0.406	10.31	3794	1.06	27.0	.312	7.9	22	3.8	.45	11	9.7	43	.42	10.7	0.047	1.2	9.00	SPR	CG	Z
0.406	10.31	H-41	1.06	27.0	.298	7.6	28	4.9	.46	12	13	57	.58	14.7	0.054	1.4	10.8	SST	CG	N
0.406	10.31	3696	1.06	27.0	.282	7.2	75	13	.27	6.9	20	91	.56	14.2	0.062	1.6	9.00	SPR	CG	Z
0.406	10.31	S-119	1.06	27.0	.262	6.7	167	29	.17	4.2	28	124	.61	15.5	0.072	1.8	7.50	SST	C	N
0.406	10.31	B8-50	1.09	27.8	.338	8.6	5.3	.93	.74	19	3.9	17	.34	8.6	0.034	0.9	9.00	SPR	C	N
0.406	10.31	O-57	1.09	27.8	.328	8.3	11	2.0	.50	13	5.6	25	.31	7.9	0.039	1.0	8.00	SPR	CG	GI
0.406	10.31	B12-31	1.13	28.6	.356	9.0	.66	.11	.69	17	.45	2.0	.44	11.1	0.025	0.6	17.5	MW	CG	N
0.406	10.31	3508	1.13	28.6	.332	8.4	7.4	1.3	.65	17	4.8	21	.38	9.6	0.037	0.9	9.25	HD	C	Z
0.406	10.31	N-117	1.13	28.6	.236	6.0	324	57	.15	3.7	48	212	.77	19.4	0.085	2.2	9.00	SPR	CG	N
0.406	10.31	FF-84	1.19	30.2	.336	8.5	6.0	1.1	.68	17	4.1	18	.35	8.9	0.035	0.9	9.00	SPR	C	N
0.406	10.31	FF-40	1.19	30.2	.326	8.3	6.7	1.2	.71	18	4.7	21	.48	12.2	0.040	1.0	12.0	SST	CG	N
0.406	10.31	3766	1.19	30.2	.324	8.2	20	3.4	.33	8.4	6.5	29	.30	7.6	0.041	1.0	6.25	SPR	C	GI
0.406	10.31	A15-46	1.19	30.2	.306	7.8	22	3.9	.49	12	11	48	.54	13.8	0.050	1.3	11.0	SPR	CG	N
0.406	10.31	S-1682	1.20	30.6	.368	9.3	.30	.05	.97	25	.29	1.3	.24	6.0	0.019	0.5	11.5	SST	C	N
0.406	10.31	Y-35	1.25	31.8	.356	9.0	1.2	.21	.96	24	1.1	5.1	.29	7.3	0.025	0.6	10.5	MW	C	N
0.406	10.31	A12-16	1.25	31.8	.330	8.4	6.7	1.2	.79	20	5.3	24	.46	11.6	0.038	1.0	11.0	MW	C	N
0.406	10.31	B11-70	1.25	31.8	.326	8.3	11	1.9	.57	14	6.1	27	.36	9.1	0.040	1.0	9.00	SPR	CG	N
0.406	10.31	3538	1.28	32.5	.336</															




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.406	10.31	10216	1.50	38.1	.304	7.7	22	3.8	.53	14	12	51	.61	15.5	0.051	1.3	12.0	SPR	CG	Z
0.406	10.31	12242	1.59	40.5	.282	7.2	47	8.3	.43	11	20	91	.81	20.5	0.062	1.6	13.0	SPR	CG	Z
0.406	10.31	942	1.63	41.3	.326	8.3	7.1	1.3	1.1	28	7.8	34	.54	13.7	0.040	1.0	12.5	MW	C	Z
0.406	10.31	B3-39	1.63	41.3	.282	7.2	45	7.9	.45	11	20	91	.84	21.3	0.062	1.6	13.5	SPR	CG	N
0.406	10.31	3621	1.63	41.3	.280	7.1	51	8.9	.58	15	30	132	.82	20.8	0.063	1.6	13.0	MW	CG	Z
0.406	10.31	H-45	1.69	42.8	.312	7.9	8.9	1.6	.79	20	7.1	31	.89	22.7	0.047	1.2	19.0	SPR	CG	Z
0.406	10.31	I-18	1.72	43.6	.298	7.6	17	3.0	.72	18	12	54	1.00	25.4	0.054	1.4	18.5	SPR	CG	Z
0.406	10.31	FF-76	1.75	44.5	.346	8.8	3.1	.55	1.2	31	3.8	17	.27	6.9	0.030	0.8	9.00	MW	CG	N
0.406	10.31	NN-44	1.75	44.5	.346	8.8	1.7	.30	1.3	32	2.1	9.5	.48	12.2	0.030	0.8	15.0	MW	C	T
0.406	10.31	S-935	1.75	44.5	.324	8.2	6.3	1.1	.97	25	6.1	27	.56	14.3	0.041	1.0	13.8	SST	CG	N
0.406	10.31	8	1.75	44.5	.282	7.2	37	6.5	.55	14	20	91	.99	25.2	0.062	1.6	16.0	HD	CG	Z
0.406	10.31	FF-88	1.75	44.5	.186	4.7	738	129	.12	3.1	89	396	1.43	36.3	0.110	2.8	13.0	SPR	CG	N
0.406	10.31	11131	1.78	45.2	.342	8.7	3.4	.59	1.3	34	4.6	20	.37	9.3	0.032	0.8	10.5	MW	C	Z
0.406	10.31	NN-53	1.78	45.2	.306	7.8	12	2.2	.88	22	11	48	.90	22.9	0.050	1.3	18.0	SPR	CG	Z
0.406	10.31	2860	1.78	45.2	.298	7.6	21	3.6	.92	23	19	84	.84	21.4	0.054	1.4	15.5	MW	CG	Z
0.406	10.31	12235	1.78	45.2	.284	7.2	44	7.7	.44	11	19	87	.79	20.1	0.061	1.5	13.0	SPR	CG	Z
0.406	10.31	GG-58	1.88	47.6	.346	8.8	1.7	.30	1.4	36	2.4	11	.45	11.4	0.030	0.8	15.0	MW	CG	N
0.406	10.31	10533	1.88	47.6	.294	7.5	21	3.7	.72	18	15	68	1.05	26.7	0.056	1.4	17.8	SPR	C	Z
0.406	10.31	12735	1.91	48.5	.302	7.7	24	4.1	.52	13	12	54	.68	17.2	0.052	1.3	12.0	SPR	C	N
0.406	10.31	3646	2.00	50.8	.336	8.5	3.8	.67	1.5	37	5.7	25	.49	12.4	0.035	0.9	13.0	MW	C	GI
0.406	10.31	11443	2.00	50.8	.322	8.2	6.2	1.1	1.1	29	7.0	31	.76	19.2	0.042	1.1	17.0	HD	C	Z
0.406	10.31	115	2.00	50.8	.312	7.9	10	1.8	.95	24	9.7	43	.83	21.2	0.047	1.2	16.8	HD	C	Z
0.406	10.31	10873	2.03	51.6	.294	7.5	22	3.8	.65	17	14	64	.86	21.8	0.056	1.4	15.3	SST	CG	N
0.406	10.31	A9-30	2.06	52.4	.310	7.9	9.2	1.6	1.1	28	10	45	.96	24.4	0.048	1.2	20.0	SPR	CG	GI
0.406	10.31	3602	2.13	54.0	.312	7.9	8.4	1.5	1.2	29	9.7	43	.94	23.9	0.047	1.2	20.0	HD	CG	GI
0.406	10.31	3574	2.31	58.7	.314	8.0	8.6	1.5	1.1	27	9.1	41	.83	21.0	0.046	1.2	18.0	HD	CG	Z
0.406	10.31	B14-40	2.34	59.5	.274	7.0	39	6.8	.63	16	24	109	1.39	35.2	0.066	1.7	20.0	SPR	C	Z
0.406	10.31	4220	2.38	60.3	.346	8.8	1.7	.30	1.9	48	3.2	14	.48	12.2	0.030	0.8	15.0	MW	C	Z
0.406	10.31	4176	2.38	60.3	.308	7.8	12	2.1	.91	23	11	49	.88	22.4	0.049	1.2	17.0	SPR	C	Z
0.406	10.31	EE-93	2.38	60.3	.306	7.8	12	2.2	.88	22	11	48	.90	22.9	0.050	1.3	18.0	SPR	CG	Z
0.406	10.31	2507	2.44	61.9	.250	6.4	77	14	.68	17	52	232	1.76	44.6	0.078	2.0	21.5	MW	C	Z
0.406	10.31	11415	2.50	63.5	.312	7.9	7.2	1.3	1.3	34	9.7	43	1.13	28.7	0.047	1.2	23.0	HD	C	Z
0.406	10.31	11307	2.50	63.5	.306	7.8	9.7	1.7	1.1	27	10	46	1.01	25.7	0.050	1.3	20.3	SST	CG	N
0.406	10.31	4261	2.56	65.1	.344	8.7	1.4	.24	1.9	48	2.6	11	.67	16.9	0.031	0.8	20.5	MW	C	Z
0.406	10.31	11480	2.59	65.9	.346	8.8	1.7	.30	2.1	54	3.6	16	.48	12.2	0.030	0.8	15.0	MW	CG	Z
0.406	10.31	4216	2.75	69.9	.344	8.7	1.6	.28	2.2	55	3.4	15	.59	15.0	0.031	0.8	18.0	MW	C	Z
0.406	10.31	22	2.75	69.9	.312	7.9	7.3	1.3	1.3	34	9.7	43	1.12	28.3	0.047	1.2	22.8	HD	C	Z
0.406	10.31	1914	2.81	71.4	.312	7.9	8.7	1.5	1.1	29	9.7	43	.96	24.5	0.047	1.2	19.5	SPR	C	Z
0.406	10.31	LL-99	3.25	82.6	.282	7.2	22	3.8	.94	24	20	91	1.61	40.9	0.062	1.6	26.0	SPR	CG	N
0.406	10.31	10575	3.31	84.1	.262	6.7	37	6.5	.80	20	30	132	2.16	54.9	0.072	1.8	30.0	SPR	CG	Z
0.406	10.31	10699	4.00	101.6	.332	8.4	2.3	.40	2.1	54	4.8	21	.94	24.0	0.037	0.9	25.5	SPR	CG	Z
0.406	10.31	3613	4.25	108.0	.322	8.2	3.3	.58	2.9	74	9.7	43	1.26	32.0	0.042	1.1	30.0	MW	CG	Z
0.406	10.31	3802	4.38	111.1	.316	8.0	3.8	.66	2.3	57	8.6	38	1.62	41.1	0.045	1.1	35.0	SPR	C	Z
0.406	10.31	11948	4.38	111.1	.306	7.8	6.0	1.1	1.8	46	11	48	1.75	44.5	0.050	1.3	35.0	SPR	CG	GI
0.406	10.31	10380	7.25	184.2	.262	6.7	21	3.6	1.4	36	30	132	3.74	95.1	0.072	1.8	52.0	SPR	CG	Z
0.406	10.31	11833	8.25	209.6	.256	6.5	20	3.5	1.6	40	31	139	4.37	111.0	0.075	1.9	57.3	SST	C	N
0.406	10.31	10908	8.50	215.9	.260	6.6	23	4.0	1.4	35	31	138	3.72	94.6	0.073	1.9	51.0	SPR	CG	N
0.410	10.41	12683	2.75	69.9	.310	7.9	15	2.7	.97	25	15	67	.78	19.7	0.050	1.3	14.5	MW	C	N
0.420	10.67	H-25	.28	7.1	.338	8.6	74	13	.09	2.2	6.3	28	.12	3.1	0.041	1.0	3.00	SPR	CG	N
0.420	10.67	K-83	.31	7.9	.340	8.6	59	10	.09	2.4	5.5	24	.12	3.0	0.040	1.0	3.00	SST	CG	N
0.420	10.67	B10-50	.31	7.9	.340	8.6	67	12	.09	2.2	5.9	26	.16	4.1	0.040	1.0	3.00	SPR	C	N
0.420	10.67	JJ-92	.31	7.9	.338	8.6	64	11	.09	2.3	5.9	26	.16	4.2	0.041	1.0	3.00	SST	C	N
0.420	10.67	LL-95	.31	7.9	.326	8.3	117	20	.08	1.9	8.8	39	.14	3.6	0.047	1.2	3.00	SST	CG	N
0.420	10.67	MM-67	.31	7.9	.320	8.1	156	27	.06	1.6	9.9	44	.15	3.8	0.050	1.3	3.00	SST	CG	N
0.420	10.67	PP-10	.34	8.7	.340	8.6	116	20	.05	1.2	5.5	24	.14	3.6	0.040	1.0	2.50	SST	C	N
0.420	10.67	XX-51	.34	8.7	.312	7.9	108	19	.12	2.9	12	55	.22	5.5	0.054	1.4	4.00	SST	CG	N
0.420	10.67	DD-21	.38	9.5	.340	8.6	59	10	.09	2.4	5.5	24	.12	3.0	0.040	1.0	3.00	SST	CG	N
0.420	10.67	A9-42	.38	9.5	.334	8.5	61	11	.12	3.0	7.3	32	.15	3.8	0.043	1.1	3.50	SPR	CG	Z
0.420	10.67	S-1090	.38	9.5	.320	8.1	51	8.9	.13	3.2	6.4	28	.25	6.4	0.050	1.3	5.00	SST	CG	N
0.420	10.67	L-17	.38	9.5	.306	7.8	137	24	.09	2.3	12	55	.29	7.2	0.057	1.4	4.00	SST	C	N
0.420	10.67	M-105	.38	9.5	.296	7.5	266	47	.07	1.8	19	83	.22	5.5	0.062	1.6	3.50	SST	CG	N
0.420	10.67	II-27	.41	10.3	.382	9.7	1.3	.22	.31	7.8	.39	1.7	.10	2.5	0.019	0.5	4.25	MW	C	N
0.420	10.67	11291	.41	10.3	.338	8.6	16	2.9	.16	4.1	2.6	12	.25	6.2	0.041	1.0	6.00	SST	CG	N
0.420	10.67	10972	.41	10.3	.328	8.3	87	15	.10	2.4	8.3	37	.15	3.8	0.046	1.2	3.25	SST	CG	N
0.420	10.67	JJ-5	.41	10.3	.300	7.6	158	28	.11	2.9	18	80	.27	6.9	0.060	1.5	4.50	SPR	CG	N
0.420	10.67	10099	.41	10.3	.332	8.4	29	5.0	.17	4.2	4.7	21	.24	6.1	0.044	1.1	5.50	SPR	CG	BO
0.420	10.67	S-400	.44	11.1	.376	9.6	2.3	.40	.35	8.9	.81	3.6	.09	2.2	0.022	0.6	4.00	SST	CG	N
0.420	10.67	S-1073	.44	11.1	.370	9.4	2.0	.34	.26	6.7	.52	2.3	.18	4.4	0.025	0.6	6.00	SST	C	N
0.420	10.67	2691	.44	11.1	.338	8.6	37	6.5	.17	4.3	6.3	28	.21	5.2	0.041	1.0	4.00	SPR	C	

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	E N D S	F I N I S H
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.420	10.67	A10-39	.50	12.7	.378	9.6	.87	.15	.33	8.4	.29	1.3	.17	4.3	0.021	0.5	7.00	MW	C	Z
0.420	10.67	B18-160	.50	12.7	.372	9.4	1.9	.33	.33	8.4	.63	2.8	.17	4.3	0.024	0.6	6.00	MW	C	N
0.420	10.67	71313	.50	12.7	.350	8.9	19	3.3	.29	7.4	5.5	24	.14	3.6	0.035	0.9	4.00	MW	CG	N
0.420	10.67	71313S	.50	12.7	.350	8.9	16	2.8	.23	5.9	3.7	16	.14	3.6	0.035	0.9	4.00	SST	CG	N
0.420	10.67	71327	.50	12.7	.344	8.7	23	3.9	.31	7.9	7.0	31	.17	4.2	0.038	1.0	4.38	MW	CG	N
0.420	10.67	71327S	.50	12.7	.344	8.7	19	3.3	.25	6.3	4.7	21	.17	4.2	0.038	1.0	4.38	SST	CG	N
0.420	10.67	GG-23	.50	12.7	.340	8.6	20	3.4	.28	7.1	5.5	24	.20	5.1	0.040	1.0	5.00	SST	CG	N
0.420	10.67	3948	.50	12.7	.338	8.6	27	4.7	.23	6.0	6.3	28	.24	6.0	0.041	1.0	4.75	SPR	C	Z
0.420	10.67	71339	.50	12.7	.336	8.5	34	6.0	.28	7.0	9.4	42	.18	4.7	0.042	1.1	4.38	MW	CG	N
0.420	10.67	71339S	.50	12.7	.336	8.5	29	5.1	.22	5.6	6.4	28	.18	4.7	0.042	1.1	4.38	SST	CG	N
0.420	10.67	71351	.50	12.7	.330	8.4	43	7.6	.27	6.8	12	51	.21	5.3	0.045	1.1	4.63	MW	CG	N
0.420	10.67	71351S	.50	12.7	.330	8.4	37	6.4	.21	5.4	7.8	35	.21	5.3	0.045	1.1	4.63	SST	CG	N
0.420	10.67	71362	.50	12.7	.326	8.3	54	9.5	.24	6.1	13	58	.21	5.4	0.047	1.2	4.50	MW	CG	N
0.420	10.67	71362S	.50	12.7	.326	8.3	46	8.0	.19	4.9	8.8	39	.21	5.4	0.047	1.2	4.50	SST	CG	N
0.420	10.67	71371	.50	12.7	.324	8.2	61	11	.23	5.8	14	62	.22	5.5	0.048	1.2	4.50	MW	CG	N
0.420	10.67	71371S	.50	12.7	.324	8.2	52	9.0	.18	4.6	9.4	42	.22	5.5	0.048	1.2	4.50	SST	CG	N
0.420	10.67	71386	.50	12.7	.318	8.1	74	13	.21	5.3	16	69	.24	6.0	0.051	1.3	4.63	MW	CG	N
0.420	10.67	71386S	.50	12.7	.318	8.1	63	11	.17	4.2	11	47	.24	6.0	0.051	1.3	4.63	SST	CG	N
0.420	10.67	71397	.50	12.7	.310	7.9	95	17	.20	5.2	19	86	.27	6.8	0.055	1.4	4.88	MW	CG	N
0.420	10.67	71397S	.50	12.7	.310	7.9	81	14	.16	4.1	13	58	.27	6.8	0.055	1.4	4.88	SST	CG	N
0.420	10.67	71408	.50	12.7	.302	7.7	137	24	.17	4.4	24	106	.28	7.1	0.059	1.5	4.75	MW	CG	N
0.420	10.67	71408S	.50	12.7	.302	7.7	116	20	.14	3.5	16	72	.28	7.1	0.059	1.5	4.75	SST	CG	N
0.420	10.67	EE-97	.50	12.7	.300	7.6	158	28	.11	2.9	18	80	.27	6.9	0.060	1.5	4.50	SPR	CG	N
0.420	10.67	71419	.50	12.7	.294	7.5	183	32	.16	4.0	29	128	.30	7.6	0.063	1.6	4.75	MW	CG	N
0.420	10.67	71419S	.50	12.7	.294	7.5	155	27	.13	3.2	19	87	.30	7.6	0.063	1.6	4.75	SST	CG	N
0.420	10.67	1803	.53	13.5	.330	8.4	44	7.8	.26	6.6	12	51	.25	6.3	0.045	1.1	4.50	MW	C	Z
0.420	10.67	F-36	.53	13.5	.312	7.9	82	14	.16	4.1	13	59	.32	8.2	0.054	1.4	5.00	SPR	C	Z
0.420	10.67	71328	.56	14.2	.344	8.7	20	3.5	.35	8.9	7.0	31	.18	4.6	0.038	1.0	4.75	MW	CG	N
0.420	10.67	71328S	.56	14.2	.344	8.7	17	3.0	.28	7.1	4.7	21	.18	4.6	0.038	1.0	4.75	SST	CG	N
0.420	10.67	71340	.56	14.2	.336	8.5	31	5.4	.30	7.7	9.4	42	.19	4.9	0.042	1.1	4.63	MW	CG	N
0.420	10.67	71340S	.56	14.2	.336	8.5	26	4.6	.24	6.1	6.4	28	.19	4.9	0.042	1.1	4.63	SST	CG	N
0.420	10.67	Z-33	.56	14.3	.370	9.4	1.2	.20	.34	8.7	.40	1.8	.22	5.6	0.025	0.6	8.75	SST	CG	N
0.420	10.67	H-62	.56	14.3	.356	9.0	13	2.2	.23	5.9	3.0	13	.12	3.0	0.032	0.8	3.75	SST	CG	N
0.420	10.67	M-116	.56	14.3	.346	8.8	12	2.1	.36	9.1	4.2	19	.20	5.2	0.037	0.9	5.50	SST	CG	N
0.420	10.67	XX-60	.56	14.3	.334	8.5	23	4.0	.28	7.2	6.4	28	.28	7.1	0.043	1.1	5.50	SST	C	N
0.420	10.67	GG-57	.56	14.3	.200	5.1	3498	613	.02	.63	87	388	.44	11.2	0.110	2.8	4.00	SPR	CG	Z
0.420	10.67	11198	.59	15.1	.390	9.9	.28	.05	.50	13	.14	.61	.10	2.5	0.015	0.4	5.50	SST	C	N
0.420	10.67	3756	.59	15.1	.270	6.9	366	64	.09	2.3	32	145	.38	9.5	0.075	1.9	5.00	SPR	CG	Z
0.420	10.67	A11-52	.59	15.1	.210	5.3	2769	485	.03	.73	80	354	.42	10.7	0.105	2.7	4.00	SPR	CG	N
0.420	10.67	LL-78	.59	15.1	.210	5.3	2769	485	.03	.73	80	354	.42	10.7	0.105	2.7	4.00	SPR	CG	N
0.420	10.67	3653	.63	15.9	.364	9.2	4.9	.85	.46	12	2.2	9.9	.17	4.3	0.028	0.7	5.00	MW	C	Z
0.420	10.67	OO-89	.63	15.9	.348	8.8	15	2.6	.27	7.0	4.0	18	.20	5.0	0.036	0.9	4.50	SST	C	N
0.420	10.67	S-387	.63	15.9	.336	8.5	24	4.2	.27	6.8	6.4	28	.25	6.4	0.042	1.1	5.00	SST	C	N
0.420	10.67	B11-13	.63	15.9	.336	8.5	27	4.8	.25	6.3	6.8	30	.25	6.4	0.042	1.1	5.00	SPR	C	N
0.420	10.67	B-96	.63	15.9	.332	8.4	22	3.8	.33	8.5	7.3	32	.26	6.7	0.044	1.1	6.00	SST	CG	N
0.420	10.67	3369	.63	15.9	.322	8.2	40	7.0	.27	6.7	11	47	.34	8.7	0.049	1.2	6.00	SPR	C	Z
0.420	10.67	FF-78	.63	15.9	.310	7.9	77	13	.18	4.6	14	62	.30	7.7	0.055	1.4	5.50	SPR	CG	Z
0.420	10.67	B10-30	.63	15.9	.292	7.4	134	24	.15	3.9	20	91	.35	8.9	0.064	1.6	5.50	SST	CG	N
0.420	10.67	A-95	.63	15.9	.270	6.9	212	37	.14	3.5	29	130	.49	12.4	0.075	1.9	6.50	SST	CG	N
0.420	10.67	71314	.63	16.0	.350	8.9	15	2.5	.38	9.6	5.5	24	.16	4.1	0.035	0.9	4.63	MW	CG	N
0.420	10.67	71314S	.63	16.0	.350	8.9	12	2.2	.30	7.6	3.7	16	.16	4.1	0.035	0.9	4.63	SST	CG	N
0.420	10.67	71329	.63	16.0	.344	8.7	18	3.2	.39	9.9	7.0	31	.19	4.8	0.038	1.0	5.00	MW	CG	N
0.420	10.67	71329S	.63	16.0	.344	8.7	15	2.7	.31	7.8	4.7	21	.19	4.8	0.038	1.0	5.00	SST	CG	N
0.420	10.67	71341	.63	16.0	.336	8.5	28	4.8	.34	8.7	9.4	42	.21	5.3	0.042	1.1	5.00	MW	CG	N
0.420	10.67	71341S	.63	16.0	.336	8.5	23	4.1	.27	6.9	6.4	28	.21	5.3	0.042	1.1	5.00	SST	CG	N
0.420	10.67	71352	.63	16.0	.330	8.4	34	6.0	.34	8.6	12	51	.24	6.0	0.045	1.1	5.25	MW	CG	N
0.420	10.67	71352S	.63	16.0	.330	8.4	29	5.1	.27	6.8	7.8	35	.24	6.0	0.045	1.1				




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS			E N D S	F N D H
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm					
0.420	10.67	U-4	.75	19.1	.376	9.6	1.3	.23	.61	15	.80	3.6	.14	3.6	0.022	0.6	5.50	SST	C	N	
0.420	10.67	S-845	.75	19.1	.350	8.9	14	2.4	.27	6.7	3.7	16	.15	3.9	0.035	0.9	4.33	SST	CG	N	
0.420	10.67	71315	.75	19.1	.350	8.9	12	2.1	.46	12	5.5	24	.18	4.7	0.035	0.9	5.25	MW	CG	N	
0.420	10.67	71315S	.75	19.1	.350	8.9	10	1.8	.37	9.4	3.7	16	.18	4.7	0.035	0.9	5.25	SST	CG	N	
0.420	10.67	A9-61	.75	19.1	.348	8.8	8.9	1.6	.47	12	4.2	19	.28	7.1	0.036	0.9	6.75	SPR	C	N	
0.420	10.67	Q-87	.75	19.1	.348	8.8	8.5	1.5	.50	13	4.2	19	.25	6.4	0.036	0.9	7.00	SPR	CG	Z	
0.420	10.67	71330	.75	19.1	.344	8.7	14	2.5	.49	12	7.0	31	.22	5.5	0.038	1.0	5.75	MW	CG	N	
0.420	10.67	71330S	.75	19.1	.344	8.7	12	2.1	.39	9.9	4.7	21	.22	5.5	0.038	1.0	5.75	SST	CG	N	
0.420	10.67	AA-56	.75	19.1	.344	8.7	11	1.9	.47	12	5.0	22	.27	6.8	0.038	1.0	7.00	SPR	CG	GI	
0.420	10.67	B14-22	.75	19.1	.342	8.7	14	2.5	.36	9.2	5.1	23	.22	5.7	0.039	1.0	5.75	SST	CG	N	
0.420	10.67	S-3007	.75	19.1	.340	8.6	17	2.9	.33	8.5	5.5	24	.26	6.6	0.040	1.0	5.50	SST	C	N	
0.420	10.67	I-35	.75	19.1	.338	8.6	11	1.9	.34	8.6	3.6	16	.41	10.4	0.041	1.0	9.00	SPR	C	G	
0.420	10.67	71342	.75	19.1	.336	8.5	22	3.9	.43	11	9.4	42	.24	6.1	0.042	1.1	5.75	MW	CG	N	
0.420	10.67	71342S	.75	19.1	.336	8.5	19	3.3	.34	8.6	6.4	28	.24	6.1	0.042	1.1	5.75	SST	CG	N	
0.420	10.67	U-50	.75	19.1	.334	8.5	18	3.2	.40	10	7.3	32	.34	8.7	0.043	1.1	7.00	SPR	C	Z	
0.420	10.67	71353	.75	19.1	.330	8.4	27	4.8	.42	11	12	51	.28	7.0	0.045	1.1	6.13	MW	CG	N	
0.420	10.67	71353S	.75	19.1	.330	8.4	23	4.1	.34	8.5	7.8	35	.28	7.0	0.045	1.1	6.13	SST	CG	N	
0.420	10.67	71364	.75	19.1	.326	8.3	34	6.0	.38	9.8	13	58	.28	7.2	0.047	1.2	6.00	MW	CG	N	
0.420	10.67	71364S	.75	19.1	.326	8.3	29	5.1	.31	7.8	8.8	39	.28	7.2	0.047	1.2	6.00	SST	CG	N	
0.420	10.67	71374	.75	19.1	.324	8.2	37	6.5	.37	9.4	14	62	.29	7.3	0.048	1.2	6.00	MW	CG	N	
0.420	10.67	71374S	.75	19.1	.324	8.2	32	5.6	.30	7.5	9.4	42	.29	7.3	0.048	1.2	6.00	SST	CG	N	
0.420	10.67	CC-12	.75	19.1	.320	8.1	25	4.4	.30	7.6	7.5	34	.45	11.4	0.050	1.3	9.00	HD	CG	N	
0.420	10.67	71388	.75	19.1	.318	8.1	46	8.0	.34	8.7	16	69	.32	8.1	0.051	1.3	6.25	MW	CG	N	
0.420	10.67	71388S	.75	19.1	.318	8.1	39	6.8	.27	6.9	11	47	.32	8.1	0.051	1.3	6.25	SST	CG	N	
0.420	10.67	3816	.75	19.1	.312	7.9	55	9.6	.24	6.1	13	59	.41	10.3	0.054	1.4	6.50	SPR	C	Z	
0.420	10.67	2959	.75	19.1	.310	7.9	67	12	.21	5.3	14	62	.33	8.4	0.055	1.4	6.00	SPR	CG	Z	
0.420	10.67	71399	.75	19.1	.310	7.9	62	11	.32	8.0	19	86	.35	8.9	0.055	1.4	6.38	MW	CG	N	
0.420	10.67	71399S	.75	19.1	.310	7.9	52	9.2	.25	6.4	13	58	.35	8.9	0.055	1.4	6.38	SST	CG	N	
0.420	10.67	71410	.75	19.1	.302	7.7	83	14	.29	7.3	24	106	.38	9.7	0.059	1.5	6.50	MW	CG	N	
0.420	10.67	71410S	.75	19.1	.302	7.7	70	12	.23	5.8	16	72	.38	9.7	0.059	1.5	6.50	SST	CG	N	
0.420	10.67	GG-97	.75	19.1	.296	7.5	83	15	.24	6.0	20	88	.47	11.8	0.062	1.6	7.50	HD	CG	N	
0.420	10.67	S-1316	.75	19.1	.296	7.5	80	14	.23	5.9	19	83	.43	11.0	0.062	1.6	7.00	SST	CG	N	
0.420	10.67	71421	.75	19.1	.294	7.5	109	19	.26	6.7	29	128	.42	10.6	0.063	1.6	6.63	MW	CG	N	
0.420	10.67	71421S	.75	19.1	.294	7.5	93	16	.21	5.3	19	87	.42	10.6	0.063	1.6	6.63	SST	CG	N	
0.420	10.67	71430	.75	19.1	.286	7.3	144	25	.24	6.0	34	153	.44	11.3	0.067	1.7	6.63	MW	CG	N	
0.420	10.67	71430S	.75	19.1	.286	7.3	123	21	.19	4.8	23	104	.44	11.3	0.067	1.7	6.63	SST	CG	N	
0.420	10.67	2876	.75	19.1	.284	7.2	140	24	.18	4.7	26	115	.48	12.1	0.068	1.7	7.00	SPR	CG	GI	
0.420	10.67	OO-40	.75	19.1	.260	6.6	263	46	.14	3.5	37	163	.56	14.2	0.080	2.0	7.00	SST	CG	N	
0.420	10.67	L-63	.78	19.8	.380	9.7	.89	.16	.64	16	.57	2.5	.14	3.6	0.020	0.5	6.00	MW	C	Z	
0.420	10.67	HH-61	.81	20.6	.376	9.6	.92	.16	.64	16	.59	2.6	.18	4.5	0.022	0.6	7.00	SST	C	N	
0.420	10.67	L-12	.81	20.6	.352	8.9	4.8	.84	.54	14	2.6	12	.27	6.9	0.034	0.9	8.00	SST	CG	N	
0.420	10.67	A9-54	.81	20.6	.352	8.9	3.7	.64	.47	12	1.7	7.7	.34	8.6	0.034	0.9	10.0	SST	CG	N	
0.420	10.67	10553	.81	20.6	.300	7.6	88	15	.20	5.2	18	80	.39	9.9	0.060	1.5	6.50	SPR	CG	Z	
0.420	10.67	S-1205	.81	20.6	.276	7.0	144	25	.19	4.8	27	120	.54	13.7	0.072	1.8	7.50	SST	CG	N	
0.420	10.67	10521	.84	21.4	.338	8.6	11	1.9	.52	13	5.6	25	.33	8.3	0.041	1.0	8.00	SST	CG	N	
0.420	10.67	1679	.84	21.4	.338	8.6	12	2.2	.47	12	5.8	26	.37	9.4	0.041	1.0	8.00	SPR	C	Z	
0.420	10.67	10880	.84	21.4	.286	7.3	97	17	.24	6.1	23	104	.54	13.6	0.067	1.7	8.00	SST	CG	N	
0.420	10.67	B2-42	.84	21.4	.312	7.9	59	10	.23	5.7	13	59	.34	8.6	0.054	1.4	6.25	SPR	CG	GI	
0.420	10.67	S-1542	.88	22.2	.338	8.6	6.4	1.1	.38	9.7	2.5	11	.49	12.5	0.041	1.0	12.0	SST	CG	N	
0.420	10.67	3593	.88	22.2	.312	7.9	45	7.9	.41	10	18	82	.46	11.7	0.054	1.4	7.50	MW	C	Z	
0.420	10.67	10298	.88	22.2	.310	7.9	54	9.4	.26	6.6	14	62	.39	9.8	0.055	1.4	7.00	SPR	CG	Z	
0.420	10.67	S-1050	.88	22.2	.296	7.5	73	13	.26	6.5	19	83	.47	11.8	0.062	1.6	7.50	SST	CG	N	
0.420	10.67	12506	.88	22.2	.296	7.5	115	20	.16	4.1	19	83	.34	8.7	0.062	1.6	5.50	SST	CG	N	
0.420	10.67	Q-76	.88	22.2	.278	7.1	126	22	.21	5.2	26	116	.57	14.4	0.071	1.8	8.00	SST	CG	N	
0.420	10.67	Z-96	.88	22.2	.276	7.0	122	21	.22	5.7	27	120	.61	15.5	0.072	1.8	8.50	SST	CG	N	
0.420	10.67	S-1052	.88	22.2	.260	6.6	235	41	.16	4.0	37	163	.60	15.2	0.080	2.0	7.50	SST	CG	N	
0.420	10.67	S-482	.88	22.2	.260	6.6	215	38	.17	4.3	37	163	.64	16.3	0.080	2.0	8.00	SST	CG	N	
0.420	10.67	71316																			

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.420	10.67	KK-79	.94	23.8	.384	9.8	.29	.05	.76	19	.22	.97	.18	4.6	0.018	0.5	9.00	SST	C	N
0.420	10.67	3587	.94	23.8	.374	9.5	1.1	.19	.73	19	.78	3.5	.21	5.3	0.023	0.6	8.00	MW	C	Z
0.420	10.67	S-1068	.94	23.8	.344	8.7	7.1	1.2	.62	16	4.4	20	.32	8.2	0.038	1.0	8.50	SST	CG	N
0.420	10.67	2547	1.00	25.4	.380	9.7	.45	.08	.78	20	.35	1.5	.22	5.6	0.020	0.5	10.0	MW	C	Z
0.420	10.67	M-38	1.00	25.4	.362	9.2	2.4	.42	.71	18	1.7	7.6	.29	7.4	0.029	0.7	9.00	MW	C	BO
0.420	10.67	OO-71	1.00	25.4	.360	9.1	1.6	.29	.63	16	1.0	4.6	.38	9.5	0.030	0.8	12.5	SST	CG	N
0.420	10.67	Q-77	1.00	25.4	.352	8.9	6.6	1.2	.57	15	3.8	17	.24	6.0	0.034	0.9	7.00	SPR	CG	N
0.420	10.67	71317	1.00	25.4	.350	8.9	8.7	1.5	.63	16	5.5	24	.22	5.7	0.035	0.9	6.38	MW	CG	N
0.420	10.67	71317S	1.00	25.4	.350	8.9	7.4	1.3	.50	13	3.7	16	.22	5.7	0.035	0.9	6.38	SST	CG	N
0.420	10.67	71332	1.00	25.4	.344	8.7	11	1.9	.64	16	7.0	31	.26	6.6	0.038	1.0	6.88	MW	CG	N
0.420	10.67	71332S	1.00	25.4	.344	8.7	9.4	1.6	.51	13	4.7	21	.26	6.6	0.038	1.0	6.88	SST	CG	N
0.420	10.67	I-40	1.00	25.4	.340	8.6	8.3	1.5	.60	15	5.0	22	.40	10.2	0.040	1.0	10.0	SPR	CG	N
0.420	10.67	I-29	1.00	25.4	.336	8.5	10	1.8	.58	15	6.0	26	.42	10.7	0.042	1.1	10.0	SPR	CG	BO
0.420	10.67	71344	1.00	25.4	.336	8.5	16	2.8	.59	15	9.4	42	.30	7.6	0.042	1.1	7.13	MW	CG	N
0.420	10.67	71344S	1.00	25.4	.336	8.5	14	2.4	.47	12	6.4	28	.30	7.6	0.042	1.1	7.13	SST	CG	N
0.420	10.67	10404	1.00	25.4	.330	8.4	20	3.5	.41	10	8.3	37	.34	8.6	0.045	1.1	7.50	SPR	CG	Z
0.420	10.67	71355	1.00	25.4	.330	8.4	20	3.5	.58	15	12	51	.34	8.7	0.045	1.1	7.63	MW	CG	N
0.420	10.67	71355S	1.00	25.4	.330	8.4	17	3.0	.46	12	7.8	35	.34	8.7	0.045	1.1	7.63	SST	CG	N
0.420	10.67	71366	1.00	25.4	.326	8.3	25	4.4	.52	13	13	58	.35	8.8	0.047	1.2	7.38	MW	CG	N
0.420	10.67	71366S	1.00	25.4	.326	8.3	21	3.7	.42	11	8.8	39	.35	8.8	0.047	1.2	7.38	SST	CG	N
0.420	10.67	71377	1.00	25.4	.324	8.2	27	4.7	.51	13	14	62	.36	9.1	0.048	1.2	7.50	MW	CG	N
0.420	10.67	71377S	1.00	25.4	.324	8.2	23	4.0	.41	10	9.4	42	.36	9.1	0.048	1.2	7.50	SST	CG	N
0.420	10.67	Z-18	1.00	25.4	.322	8.2	23	4.0	.46	12	11	47	.44	11.2	0.049	1.2	9.00	SPR	CG	Z
0.420	10.67	71390	1.00	25.4	.318	8.1	33	5.8	.47	12	16	69	.40	10.2	0.051	1.3	7.88	MW	CG	N
0.420	10.67	71390S	1.00	25.4	.318	8.1	28	4.9	.38	9.6	11	47	.40	10.2	0.051	1.3	7.88	SST	CG	N
0.420	10.67	71401	1.00	25.4	.310	7.9	45	7.8	.44	11	19	86	.45	11.4	0.055	1.4	8.13	MW	CG	N
0.420	10.67	71401S	1.00	25.4	.310	7.9	38	6.6	.35	8.8	13	58	.45	11.4	0.055	1.4	8.13	SST	CG	N
0.420	10.67	71412	1.00	25.4	.302	7.7	59	10	.40	10	24	106	.49	12.4	0.059	1.5	8.25	MW	CG	N
0.420	10.67	71412S	1.00	25.4	.302	7.7	50	8.8	.32	8.1	16	72	.49	12.4	0.059	1.5	8.25	SST	CG	N
0.420	10.67	71423	1.00	25.4	.294	7.5	78	14	.37	9.4	29	128	.53	13.4	0.063	1.6	8.38	MW	CG	N
0.420	10.67	71423S	1.00	25.4	.294	7.5	66	12	.29	7.5	19	87	.53	13.4	0.063	1.6	8.38	SST	CG	N
0.420	10.67	71431	1.00	25.4	.286	7.3	103	18	.33	8.5	34	153	.56	14.3	0.067	1.7	8.38	MW	CG	N
0.420	10.67	71431S	1.00	25.4	.286	7.3	87	15	.27	6.8	23	104	.56	14.3	0.067	1.7	8.38	SST	CG	N
0.420	10.67	S-177	1.00	25.4	.276	7.0	113	20	.24	6.1	27	120	.65	16.5	0.072	1.8	9.00	SST	CG	N
0.420	10.67	71438	1.00	25.4	.276	7.0	139	24	.29	7.4	40	180	.62	15.8	0.072	1.8	8.63	MW	CG	N
0.420	10.67	71438S	1.00	25.4	.276	7.0	118	21	.23	5.8	27	120	.62	15.8	0.072	1.8	8.63	SST	CG	N
0.420	10.67	10729	1.03	26.2	.360	9.1	4.3	.76	.84	21	3.6	16	.20	5.0	0.030	0.8	6.50	MW	CG	Z
0.420	10.67	MM-36	1.03	26.2	.340	8.6	13	2.3	.44	11	5.9	26	.32	8.1	0.040	1.0	7.00	SPR	C	Z
0.420	10.67	3650	1.03	26.2	.310	7.9	45	7.8	.31	7.9	14	62	.50	12.6	0.055	1.4	8.00	SPR	C	Z
0.420	10.67	B9-2	1.06	27.0	.332	8.4	18	3.2	.43	11	7.8	35	.33	8.4	0.044	1.1	7.50	SPR	CG	Z
0.420	10.67	2543	1.13	28.6	.356	9.0	3.2	.56	.77	20	2.5	11	.35	8.9	0.032	0.8	10.0	SPR	C	Z
0.420	10.67	S-52	1.13	28.6	.310	7.9	25	4.3	.44	11	11	48	.69	17.5	0.055	1.4	11.5	SST	C	N
0.420	10.67	B3-47	1.19	30.1	.304	7.7	37	6.5	.41	10	15	68	.58	14.7	0.058	1.5	10.0	SST	CG	N
0.420	10.67	CC-98	1.19	30.2	.370	9.4	1.5	.26	.95	24	1.4	6.3	.21	5.2	0.025	0.6	7.25	SST	C	N
0.420	10.67	3937	1.19	30.2	.276	7.0	91	16	.32	8.1	29	129	.86	21.9	0.072	1.8	12.0	SPR	CG	Z
0.420	10.67	10477	1.22	31.0	.310	7.9	35	6.1	.40	10	14	62	.54	13.6	0.055	1.4	9.75	SPR	CG	Z
0.420	10.67	B-99	1.25	31.8	.382	9.7	.37	.07	1.0	27	.39	1.7	.20	5.2	0.019	0.5	9.75	MW	C	N
0.420	10.67	10589	1.25	31.8	.378	9.6	.26	.05	.87	22	.22	1.0	.38	9.6	0.021	0.5	17.0	SST	C	N
0.420	10.67	10094	1.25	31.8	.352	8.9	3.7	.64	.84	21	3.1	14	.41	10.4	0.034	0.9	11.0	SPR	C	Z
0.420	10.67	71318	1.25	31.8	.350	8.9	6.9	1.2	.80	20	5.5	24	.26	6.7	0.035	0.9	7.50	MW	CG	N
0.420	10.67	71318S	1.25	31.8	.350	8.9	5.8	1.0	.64	16	3.7	16	.26	6.7	0.035	0.9	7.50	SST	CG	N
0.420	10.67	3617	1.25	31.8	.348	8.8	5.6	.99	.76	19	4.3	19	.34	8.7	0.036	0.9	9.50	HD	CG	Z
0.420	10.67	10596	1.25	31.8	.346	8.8	6.3	1.1	.74	19	4.7	21	.35	8.9	0.037	0.9	9.50	SPR	CG	Z
0.420	10.67	71333	1.25	31.8	.344	8.7	8.5	1.5	.82	21	7.0	31	.32	8.1	0.038	1.0	8.38	MW	CG	N
0.420	10.67	71333S	1.25	31.8	.344	8.7	7.2	1.3	.65	17	4.7	21	.32	8.1	0.038	1.0	8.38	SST	CG	N
0.420	10.67	71345	1.25	31.8	.336	8.5	13	2.3	.72	18	9.4	42	.35	8.9	0.042	1.1	8.38	MW	CG	N
0.420	10.67	71345S	1.25	31.8	.336	8.5	11	1.9	.57	1										




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.420	10.67	3548	1.28	32.5	.312	7.9	31	5.4	.59	15	18	82	.59	15.1	0.054	1.4	10.0	MW	C	Z
0.420	10.67	A11-47	1.28	32.5	.294	7.5	58	10	.36	9.1	21	92	.66	16.8	0.063	1.6	10.5	SPR	CG	Z
0.420	10.67	B9-24	1.38	34.9	.332	8.4	18	3.2	.43	11	7.8	35	.33	8.4	0.044	1.1	7.50	SPR	CG	Z
0.420	10.67	3527	1.38	34.9	.326	8.3	14	2.5	.67	17	9.4	42	.59	14.9	0.047	1.2	11.5	HD	C	Z
0.420	10.67	3675	1.41	35.7	.332	8.4	17	3.1	.44	11	7.8	35	.34	8.7	0.044	1.1	7.75	SPR	CG	Z
0.420	10.67	4257	1.41	35.7	.326	8.3	13	2.3	.70	18	9.4	42	.56	14.3	0.047	1.2	12.0	SPR	CG	N
0.420	10.67	Q-61	1.44	36.5	.374	9.5	.53	.09	1.1	29	.60	2.7	.31	7.9	0.023	0.6	12.5	SST	C	N
0.420	10.67	S-1489	1.44	36.5	.312	7.9	30	5.2	.42	11	12	55	.50	12.7	0.054	1.4	9.25	SST	CG	N
0.420	10.67	A13-30	1.44	36.5	.198	5.0	862	151	.10	2.6	89	398	1.17	29.6	0.111	2.8	10.5	SPR	CG	N
0.420	10.67	S-402	1.47	37.3	.258	6.6	161	28	.24	6.0	38	168	.85	21.6	0.081	2.1	10.5	SST	CG	N
0.420	10.67	S-1204	1.50	38.1	.380	9.7	.22	.04	1.2	29	.26	1.1	.34	8.6	0.020	0.5	16.0	SST	C	N
0.420	10.67	RR-40	1.50	38.1	.368	9.3	.89	.16	1.1	28	.99	4.4	.39	9.9	0.026	0.7	14.0	MW	C	Z
0.420	10.67	11305	1.50	38.1	.364	9.2	1.7	.30	1.2	30	2.0	9.0	.32	8.2	0.028	0.7	10.5	MW	C	GI
0.420	10.67	71319	1.50	38.1	.350	8.9	5.6	.98	.98	25	5.5	24	.31	7.8	0.035	0.9	8.75	MW	CG	N
0.420	10.67	71319S	1.50	38.1	.350	8.9	4.8	.83	.78	20	3.7	16	.31	7.8	0.035	0.9	8.75	SST	CG	N
0.420	10.67	10230	1.50	38.1	.344	8.7	7.4	1.3	.69	17	5.0	22	.39	9.9	0.038	1.0	9.25	SPR	C	Z
0.420	10.67	71334	1.50	38.1	.344	8.7	7.1	1.2	.98	25	7.0	31	.37	9.3	0.038	1.0	9.63	MW	CG	N
0.420	10.67	71334S	1.50	38.1	.344	8.7	6.0	1.1	.78	20	4.7	21	.37	9.3	0.038	1.0	9.63	SST	CG	N
0.420	10.67	71346	1.50	38.1	.336	8.5	11	1.8	.89	23	9.4	42	.41	10.5	0.042	1.1	9.88	MW	CG	N
0.420	10.67	71346S	1.50	38.1	.336	8.5	8.9	1.6	.71	18	6.4	28	.41	10.5	0.042	1.1	9.88	SST	CG	N
0.420	10.67	71357	1.50	38.1	.330	8.4	13	2.3	.89	23	12	51	.48	12.1	0.045	1.1	10.6	MW	CG	N
0.420	10.67	71357S	1.50	38.1	.330	8.4	11	1.9	.71	18	7.8	35	.48	12.1	0.045	1.1	10.6	SST	CG	N
0.420	10.67	S-3137	1.50	38.1	.326	8.3	16	2.7	.57	14	8.8	39	.45	11.3	0.047	1.2	9.50	SST	CG	N
0.420	10.67	71368	1.50	38.1	.326	8.3	16	2.7	.84	21	13	58	.51	12.8	0.047	1.2	10.8	MW	CG	N
0.420	10.67	71368S	1.50	38.1	.326	8.3	13	2.3	.67	17	8.8	39	.51	12.8	0.047	1.2	10.8	SST	CG	N
0.420	10.67	71379	1.50	38.1	.324	8.2	17	3.0	.81	21	14	62	.51	13.0	0.048	1.2	10.6	MW	CG	N
0.420	10.67	71379S	1.50	38.1	.324	8.2	15	2.6	.64	16	9.4	42	.51	13.0	0.048	1.2	10.6	SST	CG	N
0.420	10.67	71392	1.50	38.1	.318	8.1	21	3.7	.74	19	16	69	.57	14.4	0.051	1.3	11.1	MW	CG	N
0.420	10.67	71392S	1.50	38.1	.318	8.1	18	3.1	.59	15	11	47	.57	14.4	0.051	1.3	11.1	SST	CG	N
0.420	10.67	A16-68	1.50	38.1	.318	8.1	13	2.2	.62	16	7.9	35	.88	22.4	0.051	1.3	17.3	MW	CG	N
0.420	10.67	YY-69	1.50	38.1	.312	7.9	26	4.6	.51	13	13	59	.68	17.1	0.054	1.4	11.5	SPR	C	Z
0.420	10.67	71403	1.50	38.1	.310	7.9	29	5.0	.68	17	19	86	.63	16.1	0.055	1.4	11.5	MW	CG	N
0.420	10.67	71403S	1.50	38.1	.310	7.9	24	4.2	.54	14	13	58	.63	16.1	0.055	1.4	11.5	SST	CG	N
0.420	10.67	71414	1.50	38.1	.302	7.7	38	6.6	.63	16	24	106	.69	17.6	0.059	1.5	11.8	MW	CG	N
0.420	10.67	71414S	1.50	38.1	.302	7.7	32	5.6	.50	13	16	72	.69	17.6	0.059	1.5	11.8	SST	CG	N
0.420	10.67	CC-82	1.50	38.1	.300	7.6	32	5.6	.53	13	17	75	.78	19.8	0.060	1.5	13.0	SST	CG	N
0.420	10.67	S-1395	1.50	38.1	.296	7.5	44	7.8	.42	11	19	83	.68	17.3	0.062	1.6	11.0	SST	CG	N
0.420	10.67	71425	1.50	38.1	.294	7.5	50	8.7	.58	15	29	128	.76	19.2	0.063	1.6	12.0	MW	CG	N
0.420	10.67	71425S	1.50	38.1	.294	7.5	42	7.4	.46	12	19	87	.76	19.2	0.063	1.6	12.0	SST	CG	N
0.420	10.67	71433	1.50	38.1	.286	7.3	65	11	.53	13	34	153	.81	20.6	0.067	1.7	12.1	MW	CG	N
0.420	10.67	71433S	1.50	38.1	.286	7.3	55	9.7	.42	11	23	104	.81	20.6	0.067	1.7	12.1	SST	CG	N
0.420	10.67	71440	1.50	38.1	.276	7.0	88	15	.46	12	40	180	.89	22.6	0.072	1.8	12.4	MW	CG	N
0.420	10.67	71440S	1.50	38.1	.276	7.0	75	13	.36	9.2	27	120	.89	22.6	0.072	1.8	12.4	SST	CG	N
0.420	10.67	S-841	1.56	39.7	.338	8.6	7.3	1.3	.82	21	5.9	26	.45	11.3	0.041	1.0	11.0	SST	CG	N
0.420	10.67	I-56	1.63	41.3	.292	7.4	44	7.7	.49	12	22	96	.90	22.8	0.064	1.6	14.0	SPR	CG	Z
0.420	10.67	11239	1.63	41.3	.256	6.5	148	26	.26	6.7	39	174	.98	25.0	0.082	2.1	12.0	SST	CG	N
0.420	10.67	71320	1.75	44.5	.350	8.9	4.9	.85	1.1	29	5.5	24	.34	8.7	0.035	0.9	9.75	MW	CG	N
0.420	10.67	71320S	1.75	44.5	.350	8.9	4.1	.72	.90	23	3.7	16	.34	8.7	0.035	0.9	9.75	SST	CG	N
0.420	10.67	12110	1.75	44.5	.350	8.9	4.2	.73	.95	24	4.0	18	.42	10.7	0.035	0.9	11.0	SPR	C	Z
0.420	10.67	71335	1.75	44.5	.344	8.7	6.3	1.1	1.1	28	7.0	31	.40	10.1	0.038	1.0	10.5	MW	CG	N
0.420	10.67	71335S	1.75	44.5	.344	8.7	5.4	.94	.88	22	4.7	21	.40	10.1	0.038	1.0	10.5	SST	CG	N
0.420	10.67	71347	1.75	44.5	.336	8.5	9.2	1.6	1.0	26	9.4	42	.46	11.7	0.042	1.1	11.0	MW	CG	N
0.420	10.67	71347S	1.75	44.5	.336	8.5	7.8	1.4	.82	21	6.4	28	.46	11.7	0.042	1.1	11.0	SST	CG	N
0.420	10.67	71358	1.75	44.5	.330	8.4	11	2.0	1.0	26	12	51	.53	13.4	0.045	1.1	11.8	MW	CG	N
0.420	10.67	71358S	1.75	44.5	.330	8.4	9.7	1.7	.80	20	7.8	35	.53	13.4	0.045	1.1	11.8	SST	CG	N
0.420	10.67	71369	1.75	44.5	.326	8.3	14	2.4	.97	25	13	58	.56	14.3	0.047	1.2	12.0	MW	CG	N
0.420	10.67	71369S	1.75	44.5	.326	8.3	11	2.0	.77	20	8.8	39	.56	14.3	0.047	1.2	12.0	SST	CG	N
0.420	10.67	71380	1.75	44.5	.324	8.2	15	2.6	.94	24	14	62	.58	14.6	0.048	1.2	12.0	MW	CG	N
0.420	10.67	71380S	1.75	44.5	.324	8.2	13	2.2	.75	19	9.4	42	.58	14.6	0.048	1.2	12.0	SST	CG	N
0.420	10.67	3432	1.75	44.5	.320	8.1	23	4.0	.47	12	11	47	.49	12.4	0.050	1.3	9.75	SPR	CG	Z
0.420	10.67	71393	1.75	44.5	.318	8.1	17	3.0	.89	23	16	69	.67	17.0	0.051	1.3	13.1	MW	CG	N
0.420	10.67	71393S	1.75	44.5	.318	8.1	15	2.6	.71	18	11	47	.67	17.0	0.051	1.3	13.1	SST	CG	N
0.420	10.67	71404	1.75	44.5	.310	7.9	24	4.2	.80	20	19	86	.72	18.3	0.055	1.4	13.1	MW	CG	N
0.420	10.67	71404S	1.75	44.5	.310	7.9	21	3.6	.64	16	13	58	.72	18.3	0.055	1.4	13.1	SST	CG	N
0.420	10.67	71415	1.75	44.5	.302	7.7	32	5.6	.74	19	24	106	.80	20.4	0.059	1.5	13.6	MW	CG	N
0.420	10.67	71415S	1.75	44.5	.302	7.7	27	4.8	.59	15	16	72	.80	20.4	0.059	1.5	13.6	SST	CG	N
0.420	10.67	71426	1.75	44.5	.294	7.5	42	7.3	.69	17	29	128	.87	22.2	0.063	1.6	13.9	MW	CG	N
0.420	10.67	71426S	1.75	44.5	.294	7.5	36	6.2	.55	14	19	87	.87	22.2	0.063	1.6	13.9	SST	CG	N
0.420	10.67	71434	1.75	44.5	.286	7.3	55	9.6	.62	16	34	153	.94							

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.420	10.67	71336S	2.00	50.8	.344	8.7	4.8	.84	.98	25	4.7	21	.44	11.1	0.038	1.0	11.5	SST	CG	N
0.420	10.67	3555	2.00	50.8	.336	8.5	6.8	1.2	1.4	35	9.4	42	.59	14.9	0.042	1.1	14.0	MW	CG	Z
0.420	10.67	71348	2.00	50.8	.336	8.5	7.8	1.4	1.2	31	9.4	42	.53	13.5	0.042	1.1	12.6	MW	CG	N
0.420	10.67	71348S	2.00	50.8	.336	8.5	6.6	1.2	.96	24	6.4	28	.53	13.5	0.042	1.1	12.6	SST	CG	N
0.420	10.67	71359	2.00	50.8	.330	8.4	9.9	1.7	1.2	30	12	51	.60	15.1	0.045	1.1	13.3	MW	CG	N
0.420	10.67	71359S	2.00	50.8	.330	8.4	8.4	1.5	.92	23	7.8	35	.60	15.1	0.045	1.1	13.3	SST	CG	N
0.420	10.67	71370	2.00	50.8	.326	8.3	12	2.0	1.1	29	13	58	.65	16.4	0.047	1.2	13.8	MW	CG	N
0.420	10.67	71370S	2.00	50.8	.326	8.3	9.8	1.7	.90	23	8.8	39	.65	16.4	0.047	1.2	13.8	SST	CG	N
0.420	10.67	71381	2.00	50.8	.324	8.2	13	2.3	1.1	27	14	62	.65	16.5	0.048	1.2	13.5	MW	CG	N
0.420	10.67	71381S	2.00	50.8	.324	8.2	11	1.9	.86	22	9.4	42	.65	16.5	0.048	1.2	13.5	SST	CG	N
0.420	10.67	71394	2.00	50.8	.318	8.1	16	2.7	1.0	25	16	69	.74	18.8	0.051	1.3	14.5	MW	CG	N
0.420	10.67	71394S	2.00	50.8	.318	8.1	13	2.3	.80	20	11	47	.74	18.8	0.051	1.3	14.5	SST	CG	N
0.420	10.67	71405	2.00	50.8	.310	7.9	21	3.7	.92	23	19	86	.81	20.6	0.055	1.4	14.8	MW	CG	N
0.420	10.67	71405S	2.00	50.8	.310	7.9	18	3.1	.73	19	13	58	.81	20.6	0.055	1.4	14.8	SST	CG	N
0.420	10.67	71416	2.00	50.8	.302	7.7	28	4.9	.86	22	24	106	.91	23.0	0.059	1.5	15.4	MW	CG	N
0.420	10.67	71416S	2.00	50.8	.302	7.7	24	4.1	.68	17	16	72	.91	23.0	0.059	1.5	15.4	SST	CG	N
0.420	10.67	71427	2.00	50.8	.294	7.5	36	6.4	.79	20	29	128	.99	25.2	0.063	1.6	15.8	MW	CG	N
0.420	10.67	71427S	2.00	50.8	.294	7.5	31	5.4	.63	16	19	87	.99	25.2	0.063	1.6	15.8	SST	CG	N
0.420	10.67	71435	2.00	50.8	.286	7.3	48	8.3	.72	18	34	153	1.06	27.0	0.067	1.7	15.9	MW	CG	N
0.420	10.67	71435S	2.00	50.8	.286	7.3	40	7.1	.58	15	23	104	1.06	27.0	0.067	1.7	15.9	SST	CG	N
0.420	10.67	71442	2.00	50.8	.276	7.0	64	11	.63	16	40	180	1.17	29.7	0.072	1.8	16.3	MW	CG	N
0.420	10.67	71442S	2.00	50.8	.276	7.0	55	9.6	.50	13	27	120	1.17	29.7	0.072	1.8	16.3	SST	CG	N
0.420	10.67	4374	2.06	52.4	.276	7.0	62	11	.47	12	29	129	1.21	30.6	0.072	1.8	16.8	SPR	CG	Z
0.420	10.67	71324	2.25	57.2	.350	8.9	3.8	.67	1.4	37	5.5	24	.42	10.7	0.035	0.9	12.0	MW	CG	N
0.420	10.67	71324S	2.25	57.2	.350	8.9	3.2	.57	1.1	29	3.7	16	.42	10.7	0.035	0.9	12.0	SST	CG	N
0.420	10.67	S-1410	2.25	57.2	.346	8.8	5.2	.91	.85	21	4.4	19	.41	10.3	0.037	0.9	10.0	SST	C	N
0.420	10.67	71337	2.25	57.2	.344	8.7	5.0	.88	1.4	36	7.0	31	.48	12.3	0.038	1.0	12.8	MW	CG	N
0.420	10.67	71337S	2.25	57.2	.344	8.7	4.3	.74	1.1	28	4.7	21	.48	12.3	0.038	1.0	12.8	SST	CG	N
0.420	10.67	71349	2.25	57.2	.336	8.5	7.2	1.3	1.3	33	9.4	42	.57	14.4	0.042	1.1	13.5	MW	CG	N
0.420	10.67	71349S	2.25	57.2	.336	8.5	6.1	1.1	1.0	26	6.4	28	.57	14.4	0.042	1.1	13.5	SST	CG	N
0.420	10.67	71360	2.25	57.2	.330	8.4	8.7	1.5	1.3	34	12	51	.67	17.0	0.045	1.1	14.9	MW	CG	N
0.420	10.67	71360S	2.25	57.2	.330	8.4	7.4	1.3	1.1	27	7.8	35	.67	17.0	0.045	1.1	14.9	SST	CG	N
0.420	10.67	71383	2.25	57.2	.324	8.2	11	1.9	1.3	32	14	62	.74	18.7	0.048	1.2	15.4	MW	CG	N
0.420	10.67	71383S	2.25	57.2	.324	8.2	9.4	1.7	1.0	25	9.4	42	.74	18.7	0.048	1.2	15.4	SST	CG	N
0.420	10.67	71395	2.25	57.2	.318	8.1	14	2.4	1.1	29	16	69	.82	20.7	0.051	1.3	16.0	MW	CG	N
0.420	10.67	71395S	2.25	57.2	.318	8.1	12	2.1	.90	23	11	47	.82	20.7	0.051	1.3	16.0	SST	CG	N
0.420	10.67	71406	2.25	57.2	.310	7.9	18	3.2	1.1	27	19	86	.92	23.4	0.055	1.4	16.8	MW	CG	N
0.420	10.67	71406S	2.25	57.2	.310	7.9	16	2.7	.84	21	13	58	.92	23.4	0.055	1.4	16.8	SST	CG	N
0.420	10.67	71417	2.25	57.2	.302	7.7	25	4.3	.97	25	24	106	1.01	25.7	0.059	1.5	17.1	MW	CG	N
0.420	10.67	71417S	2.25	57.2	.302	7.7	21	3.6	.77	20	16	72	1.01	25.7	0.059	1.5	17.1	SST	CG	N
0.420	10.67	71428	2.25	57.2	.294	7.5	32	5.6	.90	23	29	128	1.10	28.0	0.063	1.6	17.5	MW	CG	N
0.420	10.67	71428S	2.25	57.2	.294	7.5	27	4.8	.72	18	19	87	1.10	28.0	0.063	1.6	17.5	SST	CG	N
0.420	10.67	71436	2.25	57.2	.286	7.3	42	7.4	.82	21	34	153	1.18	30.0	0.067	1.7	17.6	MW	CG	N
0.420	10.67	71436S	2.25	57.2	.286	7.3	36	6.3	.65	17	23	104	1.18	30.0	0.067	1.7	17.6	SST	CG	N
0.420	10.67	71443	2.25	57.2	.276	7.0	57	9.9	.71	18	40	180	1.31	33.4	0.072	1.8	18.3	MW	CG	N
0.420	10.67	71443S	2.25	57.2	.276	7.0	48	8.4	.56	14	27	120	1.31	33.4	0.072	1.8	18.3	SST	CG	N
0.420	10.67	4243	2.38	60.3	.360	9.1	1.5	.26	1.9	48	2.8	13	.48	12.2	0.030	0.8	15.0	MW	C	Z
0.420	10.67	10568	2.38	60.3	.268	6.8	62	11	.55	14	34	150	1.59	40.4	0.076	1.9	21.0	SPR	CG	N
0.420	10.67	10615	2.50	63.5	.370	9.4	.62	.11	2.1	53	1.3	5.8	.40	10.2	0.025	0.6	15.0	SST	C	N
0.420	10.67	71326	2.50	63.5	.350	8.9	3.4	.60	1.6	41	5.5	24	.46	11.7	0.035	0.9	13.1	MW	CG	N
0.420	10.67	71326S	2.50	63.5	.350	8.9	2.9	.51	1.3	33	3.7	16	.46	11.7	0.035	0.9	13.1	SST	CG	N
0.420	10.67	71338	2.50	63.5	.344	8.7	4.5	.79	1.6	39	7.0	31	.53	13.5	0.038	1.0	14.0	MW	CG	N
0.420	10.67	71338S	2.50	63.5	.344	8.7	3.8	.67	1.2	31	4.7	21	.53	13.5	0.038	1.0	14.0	SST	CG	N
0.420	10.67	71350	2.50	63.5	.336	8.5	6.5	1.1	1.5	37	9.4	42	.62	15.9	0.042	1.1	14.9	MW	CG	N
0.420	10.67	71350S	2.50	63.5	.336	8.5	5.5	.96	1.2	29	6.4	28	.62	15.9	0.042	1.1	14.9	SST	CG	N
0.420	10.67	71361	2.50	63.5	.330	8.4	7.9	1.4	1.5	37	12	51	.73	18.6	0.045	1.1	16.3	MW	CG	N




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	E N D S	F N I S H
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.420	10.67	B15-60	4.13	104.8	.308	7.8	12	2.1	1.2	30	14	62	1.34	34.1	0.056	1.4	24.0	SST	CG	N
0.420	10.67	4127	4.88	123.8	.332	8.4	4.4	.77	1.8	45	7.8	35	1.14	29.1	0.044	1.1	25.0	SPR	C	Z
0.420	10.67	1529	4.94	125.4	.324	8.2	5.0	.87	2.8	71	14	62	1.51	38.4	0.048	1.2	31.5	MW	CG	Z
0.420	10.67	10760	6.00	152.4	.328	8.3	2.7	.47	3.3	83	8.9	39	2.16	54.9	0.046	1.2	47.0	SPR	CG	N
0.420	10.67	10605	7.13	181.0	.336	8.5	1.4	.24	4.5	115	6.2	28	2.59	65.9	0.042	1.1	61.8	SPR	CG	GI
0.420	10.67	3979	7.75	196.9	.236	6.0	50	8.7	1.1	28	55	247	5.52	140.2	0.092	2.3	60.0	SPR	CG	Z
0.420	10.67	11289	8.00	203.2	.338	8.6	1.5	.26	3.9	100	5.9	26	1.91	48.4	0.041	1.0	45.5	SST	C	N
0.420	10.67	11666	9.50	241.3	.322	8.2	2.0	.34	5.4	137	11	47	4.12	104.5	0.049	1.2	84.0	SPR	CG	GI
0.420	10.67	S-424	15.8	400.1	.346	8.8	.32	.06	11	274	3.4	15	4.96	125.9	0.037	0.9	133.0	SST	C	N
0.432	10.97	B3-63	1.23	31.3	.280	7.1	132	23	.23	5.9	31	137	.68	17.4	0.076	1.9	9.00	SST	CG	N
0.437	11.10	S-1266	.31	7.9	.407	10.3	.21	.04	.21	5.3	.04	.19	.11	2.7	0.015	0.4	6.00	SST	C	N
0.437	11.10	12611	.31	7.9	.391	9.9	.99	.17	.13	3.3	.13	.56	.18	4.7	0.023	0.6	7.00	SST	C	N
0.437	11.10	11454	.31	7.9	.387	9.8	3.6	.62	.19	4.7	.67	3.0	.13	3.2	0.025	0.6	4.00	SST	C	N
0.437	11.10	A15-44	.34	8.7	.355	9.0	26	4.5	.16	4.0	4.1	18	.18	4.7	0.041	1.0	4.50	SPR	CG	N
0.437	11.10	S-1144	.38	9.5	.381	9.7	4.5	.78	.22	5.6	.99	4.4	.15	3.9	0.028	0.7	4.50	SST	C	N
0.437	11.10	3984	.41	10.3	.361	9.2	23	4.1	.21	5.3	4.9	22	.19	4.8	0.038	1.0	4.00	SPR	C	Z
0.437	11.10	S-876	.41	10.3	.355	9.0	34	6.0	.17	4.2	5.7	25	.15	3.8	0.041	1.0	3.75	SST	CG	N
0.437	11.10	3920	.44	11.1	.353	9.0	36	6.3	.18	4.6	6.5	29	.17	4.3	0.042	1.1	4.00	SPR	CG	Z
0.437	11.10	S-157	.44	11.1	.327	8.3	104	18	.12	3.1	13	56	.22	5.6	0.055	1.4	4.00	SST	CG	N
0.437	11.10	S-196	.44	11.1	.327	8.3	69	12	.11	2.7	7.5	33	.33	8.4	0.055	1.4	5.00	SST	C	N
0.437	11.10	JJ-30	.47	11.9	.377	9.6	6.1	1.1	.33	8.5	2.0	9.1	.14	3.4	0.030	0.8	4.50	SST	CG	N
0.437	11.10	N-84	.47	11.9	.369	9.4	10	1.8	.28	7.1	2.8	13	.19	4.7	0.034	0.9	4.50	SST	C	N
0.437	11.10	FF-60	.47	11.9	.337	8.6	45	7.8	.21	5.5	9.6	43	.25	6.4	0.050	1.3	5.00	SST	CG	N
0.437	11.10	WW-68	.47	11.9	.313	8.0	133	23	.14	3.6	19	85	.31	7.9	0.062	1.6	5.00	SPR	CG	Z
0.437	11.10	2659	.47	11.9	.311	7.9	143	25	.14	3.5	20	89	.32	8.0	0.063	1.6	5.00	SPR	CG	Z
0.437	11.10	S-1039	.47	11.9	.277	7.0	446	78	.08	2.0	35	157	.36	9.1	0.080	2.0	4.50	SST	CG	N
0.437	11.10	11219	.50	12.7	.411	10.4	.12	.02	.41	10	.05	.22	.09	2.3	0.013	0.3	6.00	SST	C	N
0.437	11.10	TT-43	.50	12.7	.397	10.1	.91	.16	.38	9.7	.35	1.5	.12	3.0	0.020	0.5	5.00	SST	C	N
0.437	11.10	2989	.50	12.7	.377	9.6	8.6	1.5	.35	8.9	3.0	13	.15	3.8	0.030	0.8	4.00	MW	C	Z
0.437	11.10	12661	.50	12.7	.377	9.6	7.5	1.3	.31	8.0	2.4	10	.15	3.8	0.030	0.8	4.00	SST	C	N
0.437	11.10	10250	.50	12.7	.367	9.3	15	2.6	.26	6.6	3.8	17	.18	4.7	0.035	0.9	4.25	SPR	C	Z
0.437	11.10	AA-88	.50	12.7	.357	9.1	17	3.0	.30	7.6	5.1	23	.20	5.1	0.040	1.0	5.00	SST	CG	N
0.437	11.10	K-25	.50	12.7	.355	9.0	28	4.9	.20	5.1	5.7	25	.21	5.2	0.041	1.0	4.00	SST	C	N
0.437	11.10	S-1557	.50	12.7	.337	8.6	54	9.4	.18	4.5	9.6	43	.23	5.7	0.050	1.3	4.50	SST	CG	N
0.437	11.10	B9-21	.50	12.7	.287	7.3	274	48	.09	2.2	24	107	.41	10.5	0.075	1.9	5.50	SPR	CG	N
0.437	11.10	S-3172	.53	13.5	.391	9.9	1.4	.24	.38	9.7	.53	2.4	.15	3.8	0.023	0.6	5.50	SST	C	N
0.437	11.10	B-48	.53	13.5	.363	9.2	15	2.5	.31	7.9	4.5	20	.18	4.6	0.037	0.9	5.00	SPR	CG	N
0.437	11.10	4206	.53	13.5	.293	7.4	263	46	.11	2.7	28	124	.36	9.1	0.072	1.8	5.00	SPR	CG	Z
0.437	11.10	11182	.56	14.3	.387	9.8	1.6	.28	.36	9.2	.58	2.6	.20	5.1	0.025	0.6	7.00	MW	C	N
0.437	11.10	3371	.56	14.3	.373	9.5	10	1.8	.31	7.8	3.1	14	.17	4.3	0.032	0.8	4.25	HD	C	Z
0.437	11.10	B-88	.56	14.3	.327	8.3	70	12	.18	4.6	13	56	.28	7.0	0.055	1.4	5.00	SST	CG	N
0.437	11.10	2993	.56	14.3	.313	8.0	133	23	.14	3.6	19	85	.31	7.9	0.062	1.6	5.00	SPR	CG	Z
0.437	11.10	4309	.56	14.3	.303	7.7	142	25	.16	4.1	23	101	.40	10.2	0.067	1.7	6.00	SPR	CG	Z
0.437	11.10	4275	.59	15.1	.313	8.0	100	17	.19	4.9	19	85	.37	9.4	0.062	1.6	6.00	SPR	CG	Z
0.437	11.10	S-1063	.63	15.9	.381	9.7	5.6	.98	.34	8.7	1.9	8.5	.14	3.6	0.028	0.7	4.00	SST	C	N
0.437	11.10	S-3062	.63	15.9	.373	9.5	9.8	1.7	.29	7.4	2.8	13	.16	4.1	0.032	0.8	4.00	SST	C	N
0.437	11.10	B11-67	.63	15.9	.373	9.5	11	2.0	.27	6.9	3.1	14	.13	3.3	0.032	0.8	4.00	SPR	CG	N
0.437	11.10	A12-6	.63	15.9	.359	9.1	18	3.1	.30	7.6	5.2	23	.23	5.9	0.039	1.0	5.00	SPR	C	N
0.437	11.10	2517	.63	15.9	.343	8.7	30	5.2	.31	7.8	9.1	40	.28	7.2	0.047	1.2	6.00	SPR	CG	Z
0.437	11.10	G-78	.63	15.9	.325	8.3	114	20	.12	3.2	14	63	.24	6.0	0.056	1.4	4.25	SPR	CG	N
0.437	11.10	JJ-64	.66	16.7	.405	10.3	.28	.05	.54	14	.15	.66	.12	3.0	0.016	0.4	6.50	MW	C	Z
0.437	11.10	S-897	.66	16.7	.385	9.8	2.1	.36	.50	13	1.0	4.6	.16	4.0	0.026	0.7	6.00	SST	CG	N
0.437	11.10	A11-48	.66	16.7	.345	8.8	33	5.8	.24	6.2	8.0	36	.27	6.9	0.046	1.2	5.00	SST	C	N
0.437	11.10	A11-69	.69	17.4	.287	7.3	317	56	.10	2.5	31	140	.38	9.5	0.075	1.9	5.00	SPR	CG	Z
0.437	11.10	12513	.69	17.5	.337	8.6	48	8.4	.30	7.5	14	63	.31	8.0	0.050	1.3	5.25	MW	C	N
0.437	11.10	S-128	.75	19.1	.397	10.1	.68	.12	.61	15	.42	1.9	.14	3.6	0.020	0.5	6.00	SST	C	N

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS			ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm		MAT'L			
0.437	11.10	1563	.88	22.2	.383	9.7	2.2	.39	.69	17	1.5	6.8	.19	4.8	0.027	0.7	7.00	MW	CG	Z	
0.437	11.10	B11-62	.88	22.2	.383	9.7	2.2	.39	.66	17	1.5	6.5	.22	5.5	0.027	0.7	7.00	MW	C	N	
0.437	11.10	3988	.88	22.2	.375	9.5	1.6	.29	.41	10	.67	3.0	.47	11.8	0.031	0.8	14.0	MW	C	Z	
0.437	11.10	S-1283	.88	22.2	.363	9.2	10	1.8	.41	10	4.2	19	.20	5.2	0.037	0.9	5.50	SST	CG	N	
0.437	11.10	S-746	.88	22.2	.353	9.0	15	2.6	.42	11	6.1	27	.30	7.7	0.042	1.1	6.25	SST	C	N	
0.437	11.10	S-750	.88	22.2	.327	8.3	41	7.1	.31	7.9	13	56	.44	11.2	0.055	1.4	7.00	SST	C	N	
0.437	11.10	F-64	.88	22.2	.317	8.1	69	12	.25	6.4	17	77	.42	10.7	0.060	1.5	7.00	SPR	CG	Z	
0.437	11.10	UU-66	.88	22.2	.313	8.0	80	14	.24	6.1	19	85	.43	11.0	0.062	1.6	7.00	HD	CG	Z	
0.437	11.10	3212	.88	22.2	.293	7.4	158	28	.18	4.5	28	124	.50	12.8	0.072	1.8	7.00	SPR	CG	Z	
0.437	11.10	S-1352	.88	22.2	.277	7.0	223	39	.16	4.0	35	157	.56	14.2	0.080	2.0	7.00	SST	CG	N	
0.437	11.10	S-1374	.91	23.0	.343	8.7	21	3.8	.40	10	8.5	38	.32	8.1	0.047	1.2	6.75	SST	CG	N	
0.437	11.10	2582	.91	23.0	.327	8.3	43	7.5	.44	11	19	83	.41	10.5	0.055	1.4	7.50	MW	CG	Z	
0.437	11.10	HH-100	.91	23.0	.293	7.4	108	19	.24	6.2	26	116	.61	15.5	0.072	1.8	8.50	SST	CG	N	
0.437	11.10	A-74	.94	23.8	.397	10.1	.39	.07	.72	18	.28	1.3	.22	5.6	0.020	0.5	10.0	MW	C	BO	
0.437	11.10	A-99	.94	23.8	.387	9.8	1.2	.20	.74	19	.85	3.8	.20	5.1	0.025	0.6	8.00	SST	CG	N	
0.437	11.10	B10-3	.94	23.8	.373	9.5	4.5	.79	.67	17	3.1	14	.26	6.5	0.032	0.8	7.00	SPR	C	Z	
0.437	11.10	S-848	.94	23.8	.367	9.3	5.8	1.0	.61	16	3.6	16	.25	6.2	0.035	0.9	7.00	SST	CG	N	
0.437	11.10	U-63	.94	23.8	.353	9.0	14	2.5	.45	12	6.5	29	.29	7.5	0.042	1.1	7.00	SPR	CG	GI	
0.437	11.10	S-787	.97	24.6	.381	9.7	2.2	.39	.77	20	1.7	7.7	.20	5.0	0.028	0.7	7.00	SST	CG	N	
0.437	11.10	S-862	.97	24.6	.369	9.4	5.2	.91	.66	17	3.4	15	.27	6.8	0.034	0.9	7.00	SST	C	N	
0.437	11.10	10206	1.00	25.4	.397	10.1	.39	.07	.78	20	.31	1.4	.22	5.6	0.020	0.5	10.0	MW	C	Z	
0.437	11.10	S-1253	1.00	25.4	.389	9.9	1.5	.26	.83	21	1.2	5.4	.17	4.3	0.024	0.6	6.00	SST	C	N	
0.437	11.10	MM-78	1.00	25.4	.381	9.7	2.5	.43	.77	20	1.9	8.5	.21	5.3	0.028	0.7	6.50	SST	C	N	
0.437	11.10	1930	1.00	25.4	.377	9.6	3.5	.60	.76	19	2.6	12	.24	6.1	0.030	0.8	7.00	MW	C	Z	
0.437	11.10	3996	1.00	25.4	.371	9.4	6.4	1.1	.52	13	3.4	15	.20	5.0	0.033	0.8	6.00	SPR	CG	Z	
0.437	11.10	S-1059	1.00	25.4	.357	9.1	8.5	1.5	.63	16	5.3	24	.36	9.1	0.040	1.0	8.00	SST	C	N	
0.437	11.10	HH-35	1.00	25.4	.357	9.1	12	2.0	.46	12	5.3	24	.26	6.6	0.040	1.0	6.50	SST	CG	N	
0.437	11.10	S-747	1.00	25.4	.353	9.0	13	2.2	.49	12	6.1	27	.34	8.5	0.042	1.1	7.00	SST	C	N	
0.437	11.10	EE-82	1.00	25.4	.353	9.0	9.0	1.6	.54	14	4.8	22	.46	11.7	0.042	1.1	10.0	SPR	C	Z	
0.437	11.10	4151	1.00	25.4	.345	8.8	16	2.9	.52	13	8.5	38	.44	11.1	0.046	1.2	8.50	SPR	C	Z	
0.437	11.10	943	1.00	25.4	.343	8.7	23	4.1	.39	9.8	9.1	40	.38	9.6	0.047	1.2	7.00	HD	C	Z	
0.437	11.10	12657	1.00	25.4	.343	8.7	24	4.1	.53	14	13	56	.33	8.4	0.047	1.2	7.00	MW	CG	N	
0.437	11.10	10936	1.00	25.4	.327	8.3	34	5.9	.40	10	13	60	.50	12.6	0.055	1.4	9.00	SPR	CG	N	
0.437	11.10	S-751	1.00	25.4	.327	8.3	34	5.9	.37	9.5	13	56	.50	12.6	0.055	1.4	8.00	SST	C	N	
0.437	11.10	Z-87	1.00	25.4	.305	7.7	77	13	.28	7.1	22	96	.53	13.4	0.066	1.7	8.00	SST	CG	N	
0.437	11.10	J-19	1.00	25.4	.295	7.5	80	14	.29	7.4	23	104	.71	18.0	0.071	1.8	10.0	SST	CG	N	
0.437	11.10	10312	1.00	25.4	.293	7.4	132	23	.21	5.4	28	124	.65	16.5	0.072	1.8	8.00	SPR	C	Z	
0.437	11.10	A9-26	1.03	26.2	.397	10.1	.39	.07	.81	21	.32	1.4	.22	5.6	0.020	0.5	10.0	MW	C	BO	
0.437	11.10	B10-31	1.03	26.2	.355	9.0	8.7	1.5	.60	15	5.2	23	.43	10.9	0.041	1.0	9.50	SPR	C	N	
0.437	11.10	520	1.06	27.0	.355	9.0	11	2.0	.54	14	6.1	27	.36	9.1	0.041	1.0	7.75	HD	C	Z	
0.437	11.10	Q-41	1.06	27.0	.347	8.8	14	2.5	.53	14	7.5	33	.36	9.1	0.045	1.1	8.00	SST	CG	N	
0.437	11.10	3454	1.06	27.0	.313	8.0	53	9.3	.36	9.1	19	85	.59	15.0	0.062	1.6	9.50	HD	CG	Z	
0.437	11.10	509	1.06	27.0	.313	8.0	80	14	.24	6.1	19	85	.50	12.6	0.062	1.6	7.00	HD	C	Z	
0.437	11.10	3534	1.06	27.0	.311	7.9	78	14	.36	9.0	28	123	.47	12.0	0.063	1.6	7.50	MW	CG	Z	
0.437	11.10	10862	1.06	27.0	.295	7.5	110	19	.23	5.8	25	112	.64	16.2	0.071	1.8	8.00	SST	C	N	
0.437	11.10	10765	1.08	27.4	.369	9.4	3.6	.64	.74	19	2.7	12	.34	8.6	0.034	0.9	10.0	SPR	CG	Z	
0.437	11.10	10480	1.09	27.8	.393	10.0	1.3	.24	.95	24	1.3	5.7	.14	3.6	0.022	0.6	5.50	MW	C	N	
0.437	11.10	V-3	1.09	27.8	.377	9.6	3.1	.54	.77	19	2.4	10	.24	6.1	0.030	0.8	7.00	SST	C	N	
0.437	11.10	B15-70	1.09	27.8	.359	9.1	5.3	.92	.63	16	3.3	15	.47	11.9	0.039	1.0	12.0	SPR	CG	N	
0.437	11.10	S-1164	1.13	28.6	.377	9.6	3.0	.52	.79	20	2.4	10	.24	6.1	0.030	0.8	7.00	SST	C	N	
0.437	11.10	10762	1.13	28.6	.343	8.7	24	4.1	.38	9.8	9.1	40	.33	8.4	0.047	1.2	7.00	SPR	CG	Z	
0.437	11.10	B9-61	1.13	28.6	.343	8.7	19	3.3	.45	11	8.5	38	.40	10.1	0.047	1.2	7.50	SST	C	N	
0.437	11.10	11126	1.13	28.6	.307	7.8	100	17	.22	5.6	22	97	.52	13.2	0.065	1.7	7.00	SPR	C	Z	
0.437	11.10	J-60	1.13	28.6	.293	7.4	105	18	.27	6.8	28	124	.68	17.4	0.072	1.8	9.50	SPR	CG	Z	
0.437	11.10	12295	1.16	29.4	.345	8.8	12	2.1	.60	15	7.2	32	.55	14.0	0.046</						




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.437	11.10	3579	1.38	34.9	.311	7.9	53	9.3	.53	13	28	123	.64	16.2	0.063	1.6	10.1	MW	CG	Z
0.437	11.10	3830	1.38	34.9	.287	7.3	95	17	.33	8.4	31	140	.90	22.9	0.075	1.9	12.0	SPR	CG	GI
0.437	11.10	3184	1.41	35.7	.373	9.5	1.4	.24	.78	20	1.1	4.7	.62	15.8	0.032	0.8	18.5	SPR	C	Z
0.437	11.10	10495	1.41	35.7	.343	8.7	9.1	1.6	.65	17	5.9	26	.75	19.1	0.047	1.2	15.0	SPR	C	Z
0.437	11.10	B3-34	1.42	36.1	.293	7.4	79	14	.35	8.9	28	124	.86	21.9	0.072	1.8	12.0	SPR	CG	N
0.437	11.10	B10-66	1.44	36.5	.363	9.2	7.3	1.3	.61	16	4.5	20	.32	8.2	0.037	0.9	7.75	SPR	CG	Z
0.437	11.10	10249	1.44	36.5	.329	8.4	31	5.4	.41	10	13	57	.49	12.3	0.054	1.4	9.00	SPR	CG	N
0.437	11.10	A-55	1.44	36.5	.297	7.5	73	13	.35	9.0	26	115	.81	20.4	0.070	1.8	11.5	SPR	CG	N
0.437	11.10	J-24	1.50	38.1	.399	10.1	.44	.08	1.3	34	.60	2.7	.15	3.9	0.019	0.5	7.00	SST	C	N
0.437	11.10	1753	1.50	38.1	.397	10.1	.71	.12	1.4	34	.95	4.2	.15	3.8	0.020	0.5	6.50	MW	C	Z
0.437	11.10	12223	1.50	38.1	.365	9.3	5.8	1.0	.72	18	4.1	18	.31	7.8	0.036	0.9	8.50	SPR	CG	GI
0.437	11.10	S-749	1.50	38.1	.353	9.0	8.1	1.4	.76	19	6.1	27	.45	11.5	0.042	1.1	9.75	SST	C	N
0.437	11.10	S-1295	1.50	38.1	.349	8.9	10	1.8	.69	17	7.0	31	.42	10.6	0.044	1.1	9.50	SST	CG	N
0.437	11.10	A11-36	1.50	38.1	.347	8.8	13	2.3	.62	16	8.0	36	.43	10.9	0.045	1.1	9.50	SPR	CG	N
0.437	11.10	CC-10	1.50	38.1	.337	8.6	21	3.6	.49	13	10	45	.48	12.1	0.050	1.3	9.50	SPR	CG	N
0.437	11.10	S-753	1.50	38.1	.327	8.3	21	3.8	.59	15	13	56	.63	16.1	0.055	1.4	11.5	SST	CG	N
0.437	11.10	B11-54	1.50	38.1	.325	8.3	27	4.7	.53	13	14	63	.70	17.8	0.056	1.4	11.5	SPR	C	Z
0.437	11.10	10262	1.50	38.1	.293	7.4	88	15	.32	8.0	28	124	.79	20.1	0.072	1.8	11.0	SPR	CG	Z
0.437	11.10	3273	1.50	38.1	.253	6.4	262	46	.21	5.2	54	239	1.06	26.9	0.092	2.3	11.5	SPR	CG	Z
0.437	11.10	12423	1.56	39.7	.401	10.2	.46	.08	1.4	36	.65	2.9	.14	3.4	0.018	0.5	6.50	MW	C	GI
0.437	11.10	10129	1.56	39.7	.355	9.0	8.7	1.5	.70	18	6.1	27	.43	10.9	0.041	1.0	9.50	SPR	C	Z
0.437	11.10	10895	1.56	39.7	.345	8.8	11	1.9	.80	20	8.5	38	.60	15.2	0.046	1.2	12.0	SPR	C	Z
0.437	11.10	10232	1.63	41.3	.397	10.1	.63	.11	1.5	37	.93	4.1	.16	4.1	0.020	0.5	7.00	MW	C	Z
0.437	11.10	10126	1.63	41.3	.393	10.0	.94	.16	1.4	37	1.4	6.1	.18	4.5	0.022	0.6	7.00	MW	C	T
0.437	11.10	S-1379	1.63	41.3	.393	10.0	.63	.11	1.4	36	.89	3.9	.21	5.3	0.022	0.6	8.50	SST	C	N
0.437	11.10	OO-77	1.63	41.3	.337	8.6	12	2.1	.85	22	10	45	.75	19.1	0.050	1.3	15.0	SPR	CG	N
0.437	11.10	10752	1.66	42.1	.293	7.4	83	15	.34	8.6	28	124	.83	21.0	0.072	1.8	11.5	SPR	CG	GI
0.437	11.10	12428	1.69	42.8	.387	9.8	.94	.17	1.4	36	1.3	5.9	.29	7.3	0.025	0.6	10.5	MW	C	N
0.437	11.10	3123	1.69	42.8	.385	9.8	1.1	.19	1.4	35	1.5	6.8	.30	7.6	0.026	0.7	10.5	MW	C	GI
0.437	11.10	S-1274	1.69	42.8	.375	9.5	2.4	.43	1.1	27	2.6	12	.31	7.9	0.031	0.8	9.00	SST	C	N
0.437	11.10	B11-27	1.69	42.8	.337	8.6	39	6.8	.26	6.7	10	45	.30	7.6	0.050	1.3	6.00	SPR	CG	N
0.437	11.10	TT-56	1.69	42.8	.287	7.3	86	15	.36	9.2	31	140	.98	24.8	0.075	1.9	13.0	SPR	CG	Z
0.437	11.10	10767	1.75	44.5	.361	9.2	3.4	.59	1.1	29	3.8	17	.61	15.4	0.038	1.0	16.0	SPR	CG	N
0.437	11.10	4154	1.75	44.5	.287	7.3	79	14	.40	10	31	140	1.13	28.6	0.075	1.9	14.0	SPR	C	Z
0.437	11.10	10374	1.78	45.2	.267	6.8	146	26	.31	7.8	45	199	1.17	29.7	0.085	2.2	13.8	SPR	CG	Z
0.437	11.10	10389	1.81	46.0	.389	9.9	.82	.14	1.5	39	1.3	5.6	.27	6.9	0.024	0.6	10.3	MW	C	N
0.437	11.10	112	1.88	47.6	.369	9.4	3.1	.54	1.2	30	3.7	16	.43	10.8	0.034	0.9	11.5	HD	C	Z
0.437	11.10	4163	1.88	47.6	.357	9.1	6.5	1.1	.87	22	5.7	25	.48	12.2	0.040	1.0	11.0	SPR	C	Z
0.437	11.10	KK-78	1.88	47.6	.217	5.5	860	151	.10	2.5	85	378	.99	25.1	0.110	2.8	9.00	SPR	CG	Z
0.437	11.10	Q-49	1.94	49.2	.327	8.3	13	2.3	.85	22	11	50	1.09	27.6	0.055	1.4	19.8	SPR	CG	GI
0.437	11.10	3652	2.00	50.8	.375	9.5	1.4	.25	1.5	37	2.1	9.2	.53	13.4	0.031	0.8	16.0	HD	C	Z
0.437	11.10	S-854	2.00	50.8	.343	8.7	6.6	1.2	1.1	29	7.4	33	.87	22.1	0.047	1.2	17.5	SST	C	N
0.437	11.10	16	2.00	50.8	.329	8.4	16	2.8	.79	20	13	57	.89	22.6	0.054	1.4	15.5	HD	C	Z
0.437	11.10	S-1154	2.00	50.8	.329	8.4	14	2.5	.83	21	12	53	.86	21.9	0.054	1.4	15.0	SST	C	N
0.437	11.10	3553	2.00	50.8	.323	8.2	15	2.7	.86	22	13	58	1.14	29.0	0.057	1.4	20.0	MW	CG	Z
0.437	11.10	502	2.00	50.8	.293	7.4	52	9.0	.54	14	28	124	1.31	33.4	0.072	1.8	17.3	HD	C	Z
0.437	11.10	527	2.13	54.0	.375	9.5	2.0	.36	1.4	35	2.8	12	.39	10.0	0.031	0.8	11.8	HD	C	Z
0.437	11.10	2527	2.13	54.0	.353	9.0	6.0	1.1	1.1	27	6.5	29	.63	16.0	0.042	1.1	14.0	SPR	C	Z
0.437	11.10	4248	2.25	57.2	.389	9.9	.48	.08	1.8	47	.88	3.9	.41	10.4	0.024	0.6	16.0	MW	C	Z
0.437	11.10	13	2.25	57.2	.355	9.0	4.9	.86	1.2	31	6.1	27	.67	16.9	0.041	1.0	15.3	HD	C	Z
0.437	11.10	S-840	2.44	61.9	.297	7.5	33	5.8	.73	19	24	107	1.42	36.0	0.070	1.8	20.3	SST	CG	N
0.437	11.10	2816	2.47	62.7	.295	7.5	40	7.1	.93	24	37	167	1.44	36.5	0.071	1.8	20.3	MW	CG	Z
0.437	11.10	11334	2.50	63.5	.341	8.7	8.9	1.6	1.1	27	9.7	43	.84	21.3	0.048	1.2	16.5	HD	C	Z
0.437	11.10	11889	2.50	63.5	.313	8.0	26	4.6	.73	19	19	85	1.09	27.6	0.062	1.6	17.5	SPR	CG	Z
0.437	11.10	3728	2.50	63.5	.277	7.0	66	12	.57	15	38	168	1.72	43.7	0.080	2.0	21.5	SPR	CG	Z
0.437	11.10	12452	2.59	65.9	.341	8.7	7.2	1.3	1.3	34	9.7	43	.96	24.4	0.048	1.2	20.0	SPR	CG	N
0.437	11.10	10403	2.75	69.9	.375	9.5	1.3	.22	2.2	55	2.8	12	.57	14.6	0.031	0.8	17.5	MW	C	Z
0.437	11.10	11968	2.78	70.6	.325	8.3	13	2.4	1.1	27	14	63	1.23	31.3	0.056	1.4	21.0	SPR	C	Z
0.437	11.10	2552	2.88	73.0	.285	7.2	46	8.1	.70	18	33	145	1.82	46.3	0.076	1.9	24.0	SPR	CG	Z
0.437	11.10	4150	3.00	76.2	.343	8.7	9.0	1.6	1.0	26	9.1	40	.75	19.1	0.047	1.2	15.0	HD	C	Z
0.437	11.10	4152	3.13	79.4	.313	8.0	22	3.9	.86	22	19	85	1.30	33.1	0.062	1.6	20.0	HD	C	Z
0.437	11.10	3217	3.22	81.8	.293	7.4	32	5.5	.89	23	28	124	1.94	49.4	0.072	1.8	27.0	SPR	CG	Z
0.437	11.10	10180	3.38	85.7	.321	8.2	10	1.7	1.5	39	15	67	1.86	47.1	0.058	1.5	32.0	SPR	CG	Z
0.437	11.10	2965	3.44	87.3	.357	9.1	2.3	.41	2.3	59	5.4	24	1.12	28.4	0.040	1.0	27.0	MW	C	Z
0.437	11.10	3690	3.44	87.3	.323	8.2	8.6	1.5	1.5	38	13	57	1.94	49.2	0.057	1.4	34.0	SPR	CG	Z
0.437	11.10	1928	3.75	95.3	.297	7.5	35	6.1	.74	19	26	115	1.54	39.1	0.070	1.8	22.0	SPR	CG	Z
0.437	11.10	10089	3.75	95.3	.287	7.3	38	6.7	.83	21	31	140	2.03	51.4	0.075	1.9	27.0	SPR	CG	Z
0.437	11.10	12476	4.25	108.0	.289	7.3	28	4.9	1.1	27	30	134	2.59	65.8	0.074	1.9	34.0	SPR	C	Z
0.437	11.10	12085	5.00	127.0	.357	9.1	1.8	.32	3.1											

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.453	11.51	EE-15	.44	11.1	.383	9.7	10	1.8	.28	7.1	2.9	13	.16	4.0	0.035	0.9	4.50	SST	CG	N
0.453	11.51	S-272	.44	11.1	.379	9.6	22	3.8	.19	4.8	4.1	18	.13	3.3	0.037	0.9	3.50	SST	CG	N
0.453	11.51	EE-67	.44	11.1	.333	8.5	136	24	.12	2.9	16	70	.24	6.1	0.060	1.5	4.00	SST	CG	N
0.453	11.51	OO-78	.44	11.1	.325	8.3	178	31	.11	2.7	19	85	.26	6.5	0.064	1.6	4.00	SST	CG	N
0.453	11.51	B2-30	.45	11.5	.377	9.6	24	4.2	.27	6.9	6.5	29	.18	4.6	0.038	1.0	3.75	MW	C	N
0.453	11.51	B15-8	.47	11.9	.329	8.4	118	21	.16	4.0	18	82	.31	7.9	0.062	1.6	5.00	SPR	CG	N
0.453	11.51	A14-38	.50	12.7	.343	8.7	74	13	.17	4.2	12	54	.25	6.4	0.055	1.4	4.50	SST	CG	N
0.453	11.51	B1-6	.50	12.7	.341	8.7	90	16	.15	3.9	14	61	.25	6.4	0.056	1.4	4.50	SPR	CG	GI
0.453	11.51	RR-16	.50	12.7	.341	8.7	70	12	.20	5.0	14	61	.29	7.5	0.056	1.4	5.25	SPR	CG	N
0.453	11.51	K-80	.53	13.5	.383	9.7	12	2.1	.31	7.9	3.7	16	.16	4.0	0.035	0.9	4.50	SPR	CG	N
0.453	11.51	JJ-2	.53	13.5	.373	9.5	17	3.0	.31	8.0	5.5	24	.20	5.1	0.040	1.0	5.00	SPR	CG	N
0.453	11.51	12517	.56	14.3	.389	9.9	8.1	1.4	.39	9.8	3.1	14	.18	4.5	0.032	0.8	4.50	MW	C	Z
0.453	11.51	B1-31	.56	14.3	.363	9.2	35	6.1	.22	5.7	7.7	34	.20	5.1	0.045	1.1	4.50	SPR	CG	N
0.453	11.51	U-60	.56	14.3	.345	8.8	59	10	.21	5.3	12	55	.28	7.2	0.054	1.4	5.25	SPR	CG	N
0.453	11.51	1767	.56	14.3	.337	8.6	88	15	.24	6.1	21	94	.29	7.4	0.058	1.5	5.00	MW	CG	Z
0.453	11.51	S-1098	.56	14.3	.325	8.3	102	18	.19	4.8	19	85	.35	8.9	0.064	1.6	5.50	SST	CG	N
0.453	11.51	S-1472	.59	15.1	.379	9.6	13	2.3	.31	7.9	4.1	18	.20	5.2	0.037	0.9	4.50	SST	C	N
0.453	11.51	PP-93	.63	15.9	.397	10.1	2.6	.45	.42	11	1.1	4.7	.21	5.3	0.028	0.7	6.50	MW	C	N
0.453	11.51	N-105	.63	15.9	.391	9.9	5.1	.90	.47	12	2.4	11	.16	3.9	0.031	0.8	5.00	SST	CG	N
0.453	11.51	B10-67	.63	15.9	.381	9.7	17	2.9	.24	6.1	4.0	18	.14	3.7	0.036	0.9	4.00	SPR	CG	Z
0.453	11.51	K-40	.63	15.9	.377	9.6	15	2.6	.30	7.7	4.4	20	.17	4.3	0.038	1.0	4.50	SST	CG	N
0.453	11.51	B7-17	.63	15.9	.373	9.5	19	3.3	.29	7.3	5.5	24	.19	4.8	0.040	1.0	4.75	SPR	CG	Z
0.453	11.51	A14-42	.63	15.9	.367	9.3	18	3.1	.37	9.3	6.5	29	.26	6.6	0.043	1.1	6.00	SPR	CG	GI
0.453	11.51	A11-61	.66	16.7	.321	8.2	118	21	.19	4.8	22	99	.40	10.1	0.066	1.7	6.00	SPR	CG	Z
0.453	11.51	YY-66	.69	17.4	.417	10.6	.32	.06	.54	14	.17	.77	.14	3.7	0.018	0.5	7.00	SST	C	N
0.453	11.51	A14-30	.69	17.4	.377	9.6	12	2.2	.35	9.0	4.4	20	.19	4.8	0.038	1.0	5.00	SST	CG	N
0.453	11.51	B12-19	.72	18.2	.389	9.9	5.8	1.0	.51	13	2.9	13	.21	5.3	0.032	0.8	5.50	SPR	C	N
0.453	11.51	B14-49	.72	18.2	.369	9.4	21	3.8	.29	7.5	6.3	28	.21	5.3	0.042	1.1	5.00	SPR	CG	Z
0.453	11.51	S-3174	.75	19.1	.409	10.4	.46	.08	.51	13	.23	1.0	.24	6.1	0.022	0.6	10.0	SST	C	N
0.453	11.51	B14-54	.75	19.1	.381	9.7	8.4	1.5	.44	11	3.7	17	.20	5.0	0.036	0.9	5.50	SST	CG	N
0.453	11.51	A14-32	.75	19.1	.375	9.5	16	2.7	.32	8.2	5.1	23	.20	5.0	0.039	1.0	5.00	SPR	CG	N
0.453	11.51	10072	.75	19.1	.371	9.4	15	2.5	.40	10	5.9	26	.29	7.3	0.041	1.0	6.00	SPR	C	Z
0.453	11.51	A13-55	.75	19.1	.363	9.2	22	3.9	.33	8.4	7.2	32	.25	6.3	0.045	1.1	5.50	SST	CG	N
0.453	11.51	10227	.75	19.1	.351	8.9	30	5.2	.35	8.9	10	46	.36	9.1	0.051	1.3	7.00	SPR	CG	Z
0.453	11.51	3441	.75	19.1	.345	8.8	35	6.1	.29	7.4	10	45	.46	11.7	0.054	1.4	7.50	SPR	C	Z
0.453	11.51	10055	.75	19.1	.341	8.7	56	9.9	.24	6.2	14	61	.39	10.0	0.056	1.4	6.00	SPR	C	GI
0.453	11.51	FF-64	.75	19.1	.333	8.5	77	13	.22	5.6	17	75	.36	9.1	0.060	1.5	6.00	SPR	CG	N
0.453	11.51	1952	.78	19.8	.401	10.2	2.8	.49	.63	16	1.8	7.8	.16	4.0	0.026	0.7	5.00	MW	C	Z
0.453	11.51	M-144	.78	19.8	.389	9.9	3.3	.57	.51	13	1.7	7.4	.27	6.9	0.032	0.8	7.50	SST	C	N
0.453	11.51	B1-40	.78	19.8	.367	9.3	22	3.8	.31	7.8	6.8	30	.23	5.7	0.043	1.1	5.25	SPR	CG	N
0.453	11.51	S-1434	.81	20.6	.371	9.4	14	2.5	.38	9.7	5.5	24	.23	5.7	0.041	1.0	5.50	SST	CG	N
0.453	11.51	3907	.81	20.6	.345	8.8	32	5.6	.33	8.3	10	47	.49	12.3	0.054	1.4	8.00	SPR	C	Z
0.453	11.51	H-91	.88	22.2	.423	10.7	.06	.01	.64	16	.04	.16	.24	6.1	0.015	0.4	15.0	SST	C	N
0.453	11.51	12424	.88	22.2	.407	10.3	1.7	.30	.74	19	1.2	5.5	.14	3.5	0.023	0.6	5.00	MW	C	GI
0.453	11.51	S-1191	.88	22.2	.393	10.0	2.2	.39	.61	15	1.3	6.0	.27	6.9	0.030	0.8	8.00	SST	C	N
0.453	11.51	PP-24	.88	22.2	.393	10.0	1.3	.22	.46	12	.58	2.6	.42	10.7	0.030	0.8	14.0	MW	CG	N
0.453	11.51	LL-97	.88	22.2	.377	9.6	10	1.8	.42	11	4.4	20	.25	6.3	0.038	1.0	5.50	SST	C	N
0.453	11.51	10143	.88	22.2	.369	9.4	16	2.8	.39	10	6.3	28	.25	6.4	0.042	1.1	6.00	SPR	CG	Z
0.453	11.51	K-36	.88	22.2	.367	9.3	14	2.5	.47	12	6.8	30	.30	7.6	0.043	1.1	7.00	SPR	CG	Z
0.453	11.51	A11-34	.88	22.2	.363	9.2	20	3.6	.38	9.6	7.7	34	.28	7.1	0.045	1.1	6.25	SPR	CG	GI
0.453	11.51	A13-42	.88	22.2	.361	9.2	21	3.6	.38	9.6	7.7	34	.28	7.2	0.046	1.2	6.00	SST	CG	N
0.453	11.51	CC-35	.88	22.2	.353	9.0	27	4.8	.36	9.1	9.8	44	.40	10.2	0.050	1.3	7.00	SPR	C	Z
0.453	11.51	DD-22	.88	22.2	.353	9.0	24	4.3	.38	9.7	9.3	41	.35	8.9	0.050	1.3	7.00	SST	CG	N
0.453	11.51	QQ-70	.88	22.2	.351	8.9	25	4.4	.42	11	10	46	.41	10.4	0.051	1.3	8.00	SPR	CG	Z
0.453	11.51	A14-45	.88	22.2	.343	8.7	39	6.8	.31	8.0	12	54	.37	9.4	0.055	1.4	6.75	SST	CG	N
0.453	11.51	10746	.88	22.2	.329	8.4	53	9.2	.33	8.4	17	77	.50	12.6	0.062	1.6	8.00	SST	CG	N
0.453	11.51	1761	.91	23.0	.407	10.3	1.7	.30	.77	20	1.3	5.8	.14	3.5	0.023	0.6	5.00	MW	C	Z




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.453	11.51	A11-30	1.13	28.6	.361	9.2	18	3.1	.46	12	8.3	37	.34	8.6	0.046	1.2	7.25	SPR	CG	GI
0.453	11.51	H-34	1.13	28.6	.341	8.7	35	6.1	.39	10	14	61	.48	12.1	0.056	1.4	8.50	SPR	CG	GI
0.453	11.51	Z-39	1.19	30.2	.361	9.2	21	3.7	.37	9.3	7.7	34	.28	7.0	0.046	1.2	6.00	SST	CG	N
0.453	11.51	10346	1.19	30.2	.345	8.8	15	2.6	.32	8.2	4.8	21	.86	21.9	0.054	1.4	15.0	SPR	C	Z
0.453	11.51	J-22	1.19	30.2	.345	8.8	19	3.4	.54	14	10	46	.65	16.5	0.054	1.4	12.0	SPR	CG	N
0.453	11.51	B17-138	1.22	31.0	.367	9.3	11	2.0	.55	14	6.3	28	.32	8.2	0.043	1.1	7.50	SST	CG	N
0.453	11.51	B8-54	1.22	31.0	.329	8.4	53	9.2	.33	8.4	17	77	.56	14.2	0.062	1.6	8.00	SST	C	N
0.453	11.51	A14-60	1.25	31.8	.369	9.4	9.5	1.7	.62	16	5.9	26	.34	8.5	0.042	1.1	8.00	SST	CG	N
0.453	11.51	S-1278	1.25	31.8	.363	9.2	13	2.2	.58	15	7.2	32	.41	10.3	0.045	1.1	8.00	SST	C	N
0.453	11.51	A11-41	1.25	31.8	.359	9.1	17	3.1	.50	13	8.8	39	.38	9.6	0.047	1.2	8.00	SPR	CG	GI
0.453	11.51	CC-93	1.25	31.8	.353	9.0	16	2.8	.57	14	9.3	41	.48	12.1	0.050	1.3	9.50	SST	CG	N
0.453	11.51	BB-81	1.25	31.8	.351	8.9	16	2.8	.60	15	9.8	44	.51	13.0	0.051	1.3	10.0	SST	CG	N
0.453	11.51	OO-80	1.25	31.8	.333	8.5	38	6.7	.44	11	17	75	.60	15.2	0.060	1.5	10.0	SPR	CG	N
0.453	11.51	A14-27	1.25	31.8	.309	7.8	69	12	.37	9.4	25	113	.79	20.1	0.072	1.8	11.0	SST	CG	N
0.453	11.51	12414	1.28	32.5	.399	10.1	1.3	.24	1.0	26	1.4	6.1	.26	6.5	0.027	0.7	8.50	SST	C	N
0.453	11.51	12434	1.28	32.5	.395	10.0	2.1	.36	1.0	26	2.1	9.2	.28	7.0	0.029	0.7	8.50	MW	C	N
0.453	11.51	S-1601	1.28	32.5	.365	9.3	12	2.0	.58	15	6.8	30	.40	10.1	0.044	1.1	8.00	SST	CG	N
0.453	11.51	WW-42	1.28	32.5	.273	6.9	263	46	.19	4.7	49	219	.86	21.7	0.090	2.3	9.50	SPR	CG	Z
0.453	11.51	12651	1.31	33.3	.407	10.3	.88	.15	1.1	29	.99	4.4	.18	4.7	0.023	0.6	7.00	SST	C	N
0.453	11.51	A11-70	1.31	33.3	.293	7.4	123	21	.30	7.6	37	163	.90	22.9	0.080	2.0	11.3	SPR	CG	Z
0.453	11.51	2849	1.34	34.1	.405	10.3	.81	.14	1.1	28	.88	3.9	.25	6.4	0.024	0.6	9.50	MW	C	Z
0.453	11.51	S-245	1.38	34.9	.361	9.2	13	2.3	.58	15	7.7	34	.38	9.6	0.046	1.2	8.25	SST	CG	N
0.453	11.51	3640	1.38	34.9	.345	8.8	26	4.5	.48	12	12	55	.51	13.0	0.054	1.4	9.50	SPR	CG	Z
0.453	11.51	S-453	1.38	34.9	.343	8.7	23	4.1	.52	13	12	54	.54	13.6	0.055	1.4	9.75	SST	CG	N
0.453	11.51	S-480	1.41	35.7	.363	9.2	6.9	1.2	.82	21	5.6	25	.59	14.9	0.045	1.1	13.0	SST	CG	N
0.453	11.51	S-386	1.44	36.5	.369	9.4	6.8	1.2	.87	22	5.9	26	.43	10.9	0.042	1.1	10.3	SST	CG	N
0.453	11.51	B1-58	1.47	37.3	.375	9.5	7.2	1.3	.70	18	5.1	23	.33	8.4	0.039	1.0	8.50	SPR	CG	N
0.453	11.51	10406	1.50	38.1	.419	10.6	.13	.02	1.3	32	.16	.71	.23	5.7	0.017	0.4	12.3	SST	C	N
0.453	11.51	3610	1.50	38.1	.405	10.3	1.1	.19	1.3	33	1.4	6.3	.20	5.2	0.024	0.6	7.50	MW	C	T
0.453	11.51	10116	1.50	38.1	.403	10.2	1.4	.25	1.3	33	1.9	8.3	.20	5.1	0.025	0.6	7.00	MW	C	BO
0.453	11.51	S-264	1.50	38.1	.395	10.0	1.8	.31	1.2	29	2.1	9.1	.28	7.0	0.029	0.7	8.50	SST	C	N
0.453	11.51	B14-12	1.50	38.1	.379	9.6	5.1	.89	.80	20	4.1	18	.31	8.0	0.037	0.9	8.50	SST	CG	N
0.453	11.51	10879	1.50	38.1	.377	9.6	5.7	1.0	.77	20	4.4	20	.32	8.2	0.038	1.0	8.50	SST	CG	N
0.453	11.51	LL-14	1.50	38.1	.373	9.5	7.5	1.3	.73	19	5.5	24	.36	9.1	0.040	1.0	9.00	SPR	CG	GI
0.453	11.51	10018	1.50	38.1	.363	9.2	12	2.0	.67	17	7.7	34	.47	12.0	0.045	1.1	9.50	SPR	C	Z
0.453	11.51	K-11	1.50	38.1	.363	9.2	12	2.1	.65	16	7.7	34	.42	10.6	0.045	1.1	9.25	SPR	CG	N
0.453	11.51	11346	1.50	38.1	.363	9.2	11	1.9	.68	17	7.2	32	.42	10.6	0.045	1.1	9.25	SST	CG	N
0.453	11.51	Z-64	1.50	38.1	.349	8.9	18	3.2	.61	15	11	49	.62	15.8	0.052	1.3	11.0	SPR	C	GI
0.453	11.51	B14-39	1.50	38.1	.347	8.8	18	3.2	.59	15	11	49	.56	14.1	0.053	1.3	10.5	SST	CG	N
0.453	11.51	10144	1.50	38.1	.343	8.7	24	4.2	.55	14	13	58	.59	15.0	0.055	1.4	10.8	SPR	CG	Z
0.453	11.51	S-875	1.50	38.1	.343	8.7	22	3.8	.56	14	12	54	.57	14.4	0.055	1.4	10.3	SST	CG	N
0.453	11.51	B1-37	1.53	38.9	.367	9.3	10	1.8	.68	17	6.8	30	.44	11.1	0.043	1.1	9.00	SPR	C	N
0.453	11.51	S-1349	1.56	39.7	.407	10.3	.52	.09	1.3	34	.68	3.0	.24	6.1	0.023	0.6	10.5	SST	CG	N
0.453	11.51	K-51	1.63	41.3	.345	8.8	20	3.5	.61	15	12	55	.62	15.8	0.054	1.4	11.5	SPR	CG	N
0.453	11.51	3775	1.69	42.8	.329	8.4	42	7.3	.44	11	18	82	.71	18.1	0.062	1.6	10.5	HD	C	Z
0.453	11.51	12241	1.69	42.8	.329	8.4	39	6.9	.47	12	18	82	.74	18.9	0.062	1.6	11.0	SPR	C	Z
0.453	11.51	S-97	1.69	42.8	.293	7.4	126	22	.27	6.9	34	153	.88	22.4	0.080	2.0	10.0	SST	C	N
0.453	11.51	B-61	1.75	44.5	.329	8.4	32	5.7	.57	15	18	82	.87	22.0	0.062	1.6	13.0	HD	C	Z
0.453	11.51	S-67	1.78	45.2	.369	9.4	8.2	1.4	.72	18	5.9	26	.42	10.7	0.042	1.1	9.00	SST	C	N
0.453	11.51	S-1486	1.81	46.0	.363	9.2	6.3	1.1	1.2	29	7.2	32	.63	16.0	0.045	1.1	14.0	SST	CG	N
0.453	11.51	10922	1.81	46.0	.309	7.8	50	8.7	.54	14	27	120	1.15	29.3	0.072	1.8	16.0	SPR	CG	Z
0.453	11.51	S-811	1.88	47.6	.385	9.8	2.2	.38	1.5	37	3.1	14	.43	10.8	0.034	0.9	12.5	SST	CG	N
0.453	11.51	11887	1.88	47.6	.355	9.0	12	2.1	.83	21	9.9	44	.66	16.8	0.049	1.2	12.5	SPR	C	Z
0.453	11.51	B17-169	1.88	47.6	.329	8.4	25	4.4	.73	18	18	82	.99	25.2	0.062	1.6	16.0	SPR	CG	Z
0.453	11.51	B-25	1.94	49.2	.379	9.6	3.7	.66	1.2	29	4.3	19	.44	11.3	0.037	0.9	12.0	HD	CG	N
0.453	11.51	HH-75	1.94	49.2	.373	9.5	3.9	.68	1.3	33	5.1	23	.62	15.7	0.040	1.0	15.5	SPR	CG	GI
0.453	11.51	11743	2.00	50.8	.345	8.8	13	2.2	.96	24	12	55	.86	21.9	0.054	1.4	15.0	SPR	O	Z
0.453	11.51	10330	2.13	54.0	.345	8.8	14	2.5	.88	22	12	55	.91	23.0	0.054	1.4	15.8	SPR	C	Z
0.453	11.51	3798	2.25	57.2	.269	6.8	219	38	.24	6.1	52	232	1.10	28.0	0.092	2.3	12.0	SPR	CG	Z
0.453	11.51	Z-28	2.34	59.5	.375	9.5	3.6	.63	1.4	36	5.1	23	.59	14.9	0.039	1.0	15.0	SPR	CG	Z
0.453	11.51	11538	2.47	62.7	.353	9.0	11	1.9	.90	23	9.8	44	.78	19.7	0.050	1.3	14.5	SPR	CG	Z
0.453	11.51	12377	2.50	63.5	.357	9.1	7.9	1.4	1.2	30	9.4	42	.84	21.3	0.048	1.2	16.5	SPR	C	Z
0.453	11.51	V-58	2.50	63.5	.355	9.0	11	2.0	.89	23	9.9	44	.65	16.5	0.049	1.2	13.3	SPR	CG	Z
0.453	11.51	4107	2.50	63.5	.353	9.0	9.8	1.7	1.0	26	9.8	44	.85	21.6	0.050	1.3	16.0	SPR	C	Z
0.453	11.51	2878	2.50	63.5	.289	7.3	85	15	.46	12	39	175	1.39	35.4	0.082	2.1	17.0	SPR	CG	Z
0.453	11.51	3684	2.53	64.3	.265	6.7	125	22	.44	11	56	247	2.01	50.9	0.094	2.4	21.0	SPR	CG	GI
0.453	11.51	W-40	2.63	66.7	.359	9.1	5.1	.89	1.6	41	8.2	37	.94	23.9	0.047	1.2	20.0	SST	CG	N
0.453	11.51	11990	2.72	69.0	.373	9.5	3.1	.54	1.8	45	5.5	24	.76	19.3	0.040	1.0	19.0	SPR	CG	GI
0.453	11.51	11817	2.75	69.9	.363	9.2	4.6	.80	1.7	43	7.7	34	.95							

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.455	11.56	71456S	.63	16.0	.363	9.2	27	4.7	.28	7.2	7.7	34	.23	5.8	0.046	1.2	5.00	SST	CG	N
0.455	11.56	71447	.75	19.1	.377	9.6	14	2.5	.49	12	7.0	31	.20	5.2	0.039	1.0	5.25	MW	CG	N
0.455	11.56	71447S	.75	19.1	.377	9.6	12	2.1	.39	9.9	4.7	21	.20	5.2	0.039	1.0	5.25	SST	CG	N
0.455	11.56	71457	.75	19.1	.363	9.2	26	4.5	.44	11	11	51	.26	6.6	0.046	1.2	5.63	MW	CG	N
0.455	11.56	71457S	.75	19.1	.363	9.2	22	3.8	.35	9.0	7.7	34	.26	6.6	0.046	1.2	5.63	SST	CG	N
0.455	11.56	71448	.88	22.4	.377	9.6	12	2.1	.58	15	7.0	31	.22	5.7	0.039	1.0	5.75	MW	CG	N
0.455	11.56	71448S	.88	22.4	.377	9.6	10	1.8	.46	12	4.7	21	.22	5.7	0.039	1.0	5.75	SST	CG	N
0.455	11.56	71458	.88	22.4	.363	9.2	21	3.8	.53	13	11	51	.29	7.4	0.046	1.2	6.38	MW	CG	N
0.455	11.56	71458S	.88	22.4	.363	9.2	18	3.2	.42	11	7.7	34	.29	7.4	0.046	1.2	6.38	SST	CG	N
0.455	11.56	71449	1.00	25.4	.377	9.6	11	1.8	.66	17	7.0	31	.25	6.3	0.039	1.0	6.38	MW	CG	N
0.455	11.56	71449S	1.00	25.4	.377	9.6	9.0	1.6	.53	13	4.7	21	.25	6.3	0.039	1.0	6.38	SST	CG	N
0.455	11.56	71459	1.00	25.4	.363	9.2	19	3.3	.61	16	11	51	.32	8.2	0.046	1.2	7.00	MW	CG	N
0.455	11.56	71459S	1.00	25.4	.363	9.2	16	2.8	.49	12	7.7	34	.32	8.2	0.046	1.2	7.00	SST	CG	N
0.455	11.56	71450	1.25	31.8	.377	9.6	8.2	1.4	.85	22	7.0	31	.30	7.6	0.039	1.0	7.63	MW	CG	N
0.455	11.56	71450S	1.25	31.8	.377	9.6	7.0	1.2	.68	17	4.7	21	.30	7.6	0.039	1.0	7.63	SST	CG	N
0.455	11.56	71460	1.25	31.8	.363	9.2	15	2.5	.78	20	11	51	.39	9.9	0.046	1.2	8.50	MW	CG	N
0.455	11.56	71460S	1.25	31.8	.363	9.2	12	2.2	.62	16	7.7	34	.39	9.9	0.046	1.2	8.50	SST	CG	N
0.455	11.56	71451	1.50	38.1	.377	9.6	6.8	1.2	1.0	26	7.0	31	.35	8.8	0.039	1.0	8.88	MW	CG	N
0.455	11.56	71451S	1.50	38.1	.377	9.6	5.7	1.0	.82	21	4.7	21	.35	8.8	0.039	1.0	8.88	SST	CG	N
0.455	11.56	71461	1.50	38.1	.363	9.2	12	2.1	.95	24	11	51	.45	11.5	0.046	1.2	9.88	MW	CG	N
0.455	11.56	71461S	1.50	38.1	.363	9.2	10	1.8	.76	19	7.7	34	.45	11.5	0.046	1.2	9.88	SST	CG	N
0.455	11.56	71452	1.75	44.5	.377	9.6	5.8	1.0	1.2	31	7.0	31	.39	9.9	0.039	1.0	10.0	MW	CG	N
0.455	11.56	71452S	1.75	44.5	.377	9.6	4.9	.86	.97	25	4.7	21	.39	9.9	0.039	1.0	10.0	SST	CG	N
0.455	11.56	71462	1.75	44.5	.363	9.2	10	1.8	1.1	28	11	51	.52	13.1	0.046	1.2	11.3	MW	CG	N
0.455	11.56	71462S	1.75	44.5	.363	9.2	8.7	1.5	.89	22	7.7	34	.52	13.1	0.046	1.2	11.3	SST	CG	N
0.455	11.56	71454	2.00	50.8	.377	9.6	5.5	.96	1.3	32	7.0	31	.40	10.3	0.039	1.0	10.4	MW	CG	N
0.455	11.56	71454S	2.00	50.8	.377	9.6	4.7	.82	1.0	26	4.7	21	.40	10.3	0.039	1.0	10.4	SST	CG	N
0.455	11.56	71464	2.00	50.8	.363	9.2	9.5	1.7	1.2	30	11	51	.55	13.9	0.046	1.2	11.9	MW	CG	N
0.455	11.56	71464S	2.00	50.8	.363	9.2	8.1	1.4	.95	24	7.7	34	.55	13.9	0.046	1.2	11.9	SST	CG	N
0.468	11.89	S-864	.25	6.4	.378	9.6	69	12	.10	2.6	7.0	31	.14	3.4	0.045	1.1	3.00	SST	CG	N
0.468	11.89	DD-28	.31	7.9	.288	7.3	1549	271	.03	.73	44	197	.27	6.9	0.090	2.3	3.00	SST	CG	N
0.468	11.89	A10-53	.34	8.7	.436	11.1	.45	.08	.26	6.7	.12	.53	.08	2.0	0.016	0.4	4.00	SST	C	N
0.468	11.89	PP-57	.44	11.1	.388	9.9	17	2.9	.26	6.6	4.3	19	.18	4.6	0.040	1.0	4.50	SST	CG	N
0.468	11.89	I-99	.44	11.1	.356	9.0	202	35	.07	1.7	13	59	.17	4.3	0.056	1.4	3.00	SPR	CG	Z
0.468	11.89	S-1409	.50	12.7	.410	10.4	6.0	1.0	.33	8.5	2.0	8.9	.11	2.8	0.029	0.7	3.75	SST	CG	N
0.468	11.89	G-42	.50	12.7	.348	8.8	159	28	.10	2.4	15	68	.21	5.3	0.060	1.5	3.50	SST	CG	N
0.468	11.89	MM-87	.50	12.7	.344	8.7	106	19	.17	4.3	18	80	.31	7.9	0.062	1.6	5.00	HD	CG	N
0.468	11.89	OO-51	.53	13.5	.408	10.4	2.5	.43	.32	8.2	.79	3.5	.21	5.3	0.030	0.8	7.00	SST	CG	N
0.468	11.89	S-35	.53	13.5	.392	10.0	13	2.3	.32	8.1	4.3	19	.21	5.3	0.038	1.0	4.50	SST	C	N
0.468	11.89	3638	.53	13.5	.344	8.7	127	22	.20	5.0	25	111	.28	7.1	0.062	1.6	4.50	MW	CG	Z
0.468	11.89	3800	.56	14.3	.384	9.8	39	6.8	.16	4.0	6.1	27	.19	4.8	0.042	1.1	3.50	SPR	C	Z
0.468	11.89	B17-148	.59	15.1	.400	10.2	12	2.1	.29	7.4	3.4	15	.14	3.5	0.034	0.9	4.00	SPR	CG	Z
0.468	11.89	S-812	.59	15.1	.398	10.1	5.9	1.0	.35	8.8	2.1	9.1	.25	6.2	0.035	0.9	6.00	SST	C	N
0.468	11.89	S-3130	.63	15.9	.422	10.7	1.3	.23	.49	12	.64	2.9	.14	3.5	0.023	0.6	5.00	SST	C	N
0.468	11.89	S-3006	.63	15.9	.420	10.7	1.6	.28	.48	12	.76	3.4	.14	3.7	0.024	0.6	5.00	SST	C	N
0.468	11.89	A15-37	.63	15.9	.414	10.5	4.5	.79	.36	9.1	1.6	7.2	.13	3.3	0.027	0.7	3.75	SST	C	N
0.468	11.89	I-7	.63	15.9	.398	10.1	9.2	1.6	.36	9.2	3.3	15	.19	4.9	0.035	0.9	4.50	SST	C	N
0.468	11.89	A10-40	.69	17.4	.410	10.4	3.3	.57	.51	13	1.7	7.4	.18	4.6	0.029	0.7	5.25	SST	C	N
0.468	11.89	3877	.69	17.4	.400	10.2	7.8	1.4	.44	11	3.4	15	.20	5.2	0.034	0.9	5.00	SPR	C	Z
0.468	11.89	L-41	.69	17.4	.382	9.7	21	3.7	.31	7.8	6.6	29	.22	5.5	0.043	1.1	5.00	SPR	CG	Z
0.468	11.89	I-91	.72	18.2	.392	10.0	6.1	1.1	.43	11	2.6	12	.29	7.2	0.038	1.0	7.50	SST	CG	N
0.468	11.89	S-451	.72	18.2	.358	9.1	47	8.3	.25	6.4	12	53	.30	7.7	0.055	1.4	5.50	SST	CG	N
0.468	11.89	S-1091	.72	18.2	.340	8.6	71	12	.26	6.7	19	82	.42	10.6	0.064	1.6	6.50	SST	CG	N
0.468	11.89	K-32	.75	19.1	.408	10.4	4.0	.69	.56	14	2.2	9.8	.20	5.0	0.030	0.8	5.50	MW	C	Z
0.468	11.89	B14-70	.75	19.1	.390	9.9	12	2.1	.41	10	4.9	22	.21	5.4	0.039	1.0	5.50	SPR	CG	Z
0.468	11.89	CC-55	.75	19.1	.384	9.8	13	2.2	.46	12	5.7	25	.25	6.4	0.042	1.1	6.00	SST	CG	N
0.468	11.89	3203	.78	19.8	.416	10.6	2.8	.48	.63	16	1.7</									




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS			E N D S	F N D H
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm					
0.468	11.89	10258	.97	24.6	.324	8.2	104	18	.25	6.4	26	117	.58	14.6	0.072	1.8	8.00	SPR	CG	Z	
0.468	11.89	3515	.97	24.6	.276	7.0	474	83	.12	3.1	57	255	.67	17.1	0.096	2.4	7.00	SPR	CG	Z	
0.468	11.89	1511	1.00	25.4	.410	10.4	2.2	.38	.75	19	1.6	7.3	.25	6.3	0.029	0.7	7.50	MW	C	Z	
0.468	11.89	2598	1.00	25.4	.408	10.4	2.5	.44	.75	19	1.9	8.3	.26	6.5	0.030	0.8	7.50	MW	C	Z	
0.468	11.89	2934	1.00	25.4	.408	10.4	3.2	.55	.78	20	2.5	11	.22	5.6	0.030	0.8	6.25	MW	C	Z	
0.468	11.89	PP-60	1.00	25.4	.408	10.4	2.8	.50	.76	19	2.2	9.7	.24	6.0	0.030	0.8	7.00	MW	C	N	
0.468	11.89	S-3144	1.00	25.4	.394	10.0	7.8	1.4	.50	13	3.9	18	.21	5.4	0.037	0.9	5.75	SST	CG	N	
0.468	11.89	S-1344	1.00	25.4	.386	9.8	10	1.8	.53	13	5.3	24	.31	7.8	0.041	1.0	6.50	SST	C	N	
0.468	11.89	3504	1.00	25.4	.358	9.1	34	5.9	.37	9.5	13	56	.41	10.5	0.055	1.4	7.50	SPR	CG	Z	
0.468	11.89	S-3079	1.00	25.4	.344	8.7	46	8.1	.37	9.3	17	75	.56	14.2	0.062	1.6	8.00	SST	C	N	
0.468	11.89	3708	1.00	25.4	.338	8.6	71	12	.29	7.3	21	92	.49	12.4	0.065	1.7	7.50	SPR	CG	Z	
0.468	11.89	PP-20	1.00	25.4	.328	8.3	100	17	.24	6.2	24	108	.53	13.3	0.070	1.8	7.50	SPR	CG	Z	
0.468	11.89	10780	1.03	26.2	.398	10.1	2.6	.46	.65	16	1.7	7.5	.39	9.8	0.035	0.9	11.0	SST	CG	N	
0.468	11.89	NN-51	1.03	26.2	.368	9.3	18	3.1	.54	14	9.6	42	.45	11.4	0.050	1.3	9.00	SPR	CG	Z	
0.468	11.89	A11-12	1.06	27.0	.408	10.4	2.5	.43	.85	22	2.1	9.3	.21	5.3	0.030	0.8	7.00	SST	CG	N	
0.468	11.89	EE-92	1.06	27.0	.374	9.5	21	3.7	.41	10	8.5	38	.31	7.8	0.047	1.2	6.50	SPR	CG	Z	
0.468	11.89	10641	1.06	27.0	.344	8.7	71	12	.25	6.5	18	80	.40	10.2	0.062	1.6	6.50	SPR	CG	N	
0.468	11.89	3962	1.06	27.0	.258	6.6	552	97	.12	3.1	68	304	.81	20.7	0.105	2.7	7.75	SST	CG	N	
0.468	11.89	A10-29	1.09	27.8	.398	10.1	3.1	.55	.76	19	2.4	11	.33	8.4	0.035	0.9	9.50	SST	CG	N	
0.468	11.89	2981	1.09	27.8	.324	8.2	89	16	.30	7.5	26	117	.65	16.5	0.072	1.8	9.00	SPR	CG	Z	
0.468	11.89	10421	1.11	28.2	.296	7.5	217	38	.20	5.1	44	195	.73	18.6	0.086	2.2	8.50	SPR	CG	Z	
0.468	11.89	Z-44	1.13	28.6	.398	10.1	6.6	1.2	.54	14	3.6	16	.25	6.2	0.035	0.9	6.00	SPR	C	Z	
0.468	11.89	S-488	1.13	28.6	.394	10.0	5.9	1.0	.67	17	3.9	18	.30	7.5	0.037	0.9	7.00	SST	C	N	
0.468	11.89	HH-88	1.13	28.6	.378	9.6	9.7	1.7	.63	16	6.1	27	.50	12.6	0.045	1.1	10.0	SPR	C	Z	
0.468	11.89	AA-78	1.13	28.6	.368	9.3	15	2.7	.58	15	8.8	39	.55	14.0	0.050	1.3	10.0	SPR	C	Z	
0.468	11.89	3591	1.13	28.6	.348	8.8	46	8.0	.49	13	23	101	.48	12.2	0.060	1.5	8.00	MW	CG	Z	
0.468	11.89	S-1341	1.13	28.6	.324	8.2	77	14	.32	8.1	25	110	.65	16.5	0.072	1.8	9.00	SST	CG	N	
0.468	11.89	B3-33	1.16	29.4	.408	10.4	2.3	.40	.89	23	2.0	9.1	.27	6.9	0.030	0.8	8.00	MW	C	N	
0.468	11.89	11770	1.16	29.4	.404	10.3	2.3	.40	.84	21	1.9	8.5	.32	8.1	0.032	0.8	10.0	SPR	CG	Z	
0.468	11.89	Y-56	1.16	29.4	.338	8.6	52	9.2	.37	9.4	19	86	.55	14.0	0.065	1.7	8.50	SST	CG	N	
0.468	11.89	11376	1.19	30.2	.374	9.5	19	3.2	.43	11	8.0	36	.31	7.8	0.047	1.2	6.50	SST	CG	N	
0.468	11.89	QQ-65	1.19	30.2	.352	8.9	30	5.2	.50	13	15	66	.58	14.7	0.058	1.5	10.0	SPR	CG	Z	
0.468	11.89	2720	1.19	30.2	.282	7.2	340	60	.22	5.5	73	326	.74	18.9	0.093	2.4	8.00	MW	CG	Z	
0.468	11.89	10470	1.19	30.2	.264	6.7	508	89	.13	3.4	68	302	.84	21.4	0.102	2.6	8.25	SPR	CG	Z	
0.468	11.89	A-25	1.22	31.0	.368	9.3	14	2.5	.66	17	9.6	42	.53	13.3	0.050	1.3	10.5	SPR	CG	N	
0.468	11.89	N-56	1.22	31.0	.362	9.2	21	3.7	.54	14	11	50	.50	12.8	0.053	1.3	9.50	SPR	CG	Z	
0.468	11.89	M-111	1.22	31.0	.360	9.1	23	4.0	.52	13	12	53	.51	13.0	0.054	1.4	9.50	SPR	CG	Z	
0.468	11.89	Z-50	1.25	31.8	.436	11.1	.06	.01	.92	23	.05	.24	.33	8.3	0.016	0.4	19.5	MW	C	Z	
0.468	11.89	10097	1.25	31.8	.398	10.1	6.6	1.2	.54	14	3.6	16	.25	6.2	0.035	0.9	6.00	SPR	C	Z	
0.468	11.89	L-42	1.25	31.8	.386	9.8	5.0	.87	.74	19	3.7	16	.51	13.0	0.041	1.0	12.5	MW	CG	Z	
0.468	11.89	F-55	1.25	31.8	.378	9.6	9.7	1.7	.77	20	7.5	33	.45	11.4	0.045	1.1	10.0	SPR	CG	GI	
0.468	11.89	TT-54	1.25	31.8	.378	9.6	8.2	1.4	.69	17	5.6	25	.56	14.3	0.045	1.1	11.5	SPR	C	Z	
0.468	11.89	KK-77	1.25	31.8	.378	9.6	11	1.9	.65	16	7.0	31	.37	9.4	0.045	1.1	8.25	SST	CG	N	
0.468	11.89	RR-67	1.25	31.8	.370	9.4	11	1.9	.71	18	7.7	34	.54	13.7	0.049	1.2	11.0	SST	CG	N	
0.468	11.89	S-1697	1.25	31.8	.368	9.3	15	2.7	.59	15	9.0	40	.45	11.4	0.050	1.3	9.00	SST	CG	N	
0.468	11.89	3086	1.25	31.8	.344	8.7	45	7.9	.40	10	18	80	.56	14.2	0.062	1.6	9.00	SPR	CG	Z	
0.468	11.89	10555	1.25	31.8	.292	7.4	180	31	.26	6.6	47	208	.95	24.0	0.088	2.2	10.8	SPR	CG	Z	
0.468	11.89	S-1167	1.28	32.5	.394	10.0	6.9	1.2	.57	15	3.9	18	.27	6.8	0.037	0.9	6.25	SST	C	N	
0.468	11.89	10696	1.31	33.3	.386	9.8	6.7	1.2	.85	22	5.7	25	.40	10.2	0.041	1.0	9.75	SPR	CG	Z	
0.468	11.89	A13-65	1.31	33.3	.372	9.4	10	1.7	.72	18	7.2	32	.59	15.0	0.048	1.2	12.3	SPR	CG	N	
0.468	11.89	B8-57	1.31	33.3	.288	7.3	249	44	.19	4.9	48	213	.81	20.6	0.090	2.3	9.00	SPR	CG	Z	
0.468	11.89	12470	1.31	33.3	.284	7.2	323	57	.16	4.0	51	226	.74	18.7	0.092	2.3	8.00	SPR	CG	Z	
0.468	11.89	3966	1.38	34.9	.414	10.5	1.3	.23	1.1	29	1.5	6.7	.24	6.0	0.027	0.7	8.75	MW	CG	Z	
0.468	11.89	10855	1.38	34.9	.408	10.4	1.9	.33	1.1	28	2.1	9.2	.29	7.2	0.030	0.8	8.50	SST	C	N	
0.468	11.89	S-1447	1.38	34.9	.392	10.0	5.7	1.0	.75	19	4.3	19	.29	7.5	0.038</						

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L		E N D S	F I N I S H
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm					
0.468	11.89	1893	1.75	44.5	.318	8.1	68	12	.61	15	41	184	.98	24.8	0.075	1.9	13.0	MW	CG	GI	
0.468	11.89	3554	1.75	44.5	.248	6.3	417	73	.27	6.9	113	503	1.43	36.3	0.110	2.8	13.0	MW	CG	Z	
0.468	11.89	S-65	1.78	45.2	.322	8.2	59	10	.44	11	26	114	.95	24.1	0.073	1.9	12.0	SST	C	N	
0.468	11.89	A13-38	1.80	45.6	.358	9.1	22	3.9	.54	14	12	53	.52	13.3	0.055	1.4	9.50	SST	CG	N	
0.468	11.89	S-918	1.81	46.0	.398	10.1	3.3	.58	1.0	26	3.3	15	.35	8.9	0.035	0.9	9.00	SST	C	N	
0.468	11.89	RR-37	1.81	46.0	.324	8.2	57	9.9	.65	17	37	163	.94	23.8	0.072	1.8	13.0	MW	CG	Z	
0.468	11.89	3714	1.94	49.2	.388	9.9	4.7	.82	1.1	29	5.3	24	.48	12.2	0.040	1.0	12.0	SPR	CG	Z	
0.468	11.89	A15-61	1.94	49.2	.376	9.6	8.7	1.5	.86	22	7.5	33	.49	12.6	0.046	1.2	10.8	SST	CG	N	
0.468	11.89	RR-62	2.00	50.8	.418	10.6	.51	.09	1.7	42	.84	3.7	.35	8.9	0.025	0.6	13.0	SST	C	N	
0.468	11.89	S-1404	2.00	50.8	.378	9.6	5.1	.90	1.3	32	6.5	29	.73	18.6	0.045	1.1	15.3	SST	C	N	
0.468	11.89	3573	2.00	50.8	.372	9.4	9.4	1.6	1.3	34	13	56	.62	15.8	0.048	1.2	13.0	MW	CG	Z	
0.468	11.89	KK-34	2.00	50.8	.348	8.8	20	3.6	.76	19	15	68	.84	21.3	0.060	1.5	14.0	SST	CG	N	
0.468	11.89	2852	2.00	50.8	.340	8.6	37	6.4	.75	19	27	121	.77	19.5	0.064	1.6	12.0	MW	CG	Z	
0.468	11.89	10923	2.06	52.4	.334	8.5	45	7.9	.50	13	22	100	.87	22.1	0.067	1.7	12.0	SPR	C	Z	
0.468	11.89	4300	2.13	54.0	.360	9.1	13	2.2	.94	24	12	53	.89	22.6	0.054	1.4	15.5	SPR	C	Z	
0.468	11.89	S-1104	2.13	54.0	.268	6.8	201	35	.30	7.5	60	265	1.45	36.8	0.100	2.5	14.5	SST	CG	N	
0.468	11.89	3225	2.34	59.5	.308	7.8	64	11	.55	14	36	158	1.41	35.9	0.080	2.0	17.8	SPR	CG	Z	
0.468	11.89	A13-32	2.41	61.1	.304	7.7	68	12	.56	14	38	170	1.52	38.5	0.082	2.1	18.5	SPR	CG	N	
0.468	11.89	10062	2.50	63.5	.388	9.9	3.2	.57	1.6	42	5.3	24	.66	16.8	0.040	1.0	16.5	SPR	CG	Z	
0.468	11.89	12	2.50	63.5	.360	9.1	11	1.9	1.1	29	12	53	1.04	26.4	0.054	1.4	18.3	HD	C	Z	
0.468	11.89	3693	2.50	63.5	.342	8.7	24	4.3	.77	20	19	84	1.07	27.2	0.063	1.6	16.0	SPR	C	Z	
0.468	11.89	S-1536	2.56	65.1	.360	9.1	7.5	1.3	1.4	35	10	46	1.19	30.2	0.054	1.4	22.0	SST	CG	N	
0.468	11.89	NN-91	2.63	66.7	.396	10.1	2.0	.35	1.8	46	3.6	16	.58	14.6	0.036	0.9	15.0	SST	C	N	
0.468	11.89	S-1153	2.63	66.7	.388	9.9	2.4	.42	1.8	46	4.4	19	.80	20.3	0.040	1.0	19.0	SST	C	N	
0.468	11.89	3014	2.88	73.0	.318	8.1	37	6.6	.79	20	30	132	1.65	41.9	0.075	1.9	22.0	SPR	CG	Z	
0.468	11.89	S-496	3.06	77.8	.374	9.5	3.8	.67	2.0	50	7.4	33	1.10	28.1	0.047	1.2	23.5	SST	CG	N	
0.468	11.89	2818	3.06	77.8	.338	8.6	25	4.3	.84	21	21	92	1.24	31.4	0.065	1.7	18.0	SPR	C	Z	
0.468	11.89	4210	3.50	88.9	.366	9.3	8.3	1.4	1.2	31	10	45	.98	24.9	0.051	1.3	18.3	SPR	C	Z	
0.468	11.89	11522	3.50	88.9	.344	8.7	17	2.9	1.1	27	18	80	1.36	34.6	0.062	1.6	21.0	SPR	CG	GI	
0.468	11.89	11893	3.50	88.9	.326	8.3	30	5.2	.80	20	24	105	1.38	35.2	0.071	1.8	19.5	SST	CG	N	
0.468	11.89	S-242	3.50	88.9	.308	7.8	33	5.8	1.0	26	33	148	2.28	57.9	0.080	2.0	28.5	SST	CG	N	
0.468	11.89	3032	4.00	101.6	.258	6.6	126	22	.58	15	74	328	3.26	82.7	0.105	2.7	31.0	SPR	CG	Z	
0.468	11.89	11822	4.94	125.4	.360	9.1	4.9	.86	2.4	62	12	53	2.05	52.1	0.054	1.4	37.0	SPR	C	Z	
0.468	11.89	1571	8.00	203.2	.348	8.8	6.2	1.1	2.6	67	16	72	2.85	72.4	0.060	1.5	46.5	SPR	C	Z	
0.468	11.89	12243	10.3	260.4	.360	9.1	2.3	.40	5.2	132	12	53	4.16	105.6	0.054	1.4	77.0	SPR	CG	Z	
0.480	12.19	71465	.50	12.7	.410	10.4	16	2.7	.31	7.8	4.8	21	.12	3.1	0.035	0.9	3.50	MW	CG	N	
0.480	12.19	71465S	.50	12.7	.410	10.4	13	2.3	.24	6.2	3.3	15	.12	3.1	0.035	0.9	3.50	SST	CG	N	
0.480	12.19	71476	.50	12.7	.404	10.3	20	3.5	.31	7.8	6.2	27	.14	3.6	0.038	1.0	3.75	MW	CG	N	
0.480	12.19	71476S	.50	12.7	.404	10.3	17	3.0	.24	6.2	4.2	19	.14	3.6	0.038	1.0	3.75	SST	CG	N	
0.480	12.19	71490	.50	12.7	.396	10.1	28	4.9	.30	7.5	8.3	37	.16	4.1	0.042	1.1	3.88	MW	CG	N	
0.480	12.19	71490S	.50	12.7	.396	10.1	24	4.2	.24	6.0	5.6	25	.16	4.1	0.042	1.1	3.88	SST	CG	N	
0.480	12.19	71504	.50	12.7	.390	9.9	35	6.1	.29	7.4	10	45	.18	4.6	0.045	1.1	4.00	MW	CG	N	
0.480	12.19	71504S	.50	12.7	.390	9.9	30	5.2	.23	5.9	6.9	31	.18	4.6	0.045	1.1	4.00	SST	CG	N	
0.480	12.19	71518	.50	12.7	.378	9.6	59	10	.23	5.9	14	61	.21	5.3	0.051	1.3	4.13	MW	CG	N	
0.480	12.19	71518S	.50	12.7	.378	9.6	50	8.8	.18	4.7	9.3	41	.21	5.3	0.051	1.3	4.13	SST	CG	N	
0.480	12.19	71532	.50	12.7	.370	9.4	72	13	.24	6.0	17	76	.24	6.1	0.055	1.4	4.38	MW	CG	N	
0.480	12.19	71532S	.50	12.7	.370	9.4	61	11	.19	4.8	12	52	.24	6.1	0.055	1.4	4.38	SST	CG	N	
0.480	12.19	71546	.50	12.7	.362	9.2	103	18	.21	5.2	21	94	.25	6.4	0.059	1.5	4.25	MW	CG	N	
0.480	12.19	71546S	.50	12.7	.362	9.2	87	15	.16	4.2	14	63	.25	6.4	0.059	1.5	4.25	SST	CG	N	
0.480	12.19	71560	.50	12.7	.354	9.0	123	21	.21	5.3	25	113	.28	7.2	0.063	1.6	4.50	MW	CG	N	
0.480	12.19	71560S	.50	12.7	.354	9.0	104	18	.17	4.2	17	77	.28	7.2	0.063	1.6	4.50	SST	CG	N	
0.480	12.19	71575	.50	12.7	.346	8.8	180	31	.17	4.3	30	136	.28	7.2	0.067	1.7	4.25	MW	CG	N	
0.480	12.19	71575S	.50	12.7	.346	8.8	153	27	.14	3.4	21	92	.28	7.2	0.067	1.7	4.25	SST	CG	N	
0.480	12.19	71588	.50	12.7	.336	8.5	256	45	.14	3.6	36	160	.31	7.8	0.072	1.8	4.25	MW	CG	N	
0.480	12.19	71588S	.50	12.7	.336	8.5</															




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	END S	FIN H
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.480	12.19	71604S	.63	16.0	.332	8.4	183	32	.14	3.6	26	116	.37	9.4	0.074	1.9	5.00	SST	CG	N
0.480	12.19	71619	.63	16.0	.318	8.1	330	58	.15	3.9	50	224	.41	10.3	0.081	2.1	5.00	MW	CG	N
0.480	12.19	71619S	.63	16.0	.318	8.1	280	49	.12	3.1	34	150	.41	10.3	0.081	2.1	5.00	SST	CG	N
0.480	12.19	12785	.66	16.7	.386	9.8	35	6.1	.33	8.5	12	51	.21	5.4	0.047	1.2	4.50	MW	CG	Z
0.480	12.19	12746	.73	18.6	.392	10.0	14	2.5	.40	10	5.8	26	.33	8.4	0.044	1.1	6.50	SPR	C	N
0.480	12.19	71467	.75	19.1	.410	10.4	9.9	1.7	.49	12	4.8	21	.16	4.0	0.035	0.9	4.50	MW	CG	N
0.480	12.19	71467S	.75	19.1	.410	10.4	8.4	1.5	.39	9.8	3.3	15	.16	4.0	0.035	0.9	4.50	SST	CG	N
0.480	12.19	71478	.75	19.1	.404	10.3	13	2.2	.49	12	6.2	27	.18	4.6	0.038	1.0	4.75	MW	CG	N
0.480	12.19	71478S	.75	19.1	.404	10.3	11	1.9	.39	9.9	4.2	19	.18	4.6	0.038	1.0	4.75	SST	CG	N
0.480	12.19	71492	.75	19.1	.396	10.1	18	3.2	.46	12	8.3	37	.21	5.3	0.042	1.1	5.00	MW	CG	N
0.480	12.19	71492S	.75	19.1	.396	10.1	15	2.7	.37	9.3	5.6	25	.21	5.3	0.042	1.1	5.00	SST	CG	N
0.480	12.19	71506	.75	19.1	.390	9.9	22	3.9	.46	12	10	45	.24	6.0	0.045	1.1	5.25	MW	CG	N
0.480	12.19	71506S	.75	19.1	.390	9.9	19	3.3	.37	9.3	6.9	31	.24	6.0	0.045	1.1	5.25	SST	CG	N
0.480	12.19	71520	.75	19.1	.378	9.6	37	6.5	.37	9.3	14	61	.27	6.8	0.051	1.3	5.25	MW	CG	N
0.480	12.19	71520S	.75	19.1	.378	9.6	32	5.6	.29	7.4	9.3	41	.27	6.8	0.051	1.3	5.25	SST	CG	N
0.480	12.19	71534	.75	19.1	.370	9.4	47	8.2	.36	9.3	17	76	.31	7.9	0.055	1.4	5.63	MW	CG	N
0.480	12.19	71534S	.75	19.1	.370	9.4	40	7.0	.29	7.4	12	52	.31	7.9	0.055	1.4	5.63	SST	CG	N
0.480	12.19	71548	.75	19.1	.362	9.2	63	11	.33	8.5	21	94	.34	8.6	0.059	1.5	5.75	MW	CG	N
0.480	12.19	71548S	.75	19.1	.362	9.2	53	9.4	.27	6.8	14	63	.34	8.6	0.059	1.5	5.75	SST	CG	N
0.480	12.19	71562	.75	19.1	.354	9.0	78	14	.33	8.4	25	113	.38	9.6	0.063	1.6	6.00	MW	CG	N
0.480	12.19	71562S	.75	19.1	.354	9.0	66	12	.26	6.7	17	77	.38	9.6	0.063	1.6	6.00	SST	CG	N
0.480	12.19	71577	.75	19.1	.346	8.8	107	19	.29	7.3	30	136	.39	10.0	0.067	1.7	5.88	MW	CG	N
0.480	12.19	71577S	.75	19.1	.346	8.8	91	16	.23	5.8	21	92	.39	10.0	0.067	1.7	5.88	SST	CG	N
0.480	12.19	71590	.75	19.1	.336	8.5	150	26	.24	6.1	36	160	.41	10.5	0.072	1.8	5.75	MW	CG	N
0.480	12.19	71590S	.75	19.1	.336	8.5	128	22	.19	4.8	24	107	.41	10.5	0.072	1.8	5.75	SST	CG	N
0.480	12.19	71605	.75	19.1	.332	8.4	169	30	.23	5.8	39	173	.43	10.8	0.074	1.9	5.75	MW	CG	N
0.480	12.19	71605S	.75	19.1	.332	8.4	144	25	.18	4.6	26	116	.43	10.8	0.074	1.9	5.75	SST	CG	N
0.480	12.19	71620	.75	19.1	.318	8.1	257	45	.20	5.0	50	224	.47	11.8	0.081	2.1	5.75	MW	CG	N
0.480	12.19	71620S	.75	19.1	.318	8.1	218	38	.15	3.9	34	150	.47	11.8	0.081	2.1	5.75	SST	CG	N
0.480	12.19	71468	.88	22.4	.410	10.4	8.3	1.5	.58	15	4.8	21	.18	4.4	0.035	0.9	5.00	MW	CG	N
0.480	12.19	71468S	.88	22.4	.410	10.4	7.1	1.2	.46	12	3.3	15	.18	4.4	0.035	0.9	5.00	SST	CG	N
0.480	12.19	71479	.88	22.4	.404	10.3	11	1.8	.59	15	6.2	27	.20	5.1	0.038	1.0	5.25	MW	CG	N
0.480	12.19	71479S	.88	22.4	.404	10.3	8.9	1.6	.47	12	4.2	19	.20	5.1	0.038	1.0	5.25	SST	CG	N
0.480	12.19	71493	.88	22.4	.396	10.1	15	2.6	.55	14	8.3	37	.23	5.9	0.042	1.1	5.50	MW	CG	N
0.480	12.19	71493S	.88	22.4	.396	10.1	13	2.2	.44	11	5.6	25	.23	5.9	0.042	1.1	5.50	SST	CG	N
0.480	12.19	71507	.88	22.4	.390	9.9	19	3.3	.53	14	10	45	.26	6.6	0.045	1.1	5.75	MW	CG	N
0.480	12.19	71507S	.88	22.4	.390	9.9	16	2.8	.42	11	6.9	31	.26	6.6	0.045	1.1	5.75	SST	CG	N
0.480	12.19	71521	.88	22.4	.378	9.6	30	5.3	.45	11	14	61	.31	7.8	0.051	1.3	6.00	MW	CG	N
0.480	12.19	71521S	.88	22.4	.378	9.6	26	4.5	.36	9.1	9.3	41	.31	7.8	0.051	1.3	6.00	SST	CG	N
0.480	12.19	71535	.88	22.4	.370	9.4	38	6.7	.45	11	17	76	.36	9.1	0.055	1.4	6.50	MW	CG	N
0.480	12.19	71535S	.88	22.4	.370	9.4	32	5.7	.36	9.1	12	52	.36	9.1	0.055	1.4	6.50	SST	CG	N
0.480	12.19	71549	.88	22.4	.362	9.2	51	8.9	.41	10	21	94	.39	9.9	0.059	1.5	6.63	MW	CG	N
0.480	12.19	71549S	.88	22.4	.362	9.2	43	7.6	.33	8.4	14	63	.39	9.9	0.059	1.5	6.63	SST	CG	N
0.480	12.19	71563	.88	22.4	.354	9.0	66	11	.39	9.9	25	113	.43	10.8	0.063	1.6	6.75	MW	CG	N
0.480	12.19	71563S	.88	22.4	.354	9.0	56	9.7	.31	7.9	17	77	.43	10.8	0.063	1.6	6.75	SST	CG	N
0.480	12.19	71578	.88	22.4	.346	8.8	88	15	.34	8.8	30	136	.44	11.3	0.067	1.7	6.63	MW	CG	N
0.480	12.19	71578S	.88	22.4	.346	8.8	75	13	.27	7.0	21	92	.44	11.3	0.067	1.7	6.63	SST	CG	N
0.480	12.19	71591	.88	22.4	.336	8.5	124	22	.29	7.4	36	160	.48	12.1	0.072	1.8	6.63	MW	CG	N
0.480	12.19	71591S	.88	22.4	.336	8.5	105	18	.23	5.8	24	107	.48	12.1	0.072	1.8	6.63	SST	CG	N
0.480	12.19	71606	.88	22.4	.332	8.4	139	24	.28	7.1	39	173	.49	12.5	0.074	1.9	6.63	MW	CG	N
0.480	12.19	71606S	.88	22.4	.332	8.4	118	21	.22	5.6	26	116	.49	12.5	0.074	1.9	6.63	SST	CG	N
0.480	12.19	71621	.88	22.4	.318	8.1	210	37	.24	6.1	50	224	.54	13.6	0.081	2.1	6.63	MW	CG	N
0.480	12.19	71621S	.88	22.4	.318	8.1	179	31	.19	4.8	34	150	.54	13.6	0.081	2.1	6.63	SST	CG	N
0.480	12.19	71469	1.00	25.4	.410	10.4	7.2	1.3	.67	17	4.8	21	.19	4.8	0.035	0.9	5.38	MW	CG	N
0.480	12.19	71469S	1.00	25.4	.410	10.4	6.1	1.1	.53	14	3.3	15	.19	4.8	0.035	0.9	5.38	SST	CG	N
0.480	12.19	71480	1.00	25.4	.404	10.3	9.3	1.6	.66	17	6.2	27	.22	5.5	0.038	1.0	5.75	MW	CG</	

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.480	12.19	71481S	1.25	31.8	.404	10.3	6.4	1.1	.65	17	4.2	19	.25	6.4	0.038	1.0	6.63	SST	CG	N
0.480	12.19	71495	1.25	31.8	.396	10.1	10	1.8	.83	21	8.3	37	.31	7.9	0.042	1.1	7.38	MW	CG	N
0.480	12.19	71495S	1.25	31.8	.396	10.1	8.5	1.5	.66	17	5.6	25	.31	7.9	0.042	1.1	7.38	SST	CG	N
0.480	12.19	71509	1.25	31.8	.390	9.9	13	2.3	.78	20	10	45	.34	8.6	0.045	1.1	7.50	MW	CG	N
0.480	12.19	71509S	1.25	31.8	.390	9.9	11	1.9	.62	16	6.9	31	.34	8.6	0.045	1.1	7.50	SST	CG	N
0.480	12.19	71523	1.25	31.8	.378	9.6	20	3.6	.67	17	14	61	.41	10.4	0.051	1.3	8.00	MW	CG	N
0.480	12.19	71523S	1.25	31.8	.378	9.6	17	3.0	.54	14	9.3	41	.41	10.4	0.051	1.3	8.00	SST	CG	N
0.480	12.19	71537	1.25	31.8	.370	9.4	27	4.7	.63	16	17	76	.46	11.7	0.055	1.4	8.38	MW	CG	N
0.480	12.19	71537S	1.25	31.8	.370	9.4	23	4.0	.51	13	12	52	.46	11.7	0.055	1.4	8.38	SST	CG	N
0.480	12.19	71551	1.25	31.8	.362	9.2	35	6.1	.60	15	21	94	.51	12.9	0.059	1.5	8.63	MW	CG	N
0.480	12.19	71551S	1.25	31.8	.362	9.2	30	5.2	.48	12	14	63	.51	12.9	0.059	1.5	8.63	SST	CG	N
0.480	12.19	71565	1.25	31.8	.354	9.0	45	7.9	.57	14	25	113	.57	14.4	0.063	1.6	9.00	MW	CG	N
0.480	12.19	71565S	1.25	31.8	.354	9.0	38	6.7	.45	11	17	77	.57	14.4	0.063	1.6	9.00	SST	CG	N
0.480	12.19	71580	1.25	31.8	.346	8.8	59	10	.52	13	30	136	.60	15.3	0.067	1.7	9.00	MW	CG	N
0.480	12.19	71580S	1.25	31.8	.346	8.8	50	8.7	.42	11	21	92	.60	15.3	0.067	1.7	9.00	SST	CG	N
0.480	12.19	71593	1.25	31.8	.336	8.5	82	14	.44	11	36	160	.64	16.2	0.072	1.8	8.88	MW	CG	N
0.480	12.19	71593S	1.25	31.8	.336	8.5	70	12	.34	8.7	24	107	.64	16.2	0.072	1.8	8.88	SST	CG	N
0.480	12.19	71608	1.25	31.8	.332	8.4	92	16	.42	11	39	173	.67	16.9	0.074	1.9	9.00	MW	CG	N
0.480	12.19	71608S	1.25	31.8	.332	8.4	78	14	.33	8.4	26	116	.67	16.9	0.074	1.9	9.00	SST	CG	N
0.480	12.19	71623	1.25	31.8	.318	8.1	139	24	.36	9.2	50	224	.73	18.5	0.081	2.1	9.00	MW	CG	N
0.480	12.19	71623S	1.25	31.8	.318	8.1	118	21	.29	7.3	34	150	.73	18.5	0.081	2.1	9.00	SST	CG	N
0.480	12.19	71566	1.38	35.1	.354	9.0	43	7.5	.60	15	25	113	.59	15.0	0.063	1.6	9.38	MW	CG	N
0.480	12.19	71566S	1.38	35.1	.354	9.0	36	6.4	.48	12	17	77	.59	15.0	0.063	1.6	9.38	SST	CG	N
0.480	12.19	71471	1.50	38.1	.410	10.4	4.7	.82	1.0	26	4.8	21	.25	6.4	0.035	0.9	7.25	MW	CG	N
0.480	12.19	71471S	1.50	38.1	.410	10.4	4.0	.70	.82	21	3.3	15	.25	6.4	0.035	0.9	7.25	SST	CG	N
0.480	12.19	71482	1.50	38.1	.404	10.3	6.0	1.1	1.0	26	6.2	27	.29	7.5	0.038	1.0	7.75	MW	CG	N
0.480	12.19	71482S	1.50	38.1	.404	10.3	5.1	.89	.82	21	4.2	19	.29	7.5	0.038	1.0	7.75	SST	CG	N
0.480	12.19	71496	1.50	38.1	.396	10.1	8.5	1.5	.97	25	8.3	37	.35	8.8	0.042	1.1	8.25	MW	CG	N
0.480	12.19	71496S	1.50	38.1	.396	10.1	7.2	1.3	.77	20	5.6	25	.35	8.8	0.042	1.1	8.25	SST	CG	N
0.480	12.19	71510	1.50	38.1	.390	9.9	11	1.9	.92	23	10	45	.38	9.7	0.045	1.1	8.50	MW	CG	N
0.480	12.19	71510S	1.50	38.1	.390	9.9	9.4	1.6	.73	19	6.9	31	.38	9.7	0.045	1.1	8.50	SST	CG	N
0.480	12.19	71524	1.50	38.1	.378	9.6	17	2.9	.82	21	14	61	.48	12.1	0.051	1.3	9.38	MW	CG	N
0.480	12.19	71524S	1.50	38.1	.378	9.6	14	2.5	.65	17	9.3	41	.48	12.1	0.051	1.3	9.38	SST	CG	N
0.480	12.19	71538	1.50	38.1	.370	9.4	22	3.9	.78	20	17	76	.54	13.6	0.055	1.4	9.75	MW	CG	N
0.480	12.19	71538S	1.50	38.1	.370	9.4	19	3.3	.62	16	12	52	.54	13.6	0.055	1.4	9.75	SST	CG	N
0.480	12.19	71552	1.50	38.1	.362	9.2	29	5.0	.73	19	21	94	.60	15.2	0.059	1.5	10.1	MW	CG	N
0.480	12.19	71552S	1.50	38.1	.362	9.2	24	4.3	.58	15	14	63	.60	15.2	0.059	1.5	10.1	SST	CG	N
0.480	12.19	71567	1.50	38.1	.354	9.0	38	6.6	.68	17	25	113	.65	16.6	0.063	1.6	10.4	MW	CG	N
0.480	12.19	71567S	1.50	38.1	.354	9.0	32	5.6	.54	14	17	77	.65	16.6	0.063	1.6	10.4	SST	CG	N
0.480	12.19	71581	1.50	38.1	.346	8.8	48	8.4	.63	16	30	136	.70	17.9	0.067	1.7	10.5	MW	CG	N
0.480	12.19	71581S	1.50	38.1	.346	8.8	41	7.2	.51	13	21	92	.70	17.9	0.067	1.7	10.5	SST	CG	N
0.480	12.19	71594	1.50	38.1	.336	8.5	67	12	.54	14	36	160	.76	19.2	0.072	1.8	10.5	MW	CG	N
0.480	12.19	71594S	1.50	38.1	.336	8.5	57	10	.42	11	24	107	.76	19.2	0.072	1.8	10.5	SST	CG	N
0.480	12.19	71609	1.50	38.1	.332	8.4	75	13	.52	13	39	173	.78	19.7	0.074	1.9	10.5	MW	CG	N
0.480	12.19	71609S	1.50	38.1	.332	8.4	64	11	.41	10	26	116	.78	19.7	0.074	1.9	10.5	SST	CG	N
0.480	12.19	71624	1.50	38.1	.318	8.1	113	20	.45	11	50	224	.86	21.9	0.081	2.1	10.6	MW	CG	N
0.480	12.19	71624S	1.50	38.1	.318	8.1	96	17	.35	8.9	34	150	.86	21.9	0.081	2.1	10.6	SST	CG	N
0.480	12.19	71483	1.63	41.4	.404	10.3	5.5	.96	1.1	28	6.2	27	.31	8.0	0.038	1.0	8.25	MW	CG	N
0.480	12.19	71483S	1.63	41.4	.404	10.3	4.7	.82	.89	23	4.2	19	.31	8.0	0.038	1.0	8.25	SST	CG	N
0.480	12.19	71497	1.63	41.4	.396	10.1	7.7	1.3	1.1	27	8.3	37	.37	9.5	0.042	1.1	8.88	MW	CG	N
0.480	12.19	71497S	1.63	41.4	.396	10.1	6.5	1.1	.85	22	5.6	25	.37	9.5	0.042	1.1	8.88	SST	CG	N
0.480	12.19	71511	1.63	41.4	.390	9.9	9.8	1.7	1.0	26	10	45	.42	10.7	0.045	1.1	9.38	MW	CG	N
0.480	12.19	71511S	1.63	41.4	.390	9.9	8.3	1.5	.83	21	6.9	31	.42	10.7	0.045	1.1	9.38	SST	CG	N
0.480	12.19	71525	1.63	41.4	.378	9.6	15	2.6	.93	24	14	61	.53	13.4	0.051	1.3	10.4	MW	CG	N
0.480	12.19	71525S	1.63	41.4	.378	9.6	13	2.2	.74	19	9.3	41	.53	13.4	0.051	1.3	10.4	SST	CG	N
0.480	12.19	71539	1.63	41.4	.370	9.4	20	3.5	.86	22	17	76	.58	14.8	0.055	1.4	10.6	MW	CG</	




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.480	12.19	71595S	1.75	44.5	.336	8.5	48	8.4	.50	13	24	107	.86	21.9	0.072	1.8	12.0	SST	CG	N
0.480	12.19	71610	1.75	44.5	.332	8.4	64	11	.61	16	39	173	.90	22.8	0.074	1.9	12.1	MW	CG	N
0.480	12.19	71610S	1.75	44.5	.332	8.4	54	9.5	.48	12	26	116	.90	22.8	0.074	1.9	12.1	SST	CG	N
0.480	12.19	71625	1.75	44.5	.318	8.1	95	17	.53	13	50	224	.99	25.2	0.081	2.1	12.3	MW	CG	N
0.480	12.19	71625S	1.75	44.5	.318	8.1	81	14	.42	11	34	150	.99	25.2	0.081	2.1	12.3	SST	CG	N
0.480	12.19	71473	2.00	50.8	.410	10.4	3.5	.61	1.4	35	4.8	21	.32	8.0	0.035	0.9	9.00	MW	CG	N
0.480	12.19	71473S	2.00	50.8	.410	10.4	3.0	.52	1.1	28	3.3	15	.32	8.0	0.035	0.9	9.00	SST	CG	N
0.480	12.19	71485	2.00	50.8	.404	10.3	4.5	.79	1.4	35	6.2	27	.37	9.3	0.038	1.0	9.63	MW	CG	N
0.480	12.19	71485S	2.00	50.8	.404	10.3	3.8	.67	1.1	27	4.2	19	.37	9.3	0.038	1.0	9.63	SST	CG	N
0.480	12.19	71499	2.00	50.8	.396	10.1	6.4	1.1	1.3	33	8.3	37	.44	11.1	0.042	1.1	10.4	MW	CG	N
0.480	12.19	71499S	2.00	50.8	.396	10.1	5.4	.95	1.0	26	5.6	25	.44	11.1	0.042	1.1	10.4	SST	CG	N
0.480	12.19	71513	2.00	50.8	.390	9.9	8.1	1.4	1.3	32	10	45	.49	12.4	0.045	1.1	10.9	MW	CG	N
0.480	12.19	71513S	2.00	50.8	.390	9.9	6.8	1.2	1.0	25	6.9	31	.49	12.4	0.045	1.1	10.9	SST	CG	N
0.480	12.19	71527	2.00	50.8	.378	9.6	12	2.2	1.1	28	14	61	.61	15.4	0.051	1.3	11.9	MW	CG	N
0.480	12.19	71527S	2.00	50.8	.378	9.6	11	1.9	.88	22	9.3	41	.61	15.4	0.051	1.3	11.9	SST	CG	N
0.480	12.19	71541	2.00	50.8	.370	9.4	16	2.9	1.0	27	17	76	.69	17.5	0.055	1.4	12.5	MW	CG	N
0.480	12.19	71541S	2.00	50.8	.370	9.4	14	2.4	.83	21	12	52	.69	17.5	0.055	1.4	12.5	SST	CG	N
0.480	12.19	71555	2.00	50.8	.362	9.2	21	3.7	1.0	25	21	94	.77	19.5	0.059	1.5	13.0	MW	CG	N
0.480	12.19	71555S	2.00	50.8	.362	9.2	18	3.1	.79	20	14	63	.77	19.5	0.059	1.5	13.0	SST	CG	N
0.480	12.19	71570	2.00	50.8	.354	9.0	27	4.8	.93	24	25	113	.84	21.4	0.063	1.6	13.4	MW	CG	N
0.480	12.19	71570S	2.00	50.8	.354	9.0	23	4.1	.74	19	17	77	.84	21.4	0.063	1.6	13.4	SST	CG	N
0.480	12.19	71583	2.00	50.8	.346	8.8	35	6.2	.87	22	30	136	.91	23.2	0.067	1.7	13.6	MW	CG	N
0.480	12.19	71583S	2.00	50.8	.346	8.8	30	5.2	.69	18	21	92	.91	23.2	0.067	1.7	13.6	SST	CG	N
0.480	12.19	71596	2.00	50.8	.336	8.5	49	8.6	.73	19	36	160	.98	24.9	0.072	1.8	13.6	MW	CG	N
0.480	12.19	71596S	2.00	50.8	.336	8.5	42	7.3	.58	15	24	107	.98	24.9	0.072	1.8	13.6	SST	CG	N
0.480	12.19	71611	2.00	50.8	.332	8.4	55	9.6	.71	18	39	173	1.02	25.8	0.074	1.9	13.8	MW	CG	N
0.480	12.19	71611S	2.00	50.8	.332	8.4	47	8.2	.56	14	26	116	1.02	25.8	0.074	1.9	13.8	SST	CG	N
0.480	12.19	71626	2.00	50.8	.318	8.1	82	14	.61	16	50	224	1.12	28.5	0.081	2.1	13.9	MW	CG	N
0.480	12.19	71626S	2.00	50.8	.318	8.1	70	12	.48	12	34	150	1.12	28.5	0.081	2.1	13.9	SST	CG	N
0.480	12.19	71486	2.25	57.2	.404	10.3	4.2	.73	1.5	37	6.2	27	.39	9.9	0.038	1.0	10.3	MW	CG	N
0.480	12.19	71486S	2.25	57.2	.404	10.3	3.6	.62	1.2	30	4.2	19	.39	9.9	0.038	1.0	10.3	SST	CG	N
0.480	12.19	71500	2.25	57.2	.396	10.1	5.7	1.0	1.5	37	8.3	37	.48	12.1	0.042	1.1	11.4	MW	CG	N
0.480	12.19	71500S	2.25	57.2	.396	10.1	4.8	.85	1.2	29	5.6	25	.48	12.1	0.042	1.1	11.4	SST	CG	N
0.480	12.19	71514	2.25	57.2	.390	9.9	7.1	1.2	1.4	37	10	45	.55	13.9	0.045	1.1	12.1	MW	CG	N
0.480	12.19	71514S	2.25	57.2	.390	9.9	6.0	1.0	1.1	29	6.9	31	.55	13.9	0.045	1.1	12.1	SST	CG	N
0.480	12.19	71528	2.25	57.2	.378	9.6	11	1.9	1.3	32	14	61	.68	17.2	0.051	1.3	13.3	MW	CG	N
0.480	12.19	71528S	2.25	57.2	.378	9.6	9.3	1.6	1.0	25	9.3	41	.68	17.2	0.051	1.3	13.3	SST	CG	N
0.480	12.19	71542	2.25	57.2	.370	9.4	15	2.5	1.2	30	17	76	.76	19.2	0.055	1.4	13.8	MW	CG	N
0.480	12.19	71542S	2.25	57.2	.370	9.4	12	2.2	.94	24	12	52	.76	19.2	0.055	1.4	13.8	SST	CG	N
0.480	12.19	71556	2.25	57.2	.362	9.2	19	3.3	1.1	29	21	94	.86	21.7	0.059	1.5	14.5	MW	CG	N
0.480	12.19	71556S	2.25	57.2	.362	9.2	16	2.8	.90	23	14	63	.86	21.7	0.059	1.5	14.5	SST	CG	N
0.480	12.19	71571	2.25	57.2	.354	9.0	24	4.3	1.0	27	25	113	.94	23.8	0.063	1.6	14.9	MW	CG	N
0.480	12.19	71571S	2.25	57.2	.354	9.0	21	3.6	.84	21	17	77	.94	23.8	0.063	1.6	14.9	SST	CG	N
0.480	12.19	71584	2.25	57.2	.346	8.8	31	5.4	.98	25	30	136	1.02	26.0	0.067	1.7	15.3	MW	CG	N
0.480	12.19	71584S	2.25	57.2	.346	8.8	26	4.6	.78	20	21	92	1.02	26.0	0.067	1.7	15.3	SST	CG	N
0.480	12.19	71597	2.25	57.2	.336	8.5	43	7.6	.83	21	36	160	1.09	27.7	0.072	1.8	15.1	MW	CG	N
0.480	12.19	71597S	2.25	57.2	.336	8.5	37	6.4	.66	17	24	107	1.09	27.7	0.072	1.8	15.1	SST	CG	N
0.480	12.19	71612	2.25	57.2	.332	8.4	48	8.5	.80	20	39	173	1.13	28.7	0.074	1.9	15.3	MW	CG	N
0.480	12.19	71612S	2.25	57.2	.332	8.4	41	7.2	.63	16	26	116	1.13	28.7	0.074	1.9	15.3	SST	CG	N
0.480	12.19	71627	2.25	57.2	.318	8.1	72	13	.70	18	50	224	1.26	31.9	0.081	2.1	15.5	MW	CG	N
0.480	12.19	71627S	2.25	57.2	.318	8.1	61	11	.55	14	34	150	1.26	31.9	0.081	2.1	15.5	SST	CG	N
0.480	12.19	71474	2.50	63.5	.410	10.4	2.8	.49	1.7	44	4.8	21	.38	9.6	0.035	0.9	10.8	MW	CG	N
0.480	12.19	71474S	2.50	63.5	.410	10.4	2.4	.42	1.4	35	3.3	15	.38	9.6	0.035	0.9	10.8	SST	CG	N
0.480	12.19	71487	2.50	63.5	.404	10.3	3.8	.66	1.6	42	6.2	27	.43	10.9	0.038	1.0	11.3	MW	CG	N
0.480	12.19	71487S	2.50	63.5	.404	10.3	3.2	.56	1.3	33	4.2	19	.43	10.9	0.038	1.0	11.3	SST	CG	N
0.480	12.19	71501	2.50	63.5	.396	10.1	5.4	.94	1.5	39	8.3	37	.50	12.8	0.042	1.1	12.0	MW	CG	N
0.480	12.19	71501S	2.50	63.5	.396	10.1	4.5	.80	1.2	31	5.6	25	.50	12.8	0.042	1.1	12.0	SST	CG	N
0.480	12.19	71515	2.50	63.5	.390	9.9	6.4	1.1	1.6	40	10	45	.60	15.1	0.045	1.1	13.3	MW	CG	N
0.480	12.19	71515S	2.50	63.5	.390	9.9	5.4	.95	1.3	32	6.9	31	.60	15.1	0.045	1.1	13.3	SST	CG	N
0.480	12.19	71529	2.50	63.5	.378	9.6	9.9	1.7	1.4	35	14	61	.74	18.8	0.051	1.3	14.5	MW	CG	N
0.480	12.19	71529S	2.50	63.5	.378	9.6	8.4	1.5	1.1	28	9.3	41	.74	18.8	0.051	1.3	14.5	SST	CG	N
0.480	12.19	71543	2.50	63.5	.370	9.4	13	2.3	1.3	34	17	76	.84	21.3	0.055	1.4	15.3	MW	CG	N
0.480	12.19	71543S	2.50	63.5	.370	9.4	11	1.9	1.1	27	12	52	.84	21.3	0.055	1.4	15.3	SST	CG	N
0.480	12.19	71557	2.50	63.5	.362	9.2	17	2.9	1.3	32	21	94	.95	24.2	0.059	1.5	16.1	MW	CG	N
0.480	12.19	71557S	2.50	63.5	.362	9.2	14	2.5	1.0	26	14	63	.95	24.2	0.059	1.5	16.1	SST	CG	N
0.480	12.19	71572	2.50	63.5	.354	9.0	22	3.8	1.2	30	25	113	1.03	26.2	0.063	1.6	16.4	MW	CG	N
0.480	12.19	71572S	2.50	63.5	.354	9.0	18	3.2	.94	24	17	77	1.03	26.2	0.063	1.6	16.4	SST	CG	N
0.480	12.19	71585	2.50	63.5	.346	8.8	28	4.9	1.1	28	30	136	1.12	28.5	0.067	1.7	16.8	MW	CG	N
0.480	12																			

COMPRESSION SPRINGS




O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.480	12.19	71516S	2.75	69.9	.390	9.9	4.9	.86	1.4	35	6.9	31	.65	16.4	0.045	1.1	14.4	SST	CG	N
0.480	12.19	71530	2.75	69.9	.378	9.6	8.8	1.5	1.6	40	14	61	.82	20.7	0.051	1.3	16.0	MW	CG	N
0.480	12.19	71530S	2.75	69.9	.378	9.6	7.4	1.3	1.2	32	9.3	41	.82	20.7	0.051	1.3	16.0	SST	CG	N
0.480	12.19	71544	2.75	69.9	.370	9.4	12	2.1	1.5	37	17	76	.91	23.2	0.055	1.4	16.6	MW	CG	N
0.480	12.19	71544S	2.75	69.9	.370	9.4	10	1.7	1.2	30	12	52	.91	23.2	0.055	1.4	16.6	SST	CG	N
0.480	12.19	71558	2.75	69.9	.362	9.2	15	2.7	1.4	35	21	94	1.03	26.0	0.059	1.5	17.4	MW	CG	N
0.480	12.19	71558S	2.75	69.9	.362	9.2	13	2.3	1.1	28	14	63	1.03	26.0	0.059	1.5	17.4	SST	CG	N
0.480	12.19	71573	2.75	69.9	.354	9.0	20	3.5	1.3	33	25	113	1.12	28.4	0.063	1.6	17.8	MW	CG	N
0.480	12.19	71573S	2.75	69.9	.354	9.0	17	3.0	1.0	26	17	77	1.12	28.4	0.063	1.6	17.8	SST	CG	N
0.480	12.19	71586	2.75	69.9	.346	8.8	25	4.4	1.2	31	30	136	1.23	31.3	0.067	1.7	18.4	MW	CG	N
0.480	12.19	71586S	2.75	69.9	.346	8.8	21	3.7	.97	25	21	92	1.23	31.3	0.067	1.7	18.4	SST	CG	N
0.480	12.19	71599	2.75	69.9	.336	8.5	35	6.1	1.0	26	36	160	1.31	33.4	0.072	1.8	18.3	MW	CG	N
0.480	12.19	71599S	2.75	69.9	.336	8.5	30	5.2	.81	21	24	107	1.31	33.4	0.072	1.8	18.3	SST	CG	N
0.480	12.19	71614	2.75	69.9	.332	8.4	39	6.8	.99	25	39	173	1.37	34.8	0.074	1.9	18.5	MW	CG	N
0.480	12.19	71614S	2.75	69.9	.332	8.4	33	5.8	.78	20	26	116	1.37	34.8	0.074	1.9	18.5	SST	CG	N
0.480	12.19	71629	2.75	69.9	.318	8.1	58	10	.87	22	50	224	1.52	38.6	0.081	2.1	18.8	MW	CG	N
0.480	12.19	71629S	2.75	69.9	.318	8.1	50	8.7	.68	17	34	150	1.52	38.6	0.081	2.1	18.8	SST	CG	N
0.480	12.19	71475	3.00	76.2	.410	10.4	2.3	.40	2.1	53	4.8	21	.44	11.2	0.035	0.9	12.6	MW	CG	N
0.480	12.19	71475S	3.00	76.2	.410	10.4	2.0	.34	1.7	42	3.3	15	.44	11.2	0.035	0.9	12.6	SST	CG	N
0.480	12.19	71489	3.00	76.2	.404	10.3	3.1	.55	2.0	50	6.2	27	.50	12.7	0.038	1.0	13.1	MW	CG	N
0.480	12.19	71489S	3.00	76.2	.404	10.3	2.6	.46	1.6	40	4.2	19	.50	12.7	0.038	1.0	13.1	SST	CG	N
0.480	12.19	71503	3.00	76.2	.396	10.1	4.4	.77	1.9	48	8.3	37	.59	14.9	0.042	1.1	14.0	MW	CG	N
0.480	12.19	71503S	3.00	76.2	.396	10.1	3.8	.66	1.5	38	5.6	25	.59	14.9	0.042	1.1	14.0	SST	CG	N
0.480	12.19	12726	3.00	76.2	.390	9.9	5.1	.89	1.3	34	6.9	31	.64	16.3	0.045	1.1	14.3	SST	CG	N
0.480	12.19	71517	3.00	76.2	.390	9.9	5.3	.93	1.9	49	10	45	.70	17.7	0.045	1.1	15.5	MW	CG	N
0.480	12.19	71517S	3.00	76.2	.390	9.9	4.5	.79	1.5	39	6.9	31	.70	17.7	0.045	1.1	15.5	SST	CG	N
0.480	12.19	71531	3.00	76.2	.378	9.6	8.0	1.4	1.7	44	14	61	.89	22.5	0.051	1.3	17.4	MW	CG	N
0.480	12.19	71531S	3.00	76.2	.378	9.6	6.8	1.2	1.4	35	9.3	41	.89	22.5	0.051	1.3	17.4	SST	CG	N
0.480	12.19	71545	3.00	76.2	.370	9.4	11	1.9	1.6	41	17	76	.99	25.1	0.055	1.4	18.0	MW	CG	N
0.480	12.19	71545S	3.00	76.2	.370	9.4	9.1	1.6	1.3	32	12	52	.99	25.1	0.055	1.4	18.0	SST	CG	N
0.480	12.19	71559	3.00	76.2	.362	9.2	14	2.4	1.5	39	21	94	1.11	28.3	0.059	1.5	18.9	MW	CG	N
0.480	12.19	71559S	3.00	76.2	.362	9.2	12	2.1	1.2	31	14	63	1.11	28.3	0.059	1.5	18.9	SST	CG	N
0.480	12.19	71574	3.00	76.2	.354	9.0	18	3.1	1.4	37	25	113	1.24	31.6	0.063	1.6	19.8	MW	CG	N
0.480	12.19	71574S	3.00	76.2	.354	9.0	15	2.6	1.2	29	17	77	1.24	31.6	0.063	1.6	19.8	SST	CG	N
0.480	12.19	71587	3.00	76.2	.346	8.8	23	4.0	1.3	34	30	136	1.33	33.8	0.067	1.7	19.9	MW	CG	N
0.480	12.19	71587S	3.00	76.2	.346	8.8	20	3.4	1.1	27	21	92	1.33	33.8	0.067	1.7	19.9	SST	CG	N
0.480	12.19	71600	3.00	76.2	.336	8.5	32	5.6	1.1	29	36	160	1.43	36.3	0.072	1.8	19.9	MW	CG	N
0.480	12.19	71600S	3.00	76.2	.336	8.5	27	4.7	.89	23	24	107	1.43	36.3	0.072	1.8	19.9	SST	CG	N
0.480	12.19	71615	3.00	76.2	.332	8.4	36	6.3	1.1	28	39	173	1.48	37.6	0.074	1.9	20.0	MW	CG	N
0.480	12.19	71615S	3.00	76.2	.332	8.4	30	5.3	.86	22	26	116	1.48	37.6	0.074	1.9	20.0	SST	CG	N
0.480	12.19	71630	3.00	76.2	.318	8.1	53	9.3	.95	24	50	224	1.64	41.7	0.081	2.1	20.3	MW	CG	N
0.480	12.19	71630S	3.00	76.2	.318	8.1	45	7.9	.75	19	34	150	1.64	41.7	0.081	2.1	20.3	SST	CG	N
0.480	12.19	71601	3.25	82.6	.336	8.5	29	5.1	1.2	31	36	160	1.54	39.1	0.072	1.8	21.4	MW	CG	N
0.480	12.19	71601S	3.25	82.6	.336	8.5	25	4.4	.97	25	24	107	1.54	39.1	0.072	1.8	21.4	SST	CG	N
0.480	12.19	71616	3.25	82.6	.332	8.4	33	5.7	1.2	30	39	173	1.60	40.6	0.074	1.9	21.6	MW	CG	N
0.480	12.19	71616S	3.25	82.6	.332	8.4	28	4.9	.93	24	26	116	1.60	40.6	0.074	1.9	21.6	SST	CG	N
0.480	12.19	71631	3.25	82.6	.318	8.1	49	8.6	1.0	26	50	224	1.77	45.0	0.081	2.1	21.9	MW	CG	N
0.480	12.19	71631S	3.25	82.6	.318	8.1	42	7.3	.81	21	34	150	1.77	45.0	0.081	2.1	21.9	SST	CG	N
0.480	12.19	71602	3.50	88.9	.336	8.5	27	4.7	1.3	34	36	160	1.66	42.1	0.072	1.8	23.0	MW	CG	N
0.480	12.19	71602S	3.50	88.9	.336	8.5	23	4.0	1.0	27	24	107	1.66	42.1	0.072	1.8	23.0	SST	CG	N
0.480	12.19	71617	3.50	88.9	.332	8.4	30	5.3	1.3	32	39	173	1.72	43.7	0.074	1.9	23.3	MW	CG	N
0.480	12.19	71617S	3.50	88.9	.332	8.4	26	4.5	1.0	26	26	116	1.72	43.7	0.074	1.9	23.3	SST	CG	N
0.480	12.19	71632	3.50	88.9	.318	8.1	45	7.9	1.1	28	50	224	1.90	48.3	0.081	2.1	23.5	MW	CG	N
0.480	12.19	71632S	3.50	88.9	.318	8.1	38	6.7	.88	22	34	150	1.90	48.3	0.081	2.1	23.5	SST	CG	N
0.484	12.29	H-35	.25	6.4	.388	9.9	92	16	.10	2.4	8.8	39	.14	3.7	0.048	1.2	3.00	SPR		




COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.484	12.29	11384	.50	12.7	.374	9.5	67	12	.25	6.4	17	75	.25	6.3	0.055	1.4	4.50	MW	CG	Z
0.484	12.29	CC-84	.53	13.5	.384	9.8	32	5.7	.27	6.8	8.7	39	.25	6.4	0.050	1.3	5.00	SST	CG	N
0.484	12.29	A11-68	.53	13.5	.338	8.6	174	30	.14	3.6	25	111	.37	9.3	0.073	1.9	5.00	SST	CG	N
0.484	12.29	1757	.56	14.3	.410	10.4	15	2.6	.37	9.5	5.6	25	.19	4.7	0.037	0.9	4.00	MW	C	Z
0.484	12.29	AA-81	.56	14.3	.410	10.4	4.8	.84	.28	7.2	1.4	6.0	.28	7.0	0.037	0.9	7.50	SST	CG	N
0.484	12.29	S-1009	.56	14.3	.404	10.3	16	2.8	.30	7.5	4.8	21	.21	5.3	0.040	1.0	4.25	SST	C	N
0.484	12.29	FF-58	.56	14.3	.394	10.0	21	3.6	.33	8.4	6.8	30	.23	5.7	0.045	1.1	5.00	SST	CG	N
0.484	12.29	XX-37	.56	14.3	.390	9.9	28	4.9	.28	7.1	7.8	35	.28	7.2	0.047	1.2	5.00	SPR	C	Z
0.484	12.29	10993	.56	14.3	.372	9.4	90	16	.14	3.6	13	57	.28	7.1	0.056	1.4	4.00	HD	C	Z
0.484	12.29	N-134	.59	15.1	.420	10.7	3.3	.57	.37	9.4	1.2	5.4	.22	5.7	0.032	0.8	7.00	SPR	CG	N
0.484	12.29	W-35	.59	15.1	.414	10.5	5.2	.91	.35	8.8	1.8	8.0	.25	6.2	0.035	0.9	6.00	SST	C	N
0.484	12.29	11197	.63	15.9	.420	10.7	3.9	.68	.41	10	1.6	7.0	.22	5.5	0.032	0.8	5.75	SST	C	N
0.484	12.29	10781	.63	15.9	.384	9.8	44	7.7	.21	5.3	9.3	41	.23	5.7	0.050	1.3	4.50	SPR	CG	N
0.484	12.29	PP-87	.63	15.9	.384	9.8	31	5.5	.29	7.5	9.3	41	.28	7.0	0.050	1.3	5.50	SPR	CG	Z
0.484	12.29	2625	.63	15.9	.372	9.4	72	13	.25	6.3	18	80	.25	6.4	0.056	1.4	4.50	MW	CG	Z
0.484	12.29	B9-12	.69	17.4	.436	11.1	3.7	.64	.47	12	1.7	7.7	.10	2.6	0.024	0.6	3.33	MW	C	Z
0.484	12.29	S-866	.72	18.2	.414	10.5	5.2	.91	.51	13	2.6	12	.21	5.3	0.035	0.9	6.00	SST	CG	N
0.484	12.29	S-1401	.72	18.2	.360	9.1	82	14	.20	5.1	16	73	.31	7.9	0.062	1.6	5.00	SST	CG	N
0.484	12.29	S-1560	.72	18.2	.304	7.7	383	67	.11	2.9	43	192	.50	12.6	0.090	2.3	5.50	SST	CG	N
0.484	12.29	W-60	.75	19.1	.448	11.4	.14	.02	.53	13	.07	.33	.22	5.6	0.018	0.5	11.3	SST	C	N
0.484	12.29	N-85	.75	19.1	.436	11.1	1.4	.25	.61	15	.86	3.8	.14	3.7	0.024	0.6	5.00	SST	C	N
0.484	12.29	FF-35	.75	19.1	.432	11.0	2.0	.35	.59	15	1.2	5.2	.16	4.0	0.026	0.7	5.00	SST	C	N
0.484	12.29	II-75	.75	19.1	.404	10.3	9.3	1.6	.47	12	4.4	19	.28	7.1	0.040	1.0	6.00	SST	C	N
0.484	12.29	JJ-97	.75	19.1	.376	9.6	38	6.7	.30	7.7	12	52	.32	8.2	0.054	1.4	6.00	SPR	CG	GI
0.484	12.29	10934	.75	19.1	.358	9.1	71	13	.26	6.5	18	81	.39	10.0	0.063	1.6	6.25	SPR	CG	Z
0.484	12.29	3594	.75	19.1	.340	8.6	138	24	.26	6.6	36	159	.43	11.0	0.072	1.8	6.00	MW	CG	GI
0.484	12.29	S-1539	.78	19.8	.426	10.8	2.0	.35	.59	15	1.2	5.1	.20	5.0	0.029	0.7	6.75	SST	CG	N
0.484	12.29	10899	.78	19.8	.334	8.5	285	50	.10	2.6	29	128	.33	8.3	0.075	1.9	4.33	SPR	CG	N
0.484	12.29	12425	.81	20.6	.430	10.9	3.2	.56	.66	17	2.1	9.4	.15	3.8	0.027	0.7	4.50	MW	C	Z
0.484	12.29	1653	.81	20.6	.350	8.9	80	14	.27	6.9	22	97	.47	11.9	0.067	1.7	7.00	HD	CG	Z
0.484	12.29	12215	.84	21.4	.424	10.8	3.1	.54	.63	16	2.0	8.8	.21	5.3	0.030	0.8	6.00	MW	C	Z
0.484	12.29	W-64	.84	21.4	.416	10.6	6.2	1.1	.50	13	3.1	14	.20	5.2	0.034	0.9	5.00	SST	C	N
0.484	12.29	10557	.84	21.4	.346	8.8	107	19	.22	5.6	24	106	.43	10.9	0.069	1.8	6.25	SPR	CG	Z
0.484	12.29	I-31	.88	22.2	.446	11.3	.31	.05	.70	18	.22	.97	.17	4.3	0.019	0.5	8.00	MW	C	N
0.484	12.29	H-90	.88	22.2	.440	11.2	.31	.05	.59	15	.18	.82	.28	7.1	0.022	0.6	11.8	SST	C	N
0.484	12.29	4285	.88	22.2	.360	9.1	47	8.2	.37	9.4	17	77	.50	12.6	0.062	1.6	8.00	SPR	CG	Z
0.484	12.29	CC-1	.88	22.2	.300	7.6	270	47	.17	4.3	46	204	.69	17.5	0.092	2.3	7.50	SST	CG	N
0.484	12.29	G-75	.88	22.2	.266	6.8	641	112	.003	.08	1.9	8.6	.87	22.1	0.109	2.8	8.00	HD	CG	N
0.484	12.29	PP-80	.91	23.0	.418	10.6	4.1	.72	.66	17	2.7	12	.25	6.3	0.033	0.8	6.50	SPR	C	N
0.484	12.29	B12-21	.94	23.8	.402	10.2	12	2.0	.47	12	5.5	25	.25	6.2	0.041	1.0	6.00	SPR	CG	N
0.484	12.29	YY-53	.94	23.8	.394	10.0	15	2.7	.45	11	6.8	30	.32	8.0	0.045	1.1	6.00	SST	C	N
0.484	12.29	TT-40	.94	23.8	.392	10.0	18	3.1	.41	10	7.3	32	.26	6.7	0.046	1.2	5.75	SST	CG	N
0.484	12.29	S-399	.94	23.8	.358	9.1	48	8.4	.36	9.1	17	76	.47	12.0	0.063	1.6	7.50	SST	CG	N
0.484	12.29	II-90	.94	23.8	.350	8.9	67	12	.33	8.3	22	97	.54	13.6	0.067	1.7	8.00	SPR	CG	N
0.484	12.29	1525	1.00	25.4	.418	10.6	2.1	.36	.60	15	1.2	5.5	.40	10.1	0.033	0.8	11.0	SPR	C	Z
0.484	12.29	S-3135	1.00	25.4	.410	10.4	6.6	1.1	.58	15	3.8	17	.22	5.6	0.037	0.9	6.00	SST	CG	N
0.484	12.29	10491	1.00	25.4	.394	10.0	14	2.4	.52	13	7.3	32	.32	8.0	0.045	1.1	7.00	SPR	CG	Z
0.484	12.29	1885	1.00	25.4	.394	10.0	17	3.1	.58	15	10	45	.27	6.9	0.045	1.1	6.00	MW	CG	Z
0.484	12.29	11815	1.00	25.4	.388	9.9	15	2.7	.57	15	8.8	39	.38	9.8	0.048	1.2	8.00	SPR	CG	Z
0.484	12.29	3088	1.00	25.4	.384	9.8	17	3.0	.55	14	9.3	41	.43	10.8	0.050	1.3	8.50	SPR	CG	Z
0.484	12.29	OO-66	1.00	25.4	.384	9.8	27	4.8	.34	8.6	9.3	41	.30	7.6	0.050	1.3	6.00	SPR	CG	N
0.484	12.29	DD-94	1.00	25.4	.384	9.8	24	4.3	.38	9.6	9.3	41	.33	8.3	0.050	1.3	6.50	SPR	CG	N
0.484	12.29	12304	1.00	25.4	.374	9.5	33	5.8	.37	9.3	12	54	.44	11.2	0.055	1.4	7.00	SPR	C	Z
0.484	12.29	TT-42	1.00	25.4	.360	9.1	41	7.2	.40	10	16	73	.50	12.6	0.062	1.6	8.00	SST	CG	N
0.484	12.29	YY-31	1.00	25.4	.360	9.1	94	16	.18	4.7	17	77	.31	7.9	0.062	1.6	5.00	SPR	CG	Z
0.484	12.29	10598	1.00	25.4	.356	9.0	54	9.5	.35	8.9	19	85	.51	13.0	0.064	1.6	8.00	SPR	CG	Z
0.484	12.29	Z-47	1.00	25.4	.294	7.5	332	58	.16	4.2	54	241	.76	19.3	0.095	2.4	8.00	SPR	CG	N
0.484	12.29	RR-60	1.03	26.2	.274	7.0	535	94	.13	3.4	72	319	.84	21.3	0.105	2.7	8.00	SPR	CG	Z
0.484	12.29	A-94	1.06	27.0	.300	7.6	270	47	.17	4.3	46	204	.69	17.5	0.092	2.3	7.50	SST	CG	N
0.484	12.29	B5-35	1.09	27.8	.400	10.2	10	1.8	.57	15	5.9	26	.34	8.5	0.042	1.1	7.00	SPR	C	N
0.484	12.29	L-21	1.09	27.8	.390	9.9	16	2.8	.48	12	7.7	34	.31	7.8	0.047	1.2	6.50	SST	CG	N
0.484	12.29	S-1092	1.13	28.6	.434	11.0	1.0	.18	.93	23	.93	4.2	.20	5.1	0.025	0.6	7.00	SST	C	N
0.484	12.29	A-35	1.13	28.6	.420	10.7	1.8	.32	.74	19	1.3	6.0	.38	9.8	0.032	0.8	11.0	SPR	C	P
0.484	12.29	H-47	1.13	28.6	.386	9.8	14	2.5	.65	16	9.3	42	.44	11.2	0.049	1.2	9.00	SPR	CG	Z
0.484	12.29	XX-68	1.13	28.6	.382	9.7	22	3.8	.45	11	9.8	44	.43	11.0	0.051	1.3	7.50	SPR	C	Z
0.484	12.29	10351	1.16	29.4	.360	9.1	35	6.2	.47	12	17	74	.68	17.3	0.062	1.6	10.0	SPR	C	Z
0.484	12.29	S-1126	1.19	30.2	.426	10.8	1.7	.30	.94	24	1.6	7.1	.25	6.3	0.029	0.7	7.50	SST	C	N
0.484	12.29	H-39	1.19	30.2	.340	8.6	60	11	.40	10	24	106	.72	18.3	0.072	1.8	10.0	SST	CG	N
0.484	12.29	A-39	1.22	31.0	.420	10.7	2.9	.51	.89	23	2.6	11	.26	6.5	0.032	0.8	7.00	SST	C	N
0.484	12.29	S-822	1.22	31.0	.390	9.9	6.8													

COMPRESSION SPRINGS



O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS				
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm		MAT'L		ENDS	FINISH
0.484	12.29	B10-61	1.35	34.3	.376	9.6	26	4.5	.45	12	12	52	.43	11.0	0.054	1.4	8.00	SPR	CG	Z	
0.484	12.29	11983	1.38	34.9	.400	10.2	10	1.8	.57	15	5.9	26	.34	8.5	0.042	1.1	7.00	SPR	C	Z	
0.484	12.29	CC-9	1.38	34.9	.394	10.0	7.6	1.3	.90	23	6.8	30	.45	11.4	0.045	1.1	10.0	SST	CG	N	
0.484	12.29	S-945	1.38	34.9	.384	9.8	13	2.4	.65	16	8.7	39	.46	11.7	0.050	1.3	9.25	SST	CG	N	
0.484	12.29	3832	1.38	34.9	.340	8.6	55	9.7	.46	12	26	113	.86	21.9	0.072	1.8	12.0	HD	CG	Z	
0.484	12.29	12226	1.38	34.9	.334	8.5	66	12	.43	11	29	128	.90	22.9	0.075	1.9	12.0	SPR	CG	N	
0.484	12.29	3903	1.38	34.9	.264	6.7	503	88	.16	4.0	79	351	1.10	27.9	0.110	2.8	10.0	SPR	CG	Z	
0.484	12.29	B14-47	1.41	35.7	.418	10.6	2.9	.50	1.1	27	3.0	14	.28	7.1	0.033	0.8	8.50	SPR	CG	N	
0.484	12.29	B9-8	1.44	36.5	.396	10.1	14	2.5	.48	12	6.8	30	.29	7.3	0.044	1.1	6.50	SPR	CG	Z	
0.484	12.29	YY-60	1.44	36.5	.392	10.0	13	2.2	.61	15	7.8	34	.41	10.5	0.046	1.2	8.00	SPR	C	Z	
0.484	12.29	A15-66	1.47	37.3	.364	9.2	29	5.1	.51	13	15	66	.57	14.5	0.060	1.5	9.50	SST	CG	N	
0.484	12.29	2620	1.47	37.3	.356	9.0	33	5.7	.59	15	19	85	.77	19.5	0.064	1.6	12.0	HD	CG	Z	
0.484	12.29	S-1376	1.50	38.1	.414	10.5	1.3	.23	.84	21	1.1	4.9	.66	16.7	0.035	0.9	17.8	SST	C	N	
0.484	12.29	3570	1.50	38.1	.408	10.4	4.2	.74	1.0	27	4.4	20	.42	10.6	0.038	1.0	10.0	SPR	C	Z	
0.484	12.29	12219	1.50	38.1	.408	10.4	6.8	1.2	.65	17	4.4	20	.27	6.8	0.038	1.0	7.00	SPR	CG	Z	
0.484	12.29	3665	1.50	38.1	.404	10.3	6.7	1.2	.76	19	5.1	23	.37	9.4	0.040	1.0	8.25	SPR	C	Z	
0.484	12.29	S-1490	1.50	38.1	.402	10.2	6.5	1.1	.80	20	5.2	23	.34	8.6	0.041	1.0	8.25	SST	CG	N	
0.484	12.29	A13-40	1.50	38.1	.390	9.9	14	2.5	.59	15	8.3	37	.38	9.6	0.047	1.2	8.00	SPR	CG	GI	
0.484	12.29	S-1413	1.50	38.1	.382	9.7	10	1.8	.84	21	8.7	39	.66	16.8	0.051	1.3	12.0	SST	C	N	
0.484	12.29	2729	1.50	38.1	.376	9.6	17	3.0	.68	17	12	52	.59	15.1	0.054	1.4	11.0	HD	CG	Z	
0.484	12.29	H-42	1.50	38.1	.370	9.4	22	3.8	.63	16	14	60	.68	17.4	0.057	1.4	11.0	SPR	C	Z	
0.484	12.29	PP-56	1.50	38.1	.364	9.2	31	5.4	.52	13	16	70	.60	15.2	0.060	1.5	10.0	SPR	CG	GI	
0.484	12.29	B9-69	1.50	38.1	.364	9.2	20	3.6	.66	17	13	60	.84	21.3	0.060	1.5	14.0	SPR	CG	N	
0.484	12.29	F-48	1.50	38.1	.360	9.1	35	6.2	.49	12	17	77	.62	15.7	0.062	1.6	10.0	SPR	CG	Z	
0.484	12.29	3153	1.50	38.1	.340	8.6	63	11	.40	10	26	113	.77	19.7	0.072	1.8	10.8	SPR	CG	Z	
0.484	12.29	Q-75	1.50	38.1	.260	6.6	628	110	.13	3.4	83	369	1.01	25.6	0.112	2.8	9.00	SPR	CG	Z	
0.484	12.29	O-96	1.53	38.9	.432	11.0	.49	.09	1.1	28	.53	2.4	.44	11.2	0.026	0.7	16.0	MW	C	N	
0.484	12.29	B15-36	1.53	38.9	.388	9.9	6.8	1.2	.86	22	5.8	26	.67	17.1	0.048	1.2	14.0	SST	CG	N	
0.484	12.29	S-223	1.56	39.7	.412	10.5	2.9	.51	1.2	31	3.5	16	.36	9.1	0.036	0.9	10.0	SST	CG	N	
0.484	12.29	4286	1.56	39.7	.374	9.5	16	2.8	.77	20	12	54	.69	17.5	0.055	1.4	12.5	SPR	CG	Z	
0.484	12.29	10039	1.59	40.5	.372	9.4	17	3.0	.75	19	13	57	.70	17.8	0.056	1.4	12.5	SPR	CG	N	
0.484	12.29	10833	1.63	41.3	.404	10.3	8.0	1.4	.64	16	5.1	23	.29	7.4	0.040	1.0	7.25	SPR	CG	Z	
0.484	12.29	J-40	1.63	41.3	.384	9.8	16	2.8	.55	14	8.7	39	.40	10.2	0.050	1.3	8.00	SST	CG	N	
0.484	12.29	11244	1.63	41.3	.360	9.1	33	5.8	.52	13	17	77	.65	16.5	0.062	1.6	10.5	SPR	CG	Z	
0.484	12.29	S-1268	1.63	41.3	.340	8.6	51	8.9	.47	12	24	106	.83	21.0	0.072	1.8	11.5	SST	CG	N	
0.484	12.29	4226	1.63	41.3	.324	8.2	85	15	.41	10	35	154	1.00	25.4	0.080	2.0	12.5	SPR	CG	GI	
0.484	12.29	10356	1.69	42.8	.408	10.4	6.8	1.2	.65	17	4.4	20	.30	7.7	0.038	1.0	7.00	SPR	C	Z	
0.484	12.29	10320	1.69	42.8	.360	9.1	29	5.1	.60	15	17	77	.79	20.1	0.062	1.6	11.8	SPR	C	Z	
0.484	12.29	S-843	1.69	42.8	.340	8.6	47	8.2	.51	13	24	106	.90	22.9	0.072	1.8	12.5	SST	CG	N	
0.484	12.29	II-40	1.69	42.8	.264	6.7	366	64	.22	5.5	79	351	1.43	36.3	0.110	2.8	13.0	SPR	CG	N	
0.484	12.29	11270	1.72	43.6	.288	7.3	210	37	.28	7.2	59	263	1.27	32.4	0.098	2.5	13.0	SPR	CG	Z	
0.484	12.29	2888	1.75	44.5	.360	9.1	24	4.1	.74	19	17	77	.93	23.6	0.062	1.6	14.0	SPR	C	Z	
0.484	12.29	3240	1.75	44.5	.324	8.2	112	20	.31	7.9	35	154	.80	20.3	0.080	2.0	10.0	SPR	CG	Z	
0.484	12.29	10493	1.81	46.0	.388	9.9	8.4	1.5	1.1	27	8.8	39	.62	15.8	0.048	1.2	13.0	SPR	CG	GI	
0.484	12.29	10282	1.81	46.0	.376	9.6	19	3.4	.60	15	12	52	.59	15.1	0.054	1.4	10.0	SPR	C	Z	
0.484	12.29	XX-66	1.81	46.0	.360	9.1	28	4.9	.62	16	17	77	.74	18.9	0.062	1.6	12.0	SPR	CG	Z	
0.484	12.29	H-46	1.81	46.0	.360	9.1	19	3.3	.87	22	16	73	.93	23.6	0.062	1.6	15.0	SST	CG	N	
0.484	12.29	2790	1.84	46.8	.356	9.0	33	5.7	.59	15	19	85	.83	21.1	0.064	1.6	12.0	SPR	C	Z	
0.484	12.29	10413	1.88	47.6	.376	9.6	15	2.7	.75	19	12	52	.65	16.5	0.054	1.4	12.0	SPR	CG	Z	
0.484	12.29	10723	1.88	47.6	.360	9.1	28	4.9	.62	16	17	77	.74	18.9	0.062	1.6	12.0	SPR	C	Z	
0.484	12.29	N-82	1.91	48.4	.424	10.8	1.2	.21	1.6	40	1.9	8.6	.33	8.4	0.030	0.8	11.0	SST	CG	N	
0.484	12.29	10853	1.94	49.2	.324	8.2	59	10	.55	14	32	144	1.24	31.5	0.080	2.0	15.5	SST	CG	N	
0.484	12.29	A-29	2.00	50.8	.434	11.0	.46	.08	1.7	43	.77	3.4	.33	8.3	0.025	0.6	13.0	SST	C	N	
0.484	12.29	S-323	2.00	50.8	.390	9.9	5.6	.98	1.3	33											



COMPRESSION SPRINGS

O.D.		CENTURY STOCK NUMBER	FREE LENGTH		I.D.		RATE		SUGG.MAX.DEFL.		SUGG.MAX.LOAD		SOLID LENGTH		WIRE DIA.		TOTAL COILS	MAT'L	ENDS	FINISH
Inches	mm		Inches	mm	Inches	mm	Lbs./In.	N/mm	Inches	mm	Lbs.	N	Inches	mm	Inches	mm				
0.484	12.29	S-3182	12.0	304.8	.422	10.7	.10	.02	8.1	206	.82	3.6	3.91	99.2	0.031	0.8	125.0	SST	C	N
0.485	12.32	12693	1.00	25.4	.277	7.0	441	77	.15	3.7	65	288	.83	21.1	0.104	2.6	8.00	SST	CG	N
0.492	12.50	12715	.97	24.6	.402	10.2	13	2.3	.65	17	8.6	38	.32	8.0	0.045	1.1	7.00	MW	CG	Z
0.500	12.70	B8-11	.25	6.4	.402	10.2	90	16	.10	2.5	9.1	40	.15	3.7	0.049	1.2	3.00	SPR	CG	GI
0.500	12.70	G-100	.38	9.5	.464	11.8	.45	.08	.27	6.8	.12	.53	.11	2.7	0.018	0.5	5.00	MW	C	N
0.500	12.70	G-19	.38	9.5	.450	11.4	5.2	.92	.28	7.0	1.4	6.4	.10	2.5	0.025	0.6	3.00	MW	C	Z
0.500	12.70	S-1097	.38	9.5	.448	11.4	1.8	.31	.22	5.6	.39	1.7	.16	4.0	0.026	0.7	5.00	SST	C	N
0.500	12.70	L-4	.38	9.5	.402	10.2	90	16	.10	2.5	9.1	40	.20	5.0	0.049	1.2	3.00	SPR	C	Z
0.500	12.70	LL-83	.38	9.5	.356	9.0	493	86	.05	1.3	25	110	.29	7.3	0.072	1.8	3.00	SPR	C	Z
0.500	12.70	BB-92	.41	10.3	.432	11.0	8.3	1.4	.27	6.9	2.2	9.9	.14	3.5	0.034	0.9	4.00	SST	CG	N
0.500	12.70	10884	.44	11.1	.468	11.9	.17	.03	.31	7.9	.05	.23	.13	3.3	0.016	0.4	7.00	MW	C	Z
0.500	12.70	H-54	.44	11.1	.448	11.4	6.2	1.1	.33	8.3	2.0	9.0	.08	2.0	0.026	0.7	3.00	MW	CG	Z
0.500	12.70	S-351	.44	11.1	.422	10.7	7.5	1.3	.20	5.2	1.5	6.8	.23	5.9	0.039	1.0	6.00	SST	CG	N
0.500	12.70	3751	.44	11.1	.386	9.8	87	15	.15	3.8	13	59	.23	5.8	0.057	1.4	4.00	SPR	CG	Z
0.500	12.70	4179	.50	12.7	.462	11.7	.56	.10	.39	9.8	.22	.96	.11	2.9	0.019	0.5	5.00	MW	C	BO
0.500	12.70	S-108	.50	12.7	.460	11.7	.60	.11	.38	9.7	.23	1.0	.12	3.0	0.020	0.5	5.00	SST	C	N
0.500	12.70	2931	.50	12.7	.456	11.6	1.0	.18	.37	9.3	.38	1.7	.13	3.4	0.022	0.6	5.00	MW	C	N
0.500	12.70	S-905	.50	12.7	.444	11.3	3.4	.60	.36	9.1	1.2	5.5	.14	3.6	0.028	0.7	4.00	SST	C	N
0.500	12.70	4118	.50	12.7	.432	11.0	19	3.3	.17	4.3	3.2	14	.14	3.5	0.034	0.9	3.00	SPR	C	Z
0.500	12.70	Y-41	.50	12.7	.430	10.9	11	1.9	.31	7.9	3.3	15	.14	3.6	0.035	0.9	4.00	SPR	CG	Z
0.500	12.70	S-118	.50	12.7	.406	10.3	33	5.7	.23	5.8	7.5	33	.19	4.8	0.047	1.2	4.00	SST	CG	N
0.500	12.70	NN-4	.50	12.7	.400	10.2	39	6.9	.23	5.8	9.0	40	.23	5.7	0.050	1.3	4.50	SPR	CG	N
0.500	12.70	B1-33	.50	12.7	.388	9.9	72	13	.16	4.2	12	52	.22	5.7	0.056	1.4	4.00	SST	CG	N
0.500	12.70	3215	.53	13.5	.460	11.7	.69	.12	.43	11	.30	1.3	.10	2.5	0.020	0.5	5.00	MW	CG	Z
0.500	12.70	G-11	.53	13.5	.398	10.1	36	6.3	.23	5.7	8.1	36	.31	7.8	0.051	1.3	5.00	SPR	C	N
0.500	12.70	O-52	.53	13.5	.310	7.9	766	134	.06	1.6	49	218	.38	9.7	0.095	2.4	4.00	SST	CG	N
0.500	12.70	L-52	.55	13.9	.300	7.6	1123	197	.05	1.4	61	271	.40	10.2	0.100	2.5	4.00	SPR	CG	Z
0.500	12.70	F-78	.56	14.3	.456	11.6	1.0	.18	.43	11	.44	2.0	.13	3.4	0.022	0.6	5.00	MW	C	Z
0.500	12.70	EE-22	.56	14.3	.420	10.7	8.2	1.4	.32	8.2	2.6	12	.24	6.1	0.040	1.0	6.00	SST	CG	N
0.500	12.70	LL-26	.56	14.3	.420	10.7	17	2.9	.30	7.5	5.0	22	.17	4.3	0.040	1.0	4.25	SPR	CG	GI
0.500	12.70	VV-37	.56	14.3	.416	10.6	23	4.1	.25	6.3	5.7	26	.21	5.3	0.042	1.1	4.00	SPR	C	GI
0.500	12.70	S-1304	.56	14.3	.392	10.0	48	8.4	.22	5.6	11	47	.24	6.2	0.054	1.4	4.50	SST	CG	N
0.500	12.70	JJ-37	.56	14.3	.380	9.7	55	9.6	.20	5.1	11	49	.36	9.1	0.060	1.5	6.00	SPR	CG	N
0.500	12.70	XX-62	.56	14.3	.316	8.0	607	106	.08	2.0	48	214	.41	10.5	0.092	2.3	4.50	SPR	CG	Z
0.500	12.70	S-1398	.56	14.3	.310	7.9	681	119	.07	1.8	49	218	.40	10.3	0.095	2.4	4.25	SST	CG	N
0.500	12.70	3611	.59	15.1	.430	10.9	11	1.9	.42	11	4.5	20	.18	4.4	0.035	0.9	4.00	MW	C	Z
0.500	12.70	12673	.59	15.1	.426	10.8	14	2.4	.40	10	5.5	24	.19	4.7	0.037	0.9	4.00	MW	C	Z
0.500	12.70	O-79	.59	15.1	.412	10.5	19	3.3	.35	8.8	6.6	29	.22	5.6	0.044	1.1	5.00	SPR	CG	Z
0.500	12.70	A14-55	.61	15.5	.420	10.7	19	3.3	.26	6.7	5.0	22	.16	4.1	0.040	1.0	4.00	SPR	CG	GI
0.500	12.70	Q-12	.63	15.9	.436	11.1	4.3	.75	.43	11	1.8	8.2	.19	4.9	0.032	0.8	5.00	SST	C	N
0.500	12.70	A14-46	.63	15.9	.424	10.8	13	2.4	.30	7.5	4.0	18	.15	3.9	0.038	1.0	4.00	SST	CG	N
0.500	12.70	PP-94	.63	15.9	.424	10.8	12	2.1	.35	8.9	4.3	19	.17	4.3	0.038	1.0	4.50	SPR	CG	GI
0.500	12.70	A11-35	.63	15.9	.422	10.7	15	2.6	.29	7.3	4.3	19	.16	4.0	0.039	1.0	4.00	SST	CG	N
0.500	12.70	AA-74	.63	15.9	.420	10.7	13	2.2	.39	9.8	4.9	22	.24	6.1	0.040	1.0	5.00	SPR	C	N
0.500	12.70	OO-8	.63	15.9	.420	10.7	15	2.6	.33	8.4	5.0	22	.18	4.6	0.040	1.0	4.50	SPR	CG	N
0.500	12.70	3831	.63	15.9	.416	10.6	16	2.7	.37	9.4	5.7	26	.25	6.4	0.042	1.1	5.00	SPR	C	Z
0.500	12.70	S-1302	.63	15.9	.412	10.5	20	3.5	.31	7.9	6.2	27	.20	5.0	0.044	1.1	4.50	SST	CG	N
0.500	12.70	3905	.63	15.9	.410	10.4	31	5.5	.23	5.7	7.0	31	.18	4.6	0.045	1.1	4.00	SPR	CG	Z
0.500	12.70	A15-4	.63	15.9	.404	10.3	20	3.4	.35	8.9	6.8	30	.28	7.0	0.048	1.2	5.75	SST	CG	N
0.500	12.70	B14-37	.63	15.9	.394	10.0	45	7.9	.22	5.7	10	45	.24	6.1	0.053	1.3	4.50	SST	CG	N
0.500	12.70	10976	.63	15.9	.392	10.0	55	9.7	.20	5.2	11	50	.30	7.5	0.054	1.4	4.50	HD	C	Z
0.500	12.70	10102	.63	15.9	.376	9.6	126	22	.13	3.4	17	75	.25	6.3	0.062	1.6	4.00	HD	CG	Z
0.500	12.70	2606	.63	15.9	.370	9.4	125	22	.16	3.9	19	86	.29	7.4	0.065	1.7	4.50	SPR	CG	Z
0.500	12.70	CC-8	.63	15.9	.356	9.0	143	25	.16	4.1	23	103	.36	9.1	0.072	1.8	5.00	SST	CG	N
0.500	12.70	B-22	.66	16.7	.394	10.0	56	9.9	.19	4.8	11	47	.28	7.1	0.053	1.3	4.25	HD	C	N
0.500	12.70	S-99	.69	17.4	.410	10.4	14	2.4	.42	11	5.8	26	.27	6.9	0.045	1.1	6.00	SST	CG	N
0.500	12.70	11444	.69	17.4	.410	10.4	12	2.2	.39	10	4.9	22	.29	7.4	0.045	1.1	6.50	SST	CG	N
0.500	12.70	S-1457	.69	17.4	.408	10.4	24	4.2	.29	7.5	7.0	31	.21	5.3	0.046	1.2	4.50	SST	CG	N
0.500	12.70	3825	.69	17.4	.372	9.4	129	23	.14	3.6	19	82	.27	6.9	0.064	1.6	4.25	SPR	CG	N
0.500	12.70	LL-4	.69	17.4	.320	8.1	342	60	.13	3.4	45	201	.54	13.7	0.090	2.3	6.00	SPR	CG	GI
0.500	12.70	B5-9	.72	18.2	.424	10.8	12	2.1	.35	8.9	4.3	19	.17	4.3	0.038	1.0	4.50	SPR	CG	N
0.500	12.70	EE-78	.72	18.2	.416	10.6	21	3.6	.28	7.1	5.7	26	.18	4.5	0.042	1.1	4.25	SPR	CG	N
0.500	12.70	1881	.72	18.2	.376	9.6	101	18	.23	5.9	23	104	.28	7.1	0.062	1.6	4.50	MW	CG	Z
0.500	12.70	1932	.72	18.2	.376	9.6	84	15	.20	5.1	17	75	.37	9.4	0.062	1.6	5.00	SPR	C	Z
0.500	12.70	G-85	.72	18.2	.296	7.5	897	157	.07	1.8	64	287	.48	12.3	0.102	2.6	4.75	SPR	CG	N
0.500	12.70	B14-6	.72	18.2	.278	7.1	1236	216	.06	1.6	79	351	.56	14.1	0.111	2.8	5.00	SPR	CG	N
0.500	12.70	3967	.75	19.1	.438	11.1	4.0	.69	.56	14	2.2	9.8	.19	4.9	0.031	0.8	5.25	MW	C	Z
0.500	12.70	PP-89	.75	19.1	.432	11.0	6.0	1.1	.50	13	3.0	13	.20	5.0	0.034	0.9	4.75	SST	C	N
0.500	12.70	B3-68	.75	19.1	.426	10.8	9.0	1.6	.53	13	4.8	21	.22	5.6	0.037	0.9	5.00	MW	C	T
0.500	12.70	S-754	.75	19.1	.416	10.6	15	2.6	.37											